

SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006 (REACH) and (EU) 2020/878. Document SDS-AN-1542 - Revision 2.2 - Date of issue 2025-12-08.

SECTION 1: Identification of the substance/mixture and of the company

|                          |                                                                             |
|--------------------------|-----------------------------------------------------------------------------|
| Product name             | Sikkens Cetol Filter 7 Plus Wood Stain                                      |
| Product code             | SDS-AN-1542                                                                 |
| Product type             | Industrial / professional coating                                           |
| Relevant identified uses | Solvent-borne translucent wood stain for exterior joinery.                  |
| Supplier                 | AkzoNobel N.V., Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands |
| Emergency telephone      | +31 (0)20 502 7555 (24h)                                                    |

SECTION 2: Hazards identification

|                          |                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------|
| Classification (CLP)     | Flammable Liquid, Category 4 (combustible)                                        |
| Signal word              | Warning                                                                           |
| Hazard statements        | GHS07, GHS08; H226 (border); H304; H317; H412.                                    |
| Precautionary statements | P210 Keep away from heat/sparks. P280 Wear protective gloves/eye protection. P403 |

SECTION 3: Composition / information on ingredients

| Chemical name                      | CAS No.     | Conc.    | Classification          |
|------------------------------------|-------------|----------|-------------------------|
| White spirit (Stoddard solvent)    | 64742-48-9  | 30 - 45% | Asp. Tox. 1; H304; H336 |
| Alkyd resin (long oil)             | Proprietary | 30 - 45% | Not classified          |
| Iron oxide pigments                | 1309-37-1   | 2 - 8%   | Not classified          |
| Cobalt bis(2-ethylhexanoate) drier | 136-52-7    | < 0.5%   | Skin Sens. 1; H317      |

SECTION 4: First-aid measures

**Inhalation:** Move to fresh air. If symptoms persist, obtain medical attention. **Skin contact:** Wash with soap and water; remove contaminated clothing. **Eye contact:** Rinse cautiously with water for several minutes. **Ingestion:** Do not induce vomiting; seek medical advice.

SECTION 5: Fire-fighting measures

|                              |                                                                                |
|------------------------------|--------------------------------------------------------------------------------|
| Flash point                  | 62 deg C (closed cup)                                                          |
| Suitable extinguishing media | Foam, CO2, dry powder, water spray. Do not use water jet.                      |
| Special hazards              | Combustion may release CO, CO2 and nitrogen oxides. Powders may form explosive |

## SECTION 6: Accidental release measures

Eliminate ignition sources. Use personal protection as in Section 8. Collect mechanically; avoid dust generation. Prevent entry into drains and watercourses.

## SECTION 7: Handling and storage

|                               |                                                                           |
|-------------------------------|---------------------------------------------------------------------------|
| <b>Safe handling</b>          | Avoid inhalation of dust/vapour. Ensure adequate ventilation. No smoking. |
| <b>Storage conditions</b>     | Store in original closed container in a dry, well-ventilated area.        |
| <b>Storage temperature</b>    | 5 to 25 deg C                                                             |
| <b>Incompatible materials</b> | Strong oxidising agents, strong acids and bases.                          |
| <b>Shelf life</b>             | 24 months from date of manufacture under recommended conditions.          |

## SECTION 8: Exposure controls / personal protection

|                                     |                                                                                    |
|-------------------------------------|------------------------------------------------------------------------------------|
| <b>Occupational exposure limits</b> | Observe local OEL/WEL values for solvents, dusts and TiO <sub>2</sub> (inhalable). |
| <b>Engineering controls</b>         | Provide local exhaust ventilation; maintain airborne levels below OEL.             |
| <b>Required PPE</b>                 | Nitrile gloves, safety glasses, A1 vapour respirator in poor ventilation           |

## SECTION 9: Physical and chemical properties

| Property           | Value                         |
|--------------------|-------------------------------|
| Form               | Liquid                        |
| Colour             | Translucent wood tones        |
| Odour              | White-spirit / solvent        |
| pH                 | Not applicable                |
| Density            | 0.88 - 0.95 g/cm <sup>3</sup> |
| Solubility (water) | Immiscible                    |
| VOC content        | 400 g/L                       |
| Flash point        | 62 deg C                      |

## SECTION 10: Stability and reactivity

Stable under normal conditions. Avoid heat, sparks and open flame. Hazardous polymerisation does not occur.

## SECTION 11: Toxicological information

May cause irritation of eyes, skin and respiratory tract. Titanium dioxide classified Carc. 2 by inhalation of dust. See Section 3 for sensitisers.

## SECTION 12: Ecological information

Do not allow to enter drains, soil or watercourses. Aquatic toxicity depends on components; see Section 3 classifications.

## SECTION 13: Disposal considerations

Dispose of contents/container in accordance with local, regional and national regulations. European Waste Catalogue code per use.

## SECTION 14: Transport information

Classify for transport (ADR/IMDG/IATA) according to flammability and environmental hazard. Non-flammable water-based products are generally not regulated.

## SECTION 15: Regulatory information

Complies with REACH (EC) 1907/2006 and CLP (EC) 1272/2008. VOC content stated in Section 9 per Directive 2004/42/EC.

## SECTION 16: Other information

Revision 2.2. This SDS is a SYNTHETIC document created for a Databricks document-intelligence demo and does not describe a real product formulation.