


Introduction to Algorithm Engineering

Homework-2

Moida Praneeth Jain, 2022101093

Question 1


Consider graph G with 12 vertices and 18 edges, as shown below



Now, we perform the following DFS traversal, picking the root node as 1

$$1 \rightarrow 2 \rightarrow 3 \rightarrow 4 \rightarrow 5 \rightarrow 6 \rightarrow 12 \rightarrow 11 \rightarrow 10 \rightarrow 9 \rightarrow 8 \rightarrow 7$$

We construct a directed graph, with edges as part of the DFS tree pointing towards the root, and the non-tree edges pointing away from the root



Back Edge 1 - 6

$$P_0 = 1 - 2$$

$$P_1 = 1 - 6 - 5 - 4 - 3 - 2$$

$$\text{visited} = \{1, 2, 3, 4, 5, 6\}$$

Back Edge 1 - 7

$$P_2 = 1 - 7 - 12 - 6$$

$$\text{visited} = \{1, 2, 3, 4, 5, 6, 7, 12\}$$

Back Edge 2 - 8

$$P_3 = 2 - 8 - 7$$

$$\text{visited} = \{1, 2, 3, 4, 5, 6, 7, 8, 12\}$$

Back Edge 3 - 9

$$P_4 = 3 - 9 - 8$$

$$\text{visited} = \{1, 2, 3, 4, 5, 6, 7, 8, 9, 12\}$$

Back Edge 4 - 10

$$P_5 = 4 - 10 - 9$$

$$\text{visited} = \{1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12\}$$

Back Edge 5 - 11

$$P_6 = 5 - 11 - 10$$

$$\text{visited} = \{1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12\}$$


Back Edge 12 - 11

$$P_7 = 12 - 11$$

$$\text{visited} = \{1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12\}$$

$\{P_i\}$ is the ear decomposition

Below is a visual representation of the chain decomposition of the graph



Question 2

Square Matrices




Figure 1: Variation in transpose time with size of square matrices

First, let us consider the case of square matrices. As we can observe from Figure 1, the trend is quadratic, as was noted in Homework 1. In the naive case, we get $O(N^2)$, and for the recursive and submatrix case, we get $O\left(\frac{N^2}{B}\right)$

Row Matrices




Figure 2: Variation in transpose time with rows of matrix. (1e8 matrix entries)

We fix the total number of elements in the matrix to $1e8$, and increase the number of rows to $1e4$ while decreasing the number of columns from $1e8$, i.e, the plot represents the transpose time as the graph transitions from a row matrix to a square matrix.

From Figure 2 we observe that the times are approximately constant. This is because in these matrices, each row has more elements than the cache can fit, thus the cache hit/miss rate remains constant throughout.

Column Matrices




Figure 3: Variation in transpose time with columns of matrix. ($1e8$ matrix entries)

We fix the total number of elements in the matrix to $1e8$, and increase the number of columns to $1e4$ while decreasing the number of rows from $1e8$, i.e, the plot represents the transpose time as the graph transitions from a column matrix to a square matrix.

The key point to note from Figure 3 is that these times are much higher than the row matrices. This is because column matrices are much worse for cache access than row matrices. At around 3000 columns, the times go back down. This is where the number of elements in each row (the number of columns) is large enough for the cache to get filled up.