
Unit – 3 : Session – 6 : SLO – 1 | Priority and Round Robin Programs — Missing Code (Priority)

Answers

BLANK 1: `pt[i] > pt[j]` (a smaller priority number means higher priority, so sort ascending by priority).

BLANK 2: `wt[i-1] + bt[i-1]`

BLANK 3: `wt[i] + bt[i]`

Completed program

```
#include <stdio.h>
int main() {
    int n, i, j;
    int bt[20], p[20], wt[20], tat[20], pt[20];

    int temp;
    printf("Enter number of processes: ");
    scanf("%d", &n);
    for(i = 0; i < n; i++) {
        printf("Enter burst time and priority for process %d: ", i + 1);
        scanf("%d%d", &bt[i], &pt[i]);
        p[i] = i + 1;
    }
    for(i = 0; i < n; i++) {
        for(j = i + 1; j < n; j++) {
            if(pt[i] > pt[j]) { // BLANK 1 (low no. = high prio)
                temp = bt[i]; bt[i] = bt[j]; bt[j] = temp;
                temp = pt[i]; pt[i] = pt[j]; pt[j] = temp;
                temp = p[i]; p[i] = p[j]; p[j] = temp;
            }
        }
    }
    wt[0] = 0;
    for(i = 1; i < n; i++) {
        wt[i] = wt[i-1] + bt[i-1]; // BLANK 2
    }
    for(i = 0; i < n; i++) {
        tat[i] = wt[i] + bt[i]; // BLANK 3
    }
    printf("\nProcess\tPriority\tBT\tWT\tTAT");
    for(i = 0; i < n; i++) {
        printf("\nP%d\t%d\t%d\t%d\t%d", p[i], pt[i], bt[i], wt[i], tat[i]);
    }
    return 0;
}
```