

PROGRAM MODELING

CONCEPTS :


Lesson-1: PROGRAM MODELS

1. Sequential Program Model

Programming using Sequential functions

- Use of multiple function calls sequentially

Programming model of Six sequential function calls



ACVM Example Sequential Program


Model

- Run function `get_user_input ()` for obtaining input for choice of chocolate from child.
- Run function `read_coins ()` for reading the coins inserted into ACVM for cost of chocolate.
- Run function `deliver_chocolate` for delivering the chocolate

ACVM Example Sequential Program Model (contd.)

- Run function display_thanks for displaying 'Collect the nice chocolate. Visit again!'

Sequential Programming Model of an ACVM



2. Data-Flow and control data flow **Models**

Data-Flow Model

- Data flow graphs (DFGs)
- Control data flow graphs (CDFGs)
- Modeling of data paths
- program flows in software.
- A program is modeled as handling the input data streams and creating output data streams

3. State Machine Model

State Machine Model

- A programming model is that there are different states and the model considers a program as a machine, which is producing the states

Example of a Mobile Phone T9 keypad key

- Key marked 5 can produce on pressing different states— $(0, 5)$, $(1, 5)$, $(1, j)$,
- The transition of the key occurs if it is pressed again within an interval.
- The state of the key undergoes in a cyclic fashion till during the interval same key is not pressed again
- $(1, 5) \rightarrow (1, j) \rightarrow (1, k) \rightarrow (1, l) \rightarrow (1, 5) \rightarrow (1, j)$ inserted between the two elements.

4. Concurrent Processes and Inter-Process Communication Model

Concurrent Processes and Inter-Process Communication Model


- There are several concurrent tasks (or processes or threads)
- Each task has the sequential codes in infinite loop.
- A task sends a message or signal (to Operating System) for another task.
- A task, which gets a message or signal (using a one-bit bit) from the Operating System , runs and remaining tasks remain in blocked state

Creation of Concurrent processes in ACVM

Concurrent Processes create

```
create process get_user_input ;  
create process read_coins ( ) ;  
create process deliver_chocolate ( ) ;  
create process display_thanks ( ) ;  
create process display_wait ( ) ; }  
}
```

Concurrent running of the processes in an ACVM



Concurrent running of the processes in an ACVM

- 1. Process `get_user_input ()`— waits for obtaining input for choice of chocolate from the child and signaling to process `read_coins` start.
- 2. Process `read_coins ()` — waits for signal `get_user_input ()` and start reading on signal from for reading the coins inserted in the ACVM for the cost of chocolate. Post a signal to process `deliver_chocolate` to start and also post a signal to process `display_wait ()` to start

Concurrent running of the processes in an ACVM

- 3. Process `deliver_chocolate ()` — waits for signal from `read_coins ()` and start delivering the chocolate and post a signal to `display_thanks ()` to start.
- 4. Process `display_wait ()` — waits for signal from `read_coins ()` and start displaying ‘Wait few moments!’ and signal `display_thanks`.

Concurrent running of the processes in an ACVM

- 5. Process `display_thanks ()` — waits for signal from `deliver_chocolate ()` and for signal from `display_wait ()` and then start displaying ‘Collect the nice chocolate. Visit again!’

5. Object Oriented Programming Model

Object Oriented Programming Model

- (i) When there is a need for re-usability of defined object or set of objects that are common within a program or between many applications,
(ii) when there is need for abstraction and
(iii) when, by defining objects by inheritance and polymorphs, new objects can be created
- There is data encapsulation within an object.

Object Oriented Programming Model

- (ii) An object is characterised by its identity (a reference to it that holds its state and behavior), by its state (its data, property, fields and attributes) and by its behavior (operations, method or methods that can manipulate state of the object).
- (iii) Objects are created from the instances of a class. Defining the logically related group makes a class.
- Class defines the state and behavior. It has internal user-level fields for its state and behavior. It defines the methods of processing the fields

Object Oriented Programming Model

- A class can thus create many objects by copying the group and making it functional. Each object is functional. Each object can interact with other objects to process the states as per the defined behavior.
- A set of classes and their objects then gives the application program

Example of the ACVM classes and objects

1. Class GUI for graphic-user interaction. It has two methods `display_menu ()` and `get_user_input ()` and for obtaining input for the choice of chocolate from the child. It has method `set_choice ()` to set the choice selected


GUI

Class GUI

Unsigned byte []: keycode
String: char [];
String: MenuItems;
MenuItems: StrLine1, StrLine2, StrLine3,
StrLine4,
Color: textLineColor, cursorTextLineColor,
screenBackgroundColor
Cursor: line, coloredBar

display_menu ();
get_user_input ();
set_choice ();
enterClick ();

Inherited classes from GUI



Class Read_Coins ()

2. Class Read_Coins () for reading the coins inserted. It has a method read (), read () and read to read one, two and five rupee coins from three ports and a method sum () for summing the total coins

Class Read_Coins

Class Read_Coins

Unsigned byte []: coinAmount

readCoin ();

sum ();

Object **read_port** of the Class Read_Coins

read_port: Read_Coins

coinAmount: coin1, coin2, coin 5

Class Deliver_chocolate

3. It has methods, get_choice () to get the choice and deliver () for delivering the chocolate.

Class Deliver_chocolate

Class Deliver_chocolate

```
get_choice ( );  
deliver ( );
```

Class MsgDisplay

4. It has methods `display_wait ()` and `display_thanks ()` for display wait message and thank message. Class GUI for graphic-user interaction. It has two methods `display_menu ()` and `get_user_input ()` and for obtaining input for the choice of chocolate from the child. It has method `set_choice ()` to set the choice selected

Class MsgDisplay

Class MsgDisplay

```
String: char [ ];  
String: MsgItems1; StrLine1;  
MsgItems2: StrLine2;  
Color: textLineColor
```

```
abstract screen_size ( )  
set_display_period ( );
```

Objects of the Class MsgDisplay

```
displayThanks: MsgDisplay
```

```
displayWait: MsgDisplay
```



Class GUI and Class MsgDisplay

- Class GUI creates GUI objects as multiple instances of GUI
- Class MsgDisplay creates message display objects as multiple instance of wait and thanks messages.
- Class MsgDisplay can be interfaced to an interface screen_size (), which has an abstract method screen_size ().
- The abstract method screen_size () is implemented in a MsgDisplay implementing class on extending

Extending class MsgDisplay

- New class Msg-Time_Display
- Extended class Msg-Time_Display inherits all attributes and methods of class MsgDisplay
- Extended class have another method display_time_date () for displaying time and date also with each message.
- Extended class can interface to an interface set_display_period.
- Msg-Time_Display will now implement the method set_display_period () to set display period of 1 or 2 minute for thanks and wait messages

Inherited classes from Class MsgDisplay



Object oriented approach features

- Re-usability of the defined objects from GUI and set of objects that are common within a program or between the many applications are created.
- Also we have abstract methods, `screen_size ()` and `set_display_period` which are implemented in the interfacing classes.

Object oriented approach features

- Inheritance in new objects, which are created by extending the class MsgDisplay.
- Encapsulation of methods and attributes in the class and objects

Summary

We learnt

- Sequential program modeling
- DFG and CDFG modeling
- State machine modeling
- Concurrent processes modeling
- Object oriented modeling

End of Lesson 1 of Chapter 6