

<i>Foreword</i>	<i>xi</i>
<i>Preface</i>	<i>xiii</i>
1. Background of QSAR and Historical Developments	1
1.1 Introduction	2
1.2 Physicochemical Aspects of Biological Activity of Drugs and Chemicals	6
1.3 Structure—Activity Relationship	20
1.4 Historical Development of QSARs: a Journey of Knowledge Enrichment	31
1.5 Applications of QSAR	35
1.6 Regulatory Perspectives of QSAR	38
1.7 Overview and Conclusion	39
References	43
2. Chemical Information and Descriptors	47
2.1 Introduction	48
2.2 Concept of Descriptors	48
2.3 Type of Descriptors	53
2.4 Descriptors Commonly Used in QSAR Studies	54
2.5 Overview and Conclusion	78
References	78
3. Classical QSAR	81
3.1 Introduction	81
3.2 The Free—Wilson Model	82
3.3 The Fujita—Ban Model	88
3.4 The LFER Model	92
3.5 Kubinyi's Bilinear Model	98
3.6 The Mixed Approach	100
3.7 Overview and Conclusions	101
References	101
4. Topological QSAR	103
4.1 Introduction	103
4.2 Topology: A Method of Chemical Structure Representation	104
4.3 Graphs and Matrices: Platforms for the Topological Paradigm	105

4.4	Topological Indices	121
4.5	Conclusion and Possibilities	140
	References	147
5.	Computational Chemistry	151
5.1	Introduction	151
5.2	Computer Use in Chemistry	152
5.3	Conformational Analysis and Energy Minimization	158
5.4	Molecular Mechanics	165
5.5	Molecular Dynamics	170
5.6	Quantum Mechanics	173
5.7	Overview and Conclusion	185
	References	188
6.	Selected Statistical Methods in QSAR	191
6.1	Introduction	191
6.2	Regression-Based Approaches	192
6.3	Classification-Based QSAR	215
6.4	Machine Learning Techniques	220
6.5	Conclusion	228
	References	228
7.	Validation of QSAR Models	231
7.1	Introduction	231
7.2	Different Validation Methods	233
7.3	A Practical Example of the Calculation of Common Validation Metrics and the AD	274
7.4	QSAR model reporting format	284
7.5	Overview and Conclusion	285
	References	286
8.	Introduction to 3D-QSAR	291
8.1	Introduction	292
8.2	Comparative Molecular Field Analysis	293
8.3	Comparative Molecular Similarity Indices Analysis	302
8.4	Molecular Shape Analysis	304
8.5	Receptor Surface Analysis	307

8.6 Other Approaches	308
8.7 Overview and Conclusions	315
References	316

Co

Contents

9. Newer QSAR Techniques	319
9.1 Introduction	320
9.2 HQSAR	321
9.3 G-QSAR	329
9.4 Other Approaches	336
9.5 Overview and Conclusions	353
References	354
10. Other Related Techniques	357
10.1 Introduction	358
10.2 Pharmacophore	359
10.3 Structure-Based Design—Docking	375
10.4 Combination of Structure- and Ligand-Based Design Tools	396
10.5 <i>In silico</i> Screening of Chemical Libraries: VS	403
10.6 Overview and Conclusions	417
References	421
11. SAR and QSAR in Drug Discovery and Chemical Design—Some Examples	427
11.1 Introduction	427
11.2 Successful Applications of QSAR and Other <i>In Silico</i> Methods: Representative Examples	428
11.3 Conclusion	450
References	450
12. Future Avenues	455
12.1 Introduction	455
12.2 Application Areas	456
12.3 Conclusion	460
References	460
<i>Index</i>	463

QSAR

1.1 Introduction

1.2 Historical aspects

1.3 Hansch Analysis

1.4 Free-Wilson Analysis

2.1 SAR vs QSAR

2.2 Designing QSAR experiments

3.3 QSAR methodology

3.4 Deriving equations (Simple and MLR, PCA, PLS, and genetic algorithms)

3.5 Selection of diverse sets (Clustering analysis, dissimilarity based algorithms, etc)

3.6 Introduction to ML (Neural networks, Random forest methods, SVM and other deep learning methods such as PyTorch platform)

4.1 Various aspects of validating results from QSAR and ML methods

4.2 Special emphasis on applicability domains

Types of QSAR:

3.1 introduction to various types of QSAR

3.2 QSAR and QSPR

3.3 2D QSAR:

- Linear free energy relationships descriptors for QSAR
- experimental & theoretical
- statistical parameters & their significance
- correlation coefficient
- cross validated correlation coefficient
- standard error
- F-value
- boot-strap analysis
- randomization

3.4 3D QSAR model -

- Introduction
- History
- Methodology

3.5 Methods:

- CoMFA
- CoMSIA
- CoRIA
- COMBINE 3D QSAR
- AFMoC
- others etc

3.6 Brief overview of High order QSAR methods (4D to 6D)

1. Introduction to QSAR

(Page 23 onwards in Roy, Kar and Das)

1.1 What is QSAR?

Definition of QSAR: QSAR is a computational technique used to predict the biological activity, toxicity, or physicochemical properties of molecules based on their chemical structure.

Imagine you're a detective trying to solve a case:

- You have a list of chemical compounds (your suspects).
- Each compound has structural features (their physical traits, like fingerprints or DNA).
- Your job is to **find a mathematical pattern** that links these features to their biological effects (e.g., toxicity, drug effectiveness).

Essentially, QSAR turns chemistry into **predictive mathematics**, helping scientists design new drugs without needing to synthesize and test each one experimentally.

Key concepts:

- ADMET
- Random walk
- The predictive modeling studies- aim in exploring all such potential attributes that affect the activity/property/toxicity of chemicals.

1.1.1 What is EC_{50} (Effective Concentration 50%)?

Definition:

EC_{50} is the **concentration of a drug** that produces **50% of its maximum effect** in a biological system.

Key Points:

- **EC_{50} measures drug efficacy.**
- Used in **agonists** (activators) that **stimulate** a biological response.
- Typically measured in **in vitro experiments** (e.g., cell cultures, enzyme assays).

EC_{50} Graph (Dose-Response Curve):

- On an **x-axis (log[drug concentration]) vs. y-axis (biological effect %)** plot, EC_{50} is the **concentration where the curve reaches 50% of the maximum effect**.
- A **lower EC_{50}** indicates a **more potent** drug (requires less concentration to be effective).

Example:

- If **Drug A** has an EC_{50} of **1 μM** and **Drug B** has an EC_{50} of **10 μM** , then **Drug A is 10 times more potent than Drug B**.

1.1.2 What is IC_{50} (Inhibitory Concentration 50%)?

Definition:

IC₅₀ is the **concentration of a drug or inhibitor** required to **reduce a specific biological activity by 50%**.

Key Points:

- **IC₅₀ measures drug potency in inhibition** (e.g., enzyme inhibitors, receptor blockers).
- Used for **antagonists** (inhibitors) that **reduce** a biological response.
- Commonly used in **cancer drugs, enzyme inhibitors, and antibiotics**.

IC₅₀ Graph (Inhibition Curve):

- On a **log[drug concentration] vs. % inhibition** plot, IC₅₀ is the **concentration where the drug inhibits 50% of the target activity**.
- A **lower IC₅₀** means the **drug is more potent**.

Example:

- If an **anti-cancer drug** has an IC₅₀ of **2 nM**, it means **only 2 nanomolar concentration** is needed to inhibit **50% of cancer cell growth**.

Parameter	EC ₅₀ (Effective Concentration)	IC ₅₀ (Inhibitory Concentration)
Measures	Activation potency	Inhibition potency
Used for	Agonists (activators)	Antagonists (inhibitors)
Higher value means	Drug is weaker	Drug is weaker
Lower value means	Drug is more potent	Drug is more potent

1.1.3 What is LD₅₀ (Lethal Dose 50%)?

Definition:

LD₅₀ is the **dose of a substance that is lethal to 50% of a tested population** (e.g., animals in toxicity studies).

Key Points:

- **Measures drug toxicity.**
- Used in **toxicology and safety assessment**.
- Expressed in **mg/kg of body weight**.
- Typically determined in **animal models (e.g., mice, rats)** before human testing.

LD₅₀ Graph (Toxicity Curve):

- On an **x-axis (dose in mg/kg) vs. y-axis (% mortality)** plot, LD₅₀ is the **dose where 50% of the population dies**.

- A lower LD_{50} means a compound is **more toxic**.

Example:

- **Nicotine LD_{50} (mice):** ~3 mg/kg (highly toxic).
- **Caffeine LD_{50} (rats):** ~200 mg/kg (moderate toxicity).
- **Aspirin LD_{50} (rats):** ~1,000 mg/kg (low toxicity)

Parameter	Definition	What It Measures	Lower Value Means
EC_{50}	Effective Concentration 50%	Drug Efficacy (How well it works)	More potent
IC_{50}	Inhibitory Concentration 50%	Drug Inhibition Potency	More potent
LD_{50}	Lethal Dose 50%	Drug Toxicity	More toxic

- **EC_{50} and IC_{50}** are used in **drug activity studies** (therapeutic effects).
- **LD_{50}** is used in **toxicology** (safety assessment).
- **Lower EC_{50}/IC_{50} is better** (higher potency).
- **Lower LD_{50} is worse** (higher toxicity).

How Are These Values Used in Drug Discovery?

1. Optimizing Drug Potency

- A low **EC_{50} or IC_{50}** means a drug is **highly effective at a lower dose**.
- Example: Cancer drugs with **$IC_{50} < 1$ nM** are considered **very potent**.

2. Determining Safe Dosages

- LD_{50} helps define the **maximum tolerable dose** for clinical use.
- Example: **Therapeutic Index (TI)** is calculated as:

$$TI = \frac{LD50}{ED50}$$

- **Higher TI = Safer Drug**

3. Comparing Drug Candidates

- If **Drug A** has an **IC_{50} of 1 nM** and **Drug B** has **10 nM**, **Drug A is 10x more potent**.
- A drug with **low IC_{50} and high LD_{50}** is ideal (potent but not toxic).

Why Are EC₅₀, IC₅₀, and LD₅₀ Important?

- EC₅₀ measures how well a drug activates a biological response.
- IC₅₀ measures how well a drug inhibits a biological process.
- LD₅₀ measures how toxic a substance is.
- These values help in drug discovery, toxicity testing, and dose selection.

How QSAR Works

1. **Molecular structures** are converted into **numerical descriptors** (e.g., molecular weight, charge, shape, hydrophobicity).
2. **Mathematical models** correlate these descriptors with **biological effects**.
3. Once trained, the model can **predict** activity for new molecules.

Equation Example (Linear QSAR Model):

$$\text{Activity} = a_1X_1 + a_2X_2 + \dots + a_nX_n + b$$

where:

- $X_1, X_2, \dots, X_n$ = molecular descriptors (like logP, molecular weight).
- $a_1, a_2, \dots, a_n$ = coefficients (weights showing the effect of each descriptor).
- b = intercept (baseline activity).

Table 1.3 Various end points employed in predictive modeling analysis using (Q)SAR technique

Nature of end point	Representative examples
Activity	Antimalarial, antipsychotic, antioxidant, antiarrhythmic, antianginal, antihypertensive, anti-HIV, antidiuretic, antibacterial, anticholinergic, antiadrenergic, antihistaminic, antianxiety, antiepileptic, antiparkinsonian, antidepressant, analgesic, antipyretic, antiemetic, hypoglycemic, etc.
Property	Melting point, boiling point, vapor pressure, glass transition temperature, adsorption, rate of reaction, octanol/water partition coefficient, water solubility, molar refractivity, chromatographic retention data, biodegradation, hydrolysis, atmospheric oxidation, bioaccumulation, critical micelle concentration of surfactants, odor threshold of flavors, etc.
Toxicity	Acute fish toxicity, long-term aquatic toxicity, acute oral toxicity, acute inhalation toxicity, acute dermal toxicity, skin irritation/corrosion, eye irritation/corrosion, skin sensitization, toxicity due to repeated dose, genotoxicity, reproductive toxicity, developmental toxicity, carcinogenicity, organ toxicity, e.g., hepatotoxicity, cardiotoxicity, and nephrotoxicity, toxicity toward ecotoxicological indicator organisms, namely, algae (<i>Scenedesmus</i> , <i>Selenastrum</i> , etc.), daphnids, <i>Tetrahymena</i> , bacteria (<i>Vibrio</i> , <i>Escherichia</i> , etc.), yeast (<i>Saccharomyces</i>), etc.

1.2 Historical Aspects (Page 36 onwards in Roy, Kar and Das)

The concept of **structure-activity relationships (SAR)** has existed for centuries, but QSAR as a **quantitative method** emerged in the **mid-20th century**. QSAR has evolved through several phases:

1. **Empirical observations (Pre-1900s) –**
 - Scientists noticed that similar molecules often have similar effects (e.g., poisons, drugs).
 - Example: Early chemists realized that opioid drugs (morphine, codeine) share structural similarities.
 2. **The Hansch Era (1960s-1980s) –**
 - Corwin Hansch pioneered the use of mathematical equations to **relate chemical structure to biological activity**.
 - **Corwin Hansch (1964)**: Introduced the first **formal QSAR equations**, using **linear regression to correlate molecular properties with activity**.
 - **Free-Wilson (1968)**: Proposed a **different approach** using **structural features instead of molecular properties**.
 3. **Expansion of QSAR (1980s-2000s) –**
 - Methods like **Free-Wilson analysis, molecular descriptors, and statistical modeling** became widely used.
 4. **Machine Learning Revolution (2000s-Present) –**
 - AI-driven techniques (neural networks, random forests) now dominate QSAR, improving predictive accuracy.
 - **Machine learning models (Random Forest, Deep Learning)** replaced older statistical QSAR models.
 - **Big Data & AI** allow QSAR models to predict activity for **millions of compounds** in drug discovery.
-

Early QSAR Methods

1.3 Hansch Analysis

Hansch analysis is one of the first formal QSAR methods. It mathematically relates **physicochemical properties** (like lipophilicity, polarity, electronic properties) to biological activity.

>> **Analogy**: Imagine designing a **parachute**—its effectiveness depends on the **weight of the person (mass)**, **air resistance (surface area)**, and **gravity**. Similarly, drug activity depends on **molecular weight, polarity, and hydrophobicity**.

Key Descriptors Used in Hansch Analysis

1. **Lipophilicity (LogP)**: Measures how fat-soluble a molecule is.
 - **Higher LogP** → More likely to pass through cell membranes.
 - **Too high LogP** → Stays in fat, doesn't dissolve in blood.

2. **Electronic Effects (σ , Hammett Substituent Constant):** Measures how electrons are distributed.
 - **Affects molecular reactivity & binding to proteins.**
3. **Steric Factors (Molar Refractivity, Verloop Parameters):** Measures molecular size and shape.
 - **Affects binding to target proteins.**

Hansch QSAR Equation Example:

$$\log(\text{Activity}) = a(\log P) + b(\sigma) + c(S) + d$$

where:

- **a, b, c** = regression coefficients.
- **logP** = lipophilicity descriptor (partition coefficient between octanol and water).
- **σ** = electronic descriptor (Hammett sigma constant).
- **S** = steric descriptor (size and shape descriptors).

Strength: Can predict activity for **chemically similar molecules**.

Weakness: Doesn't work well for **structurally diverse compounds**.

Hansch QSAR models work well for congeneric series of molecules (molecules with the same scaffold but different functional groups).

1.4 Free-Wilson Analysis

While Hansch analysis focuses on **physicochemical properties**, **Free-Wilson analysis** focuses on **specific molecular features** (functional groups).

Instead of using **logP**, **steric**, or **electronic factors**, Free-Wilson analysis **treats each functional group as a variable**.

It assumes that **each functional group contributes independently to activity**.

>> **Analogy:** Think of it like rating the ingredients in a recipe. If adding a **spicy chili pepper** always makes food **spicier**, you can mathematically determine its contribution. Similarly, Free-Wilson analysis identifies which molecular groups enhance or reduce activity.

Free-Wilson Equation: $\text{Activity} = a_1X_1 + a_2X_2 + a_3X_3 + \dots + b$

where **X_1 , X_2 , X_3** are **binary variables** (1 if a group is present, 0 if absent).


X_i = Presence or absence of specific functional groups (binary descriptors: 1 = present, 0 = absent).

a_i = Contribution of that functional group to biological activity.

b = Baseline activity.

Strength: Works for **structurally diverse molecules**.

Weakness: Doesn't account for **interactions between groups**.



(Page 52 in Roy, Kar and Das; Types of Descriptors on Page 53)

2. Understanding QSAR Design

2.1 SAR vs. QSAR

- **SAR (Structure-Activity Relationship)** is a **qualitative** approach (i.e., "this type of structure tends to be active").
- **QSAR (Quantitative SAR)** goes further by assigning **numerical values** to these relationships.

>> **Analogy:** SAR is like saying, "**Spicy food often contains chili.**" QSAR is like saying, "**The Scoville heat index of a chili correlates with spiciness.**"

2.1.1 What is SAR (Structure-Activity Relationship)?

SAR is the qualitative study of how the structural features of a molecule influence its biological activity. It helps chemists understand which parts of a molecule are responsible for enhancing or reducing activity.

Key Features of SAR:

- Qualitative approach: No mathematical model, just observational trends.
- Empirical analysis: Based on experimental data and chemical intuition.
- Fragment-based insights: Helps in identifying essential functional groups for activity.
- Used in lead optimization: Helps modify molecular structures to improve potency.

Example of SAR in Drug Discovery:

- Beta-lactam antibiotics: The beta-lactam ring is essential for antibacterial activity. Modifying the side chains affects potency and resistance.
- NSAIDs (Aspirin, Ibuprofen, etc.): The carboxyl (-COOH) group is critical for inhibiting cyclooxygenase (COX) enzymes.

2.1.2 What is QSAR (Quantitative Structure-Activity Relationship)?

QSAR is a mathematical and statistical extension of SAR, aiming to quantify the relationship between a molecule's structural features and its biological activity using numerical descriptors.

Key Features of QSAR:

- Quantitative approach: Uses mathematical models and statistical analysis.
- Computational methods: Relies on regression models, machine learning, and artificial intelligence.
- Predictive modeling: Can forecast the activity of new molecules before synthesis.
- Multivariate analysis: Considers multiple structural factors simultaneously.

Example of QSAR Equation:

$$\log(1/C) = a(\log P) + b(\sigma) + c(E_s) + d$$

Where:

- $\log(1/C)$ = Activity (inverse of concentration needed for effect).
- $\log P$ = Lipophilicity descriptor.

- σ = Electronic descriptor.
- E_s = Steric descriptor.
- a, b, c, d = Regression coefficients.

Feature	SAR (Structure-Activity Relationship)	QSAR (Quantitative Structure-Activity Relationship)
Nature	Qualitative	Quantitative
Approach	Observational and empirical	Mathematical and statistical
Complexity	Simple (focuses on functional groups)	More complex (involves multiple descriptors)
Prediction	No predictive ability	Can predict activity of new molecules
Mathematical Model	None	Regression, Machine Learning, AI-based models
Computational Tools	Not required	Uses ML, AI, statistical methods
Application	Drug design, lead optimization	Virtual screening, activity prediction
Limitations	No precise prediction, subjective	Requires extensive datasets, computational resources

2.2 Designing QSAR Experiments

To build a reliable QSAR model, we need a **carefully designed dataset**.

Key Steps in QSAR Experiment Design

1. **Select a Diverse Chemical Dataset**
 - Ensure molecules **cover a wide range of activity values**.
2. **Compute Molecular Descriptors**
 - Use **Hansch (physicochemical)** or **Free-Wilson (structural features)**.
3. **Build a QSAR Model**
 - **Linear Regression (Simple QSAR)**
 - **Machine Learning (Random Forest, Deep Learning)**
4. **Validate the Model**
 - **Cross-validation** (splitting data into training & test sets).
 - **R^2 , RMSE, p-value** to check model performance.

>> **Analogy:** Think of it as **training a dog** to recognize objects. You first show it examples (training set), identify distinguishing features (descriptors), test its recognition (modeling), and validate it with new objects.

3. QSAR Methodologies

3.3 QSAR Methodology

QSAR models require:

- **Data preprocessing** – Standardizing chemical structures.
 - **Feature selection** – Choosing important molecular descriptors.
 - **Mathematical modeling** – Using regression or AI to correlate structure and activity.
 - **Validation** – Checking how well predictions work.
-

3.4 Deriving Equations

Once molecular descriptors are chosen, QSAR models use different **mathematical techniques** to derive predictive equations:

3.4.1 Simple Linear Regression (SLR) – Basic equations like

$$\text{Activity} = a * \text{Descriptor} + b.$$

3.4.2 Multiple Linear Regression (MLR) – Handles multiple descriptors:

Multiple Linear Regression (MLR) is a statistical method used in QSAR to find a linear relationship between molecular descriptors and biological activity.

$$Y = a_1X_1 + a_2X_2 + a_3X_3 + \dots + a_nX_n + C$$

Where:

- Y = Biological activity (e.g., IC_{50} , logP, binding affinity).
- $X_1, X_2, X_3, \dots, X_n$ = Molecular descriptors (e.g., logP, molecular weight, number of H-bond donors).
- a_1, a_2, a_3 = Regression coefficients (weights assigned to each descriptor).
- C = Constant.

Example of MLR in QSAR:

For a series of benzodiazepine derivatives, a QSAR equation could be:

$$\log(1/IC_{50})=1.25\log P-0.65HBD+2.10$$

This means:

- Higher lipophilicity (logP) **increases** activity.
- More hydrogen bond donors (HBD) **decrease** activity.

Steps to Build an MLR Model in QSAR:

1. **Collect** data (chemical structures + biological activity).
2. Calculate molecular **descriptors** (logP, molecular weight, etc.).
3. Use MLR to fit a **model** using least squares regression.
4. **Validate** the model (R^2 , p-values, residual analysis).
5. **Interpret** the QSAR equation to understand which factors influence activity.

Advantages of MLR:

- Simple and easy to interpret.
- Works well for small datasets.
- Can reveal the contribution of each descriptor to activity.

Limitations of MLR:

- Assumes a linear relationship, which may not always be valid.
- Multicollinearity issue (correlated descriptors reduce accuracy).
- Overfitting risk when using too many descriptors.

3.4.3 Principal Component Analysis (PCA) – Reduces redundant descriptors.

Principal Component Regression (PCR) is an advanced form of regression that combines **Principal Component Analysis (PCA)** with **MLR** to handle **high-dimensional** and **correlated descriptors**.

Why Use PCR Instead of MLR?

- In QSAR, many descriptors are **correlated** (multicollinearity problem).
- PCR reduces the dataset into **Principal Components (PCs)** that are uncorrelated.
- Then, **MLR is applied** to these PCs instead of the original descriptors.

Steps in PCR:

1. Compute **Principal Components (PCs)** from molecular descriptors.
2. Retain the **top PCs** that explain most of the variance.
3. Perform **MLR on these PCs** instead of raw descriptors.

Advantages of PCR:

- Solves **multicollinearity** problems.
- Handles **large datasets with many descriptors**.
- Reduces noise in the data.

Limitations of PCR:

- PCs **lack physical meaning**, making interpretation harder.
- **Loss of information** if too few PCs are selected.

3.4.4 Partial Least Squares (PLS) – Handles correlated descriptors efficiently.

- **Partial Least Squares (PLS) Regression** is a **multivariate statistical technique** that finds the relationship between **molecular descriptors** and **biological activity**, while **reducing dimensionality** like PCR.

Why is PLS Used in QSAR?

- Handles **high-dimensional, correlated descriptors** better than MLR.
- Maximizes the **correlation between descriptors and activity**.
- Used in **CoMFA & CoMSIA (3D-QSAR methods)**.

Feature	MLR	PCR	PLS
Handles Multicollinearity?	✗ No	✓ Yes	✓ Yes
Dimensionality Reduction?	✗ No	✓ Yes (uses PCA)	✓ Yes
Interpretation	✓ Easy	✗ Difficult (PCs are abstract)	✓ Moderate
Application in QSAR	✓ Basic models	✗ Rarely used	✓ CoMFA, CoMSIA, 3D-QSAR

Steps in PLS Regression:

1. Compute **latent variables (LVs)** that explain both **descriptor variation** and **activity variation**.
2. Fit a **linear regression model** using these latent variables.
3. Perform **cross-validation** to ensure predictability.

PLS is commonly used in 3D-QSAR (e.g., **Comparative Molecular Field Analysis (CoMFA)**).

Advantages of PLS:

- Works well for **high-dimensional, correlated data**.
- More **interpretable** than PCR.
- More **robust** than MLR.

Limitations of PLS:

- Complex compared to MLR.
- Requires careful **parameter tuning** (number of latent variables).

3.4.5 Genetic Algorithms (GA) – Uses **evolutionary selection** to find the best QSAR equation.

>> **Analogy:** Finding the best pizza recipe by testing different ingredients (descriptors) and keeping only the ones that contribute to taste (biological activity).

A **Genetic Algorithm (GA)** is an **evolutionary optimization method** inspired by **natural selection** (Darwin's theory of evolution). It finds the **optimal set of features (molecular descriptors)** that maximize the accuracy of a QSAR model.

Why is GA Used in QSAR?

- QSAR datasets often contain **hundreds or thousands of molecular descriptors**.
- Many descriptors are **irrelevant or redundant**, leading to **overfitting**.
- GA **selects the most important descriptors**, improving model accuracy and interpretability.

Key Concepts of GA in QSAR:

GA mimics the **biological evolution** process, involving:

1. **Population:** A set of possible solutions (each solution is a subset of descriptors).
2. **Chromosome Representation:** Each individual solution (set of selected descriptors) is encoded as a **binary string** (1 = selected, 0 = not selected).
3. **Fitness Function:** A mathematical function used to evaluate the **quality of each solution** (e.g., R^2 , Q^2 in QSAR models).
4. **Selection:** The best solutions (high fitness) are chosen for reproduction.
5. **Crossover (Recombination):** Two selected solutions exchange some of their descriptors (genes) to create new solutions.
6. **Mutation:** Random changes in some descriptors to introduce diversity.
7. **Evolution:** The process repeats over several generations, gradually improving the solution.

Step 1: Generate Initial Population

- Each **chromosome (solution)** represents a **subset of molecular descriptors**.
- Each **gene (bit in the chromosome)** represents a descriptor (1 = selected, 0 = ignored).

Example:

Chromosome: 1 0 1 1 0 1 0 1 0 0

| | | | | | | | | |

Descriptor: D1 D2 D3 D4 D5 D6 D7 D8 D9 D10

- Here, **D1, D3, D4, D6, and D8** are selected for the QSAR model.

Step 2: Compute Fitness Function

- Each chromosome (subset of descriptors) is used to train a **QSAR model** (MLR, PLS, RF, etc.).
- The **fitness score** is computed based on **model performance** (e.g., R^2 , Q^2 , RMSE).
- A **higher fitness score** means the descriptors are **more relevant**.

Step 3: Selection (Natural Selection)

- The best-performing solutions (high fitness) are **selected for crossover**.
- Methods: **Roulette Wheel Selection, Tournament Selection**.

Step 4: Crossover (Recombination of Features)

- Two selected solutions **swap some of their descriptors** to create **new solutions**.

Example:

Parent 1: 1 0 1 1 0 1 0 1 0 0

Parent 2: 0 1 0 1 1 0 1 0 1 1

Offspring: 1 0 0 1 1 1 1 0 0 1

- The offspring has a **mix of features** from both parents.

Step 5: Mutation (Adding Randomness)

- Randomly flip **some genes (bits)** to explore **new feature combinations**.
- Ensures **diversity in the population** to avoid local optima.

Step 6: Generate New Population & Repeat

- The process is repeated over **multiple generations** until the **best set of descriptors** is found.

Advantages

- **Efficient Descriptor Selection:** Finds the best subset of descriptors automatically.
- **Handles Large Datasets:** Can process hundreds of molecular descriptors.
- **Avoids Overfitting:** Reduces noise by selecting only the most relevant descriptors.
- **Flexible:** Works with MLR, PLS, SVM, Random Forest, Deep Learning.

Limitations

- **Computationally Expensive:** Needs many iterations to converge.
- **Stochastic Process:** Results may vary in different runs.
- **Parameter Sensitivity:** Requires careful tuning of mutation/crossover rates.

Feature Selection Method	How It Works	Best For
Correlation Analysis	Removes highly correlated descriptors	Small datasets
Principal Component Analysis (PCA)	Reduces dimensionality by transforming variables	When interpretation is less important
Recursive Feature Elimination (RFE)	Iteratively removes less important features	Regression-based models
Genetic Algorithm (GA)	Evolves the best descriptor subset using fitness optimization	Large, complex datasets

GA is superior when there are many correlated descriptors or unknown interactions

QSAR Method	Best For	When to Use?
MLR (Multiple Linear Regression)	Small datasets	When descriptors are not correlated
PCR (Principal Component Regression)	Dimensionality reduction	When many descriptors are correlated
PLS (Partial Least Squares Regression)	Complex QSAR models	When many descriptors affect activity
Ridge/Lasso Regression	Feature selection	When too many descriptors exist

Finally, we would like to comment that by the use of suitable computer programs, it is possible to carry out various molecular modeling operations in a more rational and reliable way, eliminating possible sources of error. Using an efficient computer facility, a large

amount of data can easily be processed in a short period of time. However, remember that computers do not and cannot replace any chemical experimentation or synthesis methodology; rather, it promotes molecular modeling analysis by providing a suitable platform to the experimental results toward the design and development of a desired, better chemical entity.

3.5 Selection of Diverse Sets

Choosing a diverse dataset prevents bias. Methods include:

- **Clustering Analysis** – Grouping molecules by similarity.
- **Dissimilarity-based algorithms** – Ensuring all chemical classes are represented.

>> **Analogy:** If you're training a model to recognize animals, you don't want only dogs—you need cats, birds, and fish for a general model!

3.6 Introduction to Machine Learning for QSAR

Machine learning enhances QSAR predictions. Popular methods:

1. **Neural Networks (Deep Learning)** – Mimics brain neurons to learn patterns.
2. **Random Forest (RF)** – Uses multiple decision trees to avoid overfitting.
3. **Support Vector Machines (SVM)** – Finds the best boundary between active and inactive compounds.
4. **Deep Learning Platforms (e.g., PyTorch)** – Used for advanced QSAR modeling.

>> **Analogy:** Imagine training a self-driving car. Traditional QSAR is like rule-based driving, while ML-based QSAR is like a Tesla learning from road data!

4. Validating QSAR Models

4.1 Validating QSAR & ML Models

Validation ensures predictions are **reliable and generalizable**. Techniques include:

- **Cross-validation** – Splitting data into training and test sets.
- **External validation** – Testing with completely new molecules.
- **Statistical metrics** – R^2 (correlation), RMSE (error), etc.

>> **Analogy:** Think of QSAR validation like **testing a student**—you don't just check if they memorized answers but whether they can apply concepts to new problems.

4.2 Applicability Domain

Even the best QSAR model **has limits**—it may not work for molecules outside the trained dataset. Defining an **applicability domain** prevents misleading predictions.

>> **Analogy:** If you train a chess AI on beginner games, it won't perform well against grandmasters! Similarly, QSAR must be **trained on a wide range of molecules** to generalize well.

5. Basic Chemistry for QSAR

5.1 What is a Molecule?

A molecule is a group of atoms bonded together. The **type** and **arrangement** of these atoms determine the molecule's properties—just like the ingredients and their proportions determine the taste of a dish.

>> **Analogy:** Imagine molecules as LEGO structures. Different pieces (atoms) snap together in specific ways to form unique shapes (molecules), and their structure dictates how they interact with the world.

5.2 Functional Groups

Functional groups are specific **clusters of atoms** within a molecule that define its **chemical behavior**.

>> **Analogy:** Think of functional groups like “power-ups” in a video game. Each power-up (functional group) gives a character (molecule) a special ability:

- **Hydroxyl (-OH)** → Makes molecules more water-friendly (like sugar dissolving in water).
- **Carboxyl (-COOH)** → Adds acidity (like vinegar).
- **Amino (-NH₂)** → Helps form proteins (like LEGO connectors in biology).

Functional groups influence:

- **Lipophilicity (LogP):** Determines if a molecule prefers **fat or water**.
- **Polarity:** Affects **solubility and membrane permeability**.
- **Reactivity:** Determines how a molecule interacts with enzymes.

>> **Deep Analogy:**

Think of **functional groups** as **USB connectors** in electronics. A **USB-C** port only connects

with certain chargers, just like a **hydroxyl (-OH)** group makes molecules **water-soluble** and helps them bind to certain proteins.

5.3 Chemical Properties in QSAR

When we build QSAR models, we use **chemical descriptors**—numerical values representing molecular properties. The key ones are:

1. **Lipophilicity (LogP)** – Measures how much a molecule likes fat vs. water.
 - High LogP = Fat-soluble (stays in cell membranes, like oily vitamins).
 - Low LogP = Water-soluble (easily dissolves in blood).
 2. **Molecular Weight (MW)** – Larger molecules may not fit into biological targets.
 3. **Electronic Properties (Dipole Moment, Partial Charges)** – Affects how molecules interact with charged surfaces (like proteins).
 4. **Topological Indices** – Describe molecular shape and branching.
-

6. Statistics & Regression for QSAR

To build QSAR models, we need to understand **how to find patterns in data**. This is where statistics and regression come in.

6.1 What is Regression?

Regression finds relationships between variables—like how molecular weight affects drug activity.

>> **Analogy:** Imagine you're trying to predict **ice cream sales** based on **temperature**. You collect data:

- On hot days, ice cream sales are high.
- On cold days, sales are low.

Regression fits a mathematical equation that captures this pattern:

$$\text{Sales} = m \times \text{Temperature} + b$$

where:

- m is the slope (how much sales increase per degree of temperature).
- b is the baseline sales when it's freezing outside.

Now, let's apply this idea to **QSAR**:

$$\text{Activity} = a_1(\text{LogP}) + a_2(\text{MW}) + a_3(\text{Charge}) + b$$

This equation predicts how **biological activity** changes with molecular properties.

6.2 Multiple Linear Regression (MLR)

When we consider **more than one variable**, we use **Multiple Linear Regression (MLR)**:

$$Y = a_1X_1 + a_2X_2 + \dots + a_nX_n + b$$

>> **Analogy:** If you want to predict **house prices**, you'd use factors like:

- Size (sq ft)
- Number of bedrooms
- Distance to a school

Each factor contributes differently, just like **molecular descriptors** contribute to QSAR models.

6.3 Key Statistics for QSAR

To check if a model is good, we use:

1. **R² (Correlation Coefficient)** – Measures how well the model explains the data (closer to 1 is better).

$$R^2 = 1 - \frac{\sum (y_{\text{actual}} - y_{\text{predicted}})^2}{\sum (y_{\text{actual}} - \bar{y})^2}$$

R² (coefficient of determination) tells us how much variation in the data is explained by the model, but it doesn't directly represent statistical significance.

- **R² = 0.85** means **85% of the variation** in biological activity is explained by the molecular descriptors in the QSAR model.
- **The remaining 15%** comes from unknown factors, noise, or missing descriptors.

>> **Deep Analogy:**

Think of a **weatherman predicting rain**. If **R² = 0.85**, his predictions are **85% accurate**, but **15% of the time, it might rain unexpectedly** due to factors he didn't account for.

A very high **R²** (close to 1) might indicate **overfitting**—the model is memorizing training data instead of finding general patterns.

- If **R²** is too high, the model may **fit noise instead of true relationships**.
- A good model should also work well on **new, unseen data** (not just the training set).

- **Cross-validation** helps check if the model is generalizable.
2. **p-value** – Tells us if a variable significantly contributes to predictions.
 3. **RMSE (Root Mean Squared Error)** – Measures how much error is in the predictions.

>> **Analogy:** Think of R^2 as a **teacher grading a student's work**:

- $R^2 = 1.0$ → The student gets all answers right.
 - $R^2 = 0.5$ → The student is right half the time.
 - $R^2 = 0.1$ → The student is mostly guessing.
-

7. Machine Learning Basics for QSAR

Traditional QSAR uses linear regression, but **Machine Learning (ML)** can handle complex, nonlinear relationships better.

7.1 What is Machine Learning?

Machine Learning is a way for computers to learn patterns from data **without being explicitly programmed**.

>> **Analogy:** Imagine teaching a child to recognize dogs. Instead of giving step-by-step rules, you show them thousands of pictures, and they gradually learn to distinguish dogs from other animals.

7.2 Types of Machine Learning in QSAR

1. Decision Trees & Random Forests

- **Decision Trees** ask yes/no questions to classify molecules (e.g., “Does it contain -OH?” → “Is LogP > 3?”).
- **Random Forests** improve accuracy by combining multiple trees.

>> **Analogy:** A decision tree is like a **medical diagnosis tool**:

- “Do you have a fever?” → Yes → “Do you have a cough?” → Yes → **Flu**.

Random Forest is an ensemble of decision trees, reducing **overfitting** and improving **stability**.

Further Clarification:

- A single decision tree can **memorize noise** in data (overfitting).

- **Random Forest builds multiple trees**, averaging their predictions to get a more **generalizable** result.

>> **Deep Analogy:**

Imagine asking **100 doctors** for a diagnosis instead of just **one**. A single doctor might be biased, but **100 doctors voting** will give a more reliable diagnosis—this is how **Random Forest stabilizes predictions**.

2. Neural Networks & Deep Learning

Neural networks **mimic the brain** using layers of artificial neurons.

>> **Analogy:** Think of it as **teaching a self-driving car**. It processes images, detects objects, and learns patterns over time—just like QSAR models learn molecular features.

3. Support Vector Machines (SVM)

SVMs find the best **boundary** between active and inactive molecules.

>> **Analogy:** Imagine separating cats and dogs based on features like weight and fur length. SVMs draw the best line to separate them.

Q. What is one potential **weakness** of Random Forest compared to Deep Learning models in QSAR?

- **Random Forest is limited in capturing very complex, nonlinear relationships, whereas Deep Learning can model intricate patterns better. Random Forest is robust, but Deep Learning models capture deeper relationships.**
- **Random Forest** averages decision trees, making it **robust but less flexible**.
- **Deep Learning (Neural Networks)** can learn **subtle, nonlinear interactions** that Random Forest might miss.
- However, **Deep Learning requires more data and computational power**.
- **Deep Analogy:** Imagine **Random Forest as a team of experienced doctors** making decisions based on simple yes/no questions. They do well for most cases but might miss rare, complex diseases. Deep Learning is like **a cutting-edge AI doctor** that scans **millions of patient records** to detect subtle disease patterns humans can't see.

7.3 Why Machine Learning is Useful for QSAR

- Handles **nonlinear relationships** better than regression.
- Can process **thousands of molecular descriptors**.
- Improves **predictive accuracy** for drug discovery.

>> **Analogy:** Think of ML-based QSAR as **Netflix recommendations**—it finds patterns in what people like and predicts new movies they'll enjoy.

Traditional QSAR models (like **Multiple Linear Regression**) assume that molecular properties and biological activity have **simple linear relationships**. But in reality:

- Some molecular features interact **non-linearly**.
- Some descriptors are **redundant or irrelevant**.
- Some **patterns are too complex** for simple math to capture.

This is where **machine learning (ML) methods** shine—they detect **hidden patterns** in chemical data **without assuming linearity**.

8. PCA & PLS: Reducing Feature Complexity

Before applying ML, we often have **too many molecular descriptors**. Many of them are redundant. **PCA and PLS help reduce this complexity**.

8.1 Principal Component Analysis (PCA)

Goal: Reduce high-dimensional data while preserving important information.

>> **Analogy:** Imagine you have a **100-question personality test**, but only a few questions truly define your character. PCA finds the **few most informative questions** and summarizes the rest.

How it Works Mathematically:

- PCA finds **new axes (principal components)** that capture the most variance.
- Each new axis is a **weighted combination of original descriptors**.
- The **first principal component (PC1)** explains the most variance, **PC2 explains the second most**, etc.

Key Formula:

Each new variable (PC) is a linear combination of original descriptors:

$$PC1 = w_1X_1 + w_2X_2 + \dots + w_nX_n$$

where **weights (w)** are chosen to maximize variance.

Why PCA? Helps remove redundant descriptors, making ML models more efficient.

8.2 Partial Least Squares (PLS)

PCA reduces dimensionality **without looking at biological activity**. But in QSAR, we want to **find patterns that relate structure to activity**—that's where **PLS** comes in.

>> **Analogy:** If PCA is like summarizing a **personality test**, PLS is like summarizing **a test that predicts job performance**—it selects features that best correlate with the outcome.

How it Works Mathematically:

- Like PCA, PLS finds **new axes** (components).
- But instead of just maximizing variance, it **maximizes correlation with biological activity**.
- This is done by **computing covariance** between molecular descriptors and biological activity.

PLS Equation: $Y = a_1C_1 + a_2C_2 + \dots + a_nC_n$

where **C** are the principal components that best correlate with activity **Y**.

Why PLS? If you have **highly correlated descriptors** (like molecular weight and atom count), PLS prevents redundancy.

9. Support Vector Machines (SVM)

Goal: Find the best boundary to separate active vs. inactive molecules or predict continuous values.

>> **Analogy:** Imagine separating **cats vs. dogs** based on weight and ear shape. **SVM** finds the **best line (or plane) that maximally separates the groups**.

9.1 SVM for Classification (QSAR Applications)

- Each molecule is represented as a **point in high-dimensional space**.
- **SVM finds the hyperplane that maximizes the margin between active and inactive molecules**.
- Some points (support vectors) define this boundary.

SVM Equation for Classification:

$$wX + b = 0$$

where:

- **w** = weight vector (defines direction of separation).
- **b** = bias (offset).
- The **goal is to maximize the margin** (distance between classes).

Why SVM? Works well when QSAR data is **high-dimensional** and **non-linearly separable**.

10. Random Forest (RF): Ensemble Learning for QSAR

Goal: Use multiple decision trees to make robust QSAR predictions.

>> **Analogy:** If **one doctor diagnoses** a patient, he might make a mistake. If **100 doctors** vote on a diagnosis, the majority decision is more reliable.

10.1 How Random Forest Works

- Creates **multiple decision trees**, each trained on a **different random subset** of data.
- **Each tree makes a prediction**, and the final result is the majority vote (classification) or average (regression).
- This reduces **overfitting**, which happens when a single tree memorizes the data too well.

Why Random Forest? Handles **missing data** well, works on **both small and large datasets**, and is robust.

11. Neural Networks & Deep Learning for QSAR

Goal: Capture **complex, nonlinear relationships** between **molecular structure** and **biological activity**.

>> **Analogy:** If traditional QSAR is like a **simple recipe book**, deep learning is like a **chef who learns new recipes by tasting food and adjusting flavors**—it continuously refines its model.

11.1 How Neural Networks Work

- Composed of **layers of neurons** that transform input data.
- **Hidden layers extract complex patterns** from molecular descriptors.
- **Backpropagation** adjusts weights to minimize prediction error.

Neural Network Equation (for one neuron):

$$Y=f(w_1X_1+w_2X_2+\dots+w_nX_n+b)$$

where **f** is a nonlinear activation function (like ReLU or Sigmoid).

11.2 Deep Learning Platforms (PyTorch, TensorFlow)

- **PyTorch & TensorFlow** allow training deep QSAR models efficiently.
- Can use **convolutional neural networks (CNNs)** for molecular fingerprints.
- Can train on **large chemical datasets** (e.g., **PubChem, ChEMBL**).

Why Deep Learning? Best for **large datasets** and highly **nonlinear** QSAR problems.

12. Genetic Algorithms (GA): Evolving QSAR Models

Goal: Find the best QSAR equation using an evolutionary approach.

>> **Analogy:** Imagine designing the perfect **sports car**. Instead of building random cars, you **evolve designs** by selecting the best ones, mutating features, and improving each generation.

12.1 How Genetic Algorithms Work

- Start with **random QSAR equations**.
- **Select the best ones** (highest predictive accuracy).
- Apply **mutation (small changes)** and **crossover (combine features of two models)**.
- Repeat for multiple generations until the best QSAR model is found.

Why GA? Helps **optimize QSAR equations** when the number of descriptors is too large for brute-force testing.

13. Choosing the Right ML Model for QSAR

- **PCA/PLS** → Feature selection & dimensionality reduction.
- **SVM** → Best for **small datasets** with clear decision boundaries.
- **Random Forest** → Best for **medium datasets** with complex but structured data.
- **Neural Networks** → Best for **big data** and highly **nonlinear** QSAR.
- **Genetic Algorithms** → Best for **optimizing feature selection & equations**.

14. Various Aspects of Validating QSAR and ML Models

Why is Validation Important?

A QSAR model is built using a dataset of known molecules, but its true test is whether it can **predict the activity of unseen molecules accurately**.

>> **Analogy:** Imagine training a student on **practice problems**. If they memorize the answers but fail the **final exam with new questions**, they haven't truly learned the concepts. Similarly, a QSAR model must generalize to new molecules, not just memorize the training data.

Key Validation Techniques in QSAR & ML

To ensure model reliability, we use the following validation techniques:

1. **Internal Validation** (How well does the model fit known data?)
2. **External Validation** (How well does it predict new data?)
3. **Statistical Validation** (What metrics measure model performance?)
4. **Applicability Domain** (For which molecules can the model be trusted?)

14.1 Internal Validation (Training Set Performance)

Before using a model, we check how well it fits the training data. Common techniques:

Cross-Validation (CV)

Instead of training on all data at once, we split the dataset into multiple parts and test on different subsets.

Most common type:

- **K-Fold Cross-Validation:** The dataset is split into K parts, and the model is trained K times, each time leaving out one part for testing.

>> **Analogy:** Imagine studying for an exam by practicing 10 different mock tests, each with different questions. If you do well on all, you're truly prepared.

If cross-validation R^2 scores vary a lot, the model is unstable and might be overfitting.

14.2 External Validation (Testing on New Data)

Even if a model performs well on the training set, it must be tested on **new, unseen data** to check its **generalization ability**.

Hold-Out Validation (Train-Test Split)

- The dataset is split into **training (80%)** and **testing (20%)**.
- The model is trained on **80%** and evaluated on the **remaining 20%**.

>> **Analogy:** If a student scores 100% on practice tests but fails a **real exam**, they were memorizing rather than understanding.

If **Train R^2 >> Test R^2** , the model **overfits** and is unreliable for new data.

14.3 Statistical Validation (Evaluating Model Quality)

Once the model is trained, we use statistical metrics to evaluate its performance.

Key Metrics for QSAR Models

1. **R^2 (Coefficient of Determination)**
 - Measures how well the model explains variance in activity.
 - **Good QSAR models have $R^2 > 0.6$.**
2. **RMSE (Root Mean Squared Error)**
 - Measures the **average error** in predictions.
 - Lower RMSE = **Better predictions**.
3. **Q^2 (Cross-validated R^2 score)**
 - Measures **predictive ability** in cross-validation.
 - **$Q^2 > 0.5$** is considered acceptable for QSAR models.
4. **p-Value (Statistical Significance of Descriptors)**
 - Determines if **molecular descriptors** are meaningful.
 - **$p < 0.05$** indicates that a descriptor significantly impacts activity.

A good QSAR model should have **high R^2 , low RMSE, and statistically significant descriptors**.

15. Applicability Domains

Even a well-validated model has **limitations**—it can only make reliable predictions for **certain types of molecules**. This is called the **Applicability Domain (AD)**.

- Validation ensures QSAR models are reliable (Cross-validation, Train-Test Split).
- Applicability Domains prevent unreliable predictions.
- If a molecule is too different from training data, the model's prediction is NOT trustworthy!

>> **Analogy:** Imagine a medical AI trained only on data from **young adults**—it might not work well for **elderly patients**. Similarly, a QSAR model trained on **small organic molecules** may not work for **large proteins**.

Methods to Define Applicability Domains

We use **three main techniques** to define a model's applicability domain:

1. Leverage Method (Distance from Training Data in Descriptor Space)

- Uses **Mahalanobis Distance** or **Hat Matrix** to check if a molecule is **too different** from training data.
- If a molecule's leverage value **exceeds a threshold**, the prediction is unreliable.
- If a molecule's leverage **exceeds the threshold**, the QSAR model **cannot make a reliable prediction** for it.

2. Descriptor Ranges (Ensuring Molecules Stay Within Training Data Bounds)

- Check if a molecule's **LogP, Molecular Weight, and TPSA** fall within the **min-max range** of the training dataset.
- If a molecule has **a much larger LogP or MW**, the model **cannot generalize**.
- If a molecule falls outside the **training descriptor range**, its prediction **cannot be trusted**.

3. Similarity-Based Approaches (Tanimoto Similarity, k-Nearest Neighbors)

- Compares a test molecule to the **most similar molecules** in the training set.
- If **no similar molecules exist**, predictions may not be accurate.
- A similarity score **below 0.5** means the molecule is **too different from training data**.

16. Types of QSAR:

16.1 Introduction:

QSAR (Quantitative Structure-Activity Relationship) refers to **a mathematical modeling approach that correlates the chemical structure of compounds with their biological activity**.

Basic QSAR Equation:

$$A=f(X_1,X_2,X_3,...,X_n)$$

where:

- A = Biological activity (e.g., IC_{50} , EC_{50} , K_i).
- $X_1,X_2,...,X_n$ = Molecular descriptors (e.g., LogP, molecular weight, electronic properties).

- f = Function determined using statistical regression or machine learning methods.

QSAR Type	Key Features	Example Applications
1D QSAR	Uses molecular properties like MW, LogP	Basic physicochemical analysis
2D QSAR	Uses topological and physicochemical descriptors	Drug discovery, toxicology
3D QSAR	Considers molecular shape and electrostatic fields	Protein-ligand interactions
4D QSAR	Adds conformational flexibility over time	Time-dependent QSAR
5D QSAR	Includes solvent effects	Drug absorption studies
6D QSAR	Includes protein binding dynamics	Molecular docking and pharmacodynamics

- **2D QSAR** works well for **small molecules**.
- **3D QSAR** is better for molecules that **bind to proteins**.
- **4D-6D QSAR** models **real-life biological environments** more accurately.

What is High-Order QSAR?

- **4D QSAR** = 3D QSAR + **conformational flexibility over time**.
- **5D QSAR** = 4D QSAR + **solvent effects**.
- **6D QSAR** = 5D QSAR + **protein flexibility**.

Why Use High-Order QSAR?

- More realistic **drug-receptor modeling**.
- Can model **biological environments** (e.g., enzyme binding).

17. QSAR vs. QSPR

What is QSPR (Quantitative Structure-Property Relationship)?

- **QSPR** predicts **physicochemical properties** (e.g., solubility, boiling point) based on structure.
- **QSAR** predicts **biological activity** (e.g., toxicity, drug effectiveness).

>> Analogy:

- **QSPR** is like predicting how fast a car can go based on its **engine power and weight**.
- **QSAR** is like predicting how well a **medicine** will work based on its **molecular structure**.

Mathematical Difference:

- **QSPR Equation:** $\text{Property} = a_1X_1 + a_2X_2 + \dots + a_nX_n + b$
- **QSAR Equation:** $\text{Activity} = a_1(\text{LogP}) + a_2(\text{MW}) + a_3(\text{TPSA}) + b$

Key Difference: QSPR predicts molecular properties; QSAR predicts biological activity.

18. 2D QSAR: Classical QSAR Methods

2D QSAR models use **mathematical relationships** between **molecular descriptors** and **biological activity**.

Linear Free Energy Relationships (LFER) Descriptors

LFER assumes **biological activity** is **proportional to physicochemical properties** like **hydrophobicity, electronic effects, and steric factors**.

Hansch QSAR Model Example:

$$\log(\text{Activity}) = a(\log P) + b(\sigma) + c(\text{Steric}) + d$$

where:

- **LogP** = Lipophilicity
- σ = Electronic effects
- **Steric** = Molecular size

Experimental vs. Theoretical Descriptors

- **Experimental:** Measured in the lab (e.g., solubility).
- **Theoretical:** Computed from structure (e.g., LogP via RDKit).

18.1 Statistical Parameters for QSAR Model Evaluation

18.1.1 Correlation Coefficient (R^2)

Measures how well the QSAR model fits the training data.

$$R^2 = 1 - \frac{\sum (y_{\text{actual}} - y_{\text{predicted}})^2}{\sum (y_{\text{actual}} - \bar{y})^2}$$

R^2 should be close to 1 for a good model.

18.1.2 Cross-Validated Correlation Coefficient (Q^2)

Used to test model **predictive power** using leave-one-out cross-validation (LOO-CV).

$$Q^2 = 1 - \frac{\sum (y_{\text{test}} - y_{\text{predicted}})^2}{\sum (y_{\text{test}} - \bar{y})^2}$$

$Q^2 > 0.5$ means the model has predictive value.

18.1.3 Standard Error of Estimate (SEE)

$$SEE = \sqrt{\frac{\sum (y_{\text{actual}} - y_{\text{predicted}})^2}{n - k - 1}}$$

Lower SEE means better model accuracy.

18.1.4 F-Test (F-Value)

Used to test the statistical significance of the QSAR equation.

$$F = \frac{R^2/k}{(1 - R^2)/(n - k - 1)}$$

		Predicted	
		0	1
Actual	0	TN	FP
	1	FN	TP

$$Accuracy = \frac{T_p + T_n}{T_p + T_n + F_p + F_n}$$

$$Precision = \frac{T_p}{T_p + F_p}$$

$$Recall = \frac{T_p}{T_p + T_n}$$

$$F_1 = 2 \cdot \frac{precision \cdot recall}{precision + recall}$$

Higher F-value means the model is statistically significant.

18.1.5 What is Bootstrapping?

- **Bootstrapping:** Tests model stability by resampling data multiple times.

Bootstrapping is a **resampling technique** used to estimate the **accuracy and stability** of a QSAR model by generating **multiple random datasets** from the original data. It helps in **assessing model variability** and **reducing overfitting**.

>> **Analogy:**

- Imagine you are trying to measure the **average weight of apples** in a basket. Instead of measuring all apples, you repeatedly **pick random subsets of apples** and calculate their average weight.
- If the average remains **consistent across samples**, your measurement is **reliable**.
- If the average fluctuates **widely across subsets**, the model is **unstable** and may be **overfitted** to the original data.

How Bootstrapping Works in QSAR?

1. **Random Sampling with Replacement**
 - A subset of data is randomly selected **with replacement**, meaning the same data points can appear multiple times.
2. **Model Training on Each Sample**
 - A QSAR model is trained on **each new dataset** and evaluated.
3. **Distribution of Model Predictions**
 - The performance of multiple models is analyzed **to estimate prediction uncertainty**.

$$SE_{\text{boot}} = \sqrt{\frac{1}{B} \sum_{i=1}^B (\theta_i - \bar{\theta})^2}$$

where:

- B = Number of bootstrap samples.
- θ_i = Model estimate from each bootstrap sample.
- $\bar{\theta}$ = Mean of all bootstrapped estimates.

Bootstrapped Confidence Interval (CI):

$$CI = \bar{\theta} \pm Z \times SE_{\text{boot}}$$

where **Z** is the **critical value** from a normal distribution (e.g., **1.96 for 95% confidence interval**).

Advantages of Bootstrapping in QSAR

- Helps detect **overfitting** in QSAR models.
- Estimates **confidence intervals** for predictions.
- Provides **model stability insights** across different datasets.

Disadvantages

- Computationally expensive for **large datasets**.
- Might not work well for **small datasets**.

18.1.6 What is Randomization Testing?

- **Randomization:** Checks if model performance is due to **chance**.

Randomization (also called **Y-randomization** or **permutation testing**) checks whether a **QSAR model captures real structure-activity relationships** or if the model is built by **chance**.

>> **Analogy:**

- Imagine a **student who memorized answers** to a test without understanding the concepts.

- To test if the student really understands, you **shuffle** the questions and answers.
- If the student **performs poorly**, it means they were just **memorizing** (overfitting).
- If the student still **performs well**, it means they **understand the material** (true correlation).

How Randomization Works in QSAR?

1. **Shuffle the Response Variable (Y-values)**
 - The **biological activity (Y-values)** are randomly shuffled across molecules.
2. **Re-train the QSAR Model**
 - A new QSAR model is built on the shuffled data.
3. **Compare Performance to the Original Model**
 - If the randomized model performs **similarly** to the real model, the original model is **invalid** (overfitting).

Key Metric for Y-Randomization:

$$Q^2_{\text{rand}} < Q^2_{\text{true}}$$

where:

- Q^2_{rand} = Cross-validation score from the randomized model.
- Q^2_{true} = Cross-validation score from the original model.

If $Q^2_{\text{rand}} \approx Q^2_{\text{true}}$, the QSAR model is unreliable.

Advantages of Y-Randomization in QSAR

- Detects **overfitted or chance-correlated** models.
- Ensures **statistical validity** of QSAR equations.
- Helps distinguish **true structure-activity relationships from artifacts**.

Disadvantages

- Does not guarantee a **causal** relationship, only **correlation**.
- Computationally expensive for **large datasets**.

When to Use These Methods?

- **Bootstrapping** is used to **assess prediction uncertainty**.
- **Y-Randomization** is used to **detect chance correlations**.

Final Takeaways:

- Bootstrapping helps check model robustness by resampling data.
- Randomization testing detects overfitting by shuffling biological activity values.

- Both techniques should be applied to ensure QSAR model validity.

Method	Purpose	How it Works	Key Interpretation
Bootstrapping	Checks stability and variability of model predictions	Creates random resampled datasets and evaluates model consistency	Large standard errors → Model is unstable
Randomization (Y-Shuffling)	Checks whether the model is overfitted	Shuffles biological activity values and retrains the model	Randomized $Q^2 \approx \text{True } Q^2 \rightarrow \text{Model is invalid}$

19. 3D QSAR: Molecular Shape-Based Models

3D QSAR takes **steric, electrostatic, and hydrophobic fields** into account.

Mathematical Representation of 3D QSAR

$$A = \sum a_i F_i + b$$

where:

- F_i = Molecular field descriptors (electrostatic, steric).
- a_i = Coefficients derived from Partial Least Squares (PLS).

3D QSAR is best suited for protein-ligand interactions.

20. 3D QSAR Methods

20.1 CoMFA (Comparative Molecular Field Analysis)

- Uses **3D steric and electrostatic fields** to model activity.
- Employs **Partial Least Squares (PLS)** regression.

$$A = \sum a_i F_i^{\text{steric}} + \sum b_i F_i^{\text{electrostatic}} + c$$

20.2 CoMSIA (Comparative Molecular Similarity Indices Analysis)

- Adds **hydrophobicity and hydrogen bonding** to CoMFA models.
- **More robust than CoMFA for diverse molecules.**

$$A = \sum a_i F_i^{\text{steric}} + \sum b_i F_i^{\text{electrostatic}} + \sum c_i F_i^{\text{hydrophobic}} + d$$

20.3 CoRIA (Comparative Residue Interaction Analysis)

- Predicts how molecules interact with protein residues.

20.4 COMBINE 3D QSAR

- Merges CoMFA with molecular docking.

20.5 AFMoC (Adaptation of Molecular Fields for Molecular Comparisons)

- **Hybrid between CoMFA and molecular docking.**
- Maps steric, electrostatic, and hydrogen-bonding fields onto protein-ligand complexes.

$$A = \sum a_i F_i^{\text{steric}} + \sum b_i F_i^{\text{electrostatic}} + \sum c_i F_i^{\text{hydrogen-bonding}} + d$$

- **Why Use AFMoC?**
 - **Better accuracy than CoMFA.**
 - **Can be used for protein-ligand binding analysis.**

21. High-Order QSAR: 4D to 6D QSAR

21.1 4D QSAR

- $A=f(X,C)$
- where **C** = Conformational changes over time.

21.2 5D QSAR

- $A=f(X,C,S)$
- where **S** = Solvent effects.

21.3 6D QSAR

- $A=f(X,C,S,P)$
- where **P** = Protein flexibility.
- **High-order QSAR is used in molecular docking and pharmacodynamics modeling.**