EXP.NO: 10

Develop an application to change the font and color of the text and display toast message when the user press the button

AIM:

To develop an Android application that allows the user to change the font and color of text displayed on the screen and display a Toast message when a button is pressed.

ALGORITHM:

1. Initialize the Android Application:

   o Set up a new Android project in Android Studio.

   o Create a MainActivity Java file for the main screen of the application.

2. Design the User Interface (UI):

   o In the XML layout file, add the following UI components: TextView: For displaying the text whose font and color will be changed.

   Button: To trigger the change in font and color, and show a Toast message.

   Spinner or Color Picker: To let the user choose a color (optional, or a simple button for a predefined color change).

   RadioButtons or a Dropdown Menu to select different font styles (optional).

3. Declare Variables:

   o Create references for the TextView, Button, Color Picker (if used), and Radio Buttons (if used to change font style).

   o Define variables for the font style, color, and the message to display in the Toast.

4. Set Event Listener for the Button:

o Set an OnClickListener for the Button. o Inside the onClick() method, write the logic to:

Change the font of the TextView based on the selected font style.

Change the color of the TextView based on the selected color.

Display a Toast message indicating the action has been performed.

5. Implement Font Style Changes:

o Change the TextView's font using setTypeface() to apply a selected font style (e.g., bold, italic).

o You can either use predefined styles (like Typeface.BOLD or Typeface.ITALIC) or let the user choose from a list of font styles.

6. Implement Color Change:

o Change the TextView's text color by using the setTextColor() method and applying the selected color (e.g., Color.RED, Color.BLUE, or a color from the Color Picker).

o If using a color picker or dropdown, get the selected color and set it on the TextView.

7. Show Toast Message:

o Display a Toast message to the user when the button is clicked, informing them that the text style or color has changed. You can also show a message like "Font and color changed!" or any other appropriate message.

8. End the Operation:

o After the changes are made, the application will display the updated TextView with the new font and color, and the Toast message will appear to provide feedback.

CODE:

```
<!DOCTYPE html>
<html lang="en">
```

```
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Font & Color Changer</title>

    <style>
        :root {
            --sidebar-color: #2c3e50;
            --accent: #3498db;
            --success: #27ae60;
        }

        body {
            font-family: 'Segoe UI', Tahoma, Geneva, Verdana, sans-serif;
            margin: 0;
            display: flex;
            height: 100vh;
            background-color: #eef2f3;
        }

        nav {
            width: 240px;
            background-color: var(--sidebar-color);
            color: white;
            padding-top: 20px;
        }

        nav h2 {
            text-align: center;
```

```
    border-bottom: 1px solid #444;
    padding-bottom: 10px;
}

.nav-link {
    display: block;
    padding: 15px 25px;
    color: #bdc3c7;
    cursor: pointer;
}

.nav-link:hover {
    background-color: #34495e;
    color: white;
}

main {
    flex: 1;
    padding: 30px;
}

.container {
    background: white;
    max-width: 600px;
    margin: auto;
    padding: 30px;
    border-radius: 12px;
}
```

```
select, button {
    padding: 12px;
    margin: 10px 0;
    width: 100%;
    border-radius: 6px;
    border: 1px solid #ccc;
}

button {
    background: var(--accent);
    color: white;
    font-weight: bold;
    cursor: pointer;
}

#textDisplay {
    margin-top: 20px;
    font-size: 24px;
    text-align: center;
}

/* Toast Style */
#toast {
    visibility: hidden;
    min-width: 200px;
    background-color: #333;
    color: white;
    text-align: center;
    border-radius: 6px;
```

```
        padding: 10px;
        position: fixed;
        bottom: 30px;
        left: 50%;
        transform: translateX(-50%);
    }

    #toast.show {
        visibility: visible;
        animation: fadein 0.5s, fadeout 0.5s 2s;
    }

    @keyframes fadein {
        from {bottom: 0; opacity: 0;}
        to {bottom: 30px; opacity: 1;}
    }

    @keyframes fadeout {
        from {opacity: 1;}
        to {opacity: 0;}
    }
  </style>
</head>

<body>

<nav>
  <h2>STYLE APP</h2>
  <a class="nav-link">Font & Color</a>
```

```
</nav>

<main>
  <div class="container">
    <h2>Change Font & Color</h2>

    <select id="fontStyle">
      <option value="normal">Normal</option>
      <option value="bold">Bold</option>
      <option value="italic">Italic</option>
    </select>

    <select id="colorStyle">
      <option value="black">Black</option>
      <option value="red">Red</option>
      <option value="blue">Blue</option>
      <option value="green">Green</option>
    </select>

    <button onclick="applyChanges()">Apply Changes</button>

    <div id="textDisplay">Sample Text</div>
  </div>
</main>

<div id="toast">Font and color changed!</div>

<script>
```

```
function applyChanges() {
    let font = document.getElementById("fontStyle").value;
    let color = document.getElementById("colorStyle").value;
    let text = document.getElementById("textDisplay");

    if (font === "bold") {
        text.style.fontWeight = "bold";
        text.style.fontStyle = "normal";
    } else if (font === "italic") {
        text.style.fontStyle = "italic";
        text.style.fontWeight = "normal";
    } else {
        text.style.fontWeight = "normal";
        text.style.fontStyle = "normal";
    }

    text.style.color = color;

    showToast();
}

function showToast() {
    let toast = document.getElementById("toast");
    toast.className = "show";
    setTimeout(() => { toast.className = toast.className.replace("show", ""); }, 2500);
}

</script>
```

</body>

</html>

OUTPUT:

Result:

An mobile application is developed in Android studio to change the font and color of the textand display toast message when the user presses the button..