

Growth Revibe Hostinger Deployment Guide

What this website needs on Hostinger

This website is a static Vite site with one PHP form handler:

- `public/contact-handler.php`

That means your Hostinger plan must support:

- normal website hosting
- PHP enabled for the domain
- a connected domain
- working email accounts for the domain

Emails used by the website

The current mail handler sends form submissions to:

- `business@grothervibe.com`
- `info@growthrevibe.com`

The sender address is currently:

- `business@grothervibe.com`

If you want to change those addresses later, edit these constants in:

- `public/contact-handler.php`

```
const RECIPIENTS = 'business@grothervibe.com, info@growthrevibe.com';  
const SENDER_EMAIL = 'business@grothervibe.com';
```

Before deployment

1. Build the website locally:

- `npm run build`

2. Confirm the final output folder is:

- `dist/`

3. Make sure `contact-handler.php` is uploaded to the live website root:

- `public\_html/contact-handler.php`

Hostinger deployment steps

1. Add or connect the domain

In Hostinger hPanel:

1. Go to `Websites`
2. Open the website dashboard
3. Connect the domain if it is not connected yet
4. If the domain is outside Hostinger, point DNS to Hostinger first

2. Create the email accounts

In Hostinger hPanel:

1. Go to `Emails`
2. Open the email plan for your domain
3. Create these mailboxes if they do not already exist:
 - `business@grothervibe.com`
 - `info@growthvibe.com`
4. Save the passwords safely

3. Confirm PHP is enabled

In Hostinger hPanel:

1. Go to `Websites`
2. Open `Dashboard`
3. Open `PHP Configuration`
4. Use a supported PHP version
5. Recommended:
 - PHP `8.2` or newer

4. Upload the website files

If using File Manager:

1. Go to `Websites`
2. Open `Dashboard`
3. Open `File Manager`
4. Open the domain `public\_html` folder

5. Delete the default files if needed
6. Upload the contents of `dist/` into `public\_html`
7. Upload `contact-handler.php` into `public\_html`

Important:

- upload the contents of `dist`
- do not upload the `dist` folder itself as a nested folder unless you want the site to open from `/dist`

5. Check the form endpoint path

The front end currently sends forms to:

- `./contact-handler.php`

That means:

- `index.html` and `contact-handler.php` must sit in the same live root level
- on Hostinger this should normally be `public\_html/`

6. Test both form flows

After upload, test:

1. Homepage inquiry form
2. Contact page inquiry form
3. Meeting request / availability form

Each should:

- show a success message
- send an email to the company inbox
- include the user details in formatted layout

What the email contains

Each email now includes:

- submission type
- submitted date and time
- name
- email

- phone
- company or business
- selected service
- budget
- source page URL
- project message

Availability request emails also include:

- selected appointment date
- selected appointment time
- appointment timezone
- readable date label
- readable time label
- readable timezone label

Important Hostinger note about PHP mail

The current website uses PHP ``mail()``.

This is the fastest way to deploy, but Hostinger recommends SMTP for better deliverability.

If emails go to spam or do not arrive reliably, the next upgrade should be:

- replace PHP ``mail()`` with authenticated SMTP using a library such as PHPMailer

Recommended SMTP values for Hostinger Email

If you later switch to SMTP, Hostinger's documented outgoing settings are:

- host: ``smtp.hostinger.com``
- SSL port: ``465``
- TLS/STARTTLS port: ``587``

You will also need:

- full mailbox email
- mailbox password

Final deployment checklist

- Domain connected to Hostinger
- Website files uploaded to `public\_html`
- `contact-handler.php` uploaded to `public\_html`
- PHP enabled
- Email accounts created
- Forms tested live
- Both company inboxes receiving messages
- Spam folder checked after first tests

If you want the strongest setup

Best long-term version:

1. Keep the current front-end forms
2. Replace the PHP `mail()` handler with SMTP authentication
3. Store SMTP credentials outside the public site when possible
4. Test from the live Hostinger domain only