

Sumeru-GPS-H1000

Intelligent General Purpose Server



The Sumeru-GPS-H1000 General Purpose Server is a state-of-the-art solution engineered to meet the demands of modern workloads and complex IT environments. Powered by dual Intel Xeon Silver processors and optimized for high-performance computing, it offers exceptional scalability, reliability, and efficiency. With support for advanced RAID configurations, high-speed memory, and redundant power supplies, this server ensures seamless operations and data protection. Designed for innovation, it accelerates operations through autonomous collaboration and integrates robust security features to safeguard your infrastructure. The Sumeru-GPS-H1000 is an ideal choice for businesses seeking a powerful, resilient, and future-ready server solution.

Advanced Processing Power

Equipped with dual Intel Xeon Silver 4410Y processors, featuring 12 cores, 24 threads, and turbo capabilities for optimal performance.

High-Speed Memory

Supports 32 GB RDIMM memory running at 5600 MT/s for fast data processing and multitasking.

Scalable Storage

Includes 2 TB SATA hard drives in a RAID 1 configuration, ensuring data redundancy and reliability.

Efficient Cooling

Comes with five built-in cooling fans to maintain optimal temperature under heavy workloads.

Redundant Power Supply

Dual hot-plug 800 W power supplies provide reliability and uninterrupted operation.

Enhanced Security

Features TPM 2.0, secure boot, and factory-generated passwords for robust system protection.

Simplified Management

Includes iDRAC9 Enterprise with Quick Sync 2 for efficient remote monitoring and management.

Energy Efficiency

Designed with power-saving BIOS configurations to reduce operational costs.

Flexible Deployment

ReadyRails sliding rails and asset tagging facilitate quick and easy installation.

Comprehensive Support

Comes with ProSupport and Next Business Day Service for 36 months to ensure maximum uptime.

Dimensions



	General Information
Processor	Dual Intel Xeon Silver 4410Y (2.0 GHz base, Turbo, 12 cores, 24 threads, 16 GT/s, 30 MB Cache, DDR5-4000, 150 W each)
Memory	32 GB RDIMM, 5600 MT/s, Dual Rank
Storage	2 × 2 TB 7.2K RPM SATA, 6 Gbps, 512n, 3.5-inch hot-plug drives in RAID 1 configuration
RAID Controller	PERC H355 Controller with front load mechanical components
Power Supply	Dual (1+1) 800 W hot-plug, redundant power supplies (100–240 V AC)
Cooling	5 × Standard Cooling Fans
Chassis	3.5-inch chassis with support for up to 8 hard drives (SAS/SATA)
Motherboard	PowerEdge R760xs motherboard with Broadcom 5720 dual-port 1 Gb integrated LOM
I/O Ports (Front)	1 × iDRAC Direct (Micro-AB USB), 1 × USB 2.0, 1 × VGA, 1 × DVD
I/O Ports (Rear)	1 × USB 2.0, 1 × USB 3.0, 1 × Serial (optional), 6 × 1 Gb Ethernet, 1 × VGA
Management	iDRAC9 Enterprise with Quick Sync 2, Factory-Generated Password
Security	Trusted Platform Module (TPM) 2.0, Secure Boot, Cryptographically Signed Firmware
BIOS	UEFI BIOS Boot Mode with GPT Partition
Dimensions (H × W × D)	27.85" × 19.0" × 3.4" (707.78 mm × 482 mm × 86.8 mm)
Net Weight	63.49 lbs (28.8 kg)
Gross Weight	82.01 lbs (37.2 kg)
Operating System	None pre-installed
Warranty	Basic Supports (12 months)



Address: 190 Bluegrass Valley Parkway, Alpharetta, GA 30005

Phone: + 1 (470) 816-1970

Email: sales@armatura.us

Website: www.armatura.us

Copyright © 2025 Armatura LLC @ ARMATURA, the ARMATURA logo, are trademarks of Armatura

