PartSmith repair card

Caster wheel (family hint 'wheel')

Family: wheel

BEST EFFORT

Max error: 0.70 mm (pass: <= 0.5 mm, IoU >= 0.97)
top: IoU 0.975, Hausdorff 0.52 mm, mean 0.18 mm
side: IoU 0.985, Hausdorff 0.70 mm, mean 0.11 mm
Part tests: 20/25 passed
- top: refined in the photo frame by +0.14 deg, (-0.09, +0.01) mm on the mat
- side: refined in the photo frame by +0.06 deg, (-0.06, +0.14) mm on the mat
- top view (photo frame): IoU 0.975 (needs >= 0.97), Hausdorff 0.52 mm (needs <= 0.5 mm) (worst at x=-23.8

Key dimensions

Length: 61.73 mm ± 0.10 [measured]
Width: 61.69 mm ± 0.10 [measured]
Thickness: 15.00 mm ± 0.30 [user stated]
hole_1 Ø: 12.71 mm ± 0.06 [measured]
hole_2 Ø: 12.80 mm ± 0.06 [measured]
hole_3 Ø: 12.70 mm ± 0.05 [measured]
hole_4 Ø: 7.18 mm ± 0.06 [measured]

Print settings (suggested)

PLA, 0.4 mm nozzle, 0.2 mm layers
4 walls, 40% infill, supports: yes
Orientation: -Z: mounting face (Z=0) on the bed, as modelled