SYNTHETIC · MOCK MODELS — not a real-world measurement

PartSmith repair card

L-bracket (family hint 'bracket')

Family: bracket

VERIFIED

Max error: 0.16 mm (pass: <= 0.5 mm, IoU >= 0.97)
top: IoU 0.991, Hausdorff 0.15 mm, mean 0.07 mm
side: IoU 0.987, Hausdorff 0.13 mm, mean 0.03 mm
Part tests: 17/17 passed
- top: refined in the photo frame by +0.48 deg, (-0.14, -0.01) mm on the mat
- side: refined in the photo frame by +0.04 deg, (+1.05, +0.37) mm on the mat
- Verified: all 11 P0 tests pass and every measured view is within tolerance.

Key dimensions

Length: 46.37 mm ± 0.09 [measured]
Width: 30.53 mm ± 0.09 [measured]
Thickness: 2.50 mm ± 0.30 [user stated]
hole_1 Ø: 3.59 mm ± 0.05 [measured]
hole_2 Ø: 3.60 mm ± 0.04 [measured]

Print settings (suggested)

PLA, 0.4 mm nozzle, 0.2 mm layers
4 walls, 40% infill, supports: yes
Orientation: -Z: mounting face (Z=0) on the bed, as modelled