SYNTHETIC · MOCK MODELS — not a real-world measurement

PartSmith repair card

Caster wheel (family hint 'wheel')

Family: wheel

BEST EFFORT

Max error: 0.92 mm (pass: <= 0.5 mm, IoU >= 0.97)
side: IoU 0.976, Hausdorff 0.92 mm, mean 0.17 mm
top: IoU 0.993, Hausdorff 0.22 mm, mean 0.05 mm
Part tests: 21/21 passed
- side: refined in the photo frame by +0.25 deg, (-0.00, +0.08) mm on the mat
- top: refined in the photo frame by -0.16 deg, (-0.01, +0.03) mm on the mat
- side view (photo frame): IoU 0.976 (not gated), mean contour distance 0.17 mm (needs <= 0.15 mm), Hausd

Key dimensions

Length: 61.73 mm ± 0.10 [measured]
Width: 61.69 mm ± 0.10 [measured]
Thickness: 15.00 mm ± 0.30 [user stated]
hole_1 Ø: 12.71 mm ± 0.06 [measured]
hole_2 Ø: 12.71 mm ± 0.06 [measured]
hole_3 Ø: 12.70 mm ± 0.05 [measured]
hole_4 Ø: 7.18 mm ± 0.06 [measured]

Print settings (suggested)

PLA, 0.4 mm nozzle, 0.2 mm layers
4 walls, 40% infill, supports: no
Orientation: -Z: mounting face (Z=0) on the bed, as modelled