SYNTHETIC · MOCK MODELS — not a real-world measurement

PartSmith repair card

Cable clip (family hint 'cable_clip')

Family: cable_clip

BEST EFFORT

Max error: 1.12 mm (pass: <= 0.5 mm, IoU >= 0.97)
side: IoU 0.931, Hausdorff 1.12 mm, mean 0.12 mm
top: IoU 0.970, Hausdorff 0.44 mm, mean 0.11 mm
Part tests: 11/13 passed
- side: refined in the photo frame by +0.14 deg, (+0.06, +0.03) mm on the mat
- top: refined in the photo frame by -0.07 deg, (+0.21, -0.19) mm on the mat
- side view (photo frame): IoU 0.931 (not gated), mean contour distance 0.12 mm (needs <= 0.15 mm), Hausd

Key dimensions

Length: 34.52 mm ± 0.11 [measured]
Width: 11.96 mm ± 0.11 [measured]
Thickness: 2.50 mm ± 0.30 [user stated]
hole_1 Ø: 2.86 mm ± 0.04 [measured]
hole_2 Ø: 2.85 mm ± 0.04 [measured]

Print settings (suggested)

PLA, 0.4 mm nozzle, 0.2 mm layers
4 walls, 40% infill, supports: no
Orientation: -Z: mounting face (Z=0) on the bed, as modelled