PartSmith repair card

Knurled knob

Family: knob

BEST EFFORT

Max error: 0.50 mm (pass: <= 0.5 mm, IoU >= 0.97)
top: IoU 0.981, Hausdorff 0.48 mm, mean 0.15 mm
side: IoU 0.969, Hausdorff 0.50 mm, mean 0.20 mm
Part tests: 12/12 passed
- top: refined in the photo frame by +0.32 deg, (+0.00, -0.01) mm on the mat
- side: refined in the photo frame by +0.03 deg, (-0.02, +0.07) mm on the mat
- top view (photo frame): IoU 0.981 (needs >= 0.97), Hausdorff 0.48 mm (needs <= 0.5 mm)

Key dimensions

Length: 29.79 mm ± 0.28 [measured]
Width: 29.70 mm ± 0.28 [measured]
Thickness: 16.00 mm ± 0.30 [user stated]

Print settings (suggested)

PLA, 0.4 mm nozzle, 0.2 mm layers
4 walls, 40% infill, supports: yes
Orientation: +Z: upside down (top face on the bed)

Repair passport

9AZFWX

Broke again? Scan to reprint — your printer's clearance comes with it.

http://localhost:3000/p/9AZFWX

Or type the id on the PartSmith site at /p/<id>. No new photos needed.