SYNTHETIC · MIXED MODELS — not a real-world measurement

PartSmith repair card

AA cell reference solid

Family: custom

BEST EFFORT

Max error: 0.20 mm (pass: <= 0.5 mm, IoU >= 0.97)
top: IoU 0.995, Hausdorff 0.20 mm, mean 0.03 mm
Part tests: 10/12 passed
- top: refined in the photo frame by -0.02 deg, (+0.01, -0.01) mm on the mat
- top view (photo frame): IoU 0.995 (not gated), mean contour distance 0.03 mm (needs <= 0.15 mm), Hausd
- top view: small silhouette (14.3 mm across, under 20 mm), so IoU is reported but not gated (it shrinks with s

Key dimensions

Length: 49.93 mm ± 0.11 [measured]
Width: 14.35 mm ± 0.10 [measured]
Thickness: 14.50 mm ± 0.30 [user stated]

Print settings (suggested)

PLA, 0.4 mm nozzle, 0.2 mm layers
4 walls, 40% infill, supports: no
Orientation: -Z: mounting face (Z=0) on the bed, as modelled

Repair passport

4M4Z1F

Broke again? Scan to reprint — your printer's clearance comes with it.

http://localhost:3000/p/4M4Z1F

Or type the id on the PartSmith site at /p/<id>. No new photos needed.