

CODE :

#Initial permut matrix for the datas

```
PI = [58, 50, 42, 34, 26, 18, 10, 2,
      60, 52, 44, 36, 28, 20, 12, 4,
      62, 54, 46, 38, 30, 22, 14, 6,
      64, 56, 48, 40, 32, 24, 16, 8,
      57, 49, 41, 33, 25, 17, 9, 1,
      59, 51, 43, 35, 27, 19, 11, 3,
      61, 53, 45, 37, 29, 21, 13, 5,
      63, 55, 47, 39, 31, 23, 15, 7]
```

#Initial permut made on the key CP_1 = [57, 49, 41, 33, 25, 17, 9, 1, 58, 50, 42, 34, 26, 18, 10, 2, 59, 51, 43, 35, 27, 19, 11, 3, 60, 52, 44, 36,

63, 55, 47, 39, 31, 23, 15, 7, 62, 54, 46, 38, 30, 22, 14, 6, 61, 53, 45, 37, 29, 21, 13, 5, 28, 20, 12, 4]

#Permut applied on shifted key to get Ki+1 CP_2 = [14, 17, 11, 24, 1, 5, 3, 28,

15, 6, 21, 10, 23, 19, 12, 4, 26, 8, 16, 7, 27, 20, 13, 2, 41, 52, 31, 37, 47, 55, 30, 40, 51, 45, 33, 48, 44, 49, 39, 56, 34, 53, 46, 42, 50, 36, 29, 32]

#Expand matrix to get a 48bits matrix of datas to apply the xor with Ki

```
E = [32, 1, 2, 3, 4, 5,
      4, 5, 6, 7, 8, 9,
      8, 9, 10, 11, 12, 13,
      12, 13, 14, 15, 16, 17,
      16, 17, 18, 19, 20, 21,
      20, 21, 22, 23, 24, 25,
      24, 25, 26, 27, 28, 29,
      28, 29, 30, 31, 32, 1]
```

S_BOX = [

4, 13, 1, 2, 15, 11, 8, 3, 10, 6, 12, 5, 9, 0, 7], 15, 7, 4, 14, 2, 13, 1, 10, 6, 12, 11, 9, 5, 3, 8], [4, 1, 14, 8, 13, 6, 2, 11, 15, 12, 9, 7, 3, 10, 5, 0],

[[14, [0,

12, 8, 2, 4, 9, 1, 7, 5, 11, 3, 14, 10, 0, 6, 13],

1, 8, 14, 6, 11, 3, 4, 9, 7, 2, 13, 12, 0, 5, 10], 13, 4, 7, 15, 2, 8, 14, 12, 0, 1, 10, 6, 9, 11, 5], 14, 7, 11, 10, 4, 13, 1, 5, 8, 12, 6, 9, 3, 2, 15],

8, 10, 1, 3, 15, 4, 2, 11, 6, 7, 12, 0, 5, 14, 9],

],

[13, 6, 4, 9, 8, 15, 3, 0, 11, 1, 2, 12, 5, 10, 14, 7], [1, 10, 13, 0, 6, 9, 8, 7, 4, 15, 14, 3, 11, 5, 2, 12],

```

],
[[7, 13, 14, 3, 0, 6, 9, 10, 1, 2, 8, 5, 11, 12, 4, 15], [13, 8, 11, 5, 6, 15, 0, 3, 4, 7, 2, 12, 1, 10, 14, 9],
[10, 6, 9, 0, 12, 11, 7, 13, 15, 1, 3, 14, 5, 2, 8, 4], [3, 15, 0, 6, 10, 1, 13, 8, 9, 4, 5, 11, 12, 7, 2, 14],
],
[[2, 12, 4, 1, 7, 10, 11, 6, 8, 5, 3, 15, 13, 0, 14, 9], [14, 11, 2, 12, 4, 7, 13, 1, 5, 0, 15, 10, 3, 9, 8, 6],
[4, 2, 1, 11, 10, 13, 7, 8, 15, 9, 12, 5, 6, 3, 0, 14], [11, 8, 12, 7, 1, 14, 2, 13, 6, 15, 0, 9, 10, 4, 5, 3],
],
[[12, 1, 10, 15, 9, 2, 6, 8, 0, 13, 3, 4, 14, 7, 5, 11], [10, 15, 4, 2, 7, 12, 9, 5, 6, 1, 13, 14, 0, 11, 3, 8],
[9, 14, 15, 5, 2, 8, 12, 3, 7, 0, 4, 10, 1, 13, 11, 6], [4, 3, 2, 12, 9, 5, 15, 10, 11, 14, 1, 7, 6, 0, 8, 13],
],
[[4, 11, 2, 14, 15, 0, 8, 13, 3, 12, 9, 7, 5, 10, 6, 1], [13, 0, 11, 7, 4, 9, 1, 10, 14, 3, 5, 12, 2, 15, 8, 6],
[1, 4, 11, 13, 12, 3, 7, 14, 10, 15, 6, 8, 0, 5, 9, 2], [6, 11, 13, 8, 1, 4, 10, 7, 9, 5, 0, 15, 14, 2, 3, 12],
],
[[13, 2, 8, 4, 6, 15, 11, 1, 10, 9, 3, 14, 5, 0, 12, 7], [1, 15, 13, 8, 10, 3, 7, 4, 12, 5, 6, 11, 0, 14, 9, 2],
[7, 11, 4, 1, 9, 12, 14, 2, 0, 6, 10, 13, 15, 3, 5, 8], [2, 1, 14, 7, 4, 10, 8, 13, 15, 12, 9, 0, 3, 5, 6, 11],
]]

```

#Permut made after each SBox substitution for each round

```

P = [16, 7, 20, 21, 29, 12, 28, 17,
1, 15, 23, 26, 5, 18, 31, 10, 2, 8, 24, 14, 32, 27, 3, 9, 19, 13, 30, 6, 22, 11, 4, 25]

```

```

#Final permut for datas after the 16 rounds PI_1 = [40, 8, 48, 16, 56, 24, 64, 32,
39, 7, 47, 15, 55, 23, 63, 31,
38, 6, 46, 14, 54, 22, 62, 30,
37, 5, 45, 13, 53, 21, 61, 29,
36, 4, 44, 12, 52, 20, 60, 28,
35, 3, 43, 11, 51, 19, 59, 27,
34, 2, 42, 10, 50, 18, 58, 26,
33, 1, 41, 9, 49, 17, 57, 25]

```

#Matrix that determine the shift for each round of keys SHIFT = [1,1,2,2,2,2,2,2,1,2,2,2,2,2,2,1]

```

def string_to_bit_array(text):#Convert a string into a list of bits array = list()

```

```

    for char in text:

```

```

        binval = binvalue(char, 8)#Get the char value on one byte

```

```

    array.extend([int(x) for x in list(binval)]) #Add the bits to the final list

```

```

return array

```

```

def bit_array_to_string(array): #Recreate the string from the bit array

```

```

res = ''.join([chr(int(y,2)) for y in [''.join([str(x) for x in _bytes]) for _bytes in nsplit(array,8)]]))

return res

def binvalue(val, bitsize): #Return the binary value as a string of the given size

binval = bin(val)[2:] if isinstance(val, int) else bin(ord(val))[2:]

if len(binval) > bitsize:
raise "binary value larger than the expected size"

    while len(binval) < bitsize:
binval = "0"+binval #Add as many 0 as needed to get the wanted size

    return binval
def nsplit(s, n):#Split a list into sublists of size "n" return [s[k:k+n] for k in range(0, len(s), n)]

ENCRYPT=1
DECRYPT=0

class des():
    def __init__(self):
        self.password = None
        self.text = None
        self.keys = list()
def run(self, key, text, action=ENCRYPT, padding=False): if len(key) < 8:

raise "Key Should be 8 bytes long" elif len(key) > 8:

key = key[:8] #If key size is above 8bytes, cut to be

8bytes long

        self.password = key
        self.text = text
        if padding and action==ENCRYPT:
            self.addPadding()
elif len(self.text) % 8 != 0:#If not padding specified data size must be multiple of 8 bytes

        raise "Data size should be multiple of 8"
self.generatekeys() #Generate all the keys

text_blocks = nsplit(self.text, 8) #Split the text in blocks of 8 bytes so 64 bits

        result = list()
        for block in text_blocks:#Loop over all the blocks of data
bit array
permutation
(48bits)

Ki

```

```

block = string_to_bit_array(block)#Convert the block in block = self.permut(block,PI)#Apply the
initial

g, d = nsplit(block, 32) #g(LEFT), d(RIGHT) tmp = None
for i in range(16): #Do the 16 rounds

d_e = self.expand(d, E) #Expand d to match Ki size

    if action == ENCRYPT:
        tmp = self.xor(self.keys[i], d_e)#If encrypt use
    else:

        tmp = self.xor(self.keys[15-i], d_e)#If decrypt
start by the last key
the SBOXes

tmp = self.substitute(tmp) #Method that will apply
tmp = self.permut(tmp, P)
tmp = self.xor(g, tmp)
g=d

d = tmp

    result += self.permut(d+g, PI_1) #Do the last permut and
append the result to result
    final_res = bit_array_to_string(result)
    if padding and action==DECRYPT:
        return self.removePadding(final_res) #Remove the padding
if decrypt and padding is true
else:

    return final_res #Return the final string of data
ciphered/deciphered
def substitute(self, d_e):#Substitute bytes using SBOX
subblocks = nsplit(d_e, 6)#Split bit array into sublist of 6 bits

result = list()
for i in range(len(subblocks)): #For all the sublists
    block = subblocks[i]

    row = int(str(block[0])+str(block[5]),2)#Get the row
with the first and last bit
    column = int("".join([str(x) for x in block[1:][:-
1]]),2) #Column is the 2,3,4,5th bits
val = S_BOX[i][row][column] #Take the value in the SBOX appropriated for the round (i)

bin = binvalue(val, 4)#Convert the value to binary

    result += [int(x) for x in bin]#And append it to the
resulting list
    return result
def permut(self, block, table):#Permut the given block using the given table (so generic method)

```


