



OPERATING SYSTEM (SYNCHRONIZATION)

BY
AMAR PANCHAL



Background

- Processes can execute concurrently
 - *May be interrupted at any time, partially completing execution*
- Concurrent access to shared data may result in data inconsistency
- Maintaining data consistency requires mechanisms to ensure the orderly execution of cooperating processes

Producer

```
while (true) {  
    /* produce an item in next produced */  
  
    while (counter == BUFFER_SIZE) ;  
        /* do nothing */  
  
    buffer[in] = next_produced;  
    in = (in + 1) % BUFFER_SIZE;  
    counter++;  
}
```

Consumer

```
while (true) {  
    while (counter == 0)  
        ; /* do nothing */  
    next_consumed = buffer[out];  
    out = (out + 1) % BUFFER_SIZE;    counter-  
-;  
    /* consume the item in next consumed */  
}
```

Race Condition

- `counter++` could be implemented as

```
register1 = counter
register1 = register1 + 1
counter = register1
```

- `counter--` could be implemented as

```
register2 = counter
register2 = register2 - 1
counter = register2
```

- Consider this execution interleaving with “count = 5” initially:

S0: producer execute	<code>register1 = counter</code>	{register1 = 5}
S1: producer execute	<code>register1 = register1 + 1</code>	{register1 = 6}
S2: consumer execute	<code>register2 = counter</code>	{register2 = 5}
S3: consumer execute	<code>register2 = register2 - 1</code>	{register2 = 4}
S4: producer execute	<code>counter = register1</code>	{counter = 6}
S5: consumer execute	<code>counter = register2</code>	{counter = 4}

Critical Section Problem

- Consider system of n processes $\{p_0, p_1, \dots p_{n-1}\}$
- Each process has **critical section** segment of code
 - *Process may be changing common variables, updating table, writing file, etc*
 - *When one process in critical section, no other may be in its critical section*
- **Critical section problem** is to design protocol to solve this
- Each process must ask permission to enter critical section in **entry section**, may follow critical section with **exit section**, then **remainder section**

Critical Section

- General structure of process p_i is

```
do {  
    entry section  
    critical section  
    exit section  
    remainder section  
} while (true);
```

Solution to Critical-Section Problem

1. **Mutual Exclusion** - If process P_i is executing in its critical section, then no other processes can be executing in their critical sections
2. **Progress** - If no process is executing in its critical section and there exist some processes that wish to enter their critical section, then the selection of the processes that will enter the critical section next cannot be postponed indefinitely
3. **Bounded Waiting** - A bound must exist on the number of times that other processes are allowed to enter their critical sections after a process has made a request to enter its critical section and before that request is granted
 - Assume that each process executes at a nonzero speed
 - No assumption concerning *relative speed* of the n processes

Synchronization Hardware

- Many systems provide hardware support for critical section code
- All solutions below based on idea of **locking**
 - *Protecting critical regions via locks*
- Uniprocessors – could disable interrupts
 - *Currently running code would execute without preemption*
 - *Generally too inefficient on multiprocessor systems*
 - Operating systems using this not broadly scalable
- Modern machines provide special atomic hardware instructions
 - **Atomic** = non-interruptible
 - *Either test memory word and set value*
 - *Or swap contents of two memory words*

Solution to Critical-section Problem Using Locks

```
do {  
  
    acquire lock  
        critical section  
    release lock  
        remainder section  
} while (TRUE);
```

Semaphore

- Synchronization tool that does not require busy waiting
- Semaphore **S** – integer variable
- Two standard operations modify **S**: **wait()** and **signal()**
 - Originally called **P()** and **V()**
- Less complicated
- Can only be accessed via two indivisible (atomic) operations

```
wait (S) {  
    while (S <= 0)  
        ; // busy wait  
    S--;  
}  
  
signal (S) {  
    S++;  
}
```

Semaphore Usage

- **Counting semaphore** – integer value can range over an unrestricted domain
- **Binary semaphore** – integer value can range only between 0 and 1
 - Then a **mutex lock**
- Can implement a counting semaphore **S** as a binary semaphore
- Can solve various synchronization problems
- Consider P_1 and P_2 that require S_1 to happen before S_2
 - P1:**
 - $S_1;$
 - signal(synch);**
 - P2:**
 - wait(synch);**
 - $S_2;$

Semaphore Implementation

- Must guarantee that no two processes can execute **wait()** and **signal()** on the same semaphore at the same time
- Thus, implementation becomes the critical section problem where the wait and signal code are placed in the critical section
 - *Could now have **busy waiting** in critical section implementation*
 - But implementation code is short
 - Little busy waiting if critical section rarely occupied
- Note that applications may spend lots of time in critical sections and therefore this is not a good solution

Semaphore Implementation with no Busy waiting

- With each semaphore there is an associated waiting queue
- Each entry in a waiting queue has two data items:
 - *value (of type integer)*
 - *pointer to next record in the list*
- Two operations:
 - **block** – *place the process invoking the operation on the appropriate waiting queue*
 - **wakeup** – *remove one of processes in the waiting queue and place it in the ready queue*

Semaphore Implementation with no Busy waiting (Cont.)

```
typedef struct{

    int value;

    struct process *list;

} semaphore;

wait(semaphore *S) {

    S->value--;

    if (S->value < 0) {
        add this process to S->list;

        block();
    }

}

signal(semaphore *S) {

    S->value++;

    if (S->value <= 0) {
        remove a process P from S->list;

        wakeup(P);
    }

}
```

Deadlock and Starvation

- **Deadlock** – two or more processes are waiting indefinitely for an event that can be caused by only one of the waiting processes
- Let s and q be two semaphores initialized to 1

P_0	P_1
<code>wait(S);</code>	<code>wait(Q);</code>
<code>wait(Q);</code>	<code>wait(S);</code>
<code>.</code>	<code>.</code>
<code>signal(S);</code>	<code>signal(Q);</code>
<code>signal(Q);</code>	<code>signal(S);</code>

- **Starvation** – **indefinite blocking**
 - *A process may never be removed from the semaphore queue in which it is suspended*
- **Priority Inversion** – Scheduling problem when lower-priority process holds a lock needed by higher-priority process
 - Solved via **priority-inheritance protocol**

Classical Problems of Synchronization

- Classical problems used to test newly-proposed synchronization schemes
 - *Bounded-Buffer Problem*
 - *Readers and Writers Problem*
 - *Dining-Philosophers Problem*

Bounded-Buffer Problem

- n buffers, each can hold one item
- Semaphore **mutex** initialized to the value 1
- Semaphore **full** initialized to the value 0
- Semaphore **empty** initialized to the value n

Bounded Buffer Problem (Cont.)

- The structure of the producer process

```
do {  
  
    ...  
    /* produce an item in next_produced */  
    ...  
    wait(empty);  
    wait(mutex);  
  
    ...  
    /* add next produced to the buffer */  
    ...  
    signal(mutex);  
    signal(full);  
} while (true);
```

Bounded Buffer Problem (Cont.)

- The structure of the consumer process

```
do {  
    wait(full);  
    wait(mutex);  
  
    ...  
    /* remove an item from buffer to next_consumed */  
    ...  
    signal(mutex);  
    signal(empty);  
  
    ...  
    /* consume the item in next consumed */  
    ...  
} while (true);
```

Readers-Writers Problem

- A data set is shared among a number of concurrent processes
 - *Readers* – only read the data set; they do **not** perform any updates
 - *Writers* – can both read and write
- Problem – allow multiple readers to read at the same time
 - *Only one single writer can access the shared data at the same time*
- Several variations of how readers and writers are treated – all involve priorities
- Shared Data
 - *Data set*
 - Semaphore ***rw_mutex*** initialized to 1
 - Semaphore ***mutex*** initialized to 1
 - Integer ***read_count*** initialized to 0

Readers-Writers Problem (Cont.)

n The structure of a writer process

```
do {  
    wait(rw_mutex);  
  
    ...  
    /* writing is performed */  
    ...  
    signal(rw_mutex);  
} while (true);
```

Readers-Writers Problem (Cont.)

n The structure of a reader process

```
do {
    wait(mutex);
    read count++;
    if (read_count == 1)

        wait(rw_mutex);

    signal(mutex);

    ...
    /* reading is performed */

    ...

    wait(mutex);
    read count--;
    if (read_count == 0)


        signal(rw_mutex);

    signal(mutex);
} while (true);
```

Readers-Writers Problem Variations

- **First** variation – no reader kept waiting unless writer has permission to use shared object
- **Second** variation – once writer is ready, it performs write ASAP
- Both may have starvation leading to even more variations
- Problem is solved on some systems by kernel providing reader-writer locks

Dining-Philosophers Problem



- Philosophers spend their lives thinking and eating
- Don't interact with their neighbors, occasionally try to pick up 2 chopsticks (one at a time) to eat from bowl
 - *Need both to eat, then release both when done*
- In the case of 5 philosophers
 - *Shared data*
 - Bowl of rice (data set)
 - Semaphore `chopstick [5]` initialized to 1

Dining-Philosophers Problem

Algorithm

- The structure of Philosopher i :

```
do {  
    wait (chopstick[i] );  
    wait (chopStick[ (i + 1) % 5] );  
  
    // eat  
  
    signal (chopstick[i] );  
    signal (chopstick[ (i + 1) % 5] );  
  
    // think  
  
} while (TRUE);
```

- What is the problem with this algorithm?

Problems with Semaphores

- Incorrect use of semaphore operations:
 - *signal (mutex) wait (mutex)*
 - *wait (mutex) ... wait (mutex)*
 - *Omitting of wait (mutex) or signal (mutex) (or both)*
- Deadlock and starvation

Monitors

- A high-level abstraction that provides a convenient and effective mechanism for process synchronization
- *Abstract data type*, internal variables only accessible by code within the procedure
- Only one process may be active within the monitor at a time
- But not powerful enough to model some synchronization schemes

```
monitor monitor-name
{
    // shared variable declarations
    procedure P1 (...) { ... }

    procedure Pn (...) {.....}

    Initialization code (...) { ... }
}
}
```

Schematic view of a Monitor

