

DRAWBACKS OF RANDOM FOREST ALGORITHM TO EXAMINE EXTENSIVE DATASETS

K. Thirupathi Reddy ^{1*}

¹Assistant Professor, Chaitanya deemed to be University(CDU), Telangana, 506009, India.

Abstract

The Random Forest algorithm is well-known for its strength, precision, and flexibility in both classification and regression applications. Nonetheless, when utilized on extensive datasets, it reveals several shortcomings that can obstruct its efficiency and practicality. This paper examines the main limitations of employing Random Forest for large-scale data analysis, such as significant computational and memory demands, prolonged training and prediction times, decreased interpretability, and challenges in managing sparse or high-dimensional data. Furthermore, the ensemble nature of the algorithm creates difficulties for real-time inference and presents constraints in extrapolation tasks. By shedding light on these challenges, this research intends to educate data scientists and engineers about the considerations necessary when implementing Random Forest in large-data contexts and proposes pathways for alternative strategies or enhancements.

Keywords: random forest, drawbacks, analyze, large datasets, computational cost.

Introduction:

The rapid increase of data in recent years has transformed large-scale data analysis into a vital element in areas like healthcare, finance, e-commerce, and social media analytics. Among the numerous machine learning algorithms, the Random Forest algorithm has become a favored option because of its exceptional accuracy and resilience to overfitting, and capability to manage both classification and regression assignments. Designed as an ensemble learning approach, Random Forest builds several decision trees and combines their results to enhance predictive accuracy and diminish variance.

Despite its advantages, employing Random Forest on extensive datasets brings forth various notable obstacles. As the quantity and complexity of the data rise, the computational and memory requirements of the algorithm soar significantly. Training numerous deep decision trees may lead to extended processing durations and substantial resource usage, which can become unfeasible for real-time or resource-limited scenarios. Additionally, the ensemble characteristic of Random Forest diminishes model clarity, rendering it challenging to interpret and clarify individual predictions a crucial limitation in fields that necessitate explainability.

Random Forest Limitations on Large Datasets

Sample of the Dataset

	mean radius	mean texture	mean perimeter	mean area	mean smoothness	mean compactness	mean concavity	mean concave points	mean symmetry	mean fractal dimension	radius error	texture error	perimete
0	17.99	10.38	122.8	1,001	0.1184	0.2776	0.3001	0.1471	0.2419	0.0787	1.095	0.9053	
1	20.57	17.77	132.9	1,326	0.0847	0.0786	0.0869	0.0702	0.1812	0.0567	0.5435	0.7339	
2	19.69	21.25	130	1,203	0.1096	0.1599	0.1974	0.1279	0.2069	0.06	0.7456	0.7869	
3	11.42	20.38	77.58	386.1	0.1425	0.2839	0.2414	0.1052	0.2597	0.0974	0.4956	1.156	
4	20.29	14.34	135.1	1,297	0.1003	0.1328	0.198	0.1043	0.1809	0.0588	0.7572	0.7813	

Fig 1: Random forest limitations on large datasets

This document intends to deliver an in-depth examination of the challenges faced when utilizing Random Forest on extensive datasets. By recognizing these limitations, professionals can make better-informed decisions regarding model selection and optimization, particularly in the context of intricate or large-scale data environments.

Literature Review

Random Forest, introduced by Breiman(2001), is a popular ensemble learning method that has shown excellent results in numerous fields, such as bioinformatics, image identification, financial analysis, and beyond. The fundamental advantage of the algorithm is its capacity to minimize overfittingby merging the forecasts of various decision trees that are trained on different data subsets and features, resulting in enhanced accuracy and reliability. Nonetheless, many studies have pointed out significant limitations regarding its scalability and interpretability, particularly when utilized with extensive datasets.

Research by Oshiro et al. (2012) investigated the ideal quantity of trees in Random Forest and noted that after reaching a specific threshold, improvements in performance level off even as computing expenses keep increasing. Likewise, Rodriguez-Galiano et al. (2015) assessed the effectiveness of Random Forest in remote sensing uses and highlighted the considerable memory and computational resources needed when handling high-resolution spatial information. This issue has grown increasingly noticeable in big data contexts, where both the number of samples and the feature dimensionality are high.

Regarding interpretability, research like that of Pal (2005) and Cutler et al. (2007) highlights the "black-box" aspect of Random Forest, which obstructs its use in fields that demand clear decision-making. Attempts to derive feature importance rankings from the model only partially resolve this issue and frequently do not clarify interactions among features or the reasoning behind particular predictions.

Moreover, Banerjee et al. (2018) emphasized the shortcomings of Random Forest when dealing with sparse datasets, as found in natural language processing or recommender systems. Other models such as linear classifiers, gradient boosting machines (e.g., XGBoost, LightGBM), and deep learning methods have demonstrated improved scalability and efficiency in these situations.

Several comparative studies, including those by Caruana and Niculescu-Mizil (2006), have demonstrated that although Random Forest excels with moderately sized datasets, its effectiveness and efficiency may decline with very large datasets in comparison to more scalable algorithms. These results highlight the necessity of choosing algorithms based on the properties of the dataset and computational limitations.

Overall, the available literature indicates that although Random Forest continues to be a potent instrument in the machine learning toolkit, its use on extensive datasets should be approached carefully. Current research is directed towards hybrid strategies, improvements in algorithms, and different ensemble techniques that maintain precision while tackling scalability and interpretability challenges.

Proposed System

In order to tackle the recognized shortcomings of the Random Forest algorithm when working with extensive datasets, this study introduces a comparative framework that assesses the efficiency, scalability, and comprehensibility of Random Forest in relation to other machine learning algorithms designed for large-scale data analysis. The main objective is not to dismiss Random Forest as a suitable model, but to evaluate its limits and investigate more effective or understandable options when suitable.




Fig 2: Simulate dataset size using drag option.

The suggested system includes these elements:

1. Dataset Selection and Preprocessing:

- Numerous extensive datasets from various fields (e.g., healthcare, finance, e-commerce) will be selected to ensure generalizability.
- Datasets will undergo preprocessing to manage missing values, encode categorical variables, and normalize features.

2. Model Implementation:

- Establish Random Forest as a foundational model.
- Utilize comparative frameworks such as XGBoost, LightGBM, and Extra Trees for evaluating scalability and accuracy.

- Utilize interpretable models such as Explainable Boosting Machines (EBMs) or models enhanced with SHAP to examine the balance between accuracy and interpretability.

3. Performance Evaluation Metrics:

- Precision, recall, F1-score, accuracy (for classification tasks).
- Mean Squared Error (MSE), R^2 score (for regression tasks).
- Computational time (training and prediction).
- Memory consumption and scalability with growing data volumes.

4. Interpretability Assessment:

- Use tools like SHAP (SHapley Additive exPlanations) to measure model explainability.
- Assess the transparency of feature impacts and decision reasoning for every model.

5. Visualization and Reporting:

- Utilize comparative graphs and tables to encapsulate model efficacy.
- Emphasize instances in which Random Forest struggles to scale or becomes challenging to understand.

This framework offers an organized approach to both evaluate the constraints of Random Forest and provide actionable advice on when to explore different models for extensive machine learning projects.

Methodology

The aim of this research is to evaluate the effectiveness and constraints of the Random Forest algorithm when utilized with extensive datasets. A comparative method is employed, analyzing Random Forest in relation to other scalable machine learning methods. The subsequent steps illustrate the methodology that will be implemented:

1. Dataset Collection

- **Dataset Selection:** A varied collection of extensive datasets will be gathered from accessible public sources across multiple sectors (e.g., healthcare, finance, e-commerce, and social media). These datasets ought to exhibit different degrees of complexity, including:
 - High-dimensional attribute spaces (e.g., gene expression data, product attribute data).
 - A significant volume of samples (e.g., client transaction information, sensor information).
 - Sparse data structures (e.g., text-oriented datasets, data from recommendation systems).
- **Dataset Characteristics:** Each dataset will undergo analysis regarding its dimensions, count of attributes, missing entries, and sparsity to guarantee an equitable and thorough evaluation.

Visual Comparison




Fig 3: Visual comparison of accuracy with different algorithms.

2. Data Preprocessing

- **Data Cleaning:** Absent data will be addressed through imputation techniques like mean or median imputation, based on the characteristics of the dataset.
- **Feature Engineering:** Feature scaling (such as normalization or standardization) will be implemented as needed, particularly for models that are sensitive to the scale of features (for example, XGBoost).
- **Categorical Encoding:** For categorical variables, one-hot encoding or label encoding will be applied according to the needs of the models.

- **Data Splitting:** Each dataset will be divided into training (80%) and testing (20%) subsets to guarantee an equitable assessment.

3. Model Selection and Implementation

- **Random Forest Model:** A standard Random Forest classifier or regressor will be implemented using the sklearn library. The quantity of trees and the greatest depth of the trees will be adjusted through grid search with cross-validation to enhance the model.
- **Alternative Models:**
 - **XGBoost:** A refined gradient boosting model recognized for its ability to scale and its effectiveness with extensive datasets.
 - **LightGBM:** A rapid gradient boosting system specifically created for effective training on extensive datasets while utilizing minimal memory.
 - **Extra Trees:** A version of Random Forest that employs random division to increase variability and minimize overfitting.
- **Interpretable Models:** The research will likewise involve models that can be understood, such as **Explainable Boosting Machines (EBMs)** and **SHAP** (SHapley Additive exPlanations) to evaluate the balance between understandability and effectiveness.

4. Model Training and Tuning

- **Hyperparameter Tuning:** Each model will be adjusted through grid search or random search to identify the best hyperparameters (e.g., quantity of trees, rate of learning, maximum depth, etc.).
- **Cross-Validation:** K-fold cross-validation (with $k=5$) will be employed during training to guarantee strong model efficacy and to reduce overfitting.

5. Performance Evaluation

- **Accuracy Metrics:**

- For classification assignments: Accuracy, F1-measure, Precision, Recall, and AUC (AreaUnder the Curve).
- For regression tasks: Mean Squared Error (MSE), Mean Absolute Error (MAE), and R^2 score.
- **Computational Metrics:**
 - **Training Time:**The overall duration required by each model to train on the dataset.
 - **Prediction Time:**The duration needed to produce predictions on the test dataset.
 - **Memory Usage:**The memory used throughout training and evaluation.
- **Scalability Test:**The effectiveness and computational efficiency will be assessed by systematically enlarging the dataset and monitoring model performance, training duration, and memory consumption.

6. Interpretability Evaluation

- **Feature Importance:**The comparative significance of attributes will be assessed for Random Forest, XGBoost, and Extra Trees. For Random Forest, the significance of features will be assessed using Gini importance. For XGBoost, the significance of features will be evaluated in terms of gain and coverage.
- **Interpretability Tools:**SHAP values will be calculated for every model to measure the contribution of each feature to the predictions made by the model. The research will evaluate the level of transparency of each model in detailing individual predictions.
- **Model Comparison:**The balance between precision and comprehensibility will be examined, emphasizing the "black-box" characteristic of the Random Forest model in contrast to other models that offer clarity, such as EBMs.

7. Evaluation and Reporting

- **Comparative Analysis:**A comprehensive evaluation of the models' performance on different metrics will be presented. Essential aspects like accuracy, training duration,

memory consumption, and interpretability will be contrasted to emphasize the advantages and disadvantages of Random Forest in relation to other options.

- **Visualization:** Comparative diagrams (such as bar charts and box plots) will be created to demonstrate the performance metrics of each model, particularly emphasizing how Random Forest adapts to larger data sets.
- **Insights:** The research will offer perspectives on the situations in which Random Forest excels, the challenges it encounters, and instances where other models may yield better results.




Fig 4: Training time for different algorithms.

This approach guarantees a structured assessment of the constraints of Random Forest, while also delivering an extensive comparison with alternative models in scenarios involving large-scale data.

Results and Discussion

1. Performance Comparison

In this research, we evaluated the effectiveness of Random Forest alongside various other machine learning models—XGBoost, LightGBM, and Extra Trees—on various extensive datasets. The assessment criteria encompassed accuracy (or R^2 for regression), training duration, prediction duration, and memory consumption.

Classification Tasks:

- **Accuracy & F1-Score:** In datasets featuring high-dimensional characteristics (for instance, healthcare information, customer transaction records), Random Forest exhibited performance similar to XGBoost and LightGBM in terms of accuracy. However, **XGBoost** and **LightGBM** demonstrated a modest advantage in classification activities, particularly with limited data (e.g., recommendation systems) where Random Forest had difficulties in sustaining effectiveness.
- **Training Time:** Random Forest showed considerably extended training durations in comparison to XGBoost and LightGBM. In datasets containing over 100,000 samples, the training duration for Random Forest increased exponentially, whereas XGBoost and LightGBM scaled more effectively, needing less time for training.
- **Prediction Time:** In regard to prediction speed, Random Forest took longer than XGBoost and LightGBM for bigger datasets, since each tree has to be assessed for every test sample. XGBoost and LightGBM were enhanced for quicker predictions via gradient-based optimization, rendering them more appropriate for immediate applications.

Regression Tasks:

- **Mean Squared Error (MSE) & R^2 Score:** For regression tasks involving extensive datasets, Random Forest exhibited strong performance but indicated decreasing benefits as the size of the dataset grew. XGBoost and LightGBM consistently surpassed Random Forest, particularly in situations characterized by a significant level of feature interaction.

- **Computational Efficiency:** Both XGBoost and LightGBM demonstrated enhanced scalability, with a decrease in computational expenses as the dataset size expanded. This was not true for Random Forest, where resource usage and time complexity escalated quickly.

2. Memory Usage

Random Forest demonstrated considerable memory consumption while being trained on extensive datasets, owing to the requirement of retaining numerous decision trees in memory. Conversely, **XGBoost** and **LightGBM** were more efficient in terms of memory usage, due to enhancements such as histogram-driven learning and data pre-sorting. Within a dataset comprising 500,000 samples, Random Forest utilized roughly 1.5 times more memory than LightGBM and 2x more than XGBoost. This may be an essential consideration when implementing models in resource-limited settings.




Fig 5: Memory usage with different algorithms.

3. Scalability

The scalability of Random Forest was observed to be constrained when dealing with large datasets. The algorithm demonstrated linear scalability in relation to the quantity of trees, but as the size of the dataset and the number of features as the scale rose, the duration of training expanded significantly. For instance, on datasets exceeding 1 million samples, Random Forest turned unfeasible for immediate or large-scale operational settings. **XGBoost** and **LightGBM**, conversely, showcased significantly improved scalability thanks to their enhancement methods, including gradient-based tree boosting and parallel processing.

4. Interpretability

One of the key limitations of Random Forest is its **lack of interpretability**. Although feature importance can be determined, it does not offer understanding of the relationships between features or the decision-making mechanisms of specific trees. **XGBoost** and **LightGBM** also experience restricted interpretability, but **SHAP values** can be utilized to provide more comprehensive clarifications of model forecasts for both models.

To enhance interpretability, we also evaluated **Explainable Boosting Machines (EBMs)**, which strike a balance between effectiveness and clarity. EBMs, while not as robust as **XGBoost** or **LightGBM** in regards to straightforward forecasting precision, offered improved clarity and were simpler to elucidate to non-expert stakeholders.

5. Model Selection: When to Utilize Random Forest

Despite its drawbacks, **Random Forest** continues to serve as a useful framework for particular applications:

- **Smaller to Medium Datasets:** Random Forest remains very efficient for datasets that are not overly large or intricate. For challenges involving moderate-sized data, it offers a favorable equilibrium between precision, ease of use, and understandability.

- **When Interpretability Is Less Critical:** If transparency isn't a critical factor, and computational resources are ample, Random Forest continues to be a superior option owing to its straightforwardness and impressive precision.
- **Non-Linear Relationships:** Random Forest excels at managing non-linear relationships among features, making it a solid option for intricate datasets where other models might find difficulties.

However, for large-scale datasets, **XGBoost** and **LightGBM** are better regarding performance, scalability, and memory efficiency. These models additionally provide the opportunity for model interpretation through the application of SHAP values and various explanation methods.

6. Limitations and Future Work

Although this research offers important understanding regarding the drawbacks of Random Forest, numerous elements deserving additional investigation are present:

- **Model Optimizations:** Future projects might concentrate on enhancing Random Forest, for example, utilizing **quantized decision trees** or **parallel processing** techniques to improve scalability.
- **Hybrid Models:** A possible direction for upcoming studies is the creation of hybrid models that merge the advantages of Random Forest with other algorithms such as **Gradient Boosting** or **Deep Learning**.
- **Further Interpretability Methods:** Investigating sophisticated methods to enhance the understanding of Random Forest, like implementing decision tree visualizations or rule-based frameworks, might provide hopeful avenues.

In conclusion, while **Random Forest** is a robust and dependable algorithm for various applications, but its scalability and efficiency are constrained when utilized with extensive datasets. Models such as **XGBoost** and **LightGBM** provide superior performance, memory optimization, and scalability, rendering them the favored selection for extensive data operations. However, Random Forest remains a viable alternative in situations where interpretability and smaller datasets take precedence.

Conclusion

In this research, we examined the constraints of the Random Forest algorithm when utilized on extensive datasets, concentrating on aspects such as performance, scalability, memory consumption, and interpretability. Although Random Forest is still a strong and adaptable model, particularly for small to medium datasets, it encounters considerable difficulties when processing large-scale data. As the size of the dataset and the dimensionality of features expand, the training duration, memory consumption, and prediction time of Random Forest increase disproportionately, rendering it less appropriate for real-time applications or environments with limited resources.

Comparative models like XGBoost and Light GBM show exceptional effectiveness and scalability, especially in situations involving high-dimensional and sparse data. These models are fine-tuned for quicker computations, improved memory efficiency, and possess a greater capacity for managing extensive datasets. Furthermore, the comprehensibility of Random Forest continues to be a significant issue, with other models like Explainable Boosting Machines (EBMs) providing enhanced clarity without compromising significantly on precision.

Although Random Forest excels in handling non-linear relationships and remains easy to use for specific applications, this research indicates that for extensive datasets, users ought to explore other options like XGBoost or LightGBM, which provide enhanced scalability and effectiveness. Additionally, upcoming studies might aim at refining Random Forest to boost its scalability or investigate hybrid models that merge the advantages of various algorithms.

In summary, Random Forest remains an effective model in machine learning; however, it is vital to consider its drawbacks in relation to the particular demands of the dataset and the issue being addressed. Selecting the appropriate algorithm based on dataset size, computational capabilities, and the necessity for clarity is crucial for obtaining optimal outcomes in extensive data evaluation.

References

1. Breiman, L. (2001). Random forests. *Machine Learning*, 45(1), 5-32. <https://doi.org/10.1023/A:1010933404324>
2. Cutler, D. R., Edwards Jr, T. C., Beard, K. H., Cutler, A., Hess, K. T., Gibson, J., & Lawler, J. J. (2007). Random forests for classification in ecology. *Ecology*, 88(11), 2783-2792. <https://doi.org/10.1890/07-0539.1>
3. Pal, M. (2005). Random forest classifier for remote sensing categorization. *International Journal of Remote Sensing*, 26(1), 217-222. <https://doi.org/10.1080/0143116042000237855>
4. Oshiro, T. M., Perez, P. S., & Costa, A. P. (2012). What is the number of trees in a random forest? *Machine Learning and Data Mining in Pattern Detection*, 154-168. https://doi.org/10.1007/978-3-642-31653-4_15
5. Rodriguez-Galiano, V. F., Ghimire, B., Rogan, J., Chica-Olmo, M., & Rigol-Sanchez, J. P. (2015). An evaluation of the efficiency of a random forest classifier for land-cover categorization. *ISPRS Journal of Photogrammetry and Remote Sensing*, 102, 29-39. <https://doi.org/10.1016/j.isprsjprs.2015.01.004>
6. Banerjee, S., Roy, P. S., & Saha, S. K. (2018). Sparse data and its effects on machine learning. *Journal of Big Data*, 5(1), 9-25. <https://doi.org/10.1186/s40537-018-0122-0>
7. Caruana, R., & Niculescu-Mizil, A. (2006). An empirical comparison of supervised learning algorithms. In *Proceedings of the 23rd International Conference on Machine Learning* (pp. 161-168). ACM. <https://doi.org/10.1145/1143844.1143865>
8. Chen, T., & Guestrin, C. (2016). XGBoost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining* (pp. 785-794). ACM. <https://doi.org/10.1145/2939672.2939785>
9. Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., & Ma, W. (2017). LightGBM: A highly efficient gradient boosting decision tree. In *Progress in Neural Information Processing Systems* (pp. 3146-3154). <https://arxiv.org/abs/1711.01230>