



**Sunbeam Institute of Information Technology
Pune and Karad**

Module – Data Structures and Algorithms

Email – devendra.dhande@sunbeaminfo.com



Sunbeam Infotech

www.sunbeaminfo.com

Infix to Postfix Conversion

- Process each element of infix expression from left to right
- If element is Operand
 - Append it to the postfix expression
- If element is Operator
 - If priority of topmost element (Operator) of stack is greater or equal to current element (Operator), pop topmost element from stack and append it to postfix expression
 - Repeat above step if required
 - Push element on stack
- Pop all remaining elements (Operators) from stack one by one and append them into the postfix expression
- e.g. $a * b / c * d + e - f * h + i$



Sunbeam Infotech

www.sunbeaminfo.com

Infix to Prefix Conversion

- Process each element of infix expression from right to left
- If element is Operand
 - Append it to the prefix expression
- If element is Operator
 - If priority of topmost element of stack is greater than current element (Operator), pop topmost element from stack and append it to prefix expression
 - Repeat above step if required
 - Push element on stack
- Pop all remaining elements (Operators) from stack one by one and append them into the prefix expression
- Reverse prefix expression
- e.g. $a * b / c * d + e - f * h + i$



Sunbeam Infotech

www.sunbeaminfo.com

Postfix Evaluation

- Process each element of postfix expression from left to right
- If element is operand
 - Push it on a stack
- If element is operator
 - Pop two elements (Operands) from stack, in such a way that
 - Op2 – first popped element
 - Op1 – second popped element
 - Perform current element (Operator) operation between Op1 and Op2
 - Again push back result onto the stack
- When single value will remain on stack, it is final result
- e.g. $4\ 5\ 6\ *\ 3\ /\ +\ 9\ +\ 7\ -$



Sunbeam Infotech

www.sunbeaminfo.com

Prefix Evaluation

- Process each element of prefix expression from right to left
- If element is operand
 - Push it on a stack
- If element is operator
 - Pop two elements (Operands) from stack, in such a way that
 - Op1 – first popped element
 - Op2 – second popped element
 - Perform current element (Operator) operation between Op1 and Op2
 - Again push back result onto the stack
- When single value will remain on stack, it is final result
- e.g. - + + 4 / * 5 6 3 9 7



Thank you!

Devendra Dhande

<devendra.dhande@sunbeaminfo.com>

