LEARNING TO LOVE **FORMS**

THE AJAX EXPERIENCE 2007



Send us a me	ssage	
Name		
Email		
Message		
	Go	



FORM **Element** establishes a form

ACTION is the only required attribute and should always be a URI

METHOD defaults to "get"

NAME is depreciated; use ID instead



FIEDSET **Element** used to group related fields

LEGEND **Element**used to provide a caption for
a FIELDSET

Containing FORM Controls

P or DTV sensible choices, but not very accurate (except in certain instances)

OI, or UI, most forms are lists of questions or form controls, so these are better

Send us a message Name Ermail Message Go

```
<form id="contact-form" action="/action-page.php" method="post">
 <fieldset>
   <legend>Send us a message</legend>
   <!-- form control -->
   <!-- form control -->
   <!-- form control -->
 </fieldset>
</form>
```

```
<form id="contact-form" action="/action-page.php" method="post">
 <fieldset>
  <legend>Send us a message</legend>
  <01>
    <!-- form control -->
    <!-- form control -->
    <!-- form control -->
  </fieldset>
</form>
```

Send us a me	ssage
Name	
Email	
Message	
	Go

INPUT Text Control

type="name" is a basic text
input field

(also type="password" for content you want hidden)

NAME **vs.** ID

NAME is for the back end

ID is for the front end

Send us a me	ssage
Name	
Email	
Message	
	Go

TEXTAREA

a multiline text form control

requires ROWS and COLS attributes!!!



Working with LABEL this element provides to means of associating its content with a form control:

implicit association
LABEL wraps the form
control and the text

explicit association

LABEL'S FOR attribute is an

ID reference to the form

control

Βι	itte	on	S


trigger events in a form; use either INPUT or BUTTON element

Common TYPEs

submit - submits the form;
default button type

reset - resets all form control values back to their defaults when the page loaded






```
<form id="contact-form" action="#" method="post">
  <fieldset>
   <leqend>Send us a message</leqend>
    <01>
     <label for="contact-name">Name</label>
         <input type="text" id="contact-name"</pre>
                name="name" />
     <label for="contact-email">Email</label>
         <input type="text" id="contact-email"</pre>
                name="email" />
     <label for="contact-message">Message</label>
         <textarea id="contact-message"
                   name="message" rows="4"
                   cols="30"></textarea>
   <button type="submit">Go</button>
 </fieldset>
</form>
```

```
body {
   font: 62.5%
"Lucida Sans Unicode",
"Lucida Grande",
sans-serif;
}
ol, ul, p {
   font-size: 1.2em;
   line-height: 1.5;
}
```




```
form, fieldset, legend {
 border: 0;
 padding: 0;
 margin: 0;
legend {
  font-size: 2em;
form ol, form ul {
  list-style: none;
 margin: 0;
 padding: 0;
```



```
form li {
  margin: 0 0 .75em;
}
label {
  display: block;
}
input, textarea {
  width: 250px;
}
```



```
form li {
   clear: both;
   margin: 0 0 .75em;
   padding: 0;
}
label {
   display: block;
   float: left;
   line-height: 1.6;
   margin-right: 10px;
   text-align: right;
   width: 120px;
}
```



```
legend {
  font-size: 2em;
  line-height: 1.8;
  padding-bottom: .5em;
}
button {
  margin-left: 130px;
  cursor: pointer;
}
```

Send us a message Name Email Message Gio

```
label:after {
  content: ':';
input, textarea {
 background: #ddd;
  width: 250px;
input:focus,
textarea: focus {
  background: #fff;
/* Some styles to get
   the baselines to
   match & to unify the
   type used */
```

Send us a message

```
Name. Aaron Gustafson

Email: aaron@easy designs.net

Message: I would like to know more about how to style forms

GO
```


SIDEBAR: BUTTONS



```
body {
                                 label:after {
  font: 62.5% "Lucida Sans
                                    content: ':';
    Unicode", "Lucida Grande",
    sans-serif:
                                 input, textarea {
                                   background: #ddd;
ol, ul, p {
                                   font: 1em Arial, Helvetica,
  font-size: 1.2em:
                                      sans-serif:
                                   padding: 1px 3px;
  line-height: 1.5;
                                   width: 250px;
form, fieldset, legend {
 border: 0:
                                 textarea {
 margin: 0;
                                    line-height: 1.3em;
                                   padding: 0 3px;
 padding: 0;
                                 input:focus, textarea:focus {
legend {
  font-size: 2em;
                                   background: #fff;
  line-height: 1.8;
 padding-bottom: .5em;
                                 button {
                                   background: #ffd100;
form ol, form ul {
                                   border: 2px outset #333;
  list-style: none;
                                    color: #333;
 margin: 0;
                                    cursor: pointer;
  padding: 0;
                                    font-size: .9em;
                                    font-weight: bold;
form li {
                                    letter-spacing: .3em;
  clear: both:
                                   margin-left: 130px;
 margin: 0 0 .75em;
                                   padding: .2em .5em;
                                   text-transform: uppercase;
  padding: 0;
label {
  display: block;
  float: left;
  line-height: 1.6;
 margin-right: 10px;
  text-align: right;
  width: 120px;
```

Send us a message

Name:		
Email:		
Subject:	I noticed a website error	Ţ
Message:	I noticed a website error I have a question Other	N
	GO	



SELECTion Lists allows selection of one or more OPTIONS

On OPTION elements, the VALUE attribute is optional (contents are submitted by default)

```
<form id="contact-form" action="#" method="post">
 <fieldset>
  <legend>Send us a message</legend>
   <01>
    <label</li>
        for="contact-subject">Subject</label>
       <select id="contact-subject"</pre>
                name="subject">
        <option value="Error">I noticed a
         website error</option>
        <option value="Question">I have a
         question
        <option>Other</option>
       </select>
  <button type="submit">Go</button>
 </fieldset>
</form>
```

SIDEBAR: OPTGROUPS

```
What is your favorite kind of fruit?

Apples

Golden Delicious

Granny Smith

Macintosh

Red Delicious

Berries

Blackberries

Hueberries

Raspberries
```



```
select {
  background: #ddd;
  width: 260px;
  /* width is *usually*
        the input width +
        input padding +
        4px */
}
input:focus,
textarea:focus,
select:focus {
  background: #fff;
}
```



SIDEBAR: SELECTS

WINDOWS XP



OS X







Nested FIELDSETs a great way to organize radio or checkbox groups

The LEGEND is the question or statement

Lists organize the possible responses (OL or UL)

implicit LABELS provide an easy way to style in IE6

```
<1i>>
 <fieldset class="radio">
  <legend>I would prefer to be
   contacted by</legend>
  <u1>
   <label><input type="radio"</pre>
    name="method" value="email" />
    email</label>
   <label><input type="radio"</pre>
    name="method" value="phone" />
    phone</label>
  </fieldset>
```



```
.radio legend {
  font-size: 1em;
  line-height: 1.5;
  padding: 0 0 0 6px;
  margin: 0;
}
.radio label {
  display: inline;
  width: auto;
  margin: 0;
}
```



```
.radio {
  margin-left: 125px;
.radio ul {
  font-size: 1em;
  margin: .3em 0 0;
.radio label:after {
  content: '';
label input {
 background:
   transparent;
  width: auto;
```



```
.radio li {
  float: left;
  margin: 0;
  width: 48%;
  clear: none;
}
label input {
  width: auto;
  position: relative;
  top: 2px;
}
```




```
.radio legend {
  font-size: lem;
  line-height: 1.5;
  padding: 0 0 0 6px;
  margin: 0;
  max-width: 270px;
  width: 270px;
}
```



```
.radio legend span {
  display: block;
  width: 270px;
}
```







Confirmations
a little CLASSification goes a
long way

SIMPLE FORM: CONTACT US



SIMPLE FORM: CONTACT US

```
.confirm label {
  display: block;
  float: none;
  margin-left: 125px;
  text-align: left;
  width: 270px;
}
```



SIMPLE FORM: CONTACT US

```
.confirm {
   margin-bottom: 1.4em;
}
.radio label:after,
.confirm label:after {
   content: '';
}
```

Send us a message Name: Email: Phone: I noticed a website error Subject: Message: would prefer to be contacted by email. O phone Please add me to your mailing list GO

HORRE FORMS FORMS

Search this site for GO



POST vs. GET

Search forms are traditionally GET requests to allow the action page (i.e. the results) to be bookmarkable.

Search this site for GO

You need something
Sometimes a FIELDSET is
unnecessary, but in XHTML,
you need something to wrap
the contents of a form

```
<form id="search-form" action="/action-page.php" method="get">

  <!-- the rest of our form will go here -->

  </form>
```



Easy-peasy

Search this site for GO

It's a BUTTON big shock, I know

```
body {
  background: #54af44;
  font: 62.5% "Lucida
  Sans Unicode", "Lucida
  Grande", sans-serif;
}
ol, ul, p {
  font-size: 1.2em;
  line-height: 1.5;
}
```

```
Search this site for Go
```

```
label {
  line-height: 2em;
}
input {
  border: 1px solid #c00;
  background: #ebebeb;
  margin: 0 .5em;
  padding: 2px 4px;
}
input:focus {
  background: #fff;
}
```

```
Search this site for
```

```
button {
  background: #c00;
  border: 0;
  color: #fff;
  cursor: pointer;
  font-size: .9em;
  font-weight: bold;
  letter-spacing: .1em;
  padding: 2px 8px;
  text-transform:
    uppercase;
}
```


```
Search this site for GO
```

Post Date: 01 ▼ January ▼ 2007 ▼



Getting organized

```
<fieldset class="date">
  <!-- the rest will go here -->
</fieldset>
```



Not really a LABEL



Not just a SELECT we need some LABELing



And so on



And so forth

```
<fieldset class="date">
 <legend>Post Date</legend>
 <01>
  <1i>>
    <label for="date-day">Date</label>
   <1i>>
    <label for="date-month">Month</label>
   <1i>i>
    <label for="date-year">Year</label>
    <select id="date-year" name="year">
     <option>2007</option>
     <option>2008</option>
    </select>
  </fieldset>
```

```
body {
  background: #54af44;
   font: 62.5% "Lucida
   Sans Unicode", "Lucida
   Grande", sans-serif;
ol, ul, p, legend {
  font-size: 1.2em;
  line-height: 1.5;
legend {
  color: #000;
```

```
Post Date

1. Date 01 
2. Month January 
3. Year 2007
```

```
.date {
  border: 0;
  padding: 0;
}
.date ol {
  list-style: none;
  margin: 0 0 0 130px;
  padding: 0;
}
```

```
Post Date

Date 01 

Month January

Year 2007
```

```
.date li {
  float: left;
}
```

```
Post Date
                 Date 01 ▼ Month January ▼ Year 2007 ▼
```

```
.date select {
  background: #e2efe0;
  margin: 0 .25em 0 0;
}
.date select:focus {
  background: #fff;
}
```

```
Post Date
                 Date 01 - Month January - Year 2007 -
```

```
.date label {
  position: absolute;
  left: -999em;
}
```

```
Post Date
               01 ▼ January ▼ 2007 ▼
```


```
.date {
 border: 0;
 padding: 0;
 position: relative;
.date legend span {
 display: block;
 line-height: 1.6;
 text-align: right;
 width: 120px;
 position: absolute;
 top: 0;
 left: 0;
```

```
Post Date 01 ■ January ■ 2007 ■
```

```
.date legend
span:after {
  content: ":";
}
```


```
Post Date: 01 January 2007
```

Confine results to ○ within the last year ○ the month of January ▼ ○ a monthly range from the start of January 2006 ▼ ○ until the end of January 2006 ▼




Organization and coordination as with other elements, form components can have multiple CLASSifications

```
<fieldset class="radio related">
 <leqend>
  <span>Confine results to</span>
 </legend>
 <111>
  <1i>>
   <!-- year -->
  <1i>i>
  <!-- month -->
  <1i>i>
   <!-- range -->
  </fieldset>
```




Basic implicit LABEL nothing shocking here




LABELs can contain more than one form control

in our case, we have a radio INPUT as well as a SELECTION hox

```
<fieldset class="radio related">
 <leqend><span>Confine results to</span></leqend>
   <1i>>
    <label><input type="radio" name="confines" value="year" />
          within the last year</label>
   <1i>>
    <label>
      <input type="radio" name="confines"</pre>
       value="month" />
      the month of
      <select name="month">
       <option value="01">January</option>
       <option value="12">December</option>
      </select>
    </label>
   </111>
</fieldset>
```




How do I code that?!? think about it... what are the relationships of the fields?




We know the first bit

```
<fieldset class="radio related">
 <leqend><span>Confine results to</span></leqend>
   <1i>>
     <d1>
       \langle dt. \rangle
        <label>
           <input type="radio" name="confines"</pre>
             value="range" />
          a monthly range
         </label>
       </dt>
       < dd >
         <!-- related fields here -->
       </dd>
     </dl>
   </111>
</fieldset>
```



We need to organize this now

```
<fieldset class="radio related">
 <leqend><span>Confine results to</span></leqend>
   <1i>>
     <d1>
      \langle dt. \rangle
        <label><input type="radio" name="confines"...</pre>
      <dd>
        <01>
          <1i>>
           <!-- start -->
          <1i>>
           <!-- end -->
          </dd>
     </dl>
   </fieldset>
```



Simple explicit LABEL

```
<dd>>
 <01>
  <1i>>
   <label for="range-start">
     from the start of</label>
    <select id="range-start"</pre>
     name="range-start">
     <option value="2006-01">January
      2006</option>
     <option value="2006-12">December
      2006
    </select>
  <1i>>
   <!-- end -->
  </01>
</dd>
```



And again

```
<dd>>
 <01>
   <1i>>
    <label for="range-start">from the start of</label>
   \langle 1i \rangle
    <label for="range-end">
     until the end of</label>
    <select id="range-end"</pre>
     name="range-end">
      <option value="2006-01">January
       2006</option>
      <option value="2006-12">December
       2006</option>
    </select>
  </01>
</dd>
```

It's a lot of code...

```
<fieldset class="radio related">
  <legend><span>Confine results to</span></legend>
 <111>
   <1i>>
     <lahel>
       <input type="radio" name="confines" value="year" />
       within the last year</label>
   </1i>
   <1i>>
     <label>
       <input type="radio" name="confines" value="month" />
       the month of
       <select name="month">
         <option value="01">January</option>
       </select>
     </label>
   <1i>>
     <d1>
       < d+>
         <label>
           <input type="radio" name="confines" value="range" />
           a monthly range
         </label>
       </dt>
       <bb>
         <01>
           <1i>>
             <label for="range-start">from the start of</label>
             <select id="range-start" name="range-start">
               <option value="2006-01">January 2006</option>
             </select>
           <1i>>
             <label for="range-end">until the end of</label>
             <select id="range-end" name="range-end">
               <option value="2006-01">January 2006</option>
             </select>
           </dd>
     </dl>
   </fieldset>
```

...but the benefits are worth it

```
Confine results to
List of three items
 bullet
  Radio button (not checked) within the last year
 bullet
  Radio button (not checked) the month of
    Combo box January
 bullet
  Definition list of one item
    Radio button (not checked) a monthly range
  equals
    List of two items
     one: from the start of
      Combo box January 2006
     two: until the end of
      Combo box January 2006
    List end
  List end
List end
```

transcribed by Fangs

```
/* We'll save some space
   and inherit styles
   from .radio */
form ol, form ul,
form dl {
  list-style: none;
  margin: 0;
  padding: 0;
li ul, li ol {
  font-size: 1em;
```

```
Confine results to

Cowthin the last of the month of year January

a monthly range from until the the end start of of January January 2006
```

```
.related li {
  clear: both;
  float: none;
  margin: 0 0 .5em;
  width: auto;
}

/* For IE to recover from
  a strange margin */
.related li {
  zoom: 1;
}
```

```
Confine results to

within the last year

the month of January

a monthly range
from the start of January 2006

until the end of January 2006
```

```
<fieldset class="radio related">
    <legend><span>Confine results to</span></legend>

            <!-- year -->

            <!-- month -->

            <!-- range -->

            <!-- fieldset>
```

```
.related select {
  margin-left: .25em;
}
.related dd {
  margin: .5em 0 0;
  padding: 0 0 0 3em;
}
.related dd label {
  float: left;
  line-height: 1.9;
  width: 100px;
}
```

```
Confine results to

Within the last year

the month of January

a monthly range
from the start of January 2006

until the end of January 2006
```

```
.related legend span {
   display: block;
   line-height: 1.8;
   text-align: right;
   width: 120px;
   position: absolute;
   top: 0;
   left: -130px;
}
```

```
Confine results to Solution the last year
The month of January Solution
The monthly range
The monthly range
The monthly range
The start of January 2006 In the end of In t
```

MAKING THE MOST OF MESSAGES

MESSAGING: REQUIRED


Send us a message

Required fields are marked *.

Name 1/2		
Emai required		
Phone:		
Subject:	I noticed a website error	
Message:		

MESSAGING: REQUIRED

What is the * anyway? Well, it stands for something else and in HTML, the closest to that we have to convey that is the ABBR element.




MESSAGING: REQUIRED



If you want to go allout, you can but that seems like overkill

MESSAGING: REQUIRED



MESSAGING: REQUIRED

```
abbr {
  cursor: help;
  font-style: normal;
  border: 0;
}
```



Send us a message

Required fields are marked *.

Name*: Aaron Gustafson

Email*: aaron@easy-designs.net

Phone: 203 format: 123-456-7890

Subject*: I noticed a website error

Message*:

How should we emphasize important formatting info?



```
<1i>>
 <label for="contact-email">
   Email<abbr title="required">*</abbr>
 <input type="text" id="contact-email" name="email" />
<1i>>
 <label for="contact-phone">
   Phone<em
    class="msq"> format: 123-456-7890</em>
 </label>
 <input type="text" id="contact-phone" name="phone" />
<1i>>
 <label for="contact-subject">
   Subject<abbr title="required">*</abbr>
 <select id="contact-subject" name="subject">
   <option value="Error">I noticed a website error/option>
```



```
label em.msg {
  font-size: .8em;
  font-style: normal;
  line-height: 2.5;
}
```

Send us a message Required fields are marked *. Name*: Email*: Phone format: 123-456-7890 I noticed a website error Subject*: Message*:

```
label{
    ...
    position: relative;
}
label em.msg {
    color: #aaa;
    font-size: .8em;
    font-style: normal;
    line-height: 2.5;
    position: absolute;
    right: -266px;
    top: 0;
}
```

Send us a message Required fields are marked *. Name*: Email*: Phone: format: 123-456-7890 I noticed a website error Subject*: Message*:

```
Send us a message
Required fields are marked *.
                     Aaron Gustafson
            Name*:
                     aaron@easy-designs.net
            Email*:
                     203
            Phone:
                                           format: 123-456-7890
                     I noticed a website error
          Subject*:
         Message*:
```

Send us a message

We encountered 1 error while trying to process this form:

You forgot to include <u>your email address</u>

Required fields are marked *.

Name*:	Aaron Gustafson
Email*:	
Phone:	format: 123-456-7890
ubject*:	I noticed a website error ▼


< You forgot to fill in your email

How should we strongly emphasize even more important error advisories?


How should we highlight the field?

```
Aaron Gustafson


You forgot to fill in your email
format: 123 456 7890
I noticed a website error
Your homepage doesn't validate! And you call yourself a standardista.
```



```
strong.err {
  color: #ffdfdf;
  display: block;
  padding-left: 5px;
  text-align: left;
}
```



```
strong.err {
  color: #ffdfdf;
  display: block;
  line-height: 1.8;
  padding-left: 5px;
  text-align: left;
  white-space: nowrap;
  position: absolute;
  top: 0;
  left: 390px;
strong.err:before {
  content: "<"
```



```
.error input {
  border: 2px solid #b00;
  background: #ffdfdf;
}
.error input:focus {
  background: #fff;
}
```



How do we notify users of errors?

It is best to be upfront about errors encountered and to say, in plain language, what the user needs to do to fix it

and linking to the field with errors doesn't hurt


Send us a message

We encountered 1 error while trying to process this form:

You forgot to include your email address

Required fields are marked *.

Name*: Aaron Gustafsor



```
#errors {
  background: #ffdfdf;
  border: 2px solid #b00;
  color: #333;
  margin: .5em 0 1em;
  padding: 10px;
}
```

Send us a message We encountered 1 error while trying to process this form: You forgot to include your email address Required fields are marked *. Aaron Gustafson Name*: Email*: Phone: format: 123-456-7890 Subject* I noticed a website error Your homepage doesn't validate! And you call

format: 123-456-7890

MESSAGING: ERRORS

```
#errors p {
   margin: 0;
   padding: 0;
}
#errors ol {
   list-style: disc;
   margin: 0 0 0 20px;
}
```

Send us a message We encountered 1 error while trying to process this form: • You forgot to include your email address Required fields are marked *. Name*: Aaron Gustafson Email*: < You

I noticed a website error

Your homepage doesn't validate! And you call

Phone:

Subject*:

Message*:

```
#errors a {
  color: #b00;
}
```

Send us a message We encountered 1 error while trying to process this form: You forgot to include your email address Required fields are marked *. Aaron Gustafson Name*: Email*: Phone: format: 123-456-7890 I noticed a website error Subject*: Your homepage doesn't validate! And you call Message*:

PARTING ADVICE

- treat forms like any other piece of (X)HTML
- •be aware of browser inconsistencies & make accommodations (when possible)
- break a complex form into bite-size chunks
- ·look for ways to provide richer meaning/a better experience
- ·apply your CSS layout knowledge for the rest of the page to a form
- ·don't over-complicate form design
- · learn to love forms

FORMS ARE **NECESSARILY**

LEARNING TO LOVE **FORMS**

THE AJAX EXPERIENCE 2007