

# Development of algorithms for generating connected midsurfaces using feature information in thin-walled parts

PhD Defense Presentation

by

Yogesh H. Kulkarni

Guided by Dr. Anil Sahasrabudhe (Guide) and Dr. Mukund Kale (Co-guide)

21 January 2017


# Agenda

- Introduction
- Literature Survey
- Proposed System
- Model Defeaturing
- Feature Generalization
- Midcurve-Midsurface Computation
- Topological Validation
- Case Studies
- Conclusions

# Introduction

# Introduction


- Necessity of Time-to-market
- Quicker validation
- Modern - Digital Product Development
- CAD-CAE Workflow
- Components of Model Simplification
- Dimension Reduction: Midsurface, Bar




# Midsurface Advantages

- Thin-walled : Sheet Metal, Plastics
- Expensive Solid Mesh elements
- Advantages of Shell elements
- Comparison of results
- Lesser computations/time.

	thick	thin	very thin
Lengt / thickness	~5 to ~10	~10 to ~100	> ~100
physical characteristics	transverse shear deformations $\epsilon_{13} \neq 0$	negligible transverse shear deformations $\epsilon_{13} \approx 0$	geometrically non-linear



1D beam model  
 $N=2$   $E=1$   
 Total DOF =  $6 \times 2 = 12$



$N = 909$   $E = 800$   
 Total dof =  $909 \times 6 = 5454$   
 2D shell mesh




3D Tetra mesh  
 $N = 17,448$   $E = 9,569$   
 Total dof =  $17,448 \times 3 = 52,344$

	Nodes	Elements	Stress N/mm <sup>2</sup>	Displacement mm
Analytical	–	–	105	4.23
1D	2	1	105	4.23
2D	909	800	103	4.21
3D	17,448	9,569	104	4.21

# Motivation for Research in Midsurface


- 60%+ of analyst time for Idealization (Sandia report)
- Recent commercial results
- Variety of Midsurface Errors
- Process/tools of corrections
- Quality Midsurface, a must



# Literature Survey

# Traditional CAD-CAE Transition Approach

- Input formats
- Elimination of Details - Defeaturing
- Dimension Reduction – Medial computation
- Validation
- Output – Idealized Geometry





# CAD Model Simplification

- Feature Recognition-based: Hamdi, Belaziz
- Decomposition-based: SH Lee, B Kim
- Feature-based: Dabke, Smit




Fig.4 An example of feature-based solid modeling






Fig.5 A rearranged feature tree and its results

# Midsurface Development Milestones




# Medial Axis Transform (MAT)

- Blum, Robinson, Ramanathan, etc
- Maximal circle/ball, loci of centers
- Defined for any input shape
- Reversible
- Spurious Branches




# Chordal Axis Transform (CAT)

- Prasad, Quadros, etc
- Constrained Delaunay Triangulation
- Any input shape
- Missing ends
- Does not mimic well




# Thinning

- Montanari, Aichholzer, etc.
- Offset Inside
- Intersection events
- Spurious Branches




# Midsurface Abstraction (MA)

- Rezayat, S Kim, Sheen
- Detect Face Pairs
- Midsurface Patches
- Extend – Trim
- Most representative
- Complex, with errors
- Commercially adopted






# Feature-based Midsurface

- Stolt, Robinson, Boussuge
- Single Feature + MAT
- Decomposition + Feature Recognition/MA
- No feature interaction



# Commercial Midsurface

- CAD : Unigraphics NX, Inventor
- CAE : Hypermesh, MSc Apex
- MA based: Auto + Manual
- Quality issues





# Observations from Literature Survey


- Most are Brep based and very few leverage feature information
- Model Defeathering
  - Selection of features to remove depends on domain, analysis type, etc.
  - Most approaches are feature recognition based and size based.
  - Feature based deterministic approaches are less, and they still use size criterion
  - Size based use full feature dimensions
- Midsurface Generation:
  - Formal approaches: any shape but need post processing
  - Heuristic approaches: More practical, but complexities in Pair detection, Joining
- Limited in the range of
  - input model geometries (say, only planar or analytic surfaces),
  - feature types (say, only extruded, positive primitives) and
  - connection types (say, only, parallel, or perpendicular)

# Research Objectives

- To develop a system to generate a quality midsurface of feature based CAD model.
- To develop defeaturing algorithms to simplify CAD feature model while retaining the gross shape.
- To develop algorithms to transform existing sheet metal features to a finite set of generalized features.
- To develop algorithms for generating quality midsurfaces leveraging generalized feature based CAD model and cellular decomposition covering a wide variety of topological connectivities.
- To come up with an approach to topologically validate the generated midsurface.
- To implement a software system incorporating above algorithms and demonstrate the efficacy of the proposed approach.


# Research Scope

- Sheet Metal Parts: 40% Manufacturing parts
- Thin-walled Constant Thickness parts
- Feature based Autodesk Inventor CAD models



# Proposed System - MidAS



- Input: Feature based Autodesk Inventor CAD Model
- Each step, a module, OO Interfaces
- Model Defeaturing
- Feature Generalization
- Cellular Decomposition
- Midsurface Patch generation (incl Midcurve Computation)
- Dormant Features Reapplication
- Output: Midsurface



# Model Defeaturing


# Proposed Approach

- Need: More features, difficult computation
- Objective: Remove irrelevant features, but retain gross shape
- Phase I: Sheet Metal Features Taxonomy based
- Phase II: Remnant Feature Size based
- Phase III: Dormant feature based




# Sheet Metal Features Taxonomy

- Sheet metal features classified into categories .
- Primary (**P**) : Principal. Relevant.
- Secondary (**S**): Relevant if  $>$  Threshold.
- Tertiary/Auxiliary (**T**): Superficial. Irrelevant.
- Feature Groups (**G**): Collections Relevant if  $>$  Threshold.



# Phase I : Defeaturing based on Sheet Metal Feature Taxonomy


- Identification based on Taxonomy
- Primary features: Cannot be removed as they directly affect the gross shape
- Secondary and Group features: Removed if their sizes are below the threshold
- Tertiary features: Removed irrespective of their sizes






# Phase II : Defeaturing based on Remnant Feature Size based

- Features when booleaned, are consumed
- Erroneous if defeaturing decision is based on full feature dimensions
- Approach to detect and compute size of the remnant size of features
- Size criterion: summation of face areas



# Phase III : Defeaturing based on Dormant features


- Large Negative but relevant features
- Hindrance to midsurface computation
- Tool bodies cached
- Re-applied after Midsurface computation



# Effectiveness of Model Defeaturing

Metrics: Percentage reduction in the number of faces.

$$pR = \left(1 - \frac{rF}{nF}\right) \times 100$$



$$pR = \left(1 - \frac{64}{259}\right) \times 100 = 75.29\%$$











# Summary: Model Defeaturing

- Limitations of existing approaches:
  - Feature Recognition unreliable
  - Dominance of size based selection
  - Wrong size computation
  - Loss of negative relevant features
- Contributions
  - Sheet Metal Features Taxonomy based Approach
  - Remnant Feature Approach
  - Dormant Feature Approach
  - Effective reduction in Features/faces, while retaining the Gross Shape

# Feature Generalization

# Proposed Approach


- Need: Presence of a large variety of types of features
- Challenging to develop feature based algorithms
- Proposed: New CAD representation with Loft as generalized feature form
- Objective: To transform given feature tree to generalized feature tree
- No loss of 'feature'-ness
- No loss of re-generation

Feature type	Section of the feature
Wall	
Drawing	
Bending	
Cutout	
Hole	
Flange	
Lancing	
Coining	
Bridging	
Slot	


# Proposed New Form Features

- ABLE:
  - Affine Transformations
  - Booleans
  - Lofts
  - Entities
- CAD model as list of ABLE entities

$$\Omega\mathcal{L}^{subtype,3}[\{0, guide, 0|C_{0,1,2}\}((sketch)^{<1-n>})]$$



# Wall - Loft equivalent



## Face, Wall

**Extrude** is created by extracting *sketch* of the “Wall” feature and giving sheet metal thickness as the distance for extrusion.

$\Omega\mathcal{L}^{EnD,3}[\{0, thickness, 0|C_0\}((sketch)^{<1>})]$  Where,


$sketch = \Pi\mathcal{C}^{S,1}[\{\}(profile)^{<1><2-n>})]$

$profile = \Pi\mathcal{C}^{P,1}[\{0, 0, C_{0|1|2}\}(curve)^{<1-n>})]$

$curve = \Omega\mathcal{L}^{C,1}[\{0, 0, C_{0|1|2}\}(\bar{s})^{<1-n>})]$



# Flange - Loft equivalent



## Flange

**Sweep** is created by creating *guide* using bend radius, offset distance and a planar rectangular profile as *sketch*.

$$\Omega\mathcal{L}^{SnD,3}[\{0, guide, 0|C_0\}((rectangle)^{<1>})]$$





# Transformation to ABLE

CAD Features

Model

*ABLE* Features

Model



# Transformation in ABLE representation

- +  $Extrusion2 = \Omega\mathcal{L}^{EnD,3}[\{0, edge1, 0|C_0\}((sketch1)^{<1>})]$
- +  $Sweep1 = \Omega\mathcal{L}^{SnD,3}[\{0, guide1, 0|C_0\}((sketch2)^{<1>})],$   
 $\Omega\mathcal{B}^{U,3}[\{\}(model, Sweep1)]$
- +  $Sweep2 = \Omega\mathcal{L}^{SnD,3}[\{0, guide2, 0|C_0\}((sketch3)^{<1>})],$   
 $\Omega\mathcal{B}^{U,3}[\{\}(model, Sweep2)]$
- +  $Sweep3 = \Omega\mathcal{L}^{SnD,3}[\{0, guide3, 0|C_0\}((sketch4)^{<1>})],$   
 $\Omega\mathcal{B}^{U,3}[\{\}(model, Sweep3)]$
- +  $Sweep4 = \Omega\mathcal{L}^{SnD,3}[\{0, guide4, 0|C_0\}((sketch5)^{<1>})],$   
 $\Omega\mathcal{B}^{U,3}[\{\}(model, Sweep4)]$


# Summary: Feature Generalization

- Limitations of existing approaches:
  - Plethora of feature types
  - Lack of generic notation for CAD features/entities
- Contributions:
  - New representation scheme for Feature-based CAD
  - Loft as generalized feature form
  - Sheet Metal features as Lofts


# Midsurface Generation

# Existing Approach - MA

- Limitations
  - Face Pairing challenges
  - Patch Joining challenges
- Proposed Cellular decomposition
- Cell classification, delegation




(a) Full model view



(a) Missing target

(b) Multiple targets


(c) Angled targets




(b) Magnified view

# Interface Configurations


L



T





X



# Feature-based Cellular Decomposition



- Features Boolean types are changed from Union to “New”
- Concave Edge partitioning in the feature influence zone.
- Result:
  - non overlapping cells with feature owners
  - Face interface between cells
- Graph: Cells at nodes and overlapping faces at edges
- Classification:
  - Solid Cells (Scells)
  - Interface Cells (iCells)





# Proposed Approach



- Graph to bring connectivity information
- Makes overall complexity of original part irrelevant
- Rules:
  - sCells compute Midsurface patches
  - iCells join incident midsurface patches
- Delegation of computation
- Generic and not type spec




- $n_1 = sCell_1 = f'_1$
- $n_2 = iCell_1 = f''_1 f'_2$
- $n_3 = sCell_2 = f'_2$
- $e_{12} = O_1$
- $e_{23} = O_2$

# Midsurface Patches in Solid Cells

- Two cases
  - **Offset:** profile >> guide : offset the profile face
  - **Midcurve:** profile << guide: compute midcurve, sweep



(a) Patches, 2d view















(b) Patches, 3d view

# Generation of Midcurve

- Partition given shape into sub-shapes
- Midcurves can be generated for each sub-shape.
- Such individual Midcurves are joined


I L T X K O Y  
H U S D Q W

# Polygon Decomposition


Shape	Bayazit	Proposed
		
		
		
		

# Midcurve Computation


Each partitioning edge inserted during the decomposition is called as a 'chord'.



Midcurves are generated for individual polygons that are longer length-wise on both sides of the 'chord'.




When curves do not meet at the chord', they are extended upto the midcurve.




# Results


Glass profile by Fischer [11].




Profile by Ramanathan [24].




Plastic Part profile by Sheen [29].




# Connecting Patches





(a) Expected adjustments




(b)  $sCell - iCell$  scenario



(c)  $iCell - iCell$  scenario




# Connection Scenarios









(a) Model



(b) Decomposition



(c) 3 *sCells*, 1 *iCell*




(d) Midsurface


Figure 18: Midsurface for Curved Y Model



(a) Model



(b) Decomposition



(c) 3 *sCells*, 1 *iCell*



(d) Midsurface


Figure 19: Midsurface for Wavy Model




(a) Model



(b) Decomposition



(c) 4 *sCells*, 1 *iCell*




(d) Midsurface

# Summary: Midsurface Generation

- Limitations of existing approaches:
  - Post processing in formal approaches
  - Face pair detection and Patch Joining problems
  - Manual corrections
- Contributions:
  - Feature based Cellular Decomposition
  - Cellular Graph for connectivity and delegation of computation
  - Midcurve generation using enhanced polygon decomposition and cellular midcurve computation
  - Midsurface by generic rules

# Re-application of Dormant Features





# Topological Validation

# Validation Types

- Manual Inspection for gaps, errors
- Tools based inspection: Hausdorff distance.
- Recent: Topological Validation: Measures topological entities of the midsurface match with the ones predicted.

# Topological Validation by Lockett

L-Junction



2



1

90

0

2

3-way (T)



2



2

180

1

3

3-way (Y)



3

3

360

0

3

# Approaches for Topological validation











## Solid-to-Surface

- Find relationship between topological entities of a thin-solid and its corresponding Midsurface.
- See if the predicated Midsurface entities validate the non-manifold equation

## Surface-to-Solid











- Predict the topological entities of possible thin-wall solid that would be source of the given Midsurface.
- These predicted entities can be validated against entities of the original thin-solid as well as with the manifold equation

# Solid to Surface

Solid	Midsurface	Solid Cells	Midsurface Cells	Predicted Topological Entities
		$sCell_0^3$	$mCell_0^2$	$1f + (4 - 0)e + (4 - 2 \times 0)v$ $= 1f + 4e + 4v$
		$2 \times sCell_1^3 + iCell_2^3$	$2 \times mCell_1^2 + mCell_2^1$	$2 \times (1f + (4 - 1)e + (4 - 2 \times 1)v)$ $+ (1e + 2v)$ $= 2f + 7e + 6v$
		$3 \times sCell_1^3 + iCell_3^3$	$3 \times mCell_1^2 + mCell_3^1$	$3 \times (1f + (4 - 1)e + (4 - 2 \times 1)v) + (1e + 2v) = 3f + 10e + 8v$
		$3 \times sCell_1^3 + iCell_3^3 + sCell_h^3$	$3 \times mCell_1^2 + mCell_3^1 + mCell_h^2$	$3 \times (1f + (4 - 1)e + (4 - 2 \times 1)v) + (1e + 2v) + (1e + 1v) = 3f + 11e + 9v$
		$2 \times sCell_1^3 + 2 \times iCell_2^2 + sCell_2^3$	$2 \times mCell_1^2 + 2 \times mCell_2^1 + mCell_2^2$	$2 \times (1f + (4 - 1)e + (4 - 2 \times 1)v) + 2 \times (1e + 2v) + (1f + (4 - 2)e + (4 - 2 \times 2)v) = 3f + 10e + 8v$



# Surface to Solid

<b>M</b>	$f$	$l_p$	$e_s$	$e_{sr}$	$e_r$	$e_{rr}$	$e_i$	$v_s$	$v_r$	$v_i$	$f_m$	$e_m$	$v_m$	$\chi_{m*}$	<b>Solid</b>
	1	0	4	0	0	0	0	4	0	0	6	12	8	2	
	2	2	2	4	1	0	0	4	2	0	8	18	12	2	
	3	2	3	6	1	0	0	6	2	0	11	27	18	2	
	3	2	3	6	1	0	1	6	2	1	12	30	20	2	
	3	2	2	4	2	2	0	4	4	0	10	24	16	2	

# Results

- Solid-Surface: Predict Midsurface entities
- Surface-Solid: Predict Solid entities
- Contribution:
  - New Topological Validation Formulation




Figure 7.11: Solid to Surface Transformation Approach for Bracket

- **Predicted number of manifold-faces:**

$$\begin{aligned} f_m &= 2f + e_s + l_p + e_i \\ &= 2 \times 15 + 3 + 9 + 5 = 47 \end{aligned}$$

- **Predicted number of manifold-edges:**

$$\begin{aligned} e_m &= 2(e_s + e_{sr} + e_{rr} + e_i) + \sum n_r e_r + v_s + v_i \\ &= 2(3 + 10 + 19 + 5) + (2 \times 12 + 4 \times 2) + 8 + 5 = 119 \end{aligned}$$

- **Predicted number of manifold-vertices:**

$$\begin{aligned} v_m &= 2(v_s + v_i) + \sum n_r v_r \\ &= 2 \times (8 + 5) + 2 \times 24 = 74 \end{aligned}$$

- **Predicted number of manifold-shells-holes:**

$$s_m = s = 1, h_m = r_i = 5, r_m = 2r_i = 10$$

- **Input midsurface's non-manifold equation's left side:  $\chi_{nml}$**

$$\begin{aligned} &= v - e + f \\ &= 32 - 46 + 15 = 1 \end{aligned}$$

- **Input midsurface's non-manifold equation's right side:  $\chi_{nmr}$**

$$\begin{aligned} &= s - h + r \\ &= 1 - 5 + 5 = 1 \end{aligned}$$

- **Solid's manifold equation's left side:  $\chi_{ml}$**

$$\begin{aligned} &= v_m - e_m + f_m \\ &= 74 - 119 + 47 = 2 \end{aligned}$$


- **Solid's manifold equation's right side:  $\chi_{mr}$**

$$\begin{aligned} &= 2(s_m - h_m) + r_m \\ &= 2(1 - 5) + 10 = 2 \end{aligned}$$



# Case studies

# MidAS Implementation



- Inventor Professional 2014 – Student edition
- Feature based 3D modeller based on ACIS kernel
- API support via VB.net






# Benchmarking





# Model Defeaturing



# Feature Generalization





# Cellular Decomposition - Midsurface











# Final Midsurface by Dormant re-application





# Test-case I : Bracket



# Test-case II: Stapler lower bottom



# Test-case III



# Conclusions

# Conclusions

- Development of Feature based Midsurface Computation approach
- Feature based Defeaturing: Taxonomy, Remnant, Dormant
- Feature generalization: Loft as a generic feature
- Leveraging Cellular Decomposition for 2D (midcurve), 3D (midsurface) computation
- Bi-directional Topological Validation of midsurface
- Demonstration of efficacy of the approach in the system implemented, called MidAS

# Research Contributions

- Feature-based CAD Algorithm paradigm: Simplification – Generalization – Decomposition – Cellular Graph
- Automatic defeaturing of sheet metal feature-based CAD model
  - Based on newly developed sheet metal features taxonomy
  - Based on newly developed, more accurate criteria of Remnant feature sizes
  - Based on newly developed approach of Dormant features
- Automatic transformation of sheet metal features to generalized features
  - Newly developed generalized CAD model representation, called ABLE
  - Transformation mapping of Sheet Metal features to Loft equivalents
- Automatic computation of Midsurface
  - Midcurve Computation: Enhanced Polygon Decomposition and newly developed cellular midcurve computation
  - Midsurface Computation: Cellular graph based, generic logic for connections.
- New Topological Validation formulation framework

# Future work

- Implementation:
  - Internal Development instead of using-API.
  - Adopting to different CAD modellers
- Domain:
  - More sheet metal features
  - Catering to Injection moulding domain
- Geometric Modelling:
  - Development of Feature based Cellular Kernel
  - Expansion of ABLE transformations to other fields such as Meshing



# Research Publications

- International Journals

1. July 2016, Leveraging feature generalization and decomposition to compute a well-connected midsurface, Yogesh Kulkarni, Anil Sahasrabudhe, Mukund Kale, Engineering with Computers, **Springer**
2. July 2016, Computation of Midsurface by Feature-based Simplification-Abstraction-Decomposition, Yogesh Kulkarni, Anil Sahasrabudhe, Mukund Kale, Jrnl of Comp and Info Sc in Eng, **ASME**
3. May 2015, Topological Validation of Midsurface Computed from Sheet Metal Part, Yogesh Kulkarni, Anil Sahasrabudhe, Mukund Kale, Computer-Aided Design and Applications, **Taylor & Francis**
4. June 2016, Defeaturing Sheet Metal Part Model based on Feature Information, Yogesh Kulkarni, Ravi Kumar Gupta, Anil Sahasrabudhe, Mukund Kale, Alain Bernard, Computer-Aided Design and Appl, **Taylor & Francis**
5. January 2017, Dimension-Reduction Technique for Polygons, Yogesh Kulkarni, Anil Sahasrabudhe, Mukund Kale, Intl. Journal of Computer Aided Engineering and Technology}, **Inderscience**

- International Conferences

1. June 2015, Defeaturing Sheet Metal Part Model based on Feature Information, Yogesh Kulkarni, Ravi Kumar Gupta, Anil Sahasrabudhe, Mukund Kale, Alain Bernard, Proceedings of CAD 15, **London**
2. December 2014, Formulating Midsurface using Shape Transformations of Form Features, Yogesh Kulkarni, Anil Sahasrabudhe, Mukund Kale, 5th Intl. and 26th AIMTDR, **IIT Guwahati**
3. December 2013, Strategies for using feature information in model simplification, Yogesh Kulkarni, Anil Sahasrabudhe, Mukund Kale, Intl. Conf. on CAE, **IIT Madras**
4. May 2013, Using Features for generation of Midsurface, Yogesh Kulkarni, Anil Sahasrabudhe, Mukund Kale, Intl. Conf. on Advances in Mech Eng, **COEP, India**

- National Conferences

1. January 2014, Midcurves Generation Algorithm for Thin Polygons, Yogesh Kulkarni, Anil Sahasrabudhe, Mukund Kale, Natl. Conf. on Emerging Trends in Eng and Science, **Asansol, India.**

Thank you