



## ACTIVATION FUNCTION

Introduction to ML, DL, AI and OpenVino

Session 09

Pramod Sharma

pramod.sharma@prasami.com

2

## Agenda




1/3/2024

*pra-sâmi*

3

## Forward and Back Propagation




1/3/2024

pra-sâmi

4

## Neural Network



1/3/2024

pra-sâmi

5

## Activation Function

1/3/2024

pra-sâmi

6

## Overview

- ❑ The choice of activation functions in Deep Neural Networks has a significant impact on the training dynamics and performance.

- ❑ Till very recently, the most successful and widely-used activation function was the Rectified Linear Unit (ReLU).

- ❑ Although various alternatives to ReLU have been proposed, none have managed to outperform it in most cases.



1/3/2024

linearly scaled Hyperbolic Tangent

pra-sâmi

7

## Activation Functions

- ❑ Activation functions is a function attached to each neuron in the network
  - ❖ It determines whether it should be activated ("fired") or not, based on whether each neuron's input is relevant for the model's prediction
- ❑ Activation functions also help normalize the output of each neuron to a range:
  - ❖ Between 1 and 0 or
  - ❖ Between -1 and 1
  - ❖ Or other desired ranges
- ❑ Need to be computationally lightweight
  - ❖ It is calculated for each neuron for every data instance (row)
- ❑ It's a mathematical gate that turns a neuron on or off


1/3/2024

pra-sâmi

8


## Activation Functions

- ❑ Binary Step function



- ❑ We already seen this in previous session!!!!

- ❑ Linear Activation Function



- ❑ That will be simple linear regression!
  - ❖ There may still be some use cases...

1/3/2024

pra-sâmi

9

## Non-Linear Activation Functions


- ❑ There are many popular activation functions
  - ❖ Sigmoid / Logistic
  - ❖ Softmax
  - ❖ Tanh (Hyperbolic Tangent)
  - ❖ ReLU (Rectified Linear Unit)
  - ❖ Leaky ReLU
  - ❖ Parametric ReLU
  - ❖ Swish
  - ❖ Lisht
  - ❖ Mish
- ❑ Stay tuned... it's an active research area...

1/3/2024

pra-sâmi

10

## Sigmoid



- ❑ Takes a real value as input and outputs another value between 0 and 1 i.e. [0,1]
- ❑ It's easy to work with; Most suitable as activation functions
- ❑ Non-linear, continuously differentiable, monotonic, and has a fixed output range
- ❑ Good for binary classification tasks

1/3/2024

pra-sâmi

14

## Sigmoid – drawbacks

- ❑ Towards either end, becomes sluggish
  - ❖ Problem of “vanishing gradients”
  - ❖ The network refuses to learn further or is drastically slow
  - ❖ Another reason why we need to scale values
- ❑ Its output isn't zero centered. It makes the gradient updates go too far in different directions.
  - ❖  $0 < \text{output} < 1$ , and it makes optimization harder
- ❑ Sigmoid saturates and kills gradients

1/3/2024

pra-sâmi

15

## Softmax Function

- ❑ In physics and statistical mechanics, it is known as the **Boltzmann** distribution or the **Gibbs** distribution.
- ❑ Formulated by the Austrian physicist and philosopher **Ludwig Boltzmann** in **1868**.
- ❑ In 1959, **Robert Duncan Luce** proposed the use of the Softmax function for reinforcement learning in his book “Individual Choice Behavior: A Theoretical Analysis”.
- ❑ Take vector of N values and convert into vector of N values with sum = 1
- ❑ Input values are natural numbers (Positive, Negative).
- ❑ Output is always numbers between 0 and 1 i.e.  $A = \{ a \mid \text{real}(a) \wedge 0 \leq a \leq 1 \}$

1/3/2024

pra-sâmi

16

## Softmax Function

- ❑ Softmax is multi-class logistic regression,
  - ❖ Takes vector of N values and converts into vector of N values with sum = 1
  - ❖ Input values are natural numbers (Positive, Negative).
  - ❖ Output is always numbers between 0 and 1 i.e.  $A = \{ a \mid \text{real}(a) \wedge 0 \leq a \leq 1 \}$
  - ❖ It is differentiable everywhere.

$$S(\vec{Z}) = \frac{e^{z_i}}{\sum_{j=1}^K e^{z_j}}$$

- ❑ Its helps in representing values as probabilities
  - ❖ Smaller the value, smaller the probability and vice versa

Like Sigmoid Activation function, Vanishing Gradient is still a problem!

- ❑ Its formula is very similar to Sigmoid function,
  - ❖ Sigmoid function is one special case of Softmax
- ❑ Softmax is very useful because it converts the scores to a normalized probability distribution
  - ❖ Invariably, multi-layer neural networks end in a penultimate layer which outputs real-valued scores,
  - ❖ It is non-linear in nature. So, it introduces non-linearity in the network enabling it to learn better.

1/3/2024

pra-sâmi

17

## Softmax Function

- ❑ Its helps in representing values as probabilities
  - ❖ Smaller the value, smaller the probability and vice versa

- ❑ Softmax is multi-class logistic regression,

- ❑ Its formula is very similar to Sigmoid function,
  - ❖ Sigmoid function is one special case of Softmax

$$\sigma(z) = \frac{1}{1 + e^{-z}}$$

$$S(\vec{Z}) = \frac{e^{z_i}}{\sum_{j=1}^K e^{z_j}}$$

- ❑ Invariably, multi-layer neural networks end in a penultimate layer which outputs real-valued scores,
- ❑ Softmax is very useful because it converts the scores to a normalized probability distribution,
- ❑ For this reason, we use a softmax function as the final layer of the neural network

1/3/2024

pra-sâmi

18

## Softmax vs. Sigmoid

- Softmax

$$\sigma(z) = \frac{1}{1 + e^{-z}}$$

- Sigmoid

$$S(\vec{Z}) = \frac{e^{z_i}}{\sum_{j=1}^K e^{z_j}}$$

- For single class value will be [ 0, x], Softmax

$$S(\vec{Z}) = \frac{e^{z_i}}{\sum_{j=1}^K e^{z_j}}$$

$$S(\vec{Z}) = \frac{e^{z_1}}{e^{z_1} + e^{z_2}}$$

$$S(X) = \frac{e^x}{e^0 + e^x}$$

$$S(X) = \frac{e^x}{1 + e^x}$$

1/3/2024

pra-sâmi

19

## Softmax vs. Argmax

- Both work the same way, Softmax is expected to be a differentiable alternative to argmax
- Argmax returns index of highest value and no idea about other values.
- It is common to train using the Softmax


1/3/2024

pra-sâmi



21

## Tanh



- ❑ Mathematically shifted version of the sigmoid function with
- ❑ Non-linear, but zero-centered
  - ❖ Very useful in hidden layers
  - ❖ Helps in centering the data around zero ( bring mean closer to zero). Learning next layer becomes easier.
- ❑ The gradient is stronger than sigmoid
  - ❖ Derivatives are steeper
- ❑ Other problems are similar to sigmoid

1/3/2024

pra-sâmi

22

## Tanh


- ❑ Advantage:
  - ❖ The negative inputs will be mapped negative and the zero inputs will be mapped near zero
  - ❖ The function is differentiable.
  - ❖ The function is monotonic while its derivative is not monotonic.
  - ❖ Faster convergence for two reason:
    - Steeper than Sigmoid function
    - Zero centric output
- ❑ Disadvantage:
  - ❖ Vanishing gradient have not gone away yet!
- ❑ Different research papers different views as to why it is better or even it is not always better!
- ❑ And the debate will continue...
- ❑ Early stages of design, Tanh in intermediate layer is a good starting point

1/3/2024

pra-sâmi

23

## Rectified Linear Units (ReLU)



- ❑ Non-linear function (almost)
- ❑ Better performance than Sigmoid or Tan in almost all models
- ❑ It avoids and rectifies vanishing gradient problem.
- ❑ ReLU is less computationally expensive than tanh and sigmoid because it involves simpler mathematical operations.
- ❑ Suitable for Hidden layers only.

1/3/2024

pra-sâmi

24

## Rectified Linear Units (ReLU)


- ❑ Some gradients can be fragile during training and can die.
- ❑ Could result in Dead Neurons.
- ❑ For activations in the region ( $x < 0$ ) of ReLU, gradient will be zero
  - ❖ Weights will not get adjusted during descent
  - ❖ Neurons which go into that state will stop responding to variations in error/ input
  - ❖ Dying ReLU problem
- ❑ The range of ReLU is  $[0, \infty]$ 
  - ❖ Can blow up the activation

1/3/2024

pra-sâmi

25

## Leaky ReLU




- ❑ Attempt to fix the “dying ReLU” problem by having a small negative slope (of 0.01, or so).
- ❑ LeakyRelu is a variant of ReLU ; allows a small, non-zero negative values
  - ❖  $R(z_i) = \begin{cases} z_i & \text{if } z_i \geq 0 \\ \alpha_i \cdot z_i & \text{if } z_i < 0 \end{cases}$
  - ❖ Work-under-progress : benefits across different architectures and domains still being investigated
- ❑ As it possess linearity, it can't be used for the complex Classification.
- ❑ Lags behind the Sigmoid and Tanh for some of the use cases.

1/3/2024

pra-sâmi

26

## Exponential Linear Unit (ELU)




- ❑ Converges faster ; Has alpha constant which should be positive number
- ❑ ELU is a strong alternative to ReLU.
- ❑ Unlike to ReLU, ELU can produce negative outputs.
- ❑ For  $x > 0$ , it can blow up the activation with the output range of  $[0, \infty]$ .

1/3/2024

pra-sâmi

27

## Parameterized ReLU



- ❑ A Parametric Rectified Linear Unit, or PReLU, is an activation function that generalizes the traditional rectified unit with a slope for negative values.
- ❑ The intuition is that different layers may require different types of nonlinearity.

1/3/2024

pra-sâmi

28

## Parameterized ReLU

$$F(z_i) = \begin{cases} z_i & \text{if } z_i \geq 0 \\ a_i \cdot z_i & \text{if } z_i < 0 \end{cases}$$

- ❑ Pick your own parameter
- ❑ In experiments with convolutional neural networks, PReLus for the initial layer have more positive slopes, i.e. closer to linear.
  - ❖ Since the filters of the upper layers are edge or texture detectors,
  - ❖ This shows a circumstance where positive and negative responses of filters are respected.
- ❑ In contrast, deeper layers have smaller coefficients
  - ❖ Model becomes more discriminative at later layers
  - ❖ While it wants to retain more information at earlier layers.

1/3/2024

pra-sâmi

29

## Challenges with ReLU


- ❑ The consistent problem is that its derivative is 0 for half of the values of the input  $x$  in the Function, i.e.  $f(x)=\max(0,x)$
- ❑ As parameter update algorithm, could used Stochastic Gradient Descent and other optimizers
  - ❖ If the parameter itself is 0, then that parameter will never be updated as it just assigns the parameter back to itself
  - ❖ Leading close to 40% Dead Neurons in the Neural network environment where  $z$  is negative
  - ❖ Various substitutes like Leaky ReLU Parameterized ReLU have **unsuccessfully** tried to devoid it of this issue.

1/3/2024

pra-sâmi

30

## Scaled ELU (SELU)




- ❑ Activation was introduced in a 2017 paper by Klambauer et al
- ❑ Properly initialization, the networks will self-normalize
  - ❖ Each layer's output will roughly be zero-centered with standard deviation equal to one
- ❑ Helps prevent the vanishing or exploding gradients problems

1/3/2024

pra-sâmi

31

## Gaussian Error Linear Unit (GELU)



The GELU ( $\mu = 0, \sigma = 1$ ), ReLU, and ELU( $\alpha = 1$ )


- ❑ Contrary to the ReLU, GELU weights its inputs by their value instead of thresholding them by their sign
- ❑ Defines as The GELU activation function is  $x * \Phi(x)$ ,
  - ❖ where  $\Phi(x)$  : the standard Gaussian cumulative distribution function refer scipy's `norm.cdf(x)`
  - $$\text{GELU}(x) = xP(X \leq x) = x\Phi(x)$$
  - ❖  $\approx 0.5x(1 + \tanh[\sqrt{2/\pi}(x + 0.044715x^3)])$
  - ❖ or  $x\sigma(1.702x)$ ,

1/3/2024

pra-sâmi

32

## Swish



- ❑ Google Brain Team proposed a new activation function:
  - ❖  $f(x) = x \cdot \text{sigmoid}(x)$
- ❑ Experiments show that Swish tends to work better than ReLU on deeper models across a number of challenging data sets
  - ❖ Simply replacing ReLUs with Swish units improves top-1 classification accuracy on ImageNet by 0.9% for Mobile NASNetA and 0.6% for Inception-ResNet-v2
- ❑ The simplicity of Swish and its similarity to ReLU make it easy for practitioners to replace ReLUs with Swish units in any neural network.
- ❑ Swish is a smooth, non-monotonic function that consistently matches or outperforms ReLU on deep networks

1/3/2024

pra-sâmi

33

## Swish


- ❑ Unbounded above and bounded below
  - ❖ Non-monotonic attribute that actually creates the difference
- ❑ We can train deeper Swish networks than ReLU networks when using BatchNorm (Ioffe & Szegedy, 2015) despite having gradient squishing property
- ❑ With MNIST data set, when Swish and ReLU are compared, both activation functions achieve similar performances up to 40 layers.
- ❑ Swish outperforms ReLU by a large margin in the range between 40 and 50 layers
  - ❖ For less than 40 layers, performance is comparable
- ❑ In very deep networks, Swish achieves higher test accuracy than ReLU.
- ❑ Swish outperforms ReLU on every batch size, suggesting that the performance difference between the two activation functions remains even when varying the batch size.
- ❑ Gradient descent problem was still there may be to a lesser degree!

1/3/2024

pra-sâmi

34

## LiSHT Activation Function




- ❑ The function scale the non-linear Hyperbolic Tangent (  $\tanh$  ) function by a linear function
  - ❖ Help tackle the dying gradient problem
- ❑ According to paper it has outperformed Swish on a number of problems

1/3/2024

pra-sâmi

35

## Mish



$$f(z) = z * \tanh(\text{softplus}(z))$$

$$= z * \tanh(\ln(1 + e^z))$$

- ❑ Inspired by Swish and has been shown to outperform it in a variety of computer vision tasks
- ❑ Mish was “found by systematic analysis and experimentation over the characteristics that made Swish so effective”.
- ❑ Mish seems to be the best activation in stock,
  - ❖ But jury is still out

1/3/2024

pra-sâmi

36

## Next Session...



1/3/2024

pra-sâmi



