

Selectors- getElementById()

```
lockdown-install.js:1
> document.getElementById('title')
< <h1 id="title" class="heading">...</h1>
> document.getElementById('title').id
< 'title'
> document.getElementById('title').class This is wrong ❌
< undefined
> document.getElementById('title').className This is Right ✔️
< 'heading'
> document.getElementById('title').getAttribute
< f getAttribute() { [native code] }
> document.getElementById('title').getAttribute()
❌ ▶ Uncaught TypeError: Failed to execute 'getAttribute' on 'Element': 1 argument
   required, but only 0 present.
   at <anonymous>:1:34
> document.getElementById('title').getAttribute('id')
< 'title'
> document.getElementById('title').getAttribute('class')
< 'heading'
> document.getElementById('title').setAttribute('class', 'test') Ye override kar dega
< undefined
> document.getElementById('title').setAttribute('class', 'test heading') So Write both of them
< undefined
> const title = document.getElementById('title') We can store it in a variable easily
< undefined
```

⋮ Console AI assistance Issues

More Tools

🔍 -url:https://en.wikipedia.org/w/load.php?lang=

Default levels ▾ 1 Issue: 1

> title

< <h1 id="title" class="test heading">
 "DOM learning on Chai aur code "
 test text
</h1>

> title.style

< ▶ CSSStyleDeclaration {accentColor: '', additiveSymbols: '', alignContent: '', alignItems: '', alignSelf: '', ...}

> title.style

< ▶ CSSStyleDeclaration {accentColor: '', additiveSymbols: '', alignContent: '', alignItems: '', alignSelf: '', ...}

> title.style.backgroundColor = 'red'

< 'red'

> title.style.padding

< ''

> title.style.padding = '5px'

< '5px'

> title.style.padding = '15px'

< '15px'

> title.style.borderRadius = "15px"

< '15px'

> title

< <h1 id="title" class="test heading" style="background-color: red; padding: 15px; border-radius: 15px;">
 "DOM learning on Chai aur code "
 test text
</h1>

> title.textContent

< 'DOM learning on Chai aur code test text'

> title.innerHTML

< 'DOM learning on Chai aur code test text'

> title.innerText

< 'DOM learning on Chai aur code'

>

SES Removing unpermitted intrinsics lockdown-install.js:1

```
> document.querySelector('h2')
< h2>Lorem ipsum dolor sit.</h2>

> document.querySelector('#title')
< h1 id="title" class="heading">...</h1>

> document.querySelector('.heading')
< h1 id="title" class="heading">...</h1>

> document.querySelector('.heading')
< h1 id="title" class="heading">...</h1>

> document.querySelector('input[type="password"]')
< input type="password" name id>

> document.querySelector('p:')
```

Uncaught SyntaxError: Failed to execute 'querySelector' on 'Document': 'p:' is not a valid selector.
at <anonymous>:1:10

```
> document.querySelector('p')
< p>Lorem ipsum dolor sit amet.</p>

>
```

▶ SES Removing unpermitted intrinsics

[lockdown-install.js:1](#)

```
> document.querySelector('ul')
< ▶ <ul>...</ul>

> const myUl = document.querySelector('ul')
< undefined

> myUl
< ▶ <ul>...</ul>

> myUl.querySelector('li')
< ▶ <li>...</li>

> const turnGreen = myUl.querySelector('li')
< undefined

> turnGreen.style.backgroundColor = "green"
< 'green'

> turnGreen.style.padding = "15px"
< '15px'

> turnGreen.style.borderRadius = "15px"
< '15px'

> turnGreen.innerText
< 'one'

> turnGreen.innerText = "five"
< 'five'

>
```

```
> document.querySelectorAll('li')
< ▶ NodeList(3) [li, li, li]

> const templist = document.querySelectorAll('li')
< undefined

> templist
< ▶ NodeList(3) [li, li, li]

> templist.style.color = 'green'
✖ ▶ Uncaught TypeError: Cannot set properties of undefined (setting 'color') VM3076:1
  at <anonymous>:1:22

> templist[0].style.color = 'green'
< 'green'

> const myh1 = document.querySelectorAll('h1')
< undefined

> myh1
< ▶ NodeList [h1#title.heading]

> myh1.style.color = "green"
✖ ▶ Uncaught TypeError: Cannot set properties of undefined (setting 'color') VM3249:1
  at <anonymous>:1:18

> myh1[0].style.color = "green"
< 'green'

> templist
< ▶ NodeList(3) [li, li, li]

> templist.forEach(function (l){
  l.style.backgroundColor = "red"
})
< undefined
```


DOM

lorem i

lorem i

lorem ipsum

- one
- two
- three
- four

||

```
Console AI assistance Issues
top top -url:https://en.wikipedia.org/v Default levels 2 Issues: 1 1 1 hidden
SES Removing unpermitted intrinsics lockdown-install.js:1
> document.getElementsByClassName('list-item')
< ▶ HTMLCollection(4) [li.list-item, li.list-item, li.list-item, li.list-item]
> const tempClassList = document.getElementsByClassName('list-item')
< undefined
> tempClassList
< ▶ HTMLCollection(4) [li.list-item, li.list-item, li.list-item, li.list-item]
> tempClassList.forEach(function (li) {
  console.log(li)
})
✖ Uncaught SyntaxError: missing ) after argument list VM4285:3
> tempClassList.forEach(function (li) {
  console.log(li)
})
✖ ▶ Uncaught TypeError: tempClassList.forEach is not a function VM4292:1
  at <anonymous>:1:15
> Array.from(tempClassList)
< ▶ (4) [li.list-item, li.list-item, li.list-item, li.list-item]
> const convertedArray = Array.from(tempClassList)
< undefined
> convertedArray
< ▶ (4) [li.list-item, li.list-item, li.list-item, li.list-item]
> convertedArray.forEach(function (li) {
  li.style.color = "orange"
})
✖ Uncaught SyntaxError: Invalid or unexpected token VM4451:2
> convertedArray.forEach(function (li) {
  li.style.color = "orange"
})
< undefined
>
```

similar in name and syntax, the two languages are distinct and differ greatly in design.

History

Creation at Netscape

The first popular web browser with a graphical user interface, Mosaic, was released in 1993. The lead developers of Mosaic then founded the Netscape company, which released a more polished browser, Netscape Navigator, in 1994. It quickly became the most-used.^[13]

During these formative years of the Web, web pages could only be static documents. The capability for dynamic behavior after the page was loaded in the browser was a desire in the flourishing web development scene to remove this limitation. In 1995, Netscape decided to add a programming language to Navigator. They pursued two routes to achieve this: collaborating with Sun Microsystems to port the Java language, while also hiring Brendan Eich to embed the Scheme language.^[9]

The goal was a "language for the masses",^[14] "to help nonprogrammers create dynamic, interactive Web sites".^[15] Netscape management soon decided the best option was for Eich to devise a new language, with syntax similar to Scheme or other extant scripting languages.^{[9][6]} Although the language and its interpreter implementation were called LiveScript when shipped as part of a Navigator beta in September 1995, the name was changed to JavaScript for the official release in December.^{[9][1][16][17]}

The choice of the JavaScript name has caused confusion, implying it was related to Java. At the time, the dot-com boom had begun and Java was a new language, so Eich considered the JavaScript name a marketing strategy.^[14]

Adoption by Microsoft

Microsoft debuted Internet Explorer in 1995, leading to a browser war with Netscape. On the JavaScript front, Microsoft created its own interpreter, JScript.^[18]

Microsoft first released JScript in 1996, alongside initial support for CSS extensions to HTML. Each of these implementations was noticeably different from their counterparts in Netscape Navigator.^{[19][20]} These differences made it difficult for developers to make their websites work well in both browsers, leading

6 hidden

SES Removing unpermitted intrinsics

lockdown-install.js:1

> document.querySelectorAll('h3')

< ▶ NodeList(28) [h3#Creation_at_Netscape, h3#Adoption_by_Microsoft, h3#The_rise_of_JScript, h3#Growth_and_standardization, h3#Reaching_maturity, h3#Examples_of_scripted_behavior, h3#Libraries_and_frameworks, h3#JavaScript_engine, h3#Runtime_system, h3#Imperative_and_structured, h3#Weakly_typed, h3#Dynamic, h3#Object-orientation_(prototype-based), h3#Functional, h3#Delegative, h3#Miscellaneous, h3#Vendor-specific_extensions, h3#Cross-site_scripting, h3#Cross-site_request_forgery, h3#Misplaced_trust_in_the_client, h3#Misplaced_trust_in_developers, h3#Browser_and_plugin_coding_errors, h3#Sandbox_implementation_errors, h3#Hardware_vulnerabilities, h3#Java, h3#JSON, h3#Transpilers, h3#WebAssembly]

> const allH3 = document.querySelectorAll('h3')

< undefined

> allH3[1].innerText

< undefined

> allH3[0].textContent

< 'Creation at Netscape'

> allH3[1].textContent

< 'Adoption by Microsoft'

> allH3[2].textContent

< 'The rise of JScript'

>

The ECMAScript standard does not include any input/output (I/O), such as networking, storage, or graphics facilities. In practice, the web browser or other runtime system provides JavaScript APIs for I/O.

Although Java and JavaScript are similar in name and syntax, the two languages are distinct and differ greatly in design.

History

Creation at Netscape

The first popular web browser with a graphical user interface was Mosaic, released in 1993. The lead developers of Mosaic then founded Netscape, which released a more polished browser, Netscape Navigator, in 1994.^[13]

During these formative years of the Web, web pages were static documents. The capability for dynamic behavior after the page was loaded was a desire in the flourishing web development scene. In 1995, Netscape decided to add a programming language to its browser. It pursued two routes to achieve this: collaborating with Sun Microsystems on the Java language, while also hiring Brendan Eich to create a new scripting language.^[9]

The goal was a "language for the masses".^[14] "to create a dynamic, interactive Web sites".^[15] Netscape management's best option was for Eich to devise a new language that was less like Scheme or other extant scripting languages. The language and its interpreter implementation were shipped as part of a Navigator beta in September 1995. JavaScript for the official release in December.^{[9][16]}

The choice of the JavaScript name has caused confusion, as it is related to Java. At the time, the dot-com boom had just begun, so Eich considered the JavaScript name. Netscape.^[14]

Adoption by Microsoft

Microsoft debuted Internet Explorer in 1995, leading to competition with Netscape. On the JavaScript front, Microsoft created JScript.^[17]

Microsoft first released JScript in 1996, alongside Internet Explorer 3.0, alongside extensions to HTML. Each of these implementations had counterparts in Netscape Navigator.^{[19][20]} This led to developers making their websites work well in both browsers, using the widespread use of "best viewed in Netscape" and logos for several years.^{[19][21]}

The rise of JScript

In November 1996, Netscape submitted JavaScript to Ecma International, as the starting point for a standard specification that all browser vendors could conform to. This led to the official release of the first ECMAScript language specification in June 1997.

```
> const myh2 = document.querySelectorAll('.mw-headline')
< undefined
> myh2
< ▶ NodeList []
> const myh2 = document.querySelectorAll('.mw-heading mw-heading3')
< undefined
> const myh2 = document.querySelectorAll('.mw-heading')
< undefined
> myh2
< ▶ NodeList(57) [div.mw-heading.mw-heading2, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading2, div.mw-heading.mw-heading2,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading2, div.mw-heading.mw-heading2,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading2, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading4, div.mw-heading.mw-heading4,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading4,
div.mw-heading.mw-heading4, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading4, div.mw-heading.mw-heading4,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading4,
div.mw-heading.mw-heading4, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading4, div.mw-heading.mw-heading4,
div.mw-heading.mw-heading4, div.mw-heading.mw-heading5,
div.mw-heading.mw-heading5, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading2, div.mw-heading.mw-heading2,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading2,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading2,
div.mw-heading.mw-heading2, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading3,
div.mw-heading.mw-heading3, div.mw-heading.mw-heading2,
div.mw-heading.mw-heading2, div.mw-heading.mw-heading2]
> myh2.forEach(function (h) {
  h.style.color = 'red'
})
< undefined
> myh2.forEach(function (h) {
  h.style.color = 'red'
})
< undefined
> myh2.forEach(function (h) {
  h.style.color = 'red';
  h.style.backgroundColor = "green";
  h.style.padding = '10px'
})
< undefined
```


