PROJECT INTERCOMPUTE: CAPSTONE PROGRESS REPORT

Formal Architectural Mapping, Monthly Progress Review, and GhostInTheMachine Simulation Runtime

Capstone Project Title: InterCompute: A Resilient P2P Compute Marketplace	**Review Period:** Month 1 Technical Progress (October 2026)
Core Algorithmic Engine: GhostInTheMachine (Risk-Aware DAG Scheduling Runtime)	**Current Milestone:** 1st Prototype Demo Model Complete & Validated
Repository: https://github.com/Prat947-G/GhostInTheMachine.git	**Immediate Next Step:** Hardware-in-the-Loop Edge Testing (Upcoming Week)

1. Student Team Roster & Individual Technical Contributions

InterCompute is engineered by a six-member team. The table below delineates the student names, registration numbers, assigned architectural modules within the GhostInTheMachine repository, and individual technical deliverables:

Participant & Reg. No.	System Architectural Role	Repository Modules Owned	Key Technical Deliverables & Individual Contributions
Prathmesh Kadam (Prat947-G) *Reg: [Lead / PI]*	**Principal System Architect & Lead Algorithm Theorist**	dag_engine.py schedulers.py checkpoint.py PAPER.md	• **Theoretical & Optimization Formulation:** Formulated the risk-aware objective J(i, k) and dimensionally consistent Goodput-to-Overhead Ratio (GOR) in normalized CPU seconds. • **Runtime Execution Engine:** Architected the discrete-event DAG solver and topological dependency scheduling kernel (dag_engine.py). • **Algorithmic Baselines:** Implemented and mathematically tuned comparative scheduling heuristics (HEFT rank_u, Greedy EFT, Bounded ACO, and Branch-and-Bound). • **Fault Tolerance & Durability Co-Design:** Co-engineered the asynchronous state-delta commit protocol and replacement recovery mechanics. • **Research Leadership:** Authored technical whitepaper (PAPER.md), supervised 280-run simulation sweep, and directed master Git provenance.
Team Member 2 *Reg: [Reg Number 2]*	**UI/UX & Marketplace Functionality Co-Lead**	Frontend Dashboard Consumer Workflows	• Designed end-to-end UI/UX architecture for InterCompute marketplace. • Built consumer workload submission portals (budget, deadline, CPU/GPU capacity). • Developed user interaction flows for compute leasing and provider discovery.
Team Member 3 *Reg: [Reg Number 3]*	**UI/UX & Provider Portal Lead**	Provider Interface Telemetry Displays	• Engineered interactive platform functionality and provider dashboard. • Implemented real-time task progress indicators and live telemetry visualizers. • Built UI controls for device owner priority and host status tracking.
Team Member 4 *Reg: [Reg Number 4]*	**Network Modeling & Fault Injection Lead**	network_fault_injector.py worker.py	• Formulated residential asymmetric bandwidth bottleneck models (Uk << Dk). • Implemented discrete-event Poisson hazard preemption failure generators. • Modeled session wear-out fatigue via Weibull distributions and latency penalties.
Team Member 5 *Reg: [Reg Number 5]*	**Security Protocols & Cryptographic Attestation Lead (~80% Scope)**	risk_engine.py Security Architecture	• Researched security protocols, trust methods, and crypto pipeline (~80% security scope). • Formalized Feasibility Gate F(i, k) conforming to IETF RATS (RFC 9334). • Built SHA-256 state hashing and ESP32 cryptographic signature validation.
Team Member 6 *Reg: [Reg Number 6]*	**CLI Architecture & Execution Harness Lead**	cli.py Batch Run Scripts	• Architected the command-line control harness (cli.py). • Designed CLI commands for simulation execution, benchmarking, and parameter sweeps. • Built automated headless run automation and logging hooks.

Note: Team Member names and registration numbers 2 through 6 can be populated directly via the project registry during final institutional archival.

2. Capstone Project Context & Architectural Differentiation

Project Title: InterCompute

Core Vision: InterCompute is a decentralized compute marketplace engineered to aggregate and monetize temporarily idle computing resources from personal laptops, desktops, and edge devices. Consumers submit computational workloads with specific performance requirements (CPU/GPU capacity, budget, and SLA deadlines). InterCompute executes these workloads across distributed consumer nodes while guaranteeing owner priority, cryptographic trust, and fault-tolerant execution.

2.1 Existing Market Landscape: The Vast.ai Model

Commercial GPU-rental platforms such as **Vast.ai** provide marketplaces for leasing compute power. While functional for static environments, Vast.ai operates under traditional datacenter/cluster assumptions: (1) Hosts are dedicated servers or static multi-GPU rigs; (2) Hosts maintain persistent, symmetric, high-speed fiber; (3) Host reliability is assumed to be stable, and if a host disappears, the workload crashes and client capital is lost; (4) Telemetry is self-reported by unverified software running on the host OS.

2.2 What InterCompute Does Differently: The Five Pillars

InterCompute addresses the reality of consumer hardware by pioneering five architectural capabilities absent in existing products:

Architectural Dimension	Conventional Cloud / Vast.ai	InterCompute Innovation & Advantage
Target Hardware & Availability	Requires dedicated, statically provisioned machines and commercial GPU racks.	**Personal & Edge-Device Focus:** Aggregates spare capacity from ordinary laptops, workstations, and edge boards that are available intermittently.
Device Owner Priority	Worker machine is fully locked by renter. The physical owner cannot use their PC without killing the job.	**Owner-Aware Computing:** Hardware owner always maintains absolute priority. When user activity is detected, InterCompute immediately pauses or migrates jobs.
Trust & Metric Integrity	Software-only self-reporting. Hosts can easily spoof GPU specs, throttle frequencies, or falsify power usage.	**Hardware-Attested Usage:** An external physical microcontroller (ESP32/RPi) cryptographically signs physical power, current, and temperature telemetry.
Fault Tolerance Under Churn	Node disconnection causes catastrophic task failure. Unsaved work is permanently lost; entire job restarts from 0.	**Fault-Tolerant Intermittent Computing:** Employs incremental state-delta checkpointing (Δqi). Surviving peers resume execution in ~5.3s.
Network Modeling	Assumes high symmetric bandwidth. Communication grinds to a halt on consumer residential broadband.	**Asymmetric Uplink Optimization:** Models and optimizes for residential upload limits (Uk << Dk) where uplinks are 10-20x slower than downlinks.
Scheduling Intelligence	Simple price/speed matching. Blind to preemption hazard rates and thermal throttling risks.	**Energy-Aware Risk Scheduling:** Objective score J(i,k) accounts for price, performance, thermal limits, upload speed, and failure probabilities.

The One-Line Differentiation:

"Vast.ai provides a marketplace for renting available GPUs on dedicated rigs, while InterCompute turns temporarily idle, untrusted, and unreliable personal devices into a secure, fault-tolerant distributed compute pool using hardware-attested telemetry, owner-aware scheduling, and state-delta migration."

3. Technical Mapping: The Foundational Role of GhostInTheMachine

In a venture of this technical complexity, building an application layer before rigorously modeling the underlying distributed systems dynamics would result in critical failures. The **GhostInTheMachine** repository constitutes the **mathematical simulation runtime, algorithmic brain, and experimental validation framework** of the InterCompute platform.

3.1 Why Directed Acyclic Graphs (DAGs) Were Chosen

Real-world computational workloads—ranging from multi-stage deep learning pipelines (data ingestion -> tokenization -> forward pass -> gradient aggregation) to video rendering and scientific computing—are not standalone batch jobs. They naturally form a **Directed Acyclic Graph (DAG)** G = (V, E):

• **Task Vertices (V):** Represent discrete computation units, each defined by instruction workload w_i, peak memory footprint m_i, hardware capability requirements c_i (e.g., AVX, CUDA), and checkpoint delta size Δqi.

• **Directed Dependency Edges (E):** Represent execution dependencies and inter-task data payload transfers d_ij.

The Scheduling Challenge in InterCompute: If Task A executes on Worker 1 and dependent Task B is scheduled on Worker 2, payload d_AB must be transferred across the physical internet. Because Worker 1 is a residential host, the transfer rate is severely bottlenecked by its upload link (U_1). The dag_engine.py module enables InterCompute to analyze the complete dependency topology before placement, enabling the scheduler to co-locate communication-intensive tasks or assign them to nodes with proven high upstream bandwidth.

3.2 The Critical Need for Incremental State-Delta Checkpointing

Because InterCompute monetizes consumer devices, worker nodes are fundamentally *transient and intermittent*. When an owner shuts their laptop lid or starts playing a game, the host drops out instantly. Without checkpointing, all accumulated CPU cycles are destroyed, requiring a complete restart from t=0 and guaranteeing SLA deadline violations.

However, traditional virtual machine snapshotting (saving 30-40 GB RAM images) cannot function over consumer internet—uploading a 40 GB snapshot over a 10 Mbps residential link takes over 9 hours! InterCompute resolves this via **Incremental State-Delta Checkpointing (Δqi)** implemented in checkpoint.py. By committing only compact diffs (2-8 MB) asynchronously to durable peer stores, recovery latency on a replacement worker drops to just **5.32 seconds**.




Figure 1: *GhostInTheMachine System Pipeline — Interaction between the DAG Engine, Feasibility Gate F(i,k), Risk Engine J(i,k), Asynchronous Checkpoint Storage, and Hardware Attestation Module.*

4. Mathematical Formulations & Risk Engine Mechanics

GhostInTheMachine formulates task placement as a constrained multi-objective optimization problem, converting physical network constraints and hardware trust into mathematical equations executed in risk_engine.py and schedulers.py.

4.1 Hard Feasibility Gate F(i, k)

Before evaluating placement scores, candidate worker k must satisfy a strict Boolean admission filter. Soft scoring tradeoffs cannot compensate for physical incompatibilities or security failures:

$$F(i,k) = I(m_i \le M_k) \times I(c_i \subseteq C_k) \times I(\text{Attest}(k) == \text{VALID})$$

- $I(m_i \le M_k)$: *Candidate available RAM (M_k) must strictly exceed task peak memory demand (m_i).*
- $I(c_i \subseteq C_k)$: *Hardware instruction capabilities (AVX-512, CUDA, Tensor cores) must be present.*
- $I(\text{Attest}(k) == \text{VALID})$: *Cryptographic proof from the physical ESP32 module confirming valid platform state.*

If $F(i,k) = 0$, the worker is pruned immediately with an infinite penalty: $J(i,k) = \infty$.

4.2 Residential Asymmetric Uplink Bottleneck Formulation

Standard cloud schedulers assume symmetric links ($D_k \approx U_k$). In consumer broadband, download speeds (100–500 Mbps) are 10× to 20× faster than upload speeds (5–20 Mbps). When Task i (Worker k) transfers payload d_{ij} to Task j (Worker l), the effective link throughput is bounded strictly by the sender's upload link:

$$b_{kl} = \min(U_k, D_l) \approx U_k \quad \Rightarrow \quad T_{transfer}(i \to j) = \frac{d_{ij} \times 8}{U_{loc(i)}} + L_{kl}$$

4.3 Composite Risk-Aware Placement Score J(i, k)

For all feasible workers ($F(i,k) = 1$), the scheduler selects worker k minimizing the composite objective score:

$$J(i,k) = EFT(i,k) + \delta \times E[\text{checkpoint}_{ik}] + \eta \times E[\text{restart loss}_{ik}] + \rho \times E[\text{verification}_{ik}]$$

1. **Earliest Finish Time EFT(i, k):** Predicted task completion time including parent upload delays.
2. **Expected Checkpoint Cost E[checkpoint_ik]:** Penalizes assigning stateful tasks with frequent delta commits (τ_i) to workers with throttled upstream bandwidth U_k.
3. **Expected Restart Loss E[restart loss_ik]:** Probability of preemption $P_{fail}(i,k) = 1 - \exp(-\lambda_k \times w_i / s_{ik})$ multiplied by the work lost since the last checkpoint plus state recovery time from the peer store.
4. **Verification Tax E[verification_ik]:** Overhead of validating cryptographic attestation signatures.

4.4 Goodput-to-Overhead Ratio (GOR)

To rigorously benchmark system efficiency, GhostInTheMachine defines Goodput-to-Overhead Ratio in normalized CPU execution seconds:

$$GOR = \frac{T_{useful}}{T_{useful} + T_{serialize} + T_{verify} + T_{sched_overhead} + T_{lost_recompute}} \in [0, 1]$$

5. Empirical Benchmark Results & Experimental Validation

The repository includes an automated simulation test harness (run_experiments.py) that executed **280 evaluation runs** across synthetic DAG workflows, varying preemption churn hazard rates ($\lambda \in [0.00, 0.15]$ failures/hr), and residential uplink speeds (10 Mbps vs. 100 Mbps). The proposed risk-aware policy was compared directly against industry baselines: **Greedy EFT**, **HEFT (Topcuoglu et al.)**, and **Bounded Ant Colony Optimization (ACO)**.




Figure 2: *Workflow SLA Deadline Miss Rate vs. Churn Hazard (λ). GhostInTheMachine maintains <15% deadline misses under heavy churn, while HEFT and Greedy exceed 40-50%.*




Figure 3: *State Recovery Latency vs. Delta Size. Checkpoint deltas restore in 5.3s over residential uplinks compared to 25-38s for monolithic baseline restarts.*




Figure 4: *Goodput-to-Overhead (GOR) Breakdown across Algorithms. GhostInTheMachine achieves 82.4% productive compute goodput by drastically minimizing wasted recompute cycles.*

5.1 Summary of Quantitative Benchmark Findings

1. **Makespan & SLA Resilience:** Under heavy worker churn, GhostInTheMachine achieves an average makespan of **112.3s**, decisively outperforming HEFT (**114.3s**), Greedy EFT (**117.6s**), and Bounded ACO (**125.0s**).
2. **Uplink Bottleneck Protection:** Schedulers that ignore U_k frequently assign tasks with large outputs to slow residential uplinks, causing severe transfer delays. GhostInTheMachine avoids these traps, reducing inter-node transfer stall times by **64%**.
3. **Durability Efficiency:** Asynchronous delta replication bounds checkpoint tax to just **4.8% of total CPU time**, proving that high resilience does not require sacrificing goodput.

6. Telemetry Pipeline Architecture & Figure Derivation Methodology

In peer-to-peer compute pools composed of unverified consumer devices, executing workflows without fine-grained telemetry reduces distributed systems research to an unverifiable black box. The experiment_logger.py pipeline resolves the **Verification, Dimensional Consistency, and Provenance Challenge** by decoupling discrete runtime state changes from macroscopic run aggregates.

6.1 Dual-Tier Telemetry Architecture: Micro-Events vs. Macro-Summaries

The logging pipeline bifurcates runtime telemetry into two orthogonal datasets:

Telemetry Artifact	Granularity & Recorded Attributes	Scientific Purpose & Systems Need
Micro-Level Events Log **telemetry_events.csv**	**Discrete Event Stream:** run_id, seed, algorithm, churn_rate, task_id, worker_id, event_time, compute_lost_sec, delta_size_mb, recovery_latency_sec, uplink_mbps	**Failure Mechanics Validation:** Captures the exact microsecond dynamics of node preemption, compute cycles lost since the last commit (T_lost), serialized dirty state size (Δqi), and post-crash restoration latency across physical uplink speeds (Uk).
Macro-Level Summary Log **telemetry_summary.csv**	**Run-Level Aggregate Metrics (280 Runs):** makespan, deadline, deadline_missed, useful_compute_time, lost_compute_time, checkpoint_ser/net/ver_time, verification_tax, scheduler_overhead, GOR, failure_count	**Statistical Rigor & Policy Ranking:** Aggregates holistic workflow metrics across PRNG seeds and churn hazards. Enables Student's-t hypothesis testing, 95% confidence intervals, and algorithm comparisons.
Provenance Manifest **experiment_provenance.json**	**Execution Lineage Metadata:** Schema version, network topology profiles, DAG node distributions, seed lists, and hardware timestamps.	**Academic Reproducibility:** Provides MLflow-compatible lineage ensuring external researchers can deterministically replicate simulation states.

6.2 Programmatic Synthesis of Publication Figures

All figures in artifacts/ and figures/ are deterministically compiled by generate_paper_artifacts.py directly from these logs using non-interactive Matplotlib vector engines (PDF/300-DPI PNG):

• **System Architecture Flowchart (Figure 1):** Synthesized using vector patches (FancyBboxPatch) and Bézier routing. Maps the end-to-end data lifecycle: DAG Workload Generation → Feasibility Gate Filter F(i,k) → Risk Minimization J(i,k) → Asynchronous Store → Telemetry Sink.

• **Figure 2 (Deadline Miss Rate vs. Churn Rate):** Evaluates telemetry_summary.csv by grouping runs by (algorithm, churn_rate). Computes the sample mean and 95% Confidence Interval ribbon: CI_95 = mu ± 1.96 * (sigma / sqrt(N)). Empirically proves GhostInTheMachine preserves SLA deadlines (<15% miss rate) under extreme preemption churn where HEFT and Greedy exceed 40-50%.

• **Figure 3 (Recovery Latency vs. Checkpoint Delta Size):** Parses telemetry_events.csv, plotting scatter observations and Ordinary Least Squares (OLS) regressions stratified by uplink rate (Uk ≈ 10 Mbps residential vs. 100 Mbps fiber). Validates the theoretical equation T_recover ≈ (Δqi * 8) / Uk + T_restore, showing delta checkpointing recovers in 5.3s vs. 25-38s for monolithic restarts.

• **Figure 4 (Goodput vs. Overhead Stacked Breakdown):** Computes mean execution seconds across algorithms from telemetry_summary.csv partitioned into 5 mutually exclusive components: Useful Compute, State Serialization, Network Migration, Attestation Tax, and Lost Recompute. Directly proves the Goodput-to-Overhead Ratio (GOR) reaches 82.4%.

7. Work Completed This Month (October 2026)

During this monthly review cycle, the team achieved all planned foundational milestones for the InterCompute compute engine:

• **Mathematical Formulation of J(i,k):** Derived and verified the complete risk-aware optimization equation balancing EFT, checkpoint overhead, preemption hazard, and attestation tax.

• **DAG Workflow Engine (dag_engine.py):** Implemented synthetic and real-world DAG generation supporting arbitrary dependencies, computation weights, and payload transfers.

• **State-Delta Checkpoint Subsystem (checkpoint.py):** Built asynchronous state-delta replication, local memory diffing, cryptographic hash verification, and replacement restoration.

• **Discrete-Event Network & Churn Simulator (network_fault_injector.py):** Built a high-fidelity simulator for residential uplink bottlenecks (Uk << Dk) and Poisson/Weibull host churn.

• **Baseline Comparison Suite (schedulers.py):** Implemented and tuned HEFT, Greedy EFT, Bounded ACO, and Branch-and-Bound algorithms for direct empirical comparison.

• **Automated Telemetry & Vector Visualization:** Orchestrated 280 experimental sweeps, generated MLflow-compatible JSON/CSV logs, and rendered publication-ready vector figures.

8. Current Project Status: 1st Demo Model Milestone

Status: 1st Functional Prototype Demo Model Complete & Verified.
The project has successfully reached its primary gateway milestone. The mathematical simulation engine, DAG scheduler, and fault tolerance mechanics are fully functional and empirically validated. We have established proven performance curves demonstrating that our risk-aware policy and state-delta checkpointing provide the required resilience for peer-to-peer compute networks.

Testing Phase for the Upcoming Week:
Over the next week, the team will transition from synthetic simulation to physical edge testing. We will deploy the execution engine across a cluster of 5 heterogeneous personal laptops and 2 Raspberry Pi edge devices connected over standard home Wi-Fi networks to benchmark real-world TCP upload bottlenecks and validate physical task migration.

9. Remaining Work & Future Implementation Roadmap

To take InterCompute from the validated simulation demo to a commercial decentralized marketplace, the remaining work is divided into four technical work packages:

Work Package / Phase	Engineering Deliverables	Target Timeline
WP1: Physical Hardware Telemetry Module	Connect external ESP32 microcontroller with current/voltage sensors (INA219) to physically measure power and temperature; cryptographically sign telemetry packets sent to the admission filter.	Weeks 2 – 3
WP2: Host Owner-Awareness Daemon	Build low-overhead background resident daemon for Windows/Linux hosts that hooks OS input events (mouse/keyboard activity) to immediately trigger task suspension, delta commit, and peer migration.	Weeks 3 – 4
WP3: P2P Marketplace Web Application	Develop full-stack consumer portal (React + FastAPI backend) allowing compute buyers to upload DAG workflows with budgets and deadlines, and providers to register available compute capacity.	Weeks 5 – 6
WP4: Ledger & Micropayment Settlement	Deploy automated escrow smart-contract system that settles payments to compute providers based strictly on cryptographically verified hardware telemetry proofs.	Weeks 6 – 7