
PG – DESD

Module – Embedded C Programming

Trainer - Devendra Dhande

Email – devendra.dhande@sunbeaminfo.com

Mobile No - 9890662093



Control Statements

- Decision or Selection
 - if-else
 - switch-case
- Iteration (loop)
 - for
 - while
 - do-while
- Jump
 - break
 - continue
 - goto
 - return



if-else statement

```
if (condition) {  
    statement 1;  
    statement 2;  
}
```

```
if (condition) {  
    statement 1;  
    statement 2;  
}  
else {  
    statement 3;  
    statement 4;  
}
```

```
if (condition)  
    statement 1;
```

```
if (condition)  
    statement 1;  
else  
    statement 2;
```

- Condition is any expression – using relational, logical or other operators.
 - 0 – false condition
 - 1 – true condition



Ternary/conditional operator

```
if (condition) {  
    // execute if condition is true  
}  
else {  
    // execute if condition is false  
}
```

- if-else can be nested within each other.

condition ? expression1 : expression2

- If condition is true, expression1 is executed; otherwise expression2 is executed.
- Ternary operators can also be nested.
- expression1 & expression2 must be expressions (not statement).
 - expression – evaluate to some value.
 - statement – C statement ends with ;



switch-case

```
switch (expression) {  
    case const-expr1:  
        statement(s);  
        break;  
    case const-expr2:  
        statement(s);  
        break;  
    ...  
    default:  
        statement(s);  
        break;  
}
```

- Switch-case is used to select one of the several paths to execute depending on value of int expression.
- case constants cannot be duplicated.
- break statement skips remaining statements and continues execution at the end of switch closing brace.
- If break is missing, statements under sub-subsequent case continue to execute.
- default case is optional and it is executed only if an expression is not matching with any of the case constant.
- Sequence of cases and default case doesn't matter.



Loops

- Control statements used for repeating a set of instructions number of times is called as “LOOP”.
- Every loop has
 - Initialization statement
 - Terminating condition
 - Modification statement(Increment/Decrement)
 - Body of loop
- The variable that is used for terminating condition is referred as ‘loop variable’.



while loop

- Used to repeat a statement (or block) while an expression is true (not zero).

- **Syntax:**

```
initialization;  
while(condition) {  
    statement1;  
    statement2;  
    modification;  
}
```



for loop

- Used to repeat a statement (or block) while an expression is true (not zero).

- Syntax:

```
for(initialization; condition; modification) {  
    statement1;  
    statement2;  
}
```





Thank you!

Devendra Dhande <devendra.dhande@sunbeaminfo.com>

