

NMAP Commands

- **nmap <target>** — Basic scan of common ports
- **nmap -p- <target>** — Scan all 65,535 TCP ports
- **nmap -sT <target>** — TCP connect scan
- **nmap -sS <target>** — TCP SYN stealth scan
- **nmap -sU <target>** — UDP scan
- **nmap -sn <target>** — Ping scan only (host discovery)
- **nmap -Pn <target>** — Treat host as up, skip ping
- **nmap -sV <target>** — Service version detection
- **nmap -sV --version-intensity 5 <target>** — Aggressive version detection
- **nmap -A <target>** — Aggressive scan (version, OS, scripts, traceroute)
- **nmap -F <target>** — Fast scan (top 100 ports)
- **nmap --top-ports 50 <target>** — Scan top 50 ports
- **nmap -p 22,80,443 <target>** — Scan specific ports
- **nmap -oN output.txt <target>** — Normal output to file
- **nmap -oX output.xml <target>** — XML output
- **nmap -oG output.gnmap <target>** — Greppable output
- **nmap -T4 <target>** — Faster timing/template
- **nmap -T1 <target>** — Slow, stealthy timing
- **nmap --script default <target>** — Run default NSE scripts
- **nmap --script vuln <target>** — Run vulnerability scripts

- **nmap --script http-enum <target>** — Web application enumeration
- **nmap --script ssl-enum-ciphers <target>** — Analyze SSL/TLS ciphers
- **nmap --script ftp-anon <target>** — Check FTP anonymous login
- **nmap --script ssh-auth-methods <target>** — Enumerate SSH auth methods
- **nmap -O <target>** — OS detection
- **nmap --traceroute <target>** — Network path tracing
- **nmap -6 <target>** — IPv6 scanning
- **nmap --data-length 50 <target>** — Add random data to evade detection
- **nmap --badsum <target>** — Send invalid checksums
- **nmap -f <target>** — Fragment packets to evade IDS
- **nmap -D RND:10 <target>** — Use 10 random decoys
- **nmap -sl <zombie_host> <target>** — Idle scan via zombie host
- **nmap --spoof-mac 0 <target>** — Spoof random MAC address
- **nmap -g 53 <target>** — Source port 53 (DNS) spoofing
- **nmap -sN <target>** — TCP Null scan
- **nmap -sF <target>** — FIN scan
- **nmap -sX <target>** — Xmas scan
- **nmap -sA <target>** — ACK scan to detect firewalls
- **nmap --open <target>** — Show only open ports
- **nmap --exclude-ports 22,80 <target>** — Skip ports 22 and 80
- **nmap -p U:53,T:80,443 <target>** — Mixed UDP/TCP port scan
- **nmap --max-retries 3 <target>** — Limit retries on probes

- **nmap --max-scan-delay 20ms <target>** — Limit scan delays
- **nmap --script-args=unsafe=1 --script <script_name> <target>**
— Run unsafe scripts when permitted
- **nmap --reason <target>** — Show why a port is reported open/closed
- **nmap --script smb-enum-shares -p 445 <target>** — Enumerate SMB shares
- **nmap --script dns-zone-transfer -p 53 <target>** — Attempt DNS zone transfer
- **nmap --script http-methods -p 80 <target>** — Check allowed HTTP methods
- **nmap --script http-headers -p 80 <target>** — Retrieve HTTP headers
- **nmap --script http-crawl -p 80 <target>** — Web spidering to map structure