



TATASTEEL

At - Isamba Phata | Khopoli - 410203 | Tal - Khalepur | Dist - Raigad (Maharashtra), India



CML 7700119009

TEST CERTIFICATE

TEST CERTIFICATE NO.: 910396133

DESPATCH DATE: 28.02.2026

DO NO.: 9519583755

INVOICE NO.: 7250033805

MATERIAL NO.: 190032

CUSTOMER CODE: 163073

VEHICLE NO.: MH48CQ4697(R)

PRODUCT: CRCA COIL

SHIP-TO PARTY: 163073

RATNESH ISPAT SERVICES PVT.LTD. GAT NO.357
WAGHAJINAGAR,KHARABWADI CHAKAN
PUNE 410501

SOLD-TO PARTY: 926158

TATA STEEL DOWNSTREAM PRODUCTS LIMI
B-18,MIDC GROWTH CENTRE,RANJANGAON TALUKA-
RANJANGAON 412220

We hereby certify that the above mentioned material is tested in accordance with scheme of testing and inspection contained in BIS certification marks License no. CML 7700119009 are as indicated against each section (Please refer to IS513 (PART 1):2016-CR2* for details of specification requirements). Legal sanction can be imposed on forging. Improper use of product can cause safety issues. To validate test certificate, Scan QR Code.

TDC No: AU14

Grade: TDC FOR AUTO DQ COIL

Section(TxW): 0.960x1250.000mm

Specification Requirements as per TDC No AU14

Item	Batch No.	Mother Coil	Cast No.	Tonnage	Pcs.	Chemical Analysis, Specifications and Other Information												
						C	Mn	Si	S	P	Al	N						
03	K6R8C00919	K6R8C00919	A053067	14.440		%	%	%	%	%	%	PPM						
Test Results						0.0700	0.400	0.040	0.020	0.025	0.0700	70						
04	K6R8C01002	K6R8C01002	B054212	11.720		0.0430	0.211	0.006	0.005	0.011	0.0490	35						
TDC No: AU14						0.0440	0.220	0.012	0.006	0.014	0.0500	35						

Mechanical Analysis, Specifications and Other Information

Section (TxW): 0.960x1250.000mm	Specification Requirements as per TDC No. AU14	Mechanical Analysis, Specifications and Other Information												
		YS	UTS	EL	HRB	RA	BEND	ER						
03	K6R8C00919	MPa	MPa	%		µm		MM						
		145	270	39		0.80		8.2						
		Max	230	350	48	55	1.60							
04	K6R8C01002	Test Results	211	306	42	49	1.08	OK	10.4					
			220	318	41	51	1.02	OK	9.6					
		Max												

Route-

1 MPa = 1 N/mm2

YS = Yield Strength

UTS = Ultimate Tensile Strength

El = % elongation on standard gauge length

TxWxL = Thickness x Width X Length

CE (Carbon Equivalent) = (C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15)

*For further details please visit www.bis.gov.in

Killing type: Steel is fully Aluminium killed

Material is ROHS Compliant

Tensile Sample testing Transverse to rolling direction

Micro alloying elements (MA) : Nb+V+Ti

Material clearance date

20.02.2026

This TC is electronically generated

Head Quality Assurance
TATA STEEL LIMITED