



At - Isamba Phata | Khopoli - 410203 | Tal - Khalapur | Dist - Raigad (Maharashtra), India

TATASTEEL



## TEST CERTIFICATE

TEST CERTIFICATE NO. : 910600507 DESPATCH DATE: 28.03.2026

TEST CERTIFICATE TO:

DO NO. : 9519660802

CUSTOMER CODE: 813685

POSH METAL INDUSTRIES PRIVATE LIM GAT NO.50, OFF.CHAKAN, SHIKRAPUR

INVOICE NO. : 7250034550

VEHICLE NO.: MH48AY7654(R)

VILLAGE PIMPLE JAGTAP, TALUKA-SHIRUR

MATERIAL No. : 208536

PRODUCT: HR-COIL P&O SKIN PASSED COIL.

PUNE 412208

We hereby certify that the above mentioned material is tested in accordance with scheme of testing and inspection contained in BIS certification marks License no. CM/L-5076159 are as indicated against each section (Please refer to IS 5986 ISH390LA (HOT ROLLED STEEL SHEET, PLATE AND STRIP FOR FORMING AND FLANGING PURPOSES)\* for details of specification requirements). Legal sanction can be imposed on forging. Improper use of product can cause safety issues. To validate test certificate, Scan QR Code.

TDC No: TY13 Q Code:HPSE34

Chemical Analysis, Specifications and Other Information

| Grade: E-34                                   | C   | Mn     | S     | P     | N     | Si  | Al     | Nb     | Ti     | V      |  |  |  |  |  |  |  |  |  |  |
|-----------------------------------------------|-----|--------|-------|-------|-------|-----|--------|--------|--------|--------|--|--|--|--|--|--|--|--|--|--|
| Section (TXW): 1.600x1250.000mm               | %   | %      | %     | %     | PPM   | %   | %      | %      | %      | %      |  |  |  |  |  |  |  |  |  |  |
| Specification Requirements as per TDC No TY13 | Min | 0.450  |       |       |       |     | 0.0200 |        |        |        |  |  |  |  |  |  |  |  |  |  |
|                                               | Max | 0.1000 | 0.700 | 0.030 | 0.030 | 120 | 0.200  | 0.0550 | 0.0450 | 0.0950 |  |  |  |  |  |  |  |  |  |  |

| Item         | Batch No.  | Mother Coil | Cast No. | Tonnage | Pcs. | Test Results                                              |       |       |       |    |       |        |        |        |        |  |  |  |  |  |
|--------------|------------|-------------|----------|---------|------|-----------------------------------------------------------|-------|-------|-------|----|-------|--------|--------|--------|--------|--|--|--|--|--|
| 01           | K631515000 | K631515000  | T33754   | 21.910  | 1    | 0.0516                                                    | 0.575 | 0.003 | 0.015 | 74 | 0.066 | 0.0322 | 0.0002 | 0.0013 | 0.0278 |  |  |  |  |  |
| TDC No: TY13 |            |             |          |         |      |                                                           |       |       |       |    |       |        |        |        |        |  |  |  |  |  |
|              |            |             |          |         |      | Mechanical Analysis, Specifications and Other Information |       |       |       |    |       |        |        |        |        |  |  |  |  |  |

| Section (TXW): 1.600x1250.000mm                |            |             |          |         |              | YS  | UTS | EL  |    |  |  |  |  |  |  |  |  |  |  |  |
|------------------------------------------------|------------|-------------|----------|---------|--------------|-----|-----|-----|----|--|--|--|--|--|--|--|--|--|--|--|
| Specification Requirements as per TDC No. TY13 |            |             |          |         |              | MPa | MPa | %   |    |  |  |  |  |  |  |  |  |  |  |  |
|                                                |            |             |          |         |              | Min | 332 | 392 | 27 |  |  |  |  |  |  |  |  |  |  |  |
|                                                |            |             |          |         |              | Max | 412 | 490 |    |  |  |  |  |  |  |  |  |  |  |  |
| Item                                           | Batch No.  | Mother Coil | Cast No. | Tonnage | Test Results |     |     |     |    |  |  |  |  |  |  |  |  |  |  |  |
| 01                                             | K631515000 | K631515000  | T33754   | 21.910  | 1            | 386 | 455 | 32  |    |  |  |  |  |  |  |  |  |  |  |  |

Route-BOF>LF>CC>TSR

1 MPa = 1 N/mm2  
YS = Yield Strength  
UTS = Ultimate Tensile Strength  
El = % elongation on standard gauge length  
TXWXL = Thickness x Width X Length  
CE (Carbon Equivalent) = (C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15)



\*For further details please visit [www.bis.gov.in](http://www.bis.gov.in)

Killing type: Steel is fully Aluminium killed  
Material is ROHS Compliant  
Tensile Sample testing transverse to rolling direction

Micro alloying elements (MA): Nb+V+Ti  
Material clearance date  
25.03.2026  
This TC is electronically generated

Head Quality Assurance  
TATA STEEL LIMITED