




At - Isamba Phata | Khopoli - 410203 | Tal - Khalapur | Dist - Raigad (Maharashtra), India



TATA STEEL

TEST CERTIFICATE

TEST CERTIFICATE TO:

TEST CERTIFICATE NO. : 910801075 DESPATCH DATE: 26.04.2026

DO NO. : 9519728243 CUSTOMER CODE: 926158

INVOICE NO. : 7250035299 VEHICLE NO.: MH46DC3623(R)

MATERIAL NO. : 1114031 PRODUCT: HR COILS (P&O)

TATA STEEL DOWNSTREAM PRODUCTS LIMI
B-18,MIDC GROWTH CENTRE,RANJAGAON TALUKA-SHIRUR,PUNE -412220
RANJAGAON 412220

We hereby certify that the above mentioned material is tested in accordance with scheme of testing and inspection contained in BIS certification marks License no. CML-5076159 are as indicated against each section (Please refer to IS 5986 ISH410S (HOT ROLLED STEEL SHEET, PLATE AND STRIP FOR FORMING AND FLANGING PURPOSES)* for details of specification requirements). Legal sanction can be imposed on forging. Improper use of product can cause safety issues. To validate test certificate, Scan QR Code.

Chemical Analysis, Specifications and Other Information														
TDC No.	HA39	Q Code	THA020	C	Mn	S	P	Si	Al	N	C Eq	Cr	Mo	Nb
Grade	IS 5986 255			%	%	%	%	%	%	PPM	%	%	%	%
Section(TxV)	3.000X1250.000mm								0.0200					
Specification Requirements as per TDC No HA39				Min	0.2000	1.3000	0.0400	0.0400		120				
Max														
Item	Batch No.	Mother Coil	Cast No.	Tonnage	Pcs.	Test Results								
01	K6R8H00390	K6R8H00390	T35007	22.075	1	0.0421	0.7631	0.0035	0.0239	0.1107	0.0393	53	0.1700	0.0278
Mechanical Analysis, Specifications and Other Information														
Section (TxV)	3.000X1250.000mm					UTS	EL	BEND	YS					
Specification Requirements as per TDC No. HA39						MPa	%		MPa					
Min						410	17		255					
Max						520								
Item	Batch No.	Mother Coil	Cast No.	Tonnage	Pcs.	Test Results								
01	K6R8H00390	K6R8H00390	T35007	22.075	1	479	36	OK	425					

Route-BOF>LF>CC>TSR
Test Certificate as per EN10204 TYPE 3.1
1 MPa = 1 N/mm2
YS = Yield Strength
UTS = Ultimate Tensile Strength
EI = % elongation on standard gauge length
TxVxL = Thickness x Width x Length
CE (Carbon Equivalent) = (C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15)

*For further details please visit www.bis.gov.in
Killing type:Steel is fully Aluminium killed
Material is ROHS Compliant
Tensile Sample testing transverse to rolling direction

Micro alloying elements (MA) : Nb+V+Ti
Material clearance date
20.04.2026
This TC is electronically generated

Head Quality Assurance
TATA STEEL LIMITED