



TATA STEEL

At - Isamba Phala | Khopoli - 410203 | Tal - Khalapur | Dist - Raigad (Maharashtra), India



TEST CERTIFICATE

TEST CERTIFICATE NO. : 910617497

DESPATCH DATE: 30.03.2026

SHIP-TO PARTY: 600010

SOLD-TO PARTY:

DO NO. : 5502990638

CUSTOMER CODE: 600010

TATA STEEL PROCESSING & DISTRIBUTION LTD

INVOICE NO. : 1231274504

VEHICLE NO. : MH46BU2014(R)

MAFL MGMT CENTRE, B-18 MIDC GROWTH

MATERIAL NO. : 1250512

PRODUCT: HR COILS (P&O)

PUNE 412209

We hereby certify that the above mentioned material is tested in accordance with scheme of testing and inspection contained in BIS certification marks License no. CM/L-5076159 are as indicated against each section (Please refer to IS 5986 ISH390LA(HOT ROLLED STEEL SHEET, PLATE AND STRIP FOR FORMING AND FLANGING PURPOSES:2017)* for details of specification requirements). Legal sanction can be imposed on forging. Improper use of product can cause safety issues. To validate test certificate, Scan QR Code.

TDC No: HA12 Q Code:THA029

Grade: E34 SHEET

Section(TXW): 4.000x1250.000mm

Specification Requirements as per TDC No HA12

Min Max

0.1000 0.7000 0.0300 0.0300 0.2000 0.0200 120 0.0550 0.0450 0.0950 0.0100

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

0.0447 0.5689 0.0069 0.0192 0.0380 0.0326 44 0.0346 0.0065 0.0012 0.0095 0.0236 0.0013 0.0001 0.0108

Route-BOF>LF>CC>TSR
Test Certificate as per EN10204 TYPE 3.1

1 MPa = 1 N/mm2
YS = Yield Strength
UTS = Ultimate Tensile Strength

El= % elongation on standard gauge length
TXW/L = Thickness x Width X Length
CE (Carbon Equivalent) = (C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15)

*For further details please visit www.bis.gov.in

Killing type:Steel is fully Aluminium killed
Material is ROHS Compliant
Tensile Sample testing transverse to rolling direction

Gauge length(In mm) = 5.65 SQUARE ROOT OF

Micro alloying elements (MA) : Nb+V+Ti
Material clearance date

30.03.2026
This TC is electronically generated

Head Quality Assurance
TATA STEEL LIMITED