

Sonarqube-jenkins-integration

How to Integrate Sonarqube With Jenkins?


SonarQube is a code analysis tool that is used to find a number of bugs, duplications, security vulnerabilities, and many more. On the other hand, Jenkins is an open-source automation tool used to automate the build, test, and deploy stages of a software development lifecycle. Here in this, I have discussed what is SonarQube. Then I discussed what Jenkins is. After this, I have finally walked you through the different steps to integrate SonarQube with Jenkins and analyzed the code in a GitHub repository.

Pre-requisites


Before moving on to the next section, make sure that you have installed Jenkins and SonarQube on your system. If not installed, go and install Jenkins and SonarQube on your system.

Steps To Integrate SonarQube With Jenkins


Step 1: First go to Jenkins dashboard and download the SonarQube plugin. Then restart the Jenkins.




Step 2: Now go to sonarqube server . Here go to administration , then security and then select users.




Step 3: Now create a token for Jenkins.




Step 4: Go to Jenkins dashboard and go inside the tools section. Here you setup a sonar scanner which will scan the code.



Step 5: Now go into system section to configure sonarqube server.



Step 6: Create the secret text credential using token that is generated in step 3.



Jenkins Credentials Provider: Jenkins

Add Credentials

Domain
Global credentials (unrestricted)

Kind
Secret text


Scope ?
Global (jenkins, nodes, items, all child items, etc)

Secret
[Redacted]

ID ?
jenkins-sonar-gfg-demo

Description ?
jenkins-sonar-gfg-demo

Step 7: Then attach the credential to the sonarqube configuration.



Dashboard > Manage Jenkins > System >

SonarQube servers

If checked, job administrators will be able to inject a SonarQube server configuration as environment variables in the build.

☒ Environment variables

SonarQube installations
List of SonarQube installations

Name
Sonar

Server URL
Default is `http://localhost:9000`

`http://localhost:9000`

Server authentication token
SonarQube authentication token. Mandatory when anonymous access is disabled.


jenkins-sonar-gfg-demo

+ Add


Advanced

Save Apply


Step 8: Create a pipeline. Give the pipeline a name and select ok.



Step 9: Write the pipeline. Here i have used one of my github repository for code scanning.



Step 10: After the build is successful you can see the report generated at sonarqube server . Here you can see all the bugs and vulnerabilities report.



Conclusion

Here in this article you have first learned what is SonarQube. Then you have learned what is Jenkins. After this you have created an authentication on SonarQube server and used this token to integrate the SonarQube server with Jenkins. Here you have created a demo pipeline and analyzed the code in a Github repository using SonarQube.