

IIT JAMMU SUMMER SCHOOL 2026

IoT & Drones Program

Assignment: Fundamentals of Drones and UAV Systems

Name: Prathamesh Naik

Course: IoT & Drones Program

Institution: Adani University, Ahmedabad

Date: August 1, 2026

Assignment Answers

Q1. What is a Drone (UAV)? Definition, History, and Evolution [5 Marks]

A drone, formally known as an Unmanned Aerial Vehicle (UAV), is an aircraft that operates without a human pilot physically present on board. It is either controlled remotely by a pilot on the ground using a radio transmitter, or it flies autonomously using pre-programmed flight plans guided by onboard sensors, GPS, and a flight controller running control software.

History and Evolution: The concept of unmanned flight dates back to 1849, when Austria used unmanned balloons loaded with explosives against Venice. The first true pilotless aircraft, the Ruston Proctor Aerial Target, was developed by the British Royal Flying Corps in 1916 for military training. During World War I and World War II, radio-controlled target drones such as the Radio plane OQ-2 were used to train anti-aircraft gunners. The Cold War era saw significant advances in reconnaissance UAVs like the American Ryan Firebee, used for surveillance without risking pilot lives. From the 1990s onward, UAVs such as the Predator drone were equipped with cameras, GPS, and later armed capability, transforming them into strategic military assets.

In the 21st century, drones evolved rapidly from military-only tools into consumer, commercial, and industrial devices. Advances in MEMS sensors, lithium-polymer batteries, brushless motors, and low-cost flight controllers (such as ArduPilot and PX4) made multirotor drones affordable and easy to fly. Today drones are used across agriculture, filmmaking, delivery, mapping, disaster management, and defence, and are expected to become further autonomous with AI-based navigation and swarm technology.

Q2. Five Real-World Applications of Drones [5 Marks]

- Agriculture: Crop health monitoring, precision spraying of pesticides/fertilizers, and yield estimation using multispectral cameras.
- Disaster Management: Search and rescue operations, damage assessment after floods/earthquakes, and delivering emergency supplies to inaccessible areas.
- Aerial Photography and Filmmaking: Cinematic shots, real estate photography, and event coverage using gimbal-stabilized cameras.
- Delivery Services: Last-mile delivery of medicines, food, and e-commerce packages (e.g., Zipline's medical drone delivery in Rwanda and Ghana).
- Surveillance and Defence: Border monitoring, reconnaissance, and military strike missions using long-endurance UAVs.

Other notable applications include infrastructure inspection (power lines, pipelines, wind turbines), traffic monitoring, wildlife conservation, and construction site mapping using photogrammetry.

Q3. Differentiate Between the Following [10 Marks]

(a) UAV vs Drone

Parameter	UAV	Drone
Meaning	Formal/technical term for any unmanned aircraft	Popular/informal term, often refers to small consumer or commercial UAVs
Scope	Broad — includes military, civil, and research aircraft	Typically refers to multirotor or small fixed-wing aircraft
Usage Context	Used in engineering, aviation regulation, and defence	Used in everyday/consumer and media context

(b) Fixed-wing vs Multirotor Drones

Parameter	Fixed-Wing	Multirotor
Lift generation	Aerodynamic lift from a fixed wing surface, like an airplane	Lift from multiple spinning rotors/propellers
Flight time	Longer endurance, more energy efficient	Shorter flight time, higher power consumption
Hovering	Cannot hover in place	Can hover, take off, and land vertically (VTOL)
Applications	Large-area mapping, long-range surveillance	Photography, inspection, precision tasks in confined spaces

(c) Quadcopter vs Hexacopter

Parameter	Quadcopter	Hexacopter
Number of rotors	4	6
Redundancy	Loss of one motor causes a crash	Can often stabilize and land safely even if one motor fails
Payload capacity	Lower	Higher, suited for carrying cameras/equipment
Cost & complexity	Simpler and cheaper	More expensive, more complex wiring and ESCs

Q4. How a Quadcopter Flies [10 Marks]

A quadcopter is a rotary-wing aircraft that stays airborne by continuously balancing four fundamental forces acting on its body: thrust, lift, gravity (weight), and drag. Flight is achieved not by a fixed wing but by the rapid rotation of four propellers, each driven by its own brushless DC (BLDC) motor.

The Four Forces

- **Thrust:** The propulsive force generated when each propeller spins and accelerates air downward. By Newton's third law, as the propeller pushes air down, an equal and opposite reaction pushes the drone upward. Thrust always acts along the axis of the propeller, opposite to the direction the air is being pushed.
- **Lift:** In the context of a multirotor, lift is effectively the vertical (upward) component of the combined thrust from all four propellers. When total lift exceeds total weight, the drone climbs; when they are equal, it hovers; when lift is less than weight, it descends.
- **Gravity (Weight):** The constant downward force equal to the drone's mass multiplied by gravitational acceleration ($W = mg$). This force never changes during flight and must always be overcome or balanced by thrust.
- **Drag:** The aerodynamic resistance opposing the drone's motion through air, arising both from the frame moving forward and from air resistance on the spinning propellers themselves. Drag increases with speed and affects battery consumption and maneuverability.

Propeller Rotation and Lift Generation

Each propeller blade is shaped as a small airfoil with a pitch angle. As the BLDC motor spins the propeller at high RPM, the angled blades slice through the air, creating a pressure difference above and below the blade (lower pressure above, higher pressure below), similar to an airplane wing. This pressure difference, combined with the direct downward acceleration of air mass, generates upward thrust. Increasing motor RPM increases thrust; decreasing RPM reduces it — this is the fundamental mechanism the flight controller uses to control the drone in every axis.

Clockwise (CW) and Counter-Clockwise (CCW) Motors

A standard quadcopter arranges its four motors in an X or + pattern, with two motors spinning clockwise (CW) and two spinning counterclockwise (CCW), positioned diagonally opposite each other. This is essential because a spinning propeller also imparts a reactive torque on the drone's frame in the opposite direction to its spin (Newton's third law applied to rotation). If all four propellers spun the same way, the entire drone body would spin uncontrollably in the opposite direction. By pairing two CW and two CCW motors, the reactive torques cancel out during steady hover, keeping the frame rotationally stable. The flight controller can also deliberately unbalance this torque (speeding up the CW pair relative to the CCW pair, or vice versa) to make the drone yaw on command.

In summary: four independently controlled motors, opposing rotation directions to cancel torque, and differential thrust across the four motors together allow a quadcopter to achieve controlled, stable flight in all directions.

Forces Acting on a Quadcopter & Motor Rotation (CW/CCW)




Figure 1: Forces acting on a quadcopter and CW/CCW motor arrangement.

Q5. Take-off, Landing, Hovering, and Directional Movement [10 Marks]

Every maneuver a quadcopter performs is achieved purely by changing the relative speed of its four motors. The flight controller never physically tilts a motor; instead, it commands small, precise differences in RPM across the four propellers, and the resulting imbalance in thrust tilts or rotates the whole airframe.

Take-off

All four motors are commanded to increase speed simultaneously and by equal amounts. Since the propellers are symmetric about the centre of gravity, this produces a uniform increase in total thrust with no tilt. Once total thrust exceeds the drone's weight, a net upward force acts on the drone and it accelerates vertically upward, away from the ground.

Hovering

To hold a fixed position in the air, the flight controller continuously adjusts all four motors so that total thrust exactly equals the drone's weight ($T = W$). The IMU and barometer feedback tiny deviations in altitude and tilt, and the PID

loop makes micro-corrections many times per second, so hovering is really a continuous, rapid balancing act rather than a static state.

Landing

For landing, motor speed is reduced symmetrically across all four motors so that total thrust becomes slightly less than weight. This produces a small net downward force, causing a slow, controlled descent rather than free-fall. As the drone nears the ground, the flight controller typically reduces throttle further and may use an ultrasonic sensor or barometer to judge height and cushion the final touchdown.

Move Forward

The two rear motors are sped up while the two front motors are slowed down. This tilts the drone's nose downward (a forward pitch). Because thrust always acts perpendicular to the propeller plane, tilting the whole airframe also tilts the net thrust vector — part of it now points forward instead of straight up. This horizontal component of thrust accelerates the drone forward, while the reduced vertical component is compensated by a slight overall increase in total thrust to maintain altitude.

Move Backward

The reverse of moving forward: the front motors speed up and the rear motors slow down, pitching the nose upward. The resulting tilted thrust vector now has a horizontal component pointing backward, moving the drone in reverse.

Move Left

The motors on the right side speed up while the motors on the left side slow down, rolling the drone to the left about its front-to-back (X) axis. The tilted thrust vector gains a horizontal component pointing left, translating the drone sideways in that direction.

Move Right

The opposite of moving left: left-side motors speed up and right-side motors slow down, rolling the drone to the right and producing sideways motion to the right.

Rotate (Yaw)

Yaw does not rely on tilting the airframe at all — it exploits the reactive torque of the propellers. The flight controller speeds up the two CW motors while slowing the two CCW motors (or vice versa) by equal and opposite amounts, keeping total thrust (and hence altitude) unchanged. Since the net reactive torque no longer cancels out, the drone body rotates about its vertical Z-axis, changing the direction it is facing without changing its position.




Figure 2: Differential motor speeds producing forward motion, roll, and yaw.

Q6. Block Diagram of a Drone and Component Functions [10 Marks]

A drone is best understood as a closed-loop control system: power flows from the battery to the motors, while command and sensor signals flow into the flight controller, which continuously decides how much power each motor should receive. The block diagram below shows how the major subsystems are interconnected.




Figure 3: Labelled block diagram of a drone system

- **Flight Controller:** The 'brain' of the drone — typically a small microcontroller board (e.g., running ArduPilot or PX4 firmware) that reads sensor data from the IMU, GPS, barometer, and pilot commands from the receiver, then runs a PID control loop to compute the exact speed each motor needs in order to achieve the desired attitude and movement.
- **ESC (Electronic Speed Controller):** One ESC is fitted per motor. It converts the flight controller's low-power PWM/digital signal into the high-current three-phase AC power needed to spin the brushless motor at a precisely commanded speed, updating many times per second.
- **Brushless Motors (BLDC):** Convert electrical energy into mechanical rotation to spin the propellers. They are preferred over brushed motors for their higher efficiency, longer lifespan (no brush wear), lower electrical noise, and superior power-to-weight ratio.
- **Propellers:** Airfoil-shaped blades mounted on the motor shaft; as they rotate, they accelerate air downward, converting the motor's rotational energy into usable thrust.
- **Battery:** Always a Lithium-Polymer (Li-Po) pack in consumer/hobby drones due to its high energy density and high discharge (C) rating; it is the sole energy source for motors, flight controller, and payload.
- **Power Distribution Board (PDB):** A board that takes the single battery input and distributes it in parallel to all four ESCs and other electronics, simplifying wiring and ensuring even voltage supply.
- **GPS Module:** Receives signals from navigation satellites to compute the drone's absolute latitude, longitude, and altitude, enabling autonomous waypoint navigation, geofencing, position-hold, and return-to-home functionality.
- **Radio Receiver:** Mounted onboard, it continuously receives the pilot's stick commands transmitted from the ground-based radio transmitter and passes them as control inputs to the flight controller.
- **Frame:** The mechanical skeleton (often carbon fibre or plastic composite) that rigidly holds the motors, flight controller, battery, and other components in a fixed geometric arrangement, determining the drone's size, strength, and vibration/resonance behaviour.
- **Telemetry Module:** A radio link (separate from the control radio) that streams real-time flight data — battery voltage, GPS coordinates, altitude, speed — back to a ground control station, and in some setups allows the ground station to send commands upward as well.

Q7. Role of Key Components [10 Marks]

While Q6 focused on how these components are wired together, this section explains the specific functional role that each part plays in enabling safe and controllable flight.

Component	Role
Flight Controller	Central processing unit; fuses sensor data and executes control algorithms (e.g., PID) to stabilize and steer the drone
ESC	Regulates power delivered to each motor based on flight controller commands, controlling motor speed precisely
BLDC Motor	Produces rotational force to spin propellers; efficient, brushless design reduces wear and enables high RPM
Propeller	Converts motor rotation into aerodynamic thrust to lift and move the drone
Li-Po Battery	Lightweight, high-discharge-rate energy source that powers the entire drone system
GPS	Supplies global position/altitude data for autonomous navigation, geofencing, and return-to-home
Radio Transmitter	Handheld device the pilot uses to send control inputs (throttle, roll, pitch, yaw) to the drone
Frame	Structural chassis that mounts all components and withstands flight loads and vibration
BEC (Battery Eliminator Circuit)	Steps down battery voltage to a regulated low voltage (e.g., 5V) to safely power the flight controller and receiver
Telemetry Module	Provides two-way wireless data link between the drone and ground station for live monitoring and control

Q8. Working Principle and Application of Drone Sensors [10 Marks]

Sensor	Purpose	Working Principle	Application
IMU (Inertial Measurement Unit)	Measures orientation and motion	Combines accelerometer and gyroscope (often with magnetometer) data to estimate attitude	Core input for flight stabilization and attitude control
Accelerometer	Measures linear acceleration	MEMS-based proof mass deflection converted to electrical signal proportional to acceleration	Detects tilt and helps stabilize the drone
Gyroscope	Measures angular velocity	MEMS vibrating structure senses Coriolis force during rotation	Detects roll, pitch, and yaw rate for stability control

Magnetometer	Measures magnetic heading	Detects Earth's magnetic field to determine compass direction	Provides yaw/heading reference for navigation
Barometer	Measures altitude	Senses atmospheric pressure changes with height	Maintains stable altitude hold
GPS	Measures absolute position	Trilaterates position from satellite signal timing	Autonomous navigation, waypoint missions, return-to-home
Optical Flow Sensor	Measures relative horizontal motion	Tracks visual pixel movement between consecutive camera frames	Position holds indoors/GPS-denied environments
Ultrasonic Sensor	Measures short-range distance	Emits ultrasonic pulse and measures time of reflection	Low-altitude height holds and obstacle detection
LiDAR	Measures precise distance/mapping	Emits laser pulses and measures time-of-flight of reflections	3D terrain mapping and obstacle avoidance
Camera	Captures visual data	Optical sensor (CMOS/CCD) capturing images/video	Aerial photography, visual navigation, computer vision

Q9. Comparisons [5 Marks]

(a) GPS vs Optical Flow

GPS provides absolute global positioning using satellite signals and works best outdoors with a clear sky view but is unreliable indoors or in urban canyons. Optical flow uses a downward-facing camera to track relative ground movement and works well indoors or at low altitude, but requires adequate lighting and textured surfaces, and does not provide absolute position.

(b) LiDAR vs Ultrasonic

LiDAR uses laser pulses to measure distance with high precision and long range, and is capable of generating detailed 3D maps, but is costlier and more power-hungry. Ultrasonic sensors use sound waves, are cheaper and lightweight, but have a short range and lower accuracy, making them suitable for near-ground altitude sensing.

(c) Gyroscope vs Accelerometer

A gyroscope measures angular velocity (rate of rotation) and is used to detect roll, pitch, and yaw rates, while an accelerometer measures linear acceleration and gravitational tilt. Both are fused together (sensor fusion) inside the IMU to obtain accurate, drift-free orientation estimates.

Q10. Six Degrees of Freedom (6DOF) [5 Marks]

6 Degrees of Freedom refers to the six independent ways a rigid body, such as a drone, can move in three-dimensional space: three translational and three rotational.

- Translation along X-axis (Surge): Forward/backward movement.
- Translation along Y-axis (Sway): Left/right sideways movement.
- Translation along Z-axis (Heave): Up/down vertical movement.
- Rotation about X-axis (Roll): Tilting side to side.
- Rotation about Y-axis (Pitch): Tilting nose up or down.
- Rotation about Z-axis (Yaw): Rotating left or right about the vertical axis.

A drone's flight controller must continuously sense and control all six of these to achieve stable, controlled flight.

6 Degrees of Freedom (6DOF): Translation (Surge, Sway, Heave) & Rotation (Roll, Pitch, Yaw)




Figure 4: 6DOF — translation and rotation axes of a drone

Q11. Roll, Pitch, Yaw, Surge, Sway, and Heave [10 Marks]

These six terms describe the complete set of independent motions available to a drone (its 6 Degrees of Freedom, discussed in Q10). Roll, pitch, and yaw are rotational motions about the drone's own three axes, while surge, sway, and heave are translational (straight-line) motions along those same three axes. A drone achieves all six by varying thrust differentially across its four motors, as explained in Q5.

Term	Type	Description	Example in a Drone
Roll	Rotation (X-axis)	Tilting left or right around the front-to-back axis	Drone tilts right to move sideways to the right
Pitch	Rotation (Y-axis)	Tilting nose up or down around the side-to-side axis	Drone tilts nose down to accelerate forward
Yaw	Rotation (Z-axis)	Rotating clockwise or counterclockwise about the vertical axis	Drone spins to face a new direction without changing position
Surge	Translation (X-axis)	Straight-line movement forward or backward	Drone flies forward toward a waypoint
Sway	Translation (Y-axis)	Straight-line sideways movement	Drone drifts sideways due to wind, or shifts left deliberately
Heave	Translation (Z-axis)	Straight-line vertical movement	Drone climbs during take-off or descends while landing

In practice, a pilot's stick inputs are translated by the flight controller into a combination of these six motions — for instance, flying diagonally forward-left while climbing is simultaneous surge, sway, and heave, achieved by superimposing the individual motor-speed adjustments each motion requires.

Q12. Complete Signal Flow in a Drone [5 Marks]

The control signal in a drone travel through a well-defined chain: the pilot moves the sticks on the radio transmitter, which encodes the control inputs (throttle, roll, pitch, yaw) into a radio signal. This signal is picked up by the onboard radio receiver and passed to the flight controller. The flight controller combines these commands with real-time sensor data (IMU, GPS, barometer) and runs a PID control loop to calculate the required speed for each motor. These motor commands are sent to the ESCs, which regulate power delivery to each BLDC motor accordingly. The motors spin the propellers at the commanded speeds, generating differential thrust that produces the desired drone movement.

Complete Signal Flow in a Drone




Figure 5: Signal flow — Pilot Input → Transmitter → Receiver → Flight Controller → ESC → Motors → Propellers → Movement

Q13. Importance of PID Control in Drones [5 Marks]

A drone is an inherently unstable system — without continuous correction it will tip over or drift due to small disturbances like wind or uneven thrust. PID (Proportional-Integral-Derivative) control is the algorithm the flight controller uses to continuously compare the drone's actual state (e.g., tilt angle) against the desired state and adjust motor output to minimize this error in real time.

- Proportional (P): Produces a correction directly proportional to the current error. A larger tilt produces a larger, immediate correction, but P alone can leave a steady-state error and cause oscillation if too high.
- Integral (I): Accumulates past error over time and corrects for any persistent, steady state offset that proportional control alone cannot eliminate (e.g., a constant drift caused by an unbalanced frame).
- Derivative (D): Reacts to the rate of change of the error, effectively 'predicting' future error and damping oscillations, resulting in a smoother, more stable response.

Together, the three terms are tuned (PID gains: K_p , K_i , K_d) to give the drone a fast, stable, and accurate response, which is essential for smooth hovering, precise maneuvering, and resistance to external disturbances such as wind.

Q14. Bonus — Research Questions (Any Two) [10 Marks]

1. Compare DJI, ArduPilot, and PX4 Flight Controllers

Flight controller platforms differ in their philosophy, openness, and target audience. DJI represents the closed, consumer-optimized end of the spectrum, while ArduPilot and PX4 represent the open-source, developer-friendly end.

Parameter	DJI	ArduPilot	PX4
Nature	Proprietary, closed-source ecosystem	Open-source firmware	Open-source firmware

Ease of use	Very user-friendly, plug-and-play, minimal setup	Moderate — requires configuration via Mission Planner	Moderate — requires configuration via QGroundControl
Customization	Limited, locked to DJI hardware/software	Highly customizable, supports many vehicle types (copters, planes, rovers, submarines)	Highly customizable, modular architecture built on NuttX/POSIX RTOS
Vehicle support	Primarily DJI's own multirotor and select fixed-wing products	Multirotor, fixed-wing, VTOL, ground rovers, boats, submarines	Multirotor, fixed-wing, VTOL, ground vehicles
Typical users	Consumers, photographers, commercial operators wanting reliability out-of-the-box	Hobbyists, researchers, hardware tinkerers	Researchers, industrial/commercial developers, academia
Community & support	Official DJI support; source code closed to the public	Large, long-established open-source community	Strong open-source community backed by the Drone code Foundation (Linux Foundation)
Cost	Higher (bundled proprietary hardware)	Lower — runs on inexpensive open-source-compatible boards	Lower — runs on inexpensive open-source-compatible boards

In short, DJI suits users who want a reliable, ready-to-fly product with minimal tinkering, whereas ArduPilot and PX4 suit developers and researchers who need full access to the flight-control code to customise behaviour, add new sensors, or build entirely new types of vehicles.

2. How Do Drones Return to Home Automatically? (Return-to-Home / RTH)

Return-to-Home (RTH) is a safety feature that allows a drone to autonomously fly back to its take-off point without pilot input. It is one of the most important fail-safe mechanisms in modern UAVs and is typically triggered under three circumstances: critically low battery voltage, loss of the radio control signal beyond a timeout period, or a manual RTH command issued deliberately by the pilot.

- Step 1 — Recording home position: The instant the drone achieves a stable GPS lock at start-up (before take-off), the flight controller records this location as the 'home point' (latitude, longitude, and ground altitude).
- Step 2 — Trigger detection: The flight controller continuously monitors battery voltage, signal strength/link quality, and pilot inputs. If any RTH trigger condition is met, it switches the vehicle from its current flight mode into RTH mode.

- Step 3 — Climb to safe altitude: Before heading back, the drone typically climbs (or descends) to a pre-configured safe RTH altitude, chosen to be higher than any known obstacles such as trees or buildings along the expected path.
- Step 4 — Path computation and navigation: Using its current GPS coordinates and the stored home coordinates, the flight controller calculates the bearing and distance to home, then commands the motors to fly along this path — most basic systems fly a straight line, while more advanced systems can follow a pre-mapped safe corridor.
- Step 5 — Sensor fusion during return: GPS provides horizontal position, the barometer (and sometimes a downward-facing ultrasonic/LiDAR sensor) maintains the correct altitude, and the IMU keeps the aircraft stable, all working together throughout the return flight.
- Step 6 — Final descent and landing: Once the drone arrives above the home coordinates, it either automatically descends and lands, or holds a hover above the home point awaiting further pilot command, depending on how RTH is configured.

More advanced commercial drones add obstacle-avoidance sensors (ultrasonic, LiDAR, or stereo cameras) so that if an obstruction is detected during the return flight, the flight controller can dynamically adjust the path around it rather than blindly flying a straight line, making RTH considerably safer in cluttered environments such as forests or urban areas.

Q15. Practical Activity — Identify and Label Every Component of a Drone [10 Marks]

The diagram below is an original labelled illustration (top view) identifying every major structural and electronic component of a standard quadcopter, including the frame arms connecting the central body to each motor.

Labeled Components of a Quadcopter Drone (Top View)




Figure 6: Labelled components of a quadcopter drone (top view)

Component	Function
Frame / Arms	The four rigid struts extending from the central body to each motor. They hold the motors at a fixed distance and angle from the centre of gravity, which is essential for stable, predictable thrust distribution; arm length and material (plastic, carbon fibre) directly affect the drone's rigidity, weight, and vibration behaviour.
Flight Controller (FC/APM)	The onboard computer that reads all sensor data (IMU, GPS) and pilot commands, then runs the PID control loop to compute individual motor speeds for stable flight.
GPS Module	Mounted on a raised mast (to keep it away from motor electromagnetic interference), it supplies absolute position and altitude data for autonomous navigation, position-hold, and return-to-home.
ESC (Electronic Speed Controller)	One per motor, mounted along each arm; converts the flight controller's low-power command into the high-current three-phase power that drives that motor at the exact commanded speed.

BLDC Motor	Mounted at the tip of each arm; spins the propeller. Brushless motors are used for their efficiency, durability, and high power-to-weight ratio.
Propeller	Attached directly to each motor shaft; converts rotational motion into thrust by accelerating air downward.
Li-Po Battery	Mounted centrally (usually underneath the flight controller) to keep the centre of gravity balanced; supplies power to the entire drone.
Landing Gear	The legs extending below each arm; support the drone's weight on the ground during take-off and landing and protect the underside electronics and camera/gimbal (if fitted) from ground impact.

Together, these components form a complete, self-contained flying system: the battery powers everything; the GPS and other sensors feed the flight controller with positional and orientation data; the flight controller computes the required correction and sends it to the ESCs; the ESCs drive the BLDC motors at the arms' ends; and the arms and landing gear provide the rigid mechanical structure that keeps all of this correctly positioned in flight and safely supported on the ground.

Higher-Order Thinking Questions

1. Why do quadcopters require four motors instead of one?

A quadcopter needs four motors because each motor helps control both lift and movement. By changing the speed of individual motors, the drone can move forward, backward, sideways, and rotate. With only one motor, the drone would simply spin and wouldn't be able to stay balanced or controlled.

2. What would happen if one motor stops working during flight?

If one motor suddenly stops, the drone loses its balance because the thrust is no longer equal. It will start spinning uncontrollably and usually crash. That's why it's important to regularly check the motors and propellers before flying.

3. Why are brushless motors preferred over brushed motors?

Brushless motors are more efficient, last much longer, and produce more power. Since they don't have brushes rubbing inside, they generate less heat and require very little maintenance. This makes them the best choice for drones that need reliable performance.

4. Can a drone fly indoors without GPS? Explain.

Yes, it can. Indoors, GPS signals are usually weak or unavailable, so the drone relies on its IMU, gyroscope, accelerometer, and sometimes optical flow or vision sensors to maintain stability. However, flying indoors requires careful control because the drone can't hold its position using GPS.

5. Why are Li-Po batteries used in drones instead of standard batteries?

Li-Po batteries are lightweight and can deliver a high amount of current in a short time, which is exactly what drone motors need during takeoff and quick movements. Standard batteries are heavier and cannot provide enough power, making them unsuitable for drone applications.

6. What factors reduce a drone's flight time?

Several factors can reduce flight time, such as carrying extra payload, flying in strong winds, frequent rapid acceleration, old or damaged batteries, and low temperatures. Efficient flying and a healthy battery usually result in longer flight times.

7. How can drone stability be improved during strong winds?

To improve stability in strong winds, I would use a well-tuned flight controller, calibrate the sensors properly, and use GPS with IMU for better position control. A stronger frame, efficient motors, and slightly reducing the flying speed also help the drone remain stable.

8. Why is sensor fusion important in drones?

Sensor fusion combines data from multiple sensors, such as the IMU, GPS, magnetometer, and barometer, to give the flight controller a more accurate understanding of the drone's position and movement. This improves stability, navigation, and overall flight safety because relying on a single sensor can lead to inaccurate readings.

9. Explain how GPS and IMU work together for stable navigation.

The IMU measures the drone's acceleration, rotation, and orientation many times every second, giving quick movement information. GPS provides the drone's actual position on Earth but updates more slowly. By combining both, the drone gets fast response from the IMU and accurate location from GPS, allowing it to fly smoothly and maintain its position.

10. If you were designing a drone for mountain rescue operations, which sensors and components would you choose, and why?

For a mountain rescue drone, I would choose:

- **Thermal camera** to detect people in low visibility or at night.
- **High-resolution RGB camera** for live video monitoring.
- **LiDAR or ultrasonic sensors** to avoid obstacles like trees and rocks.
- **GPS with RTK** for accurate positioning.
- **IMU and barometer** for stable flight and altitude measurement.
- **Long-range communication module** for reliable control in remote areas.
- **High-capacity Li-Po battery** for longer flight time.
- **Powerful brushless motors** to handle strong winds and carry emergency supplies.
- **Flight controller (like Pixhawk)** for autonomous navigation and mission planning.

These components would help the drone fly safely in difficult terrain, locate missing people quickly, and deliver small medical supplies if needed.

Citations / References

- ArduPilot Documentation — <https://ardupilot.org/>
- PX4 Autopilot Documentation — <https://docs.px4.io/>
- DJI Official Website — <https://www.dji.com/>
- NASA — Unmanned Aerial Vehicles overview — <https://www.nasa.gov/>
- Federal Aviation Administration (FAA) — UAS basics — <https://www.faa.gov/uas>