



# Angular 5 CT Specialization

## Angular Material Lab 3

January 2019

CitiusTech has prepared the content contained in this document based on information and knowledge that it reasonably believes to be reliable. Any recipient may rely on the contents of this document at its own risk and CitiusTech shall not be

responsible for any error and/or omission in the preparation of this document. The use of any third party reference should not be regarded as an indication of an endorsement, an affiliation or the existence of any other kind of relationship between CitiusTech and such third party

## Document Control

Version	1.0
Created by	Karthikeyan J
Updated by	Karthikeyan J
Reviewed by	
Date	January, 2019
Earlier versions	



## Table of Contents

Creating a <i>demo</i> module for experimenting with Angular Material .....	3
Lazy Loading the feature module.....	4

## Creating a *demo* module for experimenting with Angular Material

1. Create a module named **demo** with its own routing logic using the following command:

```
D:\angular5specialization\angularmaterialapp>ng generate module demo --routing
```

2. Create a component named **buttons** inside the **demo** module with an inline template & style & without any testing code using the following command:

```
D:\angular5specialization\angularmaterialapp>ng g c demo/buttons --flat --inline-style --inline-template --skipTests
```

3. Move all the code from **app.component.html** to the above created component's inline template.

## Lazy Loading the feature module

4. Add the following markup inside **app.component.html**:

```
<router-outlet></router-outlet>
```

5. Open **app.module.ts** file & add the following import statement:

```
import {Routes,RouterModule} from '@angular/router';
```

6. Add the following routes as well:

```
const routes = [  
  {path:'demo', loadChildren:'./demo/demo.module#DemoModule'},  
  {path:'**', redirectTo:'demo'}  
];
```

7. Add the following inside the **imports** array of the **NgModule** decorator:

```
RouterModule.forRoot(routes)
```

8. Add the following code inside the **AppModule** class:

```
constructor()  
{  
  console.log("AppModule loaded");  
}
```

9. Open **demo-routing.module.ts** file & add the following import statement:

```
import {ButtonsComponent} from './buttons.component';
```

10. Add the following inside the **routes** array:

```
{path:'buttons', component:ButtonsComponent},  
{path:'**', redirectTo:'buttons'}
```

11. Add the following code inside the **DemoRoutingModule** class:

```
constructor()  
{  
  console.log("DemoRoutingModule loaded");  
}
```

12. From **app.module.ts**, remove the import statement which imports the **MaterialModule** & add that import statement in the **DemoModule** instead.
13. Serve the application. Notice that the URL shows <http://localhost:4200/demo/buttons> by default & the browser's console log displays a message saying that the **DemoModule** was loaded. Change the URL to <http://localhost:4200> & notice that the application navigates to the **DemoModule** by default which is lazily loaded.
14. Create a new component named **flexbox** in the **demo** module using the following command:  

```
D:\angular5specialization\angularmaterialapp>ng g c demo/flexbox --flat --inline-style --inline-template --skipTests
```
15. Add the following in the **routes** array of **demo-routing.module.ts** file before the last item in the array:  

```
{path: 'flexbox', component: FlexboxComponent}
```
16. Serve the application. Notice that the URL shows <http://localhost:4200/demo/buttons> by default & the browser's console log displays a message saying that the **DemoModule** was loaded. Change the URL to <http://localhost:4200/flexbox> & notice that the application navigates to the **FlexboxComponent**.