```
455. Assign Cookies
                                                                                   Solved ⊗
  Assume you are an awesome parent and want to give your children some cookies. But, you should
  give each child at most one cookie.
  Each child i has a greed factor g[i], which is the minimum size of a cookie that the child will be
  content with; and each cookie j has a size s[j]. If s[j] >= g[i], we can assign the cookie j to
  the child \hat{\mathbf{1}}, and the child \hat{\mathbf{1}} will be content. Your goal is to maximize the number of your content
  children and output the maximum number.
  Example 1:
    Input: g = [1,2,3], s = [1,1]
    Output: 1
    Explanation: You have 3 children and 2 cookies. The greed factors of 3
    children are 1, 2, 3.
    And even though you have 2 cookies, since their size is both 1, you could
    only make the child whose greed factor is 1 content.
    You need to output 1.
class Solution {
  func findContentChildren(_ g: [Int], _ s: [Int]) -> Int {
     let gg = g.sorted()
     let ss = s.sorted()
     var ans = 0
     vari = 0
     var j = 0
     while(i < gg.count && j < ss.count) {
       if(ss[i] >= gg[i]) {
          i = i + 1
          j = j + 1
          ans = ans + 1
       } else {
          j = j + 1
       }
     }
     return ans
  }
}
```