

1.First Web Api using .Net core

FirstWebApi.csproj

```
<Project Sdk="Microsoft.NET.Sdk.Web">
  <PropertyGroup>
    <TargetFramework>net8.0</TargetFramework>
    <Nullable>enable</Nullable>
    <ImplicitUsings>enable</ImplicitUsings>
  </PropertyGroup>
  <ItemGroup>
    <PackageReference Include="Swashbuckle.AspNetCore" Version="6.5.0" />
  </ItemGroup>
</Project>
```

Program.cs

```
var builder = WebApplication.CreateBuilder(args);
builder.Services.AddControllers();
builder.Services.AddEndpointsApiExplorer();
builder.Services.AddSwaggerGen();
var app = builder.Build();
app.UseSwagger();
app.UseSwaggerUI();
app.UseAuthorization();
app.MapControllers();
app.Run();
```

Controllers/ValuesController.cs

```
using Microsoft.AspNetCore.Mvc;
namespace FirstWebApi.Controllers
{
```

```

[Route("api/[controller]")]
[ApiController]
public class ValuesController : ControllerBase
{
    [HttpGet]
    public ActionResult<IEnumerable<string>> Get()
    {
        var values = new List<string> { "value1", "value2" };
        return Ok(values);
    }

    [HttpGet("{id}")]
    public ActionResult<string> Get(int id)
    {
        return Ok($"value with id = {id}");
    }

    [HttpPost]
    public ActionResult Post([FromBody] string value)
    {
        return Ok($"Received: {value}");
    }

    [HttpPut("{id}")]
    public ActionResult Put(int id, [FromBody] string value)
    {
        return Ok($"Updated id {id} with value: {value}");
    }

    [HttpDelete("{id}")]
    public ActionResult Delete(int id)
    {
        return Ok($"Deleted id {id}");
    }
}

```

```
}  
}
```

appsettings.json

```
{  
  "Logging": {  
    "LogLevel": {  
      "Default": "Information",  
      "Microsoft.AspNetCore": "Warning"  
    }  
  },  
  "AllowedHosts": "*"   
}
```

OUTPUT

```
[  
  "value1",  
  "value2"  
]
```