

1. Bug Report Table Structure

	Title / Summary	Steps to Reproduce	Expected vs Actual	Severity	Suspected Cause
1	Race Condition: Multi-click Duplicate Submission	1.Navigate to 'New Article' view. 2. Populate mandatory form fields. 3. Trigger 'Publish' button multiple times in rapid succession.	Expected: UI blocks subsequent inputs; fires single payload. Actual: UI remains active, processing parallel requests and creating duplicate database rows.	High	Missing “disabled” state toggle or UI component locking on the submit button during active promise resolution.
2	Unhandled Server Exception on Malformed Email Auth	1. Access the Sign-up screen. 2. Input string lacking standard pattern constraints (e.g., "pratik_kumar"). 3. Submit the registration form.	Expected: Client-side validation blocks execution with a localized formatting alert. Actual: Form execution bypasses UI check, forcing an unhandled HTTP 500 server exception.	Medium	Client-side Regex input validation hooks are missing or unlinked from the form submission handler.
3	Stored XSS via Malicious Script Payload Injection	1. Create a new article draft. 2. Inject <code><script>alert('XS S')</script></code> directly inside the article body field. 3. Save, publish, and load the rendered view.	Expected: Vulnerable tags should be html-escaped and rendered strictly as static strings. Actual: The script executes live in the user's DOM context on page render.	Critical	Frontend template uses raw unescaped innerHTML binding blocks instead of passing strings through sanitization filters like DOMPurify.

	Title / Summary	Steps to Reproduce	Expected vs Actual	Severity	Suspected Cause
4	App Hang / Black-Hole State on Authentication Expiry	1. Authenticate and log in. 2. Clear the active JWT bearer string from browser LocalStorage manually. 3. Click any restricted route (e.g., Profile section).	Expected: Clean interception of unauthorized traffic with automatic routing back to “/login”. Actual: Application crashes into a permanent blank screen freeze with no user feedback.	High	Global Axios/ Fetch interceptor configuration does not explicitly parse HTTP 401 hooks to force clean path redirects.
5	Memory Overload via Unbounded Endpoint Pagination	1. Launch the application landing page. 2. Open browser Network Inspector panel. 3. Select and examine the global /articles GET pipeline.	Expected: API fetches structured chunked objects using data cursors. Actual: The target router dumps the entire unbounded collection array at once, driving high latency.	Medium	Backend controller layer omits explicit default “limit and offset “ query parameters on database select queries.

2. Root-Cause Analysis (RCA)

"The duplicate article creation bug (Issue #1) represents a critical async race condition flaw in the frontend UI rendering tier. When a user fires the click action on the submit handler element, the application lifecycle initiates an asynchronous HTTP POST request to map backend entities. However, the component state fails to immediately latch and implement a state locking mechanism on the event target node. Under low network bandwidth or high user click rates, multiple duplicate network frames escape into flight simultaneously.

Since the backend layer lacks unique transactional idempotency keys for this operational route, it processes every incoming thread as a brand-new distinct record entry. Resolving this requiring binding a reactive state machine flag (like an `isSubmitting` boolean) onto the component lifecycle to force an absolute absolute element block until state promises successfully settle."