



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence & Data Science

Name:	Pratik Sanjay Avhad
Roll No:	01
Class/Sem:	TE/V
Experiment No.:	10
Title:	Implementation of page rank algorithm
Date of Performance:	
Date of Submission:	
Marks:	
Sign of Faculty:	



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence & Data Science

Aim: To implement Page Rank Algorithm

Objective: Develop a program to implement a page rank algorithm.

Theory:

PageRank (PR) is an algorithm used by Google Search to rank web pages in their search engine results. PageRank works by counting the number and quality of links to a page to determine a rough estimate of how important the website is. Page Rank Algorithm is designed to increase the effectiveness of search engines and improve their efficiency. It is a way of measuring the importance of website pages. Page rank is used to prioritize the pages returned from a traditional search engine using keyword searching. Page rank is calculated based on the number of pages that point to it. The value of the page rank is the probability will be between 0 and 1. A web page is a directed graph having two important components: nodes and connections. The pages are nodes and hyperlinks are the connections, the connection between two nodes. Page rank works by counting the number and quality of links to a page to determine a rough estimate of how important the website is. The underlying assumption is that more important website are likely to receive more links from other websites. The page rank value of individual node in a graph depends on the page rank value of all the nodes which connect to it and those nodes are cyclically connected to the nodes whose ranking we want; we use converging iterative method for assigning values to page rank. In short page rank is a vote, by all the other pages on the web, about how important a page is. A link to a page count as a vote of support. If there is no link, there is no support.

We assume that page A has pages B.....N which point to it. Page rank of a page A is given as follows:

$$PR(A) = (1 - \beta) + \beta ((PR(B)/\text{cout}(B)) + (PR(C)/\text{cout}(C)) + \dots + (PR(N)/\text{cout}(N)))$$

Parameter β is a teleportation factor which can be set between 0 and 1. Cout(A) is defined as the number of links going out of page A.

CODE:

```
import java.util.*;
import java.io.*;
```

CSL503: Data warehousing and Mining Lab



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence & Data Science

```
public class PageRank {
public int path[][] = new int[10][10];
public double pagerank[] = new double[10];
public void calc(double totalNodes) {
double InitialPageRank;
double OutgoingLinks = 0;
double DampingFactor = 0.85;
double TempPageRank[] = new double[10];
int ExternalNodeNumber;

int InternalNodeNumber;
int k = 1; // For Traversing
int ITERATION_STEP = 1;
InitialPageRank = 1 / totalNodes;
System.out.printf(" Total Number of Nodes : " + totalNodes + "\t Initial PageRank of All
Nodes : " + InitialPageRank + "\n");
// 0th ITERATION _ OR _ INITIALIZATION PHASE //
for (k = 1; k <= totalNodes; k++) {
this.pagerank[k] = InitialPageRank;
}
System.out.printf("\n Initial PageRank Values , 0th Step \n");
for (k = 1; k <= totalNodes; k++) {
System.out.printf(" Page Rank of " + k + " is :\t" + this.pagerank[k] + "\n");
}
while (ITERATION_STEP <= 2) // Iterations
{
// Store the PageRank for All Nodes in Temporary Array
for (k = 1; k <= totalNodes; k++) {
TempPageRank[k] = this.pagerank[k];
this.pagerank[k] = 0;
}
for (InternalNodeNumber = 1; InternalNodeNumber <= totalNodes;
InternalNodeNumber++) {
for (ExternalNodeNumber=1;
ExternalNodeNumber <= totalNodes;
ExternalNodeNumber++) {
if (this.path[ExternalNodeNumber][InternalNodeNumber] == 1) {
k = 1;
OutgoingLinks = 0; // Count the Number of Outgoing Links for each
ExternalNodeNumber
while (k <= totalNodes) {
if (this.path[ExternalNodeNumber][k] == 1) {
OutgoingLinks = OutgoingLinks + 1; // Counter for Outgoing Links
```



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence & Data Science

```
}  
k = k + 1;  
}  
// Calculate PageRank  
this.pagerank[InternalNodeNumber] += TempPageRank[ExternalNodeNumber] * (1 /  
OutgoingLinks);  
}  
}  
}
```

Output:

Enter the Number of WebPages

4

Enter the Adjacency Matrix with 1->PATH & 0->NO PATH Between two WebPages:

0 1 1 0

0 0 1 1

1 0 0 0

0 0 1 0

Total Number of Nodes: 4 Initial PageRank of All Nodes: 0.25

Initial PageRank Values, 0th Step

Page Rank of 1 is : 0.25

Page Rank of 2 is : 0.25

Page Rank of 3 is : 0.25

Page Rank of 4 is : 0.25

After 1th Step

Page Rank of 1 is : 0.125

Page Rank of 2 is : 0.2125

Page Rank of 3 is : 0.375

Page Rank of 4 is : 0.25

After 2th Step

Page Rank of 1 is : 0.15625

Page Rank of 2 is : 0.24625

Page Rank of 3 is : 0.35625

Page Rank of 4 is : 0.24125



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence & Data Science

Final Page Rank:

Page Rank of 1 is : 0.1833125

Page Rank of 2 is : 0.2593125

Page Rank of 3 is : 0.3528125

Page Rank of 4 is : 0.2385625

Conclusion:

What are the key parameters of the PageRank algorithm, and how do they affect the algorithm's performance?

The key parameters of the PageRank algorithm and their effects are:

1. **Damping Factor (d):** A value (typically around 0.85) that controls the probability of continuing to click links versus jumping randomly. A higher value emphasizes link structure.
2. **Number of Iterations:** The number of times the algorithm runs. More iterations can improve accuracy but increase computation time.
3. **Convergence Threshold:** A criterion for stopping iterations based on changes in PageRank values. A smaller threshold enhances accuracy but requires more computation.
4. **Graph Structure:** The arrangement of nodes and links. Sparse or dense graphs can affect the distribution of PageRank values.
5. **Initial PageRank Values:** Starting values assigned to pages. Though theoretically independent of initial values, poor initialization can slow convergence.
6. **Handling Dead Ends and Spider Traps:** Strategies for pages without outgoing links or that lead back to themselves. Proper handling prevents the algorithm from getting stuck.