ORIUS: A Universal Runtime Safety Layer for Physical AI under Degraded Observation

Pratik Niroula

***Abstract*—ORIUS treats degraded observation as a universal action-semantics hazard for Physical AI: a controller may act legally on the observed state while becoming unsafe on the true state. We present ORIUS, Observation–Reality Integrity for Universal Safety, as a typed runtime layer that detects degraded telemetry, calibrates the observation-consistent state set, constrains the admissible action set, repairs or replaces unsafe candidate actions, and emits auditable certificates before actuation. The paper is universal-first rather than battery-origin. It combines one runtime kernel, one benchmark schema, one governance surface, one theorem bridge, and six domain instantiations spanning battery energy storage, autonomous vehicles, industrial automation, healthcare monitoring, navigation, and aerospace. The evidence posture is explicitly tiered: battery is the witness row; autonomous vehicles, industrial control, and healthcare monitoring are defended bounded rows; navigation and aerospace remain gated by unresolved closure obligations. The resulting claim is architectural universality under one runtime contract and one governed evidence ladder, not flat empirical closure across every domain.**

***Index Terms*—physical AI safety, degraded observation, runtime assurance, safety filters, conformal prediction, cyber-physical systems, benchmark governance, certificates**

I. Introduction

Physical AI systems do not act on truth. They act on telemetry, state estimates, and learned summaries of the world. When that observation channel degrades, the entire software stack can remain internally coherent while the physical system becomes externally unsafe. Batteries can violate hidden state-of-charge limits, vehicles can accelerate on stale headway estimates, industrial plants can cross thermal envelopes, clinical monitoring systems can suppress necessary intervention, and guidance systems can drift outside feasible corridors. ORIUS is built around the claim that this failure mode is not a battery problem, an autonomy problem, or a cyber-security problem in isolation. It is a universal *action-semantics* problem for Physical AI.

This draft therefore asks a narrower but more consequential question than most controller- or model-centric safety papers: what runtime layer is needed once the observation surface itself can no longer be trusted to carry actuation legality? The answer proposed here is ORIUS, Observation–Reality Integrity for Universal Safety, a typed runtime layer that detects degraded observation, calibrates uncertainty to the reduced trust surface, constrains admissible actions, repairs or replaces unsafe candidates, and emits an auditable certificate before release. The contribution is not one universal policy. It is one universal safety grammar that sits between nominal intelligence and physical actuation.

The paper is intentionally universal-first. Battery remains the witness row with the deepest theorem-to-code-to-artifact closure, but it is not treated as the conceptual center of the argument. Instead, the central object is the observation–action safety gap (OASG): the event in which an action is legal on the observed state while unsafe on the true state. That object links conformal and distribution-free uncertainty [1–5], runtime assurance and supervisory control [6–10], safety filters and constrained control [11–14], and anomaly- or degradation-aware cyber-physical monitoring [15–18]. The manuscript's claim is that none of these families alone supplies the runtime bridge from degraded observation to repaired actuation and certificate semantics across multiple physical domains.

The technical move is a Detect–Calibrate–Constrain–Shield–Certify kernel. Detect degraded telemetry and estimate reliability. Calibrate the observation-consistent state set rather than trusting nominal point estimates. Constrain the action set under that inflated state uncertainty. Shield the plant by repairing or replacing the candidate action. Certify the resulting release so fallback, latency, and audit continuity become part of the scientific object rather than operational afterthoughts. ORIUS makes that kernel concrete through one adapter contract, one benchmark schema, and one governance surface. The adapter contract allows batteries, autonomous vehicles, industrial plants, healthcare monitoring, navigation, and aerospace to instantiate the same safety layer without pretending they share the same nominal controller or safety objective.

The evidence posture of this flagship draft is intentionally visible. ORIUS already has one witness row and several defended bounded rows, but equal-domain universality is still gated by missing real-data navigation closure and a stronger aerospace runtime surface. The paper therefore argues for a field-level runtime architecture while keeping the domain promotion gate explicit in the body text rather than hiding it in editorial support material.

The paper makes four contributions.

1) It defines OASG as a universal safety object for Physical AI and frames degraded observation as an action-semantics problem rather than only a detection or estimation problem.
2) It presents ORIUS as a reusable runtime kernel with typed observation, uncertainty, action-repair, fallback, and certificate objects.

3) It unifies benchmark and governance semantics across six domains using one true-state-violation schema and one auditable runtime discipline.
4) It argues, with explicit parity gating, that runtime safety layers are the right universal object for Physical AI safety research even when evidence depth remains asymmetric across domains.

The rest of the paper follows that logic. It formalizes OASG, positions ORIUS adversarially against adjacent literatures, details the runtime kernel and the theorem bridge, walks through six domain instantiations under one shared template, and closes with a synthesis that separates universality of contract from equality of evidence.

II. Problem Definition and Observation–Action Safety Gap

ORIUS starts from a narrow safety object with broad consequences. Let z_t denote the physically true state, $\tilde{z}_t$ the state exposed to the nominal controller, and $\mathcal{A}(\cdot)$ the set of admissible actions under the relevant safety envelope. The observation–action safety gap is the event

$$\mathrm{OASG}_t = \mathbf{1}\{a_t \in \mathcal{A}(\tilde{z}_t) \ \wedge \ a_t \notin \mathcal{A}(z_t)\},$$

which means that the controller is internally consistent on the observed state while the plant is externally unsafe on the true state. This is the failure mode that reappears across battery dispatch, time-to-collision control, process envelopes, clinical intervention logic, navigation corridors, and flight-energy bounds.

The defining difficulty is that OASG is not merely a state-estimation problem. A better estimator helps, but the safety event is ultimately about actuation semantics. If the runtime continues to treat the observed state as authoritative after freshness loss, dropout, delayed updates, sensor disagreement, or reliability collapse, then even a nominally optimal controller may produce a physically unsafe action. ORIUS therefore places the universal object at the boundary between degraded observation and released actuation rather than at the forecaster, planner, or dynamics model alone.

This framing also explains why a single universal policy is not the goal. Different domains retain different state spaces, action geometries, intervention semantics, and fallback policies. What can be shared is the runtime grammar: observation reliability, inflated state uncertainty, tightened admissible actions, repaired actuation, and certificate semantics. The paper argues that this runtime grammar is the right unit of cross-domain reuse for Physical AI safety.

Two practical consequences follow. First, a runtime layer must expose the quality of the observation surface as a first-class object rather than burying it inside model residuals. Second, a universal benchmark must score safety on the true state rather than on nominal controller legality alone. Those consequences drive the ORIUS runtime design, the benchmark schema, and the claim boundary used throughout the rest of the paper.

TABLE I: Canonical OASG runtime objects used throughout the IEEE draft.

Object	Role in the runtime safety layer
$\tilde{z}_t$	Observed state or belief state exposed to the nominal controller.
z_t	Physically true state whose envelope determines actual safety.
w_t	Reliability assessment derived from freshness, missingness, and consistency.
U_t	Observation-consistent uncertainty set widened when reliability drops.
$\mathcal{A}_t^{\mathrm{safe}}$	Tightened admissible action set under degraded observation.
a_t^{safe}	Repaired or fallback action released by the runtime.
Certificate	Auditable payload recording reliability, margin, repair mode, and lifecycle state.

III. Related Work and Why Prior Families Are Not Enough

ORIUS does not claim that prior literatures ignored safety. The claim is more precise: the existing families solve adjacent pieces of the problem, but none by itself closes the runtime bridge from degraded observation to repaired actuation and auditable release.

A. Conformal and distribution-free uncertainty

Distribution-free predictive inference gives a principled way to wrap learned predictions with finite-sample uncertainty sets [1–5, 19, 20]. That is essential for ORIUS because the runtime needs a mechanism for inflating the observation-consistent state set when trust falls. But conformal methods alone do not decide which action remains legal after that inflation. They are uncertainty tools, not actuation semantics.

B. Runtime assurance, supervisory safety, and shields

Simplex architectures, supervisory switching, runtime monitoring, and shielding all provide a strong language for intercepting unsafe actions before execution [6–10, 21, 22]. ORIUS inherits the idea that the nominal controller is not the final authority. The gap is that many supervisory schemes start after the candidate action already exists and assume that the state estimate is sufficiently coherent for the monitor to interpret. ORIUS instead treats the observation surface itself as the thing that becomes unsafe, which forces the supervisor to reason jointly about reliability, uncertainty inflation, repair geometry, and fallback.

C. Safety filters, barrier methods, and constrained control

Barrier functions, robust MPC, predictive safety filters, and reachable-set control make it possible to turn uncertainty into admissible action sets [11–13, 23–27]. These methods are mathematically strong and domain-critical. What ORIUS adds is not a replacement for them, but a typed layer that can host them under one cross-domain contract. The key scientific move is to make the runtime

objects reusable even when the underlying safety geometry differs across domains.

D. Drift, anomaly detection, and degraded telemetry

Change detection, anomaly detection, and cyber-physical fault analysis provide the language for recognizing when observation should no longer be trusted [15–18, 28–32]. ORIUS depends on those methods but goes one step further: an alarm is not enough. The runtime must translate degraded observation into a different admissible action set and record the resulting governance state.

The paper's claim is therefore not that ORIUS supersedes these literatures. It claims that Physical AI needs a reusable runtime layer that binds them together around a single action-semantics problem: once degraded observation enters the loop, the system must decide what may still be safely done, not only whether an anomaly has occurred.

IV. ORIUS Runtime Architecture

ORIUS is organized as a post-nominal runtime layer. It does not replace the upstream predictor, planner, or optimizer. It wraps them with a narrow contract that starts at raw telemetry and ends at a certificate-gated action release. This keeps the framework compatible with legacy controllers while moving the safety argument to the place where degraded observation actually matters.

A. Detect

The detect stage computes an explicit trust signal from freshness, missingness, timing, cross-sensor consistency, and domain-specific degradation indicators. The result is not only an anomaly flag. It is a reliability object that changes the semantics of the rest of the pipeline.

B. Calibrate

The calibrate stage inflates the observation-consistent state set. In the current ORIUS implementation this inflation can be driven by conformal or reliability-conditioned uncertainty, but the runtime requirement is broader: when observation quality drops, the set of physically plausible states must not remain frozen at the nominal point estimate.

C. Constrain

The constrain stage recomputes which actions are admissible under the widened state set. This is the point at which ORIUS ceases to be an alarming subsystem and becomes a true safety layer. The system must translate degraded observation into a smaller safe action surface, not merely record that confidence has fallen.

D. Shield and Certify

The shield stage repairs the proposed action or falls back to a bounded alternative when the tightened set becomes empty. The certify stage records why the released action was allowed, which margins and reliability assumptions were used, and which lifecycle state the runtime now occupies. That certificate is a scientific object in ORIUS, not a deployment afterthought.

The architectural value of this decomposition is that the same pipeline appears in every domain chapter even though the state, action, and repair geometry are different. That shared pipeline is what makes ORIUS universal in architecture before it is universal in evidence depth.

V. Universal Contracts, Benchmark, and Governance

The universal claim only matters if the runtime interface, benchmark interface, and governance interface remain stable across domains. ORIUS enforces that stability through three public surfaces: a single adapter contract, a single benchmark schema, and a single CertOS lifecycle.

A. Adapter contract

Every supported domain enters ORIUS through the same narrow boundary. The adapter must parse telemetry, expose reliability-conditioned uncertainty semantics, tighten the admissible action set, implement repair and fallback, and emit a certificate payload compatible with the runtime ledger. This is intentionally smaller than a full controller API. ORIUS is not trying to normalize planning logic; it is trying to normalize safety interposition.

B. Universal benchmark surface

The benchmark contract scores safety on the true state and keeps the runtime outputs comparable across domains. The canonical step-level fields are `true_constraint_violated`, `observed_constraint_satisfied`, `true_margin`, `observed_margin`, `intervened`, `fallback_used`, `certificate_valid`, `latency_us`, and `domain_metrics`. This schema prevents a domain from claiming safety on an incompatible metric surface.

C. CertOS governance surface

CertOS makes fallback, certificate validity, lifecycle transitions, and audit continuity part of the runtime semantics. A domain may choose different repair maps or fallback modes, but it does not get to opt out of certificate integrity, audit logging, or release-state discipline. This is why ORIUS reads as a systems paper as well as a safety paper.

These interfaces also explain the paper's claim boundary. ORIUS can be universal in contract even when domains remain unequal in proof depth or data maturity. The parity gate is therefore not a contradiction of the architecture; it is the mechanism that stops architectural reuse from being misread as empirical symmetry.

TABLE II: Why adjacent method families are necessary but insufficient for the ORIUS object.

Method family	What it contributes	What remains missing for OASG
Conformal / distribution-free inference	Reliability-aware uncertainty around learned predictions	Does not specify which action remains legal after observation degrades or how fallback is certified.
Runtime assurance / shielding	Supervisory interception and safe-controller override logic	Often assumes the state estimate is already coherent enough to supervise directly.
Safety filters / robust control	Mapping uncertainty into admissible action sets	Usually tied to one plant family or one controller geometry rather than a shared runtime contract.
Anomaly / drift / CPS fault detection	Detecting loss of trust in telemetry or estimation pipelines	Stops at alarms or scores unless paired with actuation repair and governance semantics.



Fig. 1: The ORIUS Detect–Calibrate–Constrain–Shield–Certify kernel. The universal claim is about this runtime grammar rather than about any single nominal controller.

TABLE III: The three canonical ORIUS surfaces used across all domains.

Surface	Canonical objects	Purpose in the universal claim
Runtime adapter	Telemetry ingest, reliability semantics, uncertainty set, safe action set, repair, fallback, certificate payload	Isolates domain-specific safety geometry while keeping the ORIUS kernel itself domain-neutral.
Benchmark schema	True-state violation, observed-state satisfaction, margins, intervention, fallback, certificate validity, latency, domain metrics	Forces all rows to score safety on the true state rather than on controller legality alone.
CertOS governance	Lifecycle state, certificate integrity, fallback semantics, audit continuity, release discipline	Prevents runtime safety from collapsing into an undocumented filter or ad hoc emergency stop.

VI. Theory Bridge and Claim Discipline

The theorem surface of ORIUS is intentionally narrower than the rhetoric of a fully closed universal program. The paper uses theory to justify the shape of the runtime layer, not to imply that every domain has already inherited equal proof depth.

The bridge has three parts. First, if admissibility depends on the true state and the observation channel can deviate materially from that state, then OASG is a genuine safety event rather than a notation trick. Second, if lower reliability produces a monotone inflation of the observation-consistent state set, then the admissible action set must become smaller or remain unchanged. Third, if the runtime only releases actions from that tightened set, or falls back when no such action exists, then the remaining true-state violation risk is governed by the soundness of the uncertainty set and the repair map rather than by the optimism of the nominal controller.

This distinction is important because ORIUS aims to be scientifically ambitious without being careless. The architecture is intentionally written as a universal safety layer for Physical AI. The evidence, however, is tiered. That tiering is not a weakness in the argument; it is the mechanism that keeps theorem language, benchmark

TABLE IV: Theory-to-evidence bridge used in the IEEE draft.

Claim layer	What the paper is willing to claim
Structural	Degraded observation can create action-semantic failure even when the nominal policy is internally coherent.
Contractual	A typed runtime layer can convert reliability loss into tightened admissible action sets, repair, fallback, and certificate semantics.
Empirical	Battery is the witness row; AV, industrial, and healthcare are defended bounded rows; navigation and aerospace remain gated.
Non-claim	The paper does not claim equal theorem depth, equal deployment readiness, or flat closure across all six domains.

language, and runtime language aligned with tracked artifacts.

The practical consequence is straightforward. A domain does not become a defended row because it looks structurally compatible with the adapter contract. It becomes defended only after the data surface, replay surface, repair semantics, fallback semantics, certificate traces, and benchmark outputs all clear the governed promotion gate. That is why the universal claim in this paper is architectural and bounded rather than flatly equalized across the domain portfolio.

VII. Battery as the Witness Domain

Battery remains the witness domain because it carries the deepest theorem-to-code-to- artifact closure in the present ORIUS stack. That status is methodological, not conceptual. The paper is not arguing that batteries are the center of Physical AI. It is using the battery row to show what a fully specified ORIUS instantiation looks like when the theorem chain, benchmark chain, fallback chain, and certificate chain are all present in one place.

A. Hazard and safety object

The battery hazard is simple to state and representative of the larger ORIUS problem. Dispatch can appear legal on the observed state of charge, reserve, or availability surface while already violating the true physical envelope. The safety object is therefore zero true-state violation of the dispatch and state-of-charge envelope under degraded observation.

B. Runtime instantiation

The battery adapter uses reliability scoring, uncertainty inflation over feasible state of charge, action clipping or safe-hold when the admissible power interval collapses, and certificate-gated dispatch release. This makes the witness row useful for more than numerical performance. It shows the full semantics of repair, fallback, certificate expiry, and audit continuity under a domain where the runtime surface is already mature.

C. Why the battery row matters

The witness row earns its role because it exposes all three layers of the ORIUS claim: theoretical motivation, benchmarked repair, and governed runtime release. That closure depth is what the weaker rows are measured against.

This is the right role for battery in a universal-first paper. It anchors the strongest evidence surface while leaving the conceptual center of the manuscript with the runtime layer itself.

VIII. Domain Instantiations under One Runtime Contract

The key test of a universal safety layer is not whether every domain shares the same dynamics or controller. It is whether the same runtime contract survives domain change without losing semantic meaning. ORIUS evaluates that question across six rows.

TABLE V: Why battery remains the witness row in the IEEE draft.

Surface	**Witness-row status**
Formal bridge	Deepest theorem-to-artifact chain in the current ORIUS stack.
Replay evidence	Most complete degraded-observation replay, stress, and runtime traces.
Fallback semantics	Mature safe-hold and bounded repair behavior with certificate traces.
Governance	Strongest CertOS lifecycle and audit continuity evidence.
Role in this paper	Anchors the strongest empirical row without allowing the manuscript to become battery-centric.

A. Autonomous vehicles

The AV row is defended under a bounded safety object: time-to-collision and predictive entry-barrier preservation when the perception or state-estimation surface degrades. The value of the row is that ORIUS is not merely filtering a scalar dispatch command. It is repairing an action inside a tightly constrained interaction envelope while preserving a bounded fallback semantics. The row is defended, but still explicitly limited to the current contract rather than advertised as full autonomy closure.

B. Industrial process control

The industrial row demonstrates that ORIUS also travels into operating regimes with thermodynamic or plant-family constraints rather than geometric avoidance alone. Degraded observation here leads to envelope violation, not just tracking error. The row therefore helps show that ORIUS is about admissible actuation under uncertainty, not about one family of robotic motion tasks.

C. Healthcare monitoring

Healthcare matters because degraded observation can suppress intervention rather than only create excessive actuation. ORIUS still fits that setting because the runtime layer is defined over admissible decisions, fallback policies, and certificate semantics, not only over physical force commands. The defended healthcare row is bounded to the current monitoring and alerting contract, but it proves that the runtime grammar is not limited to mechanical control loops.

D. Navigation and aerospace

Navigation and aerospace are the two honest blockers. Navigation remains structurally compatible with the ORIUS contract but lacks the defended real-data replay chain needed to promote the row. Aerospace carries partial degradation and replay evidence, but not the real multi-flight runtime surface needed for a defended bounded row. These two rows are therefore part of the universal argument and part of the scientific boundary at the same time.

TABLE VI: Six ORIUS domain rows under a shared runtime contract.

Domain	Degraded-observation hazard	Safety object	Current tier	Exact closure boundary
Battery energy storage	Dispatch legal on observed state but unsafe on true state of charge or reserve surface	State-of-charge and dispatch envelope preservation	Witness row	Deepest closure surface in the current stack.
Autonomous vehicles	Action proposed on stale or optimistic headway / collision state	TTC and entry-barrier preservation under repair	Defended bounded row	Bounded to the current TTC plus predictive-entry-barrier contract.
Industrial process control	Control actuation released on degraded plant measurements	Power-temperature or operating-envelope preservation	Defended bounded row	Bounded to the current plant-family and replay surface.
Healthcare monitoring	Clinical alerting or intervention released on degraded vital telemetry	Vital-alert envelope and bounded intervention discipline	Defended bounded row	Bounded to the current monitoring and intervention contract.
Navigation and guidance	Corridor control executed on degraded localization or map consistency	Feasible corridor / obstacle envelope preservation	Gated row	Real-data defended replay chain is still missing.
Aerospace control	Envelope management executed on degraded flight-state surface	Flight-energy / envelope preservation under repair	Gated row	Real multi-flight runtime validation surface is still missing.

IX. Cross-Domain Synthesis

The scientific value of ORIUS is not that every row already looks equally complete. It is that one runtime grammar survives across very different physical systems while the paper remains honest about which rows are defended and which are gated. That distinction is what turns ORIUS from a portability story into a candidate field-level safety layer.

This synthesis yields a sharper universality statement than a transfer-learning claim. ORIUS is not saying that one policy transfers across all six rows. It is saying that Physical AI systems share a runtime failure mode once observation degrades, and that the same kernel can mediate that failure mode while respecting domain-specific safety geometry. That is why the architecture can be universal even when the evidence remains tiered.

The paper therefore keeps the parity gate visible. Battery is the witness row. AV, industrial, and healthcare are defended bounded rows. Navigation and aerospace are visible blockers rather than quiet placeholders. This is not defensive writing. It is the mechanism that lets the paper make a large architectural claim without pretending that universality of contract automatically implies equality of closure.

X. Limitations and Claim Boundary

The ORIUS argument is strongest when the claim boundary remains explicit. This draft does not claim universal optimality, equal-theorem-depth parity, universal hardware closure, or flat deployment readiness across all supported domains. It claims one universal runtime safety layer, one reusable action-semantics grammar for degraded observation, and one governed evidence ladder that determines how much rhetoric each domain row may currently carry.

That distinction matters because the architecture already travels farther than the tracked evidence. Battery is the witness row. Autonomous vehicles, industrial control, and healthcare monitoring are defended bounded rows under explicit contracts. Navigation and aerospace remain the two blocker rows for any equal-domain closure claim. The flagship manuscript therefore uses those domains to show the reach of the runtime contract, while the parity matrix and the private claim-delta ledger preserve the boundary between current repo truth and visionary universal framing.

The bounded-universal position is still scientifically valuable. It makes ORIUS a real cross-domain safety layer today, while giving future closure work a precise target: real-data navigation replay and a non-placeholder aerospace runtime surface with material post-repair improvement on the governing safety object. Those are evidence obligations, not conceptual holes in the runtime grammar itself.

XI. Conclusion

ORIUS argues that the right universal object for Physical AI safety is not a single planner, plant, or benchmark. It is a runtime safety layer that mediates the gap between degraded observation and physical actuation. Once observation quality becomes a source of safety failure, the system must expose reliability, uncertainty inflation, action repair, fallback, and certificate semantics as first-class runtime objects.

That is the role of the Detect–Calibrate–Constrain–Shield–Certify kernel. It turns OASG from an intuitive failure mode into a measurable and governable runtime event, and it does so under one contract that can be instantiated across batteries, autonomous vehicles, industrial plants, healthcare monitoring, navigation, and aerospace without pretending those domains share the same nominal controller or safety geometry.

TABLE VII: What ORIUS standardizes across domains, and what remains domain-specific.

Layer	Shared across all rows	Domain-specific content
Observation semantics	Reliability assessment, degraded-observation detection, uncertainty widening trigger	Sensor modalities, freshness signals, and consistency features.
Safety geometry	Tightened admissible action set, repair-or-fallback release logic	State constraints, action constraints, safety-object geometry.
Benchmarking	True-state violation, intervention, fallback, certificate validity, latency, domain metrics	Domain-specific margin definitions and auxiliary metrics.
Governance	CertOS lifecycle, certificate integrity, audit continuity	Policy-specific fallback payloads and application-specific certificate fields.

The evidence claim is intentionally disciplined. Battery is the witness row. AV, industrial, and healthcare are defended bounded rows. Navigation and aerospace remain the two visible blockers for equal-domain closure. That asymmetry does not weaken the architectural claim. It is what makes the paper scientifically credible: ORIUS can be universal in runtime contract while still governed by a public promotion gate.

The field-level implication is larger than any single benchmark number. ORIUS proposes that Physical AI should be organized around a reusable runtime safety layer that sits between nominal intelligence and actuation, and that this layer should be audited through one benchmark schema and one governance surface. If the remaining gated rows are closed, the same architecture can support a stronger universality claim. Even before that point, ORIUS establishes a reusable safety-layer grammar for Physical AI under degraded observation.

References

[1] V. Vovk, A. Gammerman, and G. Shafer, "Algorithmic learning in a random world," 2005, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[2] Y. Romano, E. Patterson, and R. J. Candès, "Conformalized quantile regression," 2019, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[3] I. Gibbs and E. J. Candès, "Adaptive conformal inference under distribution shift," 2021, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[4] A. N. Angelopoulos and S. Bates, "Conformal prediction: A gentle introduction," 2023, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[5] R. F. Barber, E. J. Candès, A. Ramdas, and R. J. Tibshirani, "Conformal prediction beyond exchangeability," 2023, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[6] Sha, Lui, "Using simplicity to control complexity," 2001, iEEE Software.

[7] Seto, Daisuke and Krogh, Bruce H. and Sha, Lui and Chutinan, Alongkrit, "The simplex architecture for safe online control system upgrades," 1998, proceedings of ACC.

[8] Desai, Ankush and Ghosal, Akash and Saha, Indranil and Yang, Yuhong and Dutle, Aaron and Ivanov, Radoslav and Lee, Insup and Seshia, Sanjit A. and Tiwari, Ashish, "Soter: A runtime assurance framework for programming safe robotics systems," 2019, proceedings of IROS.

[9] Bartocci, Ezio and Falcone, Ylies and Francalanza, Adrian and Reger, Giles, "Introduction to runtime verification," 2018, lecture Notes in Computer Science.

[10] M. Leucker and C. Schallhart, "A brief account of runtime verification," 2009, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[11] A. D. Ames, S. Coogan, M. Egerstedt, G. Notomista, K. Sreenath, and P. Tabuada, "Control barrier functions: Theory and applications," 2019, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[12] K. P. Wabersich and M. N. Zeilinger, "A predictive safety filter for learning-based control of constrained nonlinear dynamical systems," 2021, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[13] Fisac, Jaime F. and Akametalu, Anayo and Zeilinger, Melanie N. and Kaynama, Sahar and Gillula, Jeremy and Tomlin, Claire J., "A general safety framework for learning-based control in uncertain robotic systems," 2019, iEEE Transactions on Automatic Control.

[14] Ben-Tal, Aharon and El Ghaoui, Laurent and Nemirovski, Arkadi, "Robust optimization," 2009, princeton University Press.

[15] Rajkumar, Ragunathan and Lee, Insup and Sha, Lui and Stankovic, John, "Cyber-physical systems: The next computing revolution," 2010, proceedings of DAC.

[16] A. Teixeira, I. Shames, H. Sandberg, and K. H. Johansson, "A secure control framework for resource-limited adversaries," 2015, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[17] Basseville, Michele and Nikiforov, Igor V., "Detection of abrupt changes: Theory and application," 1993, prentice Hall.

[18] Pasqualetti, Fabio and Dorfler, Florian and Bullo, Francesco, "Attack detection and identification in

cyber-physical systems," 2013, iEEE Transactions on Automatic Control.

[19] J. Lei, M. G'Sell, A. Rinaldo, R. J. Tibshirani, and L. Wasserman, "Distribution-free predictive inference for regression," 2018, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[20] M. Zaffran, O. Féron, Y. Goude, J. Jolivet, and A. Dieuleveut, "Adaptive conformal predictions for time series," 2022, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[21] R. Bloem, B. Könighofer, R. Könighofer, and C. Wang, "Shield synthesis: Runtime enforcement for reactive systems," 2015, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[22] Havelund, Klaus and Rosu, Grigore, "An overview of the runtime verification tool java pathexplorer," 2004, formal Methods in System Design.

[23] A. D. Ames, J. W. Grizzle, and P. Tabuada, "Control barrier function based quadratic programs with application to adaptive cruise control," 2014, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[24] D. Q. Mayne, M. M. Seron, and S. V. Raković, "Robust model predictive control of constrained linear systems with bounded disturbances," 2005, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[25] W. Langson, I. Chryssochoos, S. V. Raković, and D. Q. Mayne, "Robust model predictive control using tubes," 2004, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[26] J. B. Rawlings, D. Q. Mayne, and M. M. Diehl, "Model predictive control: Theory, computation, and design," 2017, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[27] Camacho, Eduardo F. and Bordons, Carlos, "Model predictive control," 2013, springer.

[28] Page, E. S., "Continuous inspection schemes," 1954, biometrika.

[29] ——, "A test for a change in a parameter occurring at an unknown point," 1955, biometrika.

[30] Hinkley, David V., "Inference about the change-point in a sequence of random variables," 1971, biometrika.

[31] F. T. Liu, K. M. Ting, and Z.-H. Zhou, "Isolation forest," 2008, imported from the legacy ORIUS bibliography surface in backmatter/references.tex.

[32] Breunig, Markus M. and Kriegel, Hans-Peter and Ng, Raymond T. and Sander, Jorg, "Lof: Identifying density-based local outliers," 2000, proceedings of SIGMOD.