From Human Markets to Machine Markets

Feedback Stability, Auditable Memory, and Financial Constraints

Integrated research manuscript, version 0.5
18 September 2026

Abstract

Adaptive financial agents can alter the market observations on which they subsequently act. This paper studies what measurements can establish about that feedback, rather than claiming that artificial intelligence replaces fundamental financial identities. We integrate a joint market–learning framework, finite-window counterexamples, a full-horizon identification audit, and observable order–price experiments. Earlier findings favor conventional full-information bounds over the original summary diagnostic and show that a false learning-rate floor can invalidate an otherwise accurate response estimate. We extend the analysis with explicit implementation-conditioned tail bounds, terminal-row inference from public price histories and audited update rules, and a funded transaction model. The architectural contract is stronger than a black-box rate assumption and requires a truthful reset and complete channel inventory; a self-issued manifest is not sufficient. In 2,880 primary audited-model panels, gain intervals cover the truth in 95.76% of cases. A fresh-seed endpoint-design comparison improves definite decisions at small episode budgets but loses that advantage at the largest budget; wrong calls are retained. The funded model enforces inventory, leverage and credit constraints, forced liquidation, rejected fills and dealer halts. Its local linear certificate is not extrapolated through those nonlinearities. Instead, exact binomial intervals quantify a specified finite-horizon loss event. A preloaded dealer can halt frequently even when the isolated signal-feedback model is locally stable. All experiments are synthetic and uncalibrated; several primary financial settings are easy probability extremes. Source, observations, complete result rows, failure controls and alternate internal verifiers are released. No outside replication, authenticated institutional audit, established novelty or real-market crisis-prediction capability is claimed.

Keywords: adaptive agents; endogenous risk; financial stability; market microstructure; performative prediction; system identification.
JEL codes: C63, D83, G01, G14.

Evidence status. Model-conditioned theory and synthetic experiments are complete for the declared protocols; real-market validation is not. The original framework and both companion findings are integrated, not silently replaced. Version 0.5 adds audited-memory inference and binding simulated balance sheets. No trained neural agents, calibrated exchange implementation, independent outside replication, established priority, or financial-safety deployment is claimed. A correct response estimate does not validate unobserved model assumptions.

1 Introduction

The central question of this research program is whether large-scale delegation of financial decisions to adaptive artificial agents changes the conditions under which financial markets absorb or amplify disturbances. A trader may update a forecast in response to a price movement; execution based on that forecast can then alter the next observation used for learning. When

many agents share information, response patterns, infrastructure, or update schedules, assessing each decision system separately may miss important properties of their interaction.

This is not a claim that learning, reflexivity, or endogenous instability began with modern artificial intelligence. The Santa Fe artificial stock market explicitly studied agents whose expectations adapt to the market they collectively generate [1]. Heterogeneous-agent asset-pricing models likewise generate complex dynamics through endogenous strategy selection [2]. The present problem must build on those contributions rather than restate their central insight with new terminology.

Nor does a change in the identity of decision makers invalidate accounting identities or logically derived no-arbitrage implications under their maintained assumptions. What may change are the behavior of decision rules, the selection and stability of equilibria, the persistence of disturbances, and the applicability of estimated relationships when the population of decision systems changes. The phrase "from human markets to machine markets" names a research question about mechanisms and measurement, not an asserted replacement of economic theory.

There is a concrete reason to investigate those mechanisms. The Financial Stability Board identifies common-model correlations, third-party dependencies, cyber vulnerabilities, and model-governance issues as possible channels of AI-related financial risk [10]. Its subsequent monitoring report emphasizes information and measurement limitations [11]. These documents motivate a research agenda; they do not establish the magnitude of AI-caused market losses or a threshold beyond which markets become unstable.

Recent research also makes a broad claim that "architecture matters" insufficient as a novelty claim. Anand et al. [8] compare Q-learning and large-language-model investors in a stylized fund-redemption environment and obtain different coordination and fragility outcomes. Colliard et al. [9] study learning-based market makers and show how experimentation and noisy profit feedback affect pricing. Our research target is narrower and more demanding: determine when observable market–learning feedback can support transferable stability diagnostics, and specify the evidence needed to interpret those diagnostics causally.

The economic intuition is straightforward. Suppose a market has a stabilizing adjustment mechanism when strategies are held fixed. A price disturbance nevertheless changes a learning state, such as a return forecast or perceived risk level. The updated state generates an order response whose price impact reinforces the original disturbance. Even when the market-adjustment block and the learning-memory block each decay on their own, their coupling can destabilize the joint system. Conversely, the same adaptation can be harmless, or stabilizing in models with negative feedback. The sign, direction, magnitude, and timing of the response matter more than the label attached to the decision maker.

We organize the analysis around three questions. First, what mathematical object describes the joint response of the market and its adaptive participants? Second, what information is required to estimate that object or a useful proxy? Third, what evidence would justify using it to predict instability or evaluate a preventive intervention? Treating these as separate questions avoids presenting a theoretical quantity as though it were already an observable supervisory statistic.

The first four evidential layers, retained from version 0.4, are the following. The original framework derives the complete first-order system and tests its algebra. The first companion constructs exact finite-window ambiguity. The second tests a proposed diagnostic against stronger full-information estimators and narrows the defensible claim. The new study supplies an observable-only measurement protocol, propagates its uncertainty and executes it in a simple account-consistent market. The mathematical ingredients are largely established; the contribution proposed here is the explicit measurement chain and its documented limits, not a renaming of ordinary stability or system identification.

Sections 4–7 retain the general framework; Sections 8–9 integrate the two companion findings;

Sections 10–13 report the new observable experiment. Sections 14–16 add the v0.5 source-contract, observation-budget and binding-finance studies. Rich trained-agent, calibrated exchange and institutional studies remain prospective. Appendix E records source lineage, numerical provenance and reproduction instructions.

2 Related work and the precise research gap

2.1 Adaptive expectations and endogenous financial risk

Arthur et al. [1] model endogenous expectations in an artificial stock market. Brock and Hommes [2] analyze heterogeneous beliefs and routes to complex asset-price dynamics. These are direct precedents for any claim that agents and market conditions co-evolve. A convincing extension must identify something not already explained by adaptive strategy selection: for example, a measurable feedback operator that predicts behavior across materially different decision architectures.

Funding and trading conditions provide a second foundation. Brunnermeier and Pedersen [3] connect market liquidity and funding liquidity, including mutually reinforcing liquidity deterioration under specified conditions. Consequently, losses generated by common risk controls or liquidation pressure cannot automatically be attributed to AI. A meaningful test must retain ordinary liquidity and balance-sheet feedback in the non-AI benchmark.

2.2 Algorithmic interaction and financial-market experiments

Calvano et al. [4] show that Q-learning pricing algorithms can sustain supracompetitive outcomes in a repeated oligopoly experiment without direct communication. This establishes that individually trained agents can generate consequential collective behavior, although product-market pricing is not itself a model of systemic financial loss. Colliard et al. [9] bring learning algorithms into securities-market pricing and identify consequences of limited experimentation and noisy feedback. Their mechanisms are necessary comparators for a proposed market-making application.

The closest architecture-oriented predecessor is Anand et al. [8]. Their fund-redemption experiments connect learning and reasoning architectures to coordination and financial fragility. A manuscript that simply compares an LLM with a Q-learning agent would therefore require a much more specific contribution. Our proposed distinction is to estimate a common feedback representation, evaluate when it transfers across agent families, and test the additional predictive value of that representation over conventional market statistics. That distinction is a target, not an achieved empirical result.

2.3 Performative prediction and learning in games

Perdomo et al. [5] formalize situations in which a deployed predictor changes the distribution on which it is subsequently evaluated. Narang et al. [6] extend the analysis to multiple decision makers and distinguish performatively stable equilibria from Nash equilibria. These works already provide a language for prediction–action–distribution feedback.

A recent preprint by Farina and Perdomo [7] studies online algorithms and mixed performative stability. It is important not to equate that learning-theoretic solution concept with every form of financial stability. Convergence of average decisions or equilibrium distributions does not, without an additional argument, bound interim drawdowns, market depth, collateral shortfalls, or the solvency of a leveraged institution. Our intended bridge concerns such financial outcomes, not a denial of existing convergence results.

2.4 Dynamical systems, robustness, and market simulation

Linearization, Lyapunov analysis, and common-metric robustness are established mathematical tools [13, 14]. Rebranding a spectral radius is not a new theorem. Their use here is to make assumptions, state variables, and failure modes explicit before attempting empirical measurement. The challenge is particularly acute for time-varying agents, discrete decisions, and partially observed policy states.

For experimental infrastructure, the ABIDES paper describes a discrete-event market simulator with exchange interaction and configurable communication latency [15]. It is an appropriate candidate for a later implementation, not evidence that our proposed agent population or market mechanism has already been validated. A second implementation or an independent simulator would help distinguish a general result from a software-specific artifact.

2.5 Identification from imperfect input–output observations

Set-membership identification already asks which models are compatible with measured data and declared uncertainty [19]. Data informativity distinguishes recovering a unique model from learning enough to establish a property such as stability or stabilizability [21]. Positive-realization and steady-state-gain information have also been incorporated into regularized identification [23, 24]. Consequently, positivity constraints, confidence sets and gain side-information are essential predecessors, not newly invented concepts in this paper.

Our finite-family confidence construction is deliberately narrow: Gaussian independent episode vectors with arbitrary within-episode covariance. Sign-perturbed sums demonstrates that exact finite-sample identification methods also exist under other assumptions [25]; we have not implemented or subsumed them. Likewise, linear-system sample-complexity lower bounds are an established literature [22]. The new price-response two-point example supplies a model-specific observation limit, not a new general testing principle. The difference between noisy hidden kernels and noisy measured prices is central to the present integration.

2.6 What would be new, and what would not

Table 1: Contribution boundaries relative to the cited literature.

Research element	Already established or directly studied	Contribution this project must demonstrate
Endogenous learning	Adaptive expectations and performative feedback	A financially interpretable, estimable joint response object
Architecture effects	Different collective outcomes for different AI designs	Transfer across designs after matched economic controls
Liquidity feedback	Funding–market liquidity amplification	Incremental effect of adaptive policies, not relabeled deleveraging
Spectral stability	Standard fixed-system local analysis	Reliable estimation and useful out-of-sample financial prediction
Safety interventions	General robustness and control methods	Lower losses without hidden liquidity withdrawal or shifted harm

The literature review is targeted, not exhaustive. Priority for any final theorem, index, or empirical finding requires a dedicated nearest-neighbor review, including additional work on endogenous risk, system identification, nonlinear financial networks, and adaptive games. The name “Machine-Market Transition Theory” is retained as a research-program label rather than asserted as an established field.

3 Research question, scope, and claim discipline

The operational question is:

> Can changes in the joint market–learning feedback system identify economically meaningful changes in disturbance amplification, beyond what is explained by conventional liquidity, leverage, and volatility measures?

There are three different levels of claim. A *mathematical result* follows from an explicitly stated model. A *mechanism result* requires controlled experiments demonstrating that a specified feedback channel causes an outcome. An *external-validity result* requires evidence that the mechanism and its measurement apply beyond the experimental environment. This version supplies model results, an executed synthetic measurement-mechanism study, and protocols for richer mechanism tests and external validity. The new study does not establish a causal AI-specific effect relative to equally adaptive non-AI institutions.

The primary domain for the first empirical paper should be a single market with an explicit price-formation mechanism, inventories, and funding constraints. An equity-like limit-order-book environment is a reasonable experimental starting point. A fund-redemption game is a possible alternative, but these should not be combined into one vaguely specified "global market" simulation. Banking, insurance, payments, and household finance have different state variables and institutional constraints; they are later transfer tests.

We preserve the concept note's six dimensions: machine autonomy exposure, behavioral concentration, adaptation rate, leverage, liquidity, and intervention latency. These are organizing dimensions rather than sufficient statistics by assumption. A critical surface in those coordinates may be model dependent, nonmonotone, or not estimable with available observations. Failure to find a sharp boundary is an admissible research outcome.

4 A joint market–learning system

4.1 States, decisions, and update timing

Let $x_t \in \mathbb{R}^d$ denote market state and $\theta_t \in \mathbb{R}^p$ denote the collection of adaptive policy states. Market state can include price deviations, inventory, funding conditions, and lagged variables. Policy state can include learned value estimates, forecasts, risk estimates, memory, and version identifiers represented in an appropriate local state description. Let $u_t \in \mathbb{R}^k$ collect economically consequential decisions. We write

$$u_t = \Pi(x_t, \theta_t), \tag{1}$$

$$x_{t+1} = F(x_t, u_t, \varepsilon_{t+1}), \tag{2}$$

$$\theta_{t+1} = G(\theta_t, x_t, u_t). \tag{3}$$

The ordering is part of the model. If learning uses the newly realized price or reward, that dependency must be substituted into an effective G before differentiation. If decisions are delayed, the necessary lags must be included in the state. A delay cannot be appended as an informal qualifier after calculating a delay-free Jacobian.

For local deterministic analysis, set the innovation to zero and define

$$z_t = \begin{bmatrix} x_t \\ \theta_t \end{bmatrix}, \qquad \Phi(z_t) = \begin{bmatrix} F(x_t, \Pi(x_t, \theta_t), 0) \\ G(\theta_t, x_t, \Pi(x_t, \theta_t)) \end{bmatrix}. \tag{4}$$

Assume z^* is a fixed point and that the effective map is continuously differentiable in a neighborhood of z^*. This assumption excludes unmodeled discontinuous execution rules. For stochastic agents it may describe an explicitly defined conditional-mean map, but mean-map stability alone is not a claim of stochastic or almost-sure stability.

4.2 The complete feedback Jacobian

Applying the chain rule at z^* gives

$$J^* = D\Phi(z^*) = \begin{bmatrix} F_x + F_u\Pi_x & F_u\Pi_\theta \\ G_x + G_u\Pi_x & G_\theta + G_u\Pi_\theta \end{bmatrix}_{z^*}. \tag{5}$$

The upper-left block includes the market's direct persistence and instantaneous decision feedback. The upper-right block transmits a change in learned state into market outcomes. The lower-left block transmits a market disturbance into policy adaptation. The lower-right block describes policy-state persistence and action-dependent updating.

The product $F_u\Pi_x$ is only one channel. It is generally not the full transition derivative. Omitting the learning blocks can classify the frozen-policy system correctly while classifying the actual adaptive system incorrectly. This is a substantive revision of the abbreviated formula in the supplied concept note.

4.3 Units and financial interpretation

Prices, inventories, and learning states have different units. Specify a diagonal scaling matrix D using an ex ante reference regime, then use $\widetilde{J} = DJD^{-1}$ for norm-based comparisons. Eigenvalues are invariant under this change of coordinates, but Euclidean finite-horizon gains are not. An economically meaningful output map C_y and disturbance map B_ε should connect the state to such outcomes as price dislocation, funding demand, or inventory loss:

$$\delta z_{t+1} = J^*\delta z_t + B_\varepsilon \varepsilon_{t+1}, \qquad y_t = C_y \delta z_t. \tag{6}$$

The specification of C_y is necessary. Instability of an unobservable or economically irrelevant internal coordinate is not automatically systemic financial instability.

5 Local stability, finite-horizon risk, and switching

5.1 A standard local criterion

Proposition 5.1 (Fixed-system local stability; standard result)**.** *Suppose the deterministic joint map in equation* (4) *is continuously differentiable near a fixed point z^*. If $\rho(J^*) < 1$, that fixed point is locally exponentially asymptotically stable. If $\rho(J^*) > 1$, it is unstable. The case $\rho(J^*) = 1$ is not resolved by this first-order criterion.*

A proof of the stable case and the scope of the unstable case are given in section A. This proposition applies an established linearization principle; it is not a claim of a new financial law [14].

For continuity with the concept note, define the descriptive quantity

$$\mathrm{MMC}_{\mathrm{local}} = \rho(J^*). \tag{7}$$

It is a local, model-conditioned diagnostic. Values above or below one do not by themselves specify crisis probability, loss magnitude, or welfare. At equality, nonlinear terms can determine the outcome: $z_{t+1} = z_t - z_t^3$ is attracting sufficiently near zero, whereas $z_{t+1} = z_t + z_t^3$ is repelling, although both derivatives at zero equal one.

5.2 Stable eigenvalues can conceal transient amplification

For a fixed linear system, define the finite-horizon state gain

$$\mathcal{A}_H(J) = \max_{0 \le h \le H} \left\| J^h \right\|_2 . \tag{8}$$

A nonnormal matrix can have $\rho(J) < 1$ and a large $\mathcal{A}_H(J)$. Consider

$$J_N = \begin{bmatrix} 0.8 & 4 \\ 0 & 0.8 \end{bmatrix}, \qquad J_N^h = \begin{bmatrix} 0.8^h & 4h(0.8)^{h-1} \\ 0 & 0.8^h \end{bmatrix}. \tag{9}$$

Its spectral radius is 0.8, but the executed numerical calculation gives $\mathcal{A}_{50}(J_N) \approx 8.2124$, attained at $h = 4$. Such a state amplification can matter before eventual convergence. Whether it causes financial loss depends on state scaling, shock direction, output exposure, and constraints. This example establishes a diagnostic limitation, not the existence of a particular market event.

5.3 Frozen-time stability is not switching stability

A model update or time-varying policy changes the transition matrix. Define

$$\Phi_{t,h} = J_{t+h-1} \cdots J_t, \qquad \lambda_{t,h} = h^{-1} \log \|\Phi_{t,h}\| . \tag{10}$$

The norm and time unit must be fixed before comparing finite-horizon values. Consider

$$J_1 = \begin{bmatrix} 0.5 & 2 \\ 0 & 0.5 \end{bmatrix}, \qquad J_2 = \begin{bmatrix} 0.5 & 0 \\ 2 & 0.5 \end{bmatrix}. \tag{11}$$

Both have spectral radius 0.5, yet $\rho(J_2 J_1) \approx 4.4861$. Alternation therefore amplifies disturbances despite each frozen matrix being stable. Monitoring $\rho(J_t)$ alone cannot certify stability under arbitrary updates. Common-norm conditions in section 17 provide one sufficient alternative.

5.4 Calm observations do not identify weak feedback

Proposition 5.2 (Volatility and amplification need not move together)**.** *For the stable scalar process $x_{t+1} = rx_t + \sigma\varepsilon_{t+1}$ with $0 \le r < 1$ and independent, zero-mean, unit-variance innovations, stationary variance is $\sigma^2/(1-r^2)$ and the response sum to a unit additive state shock (rather than a unit standardized ε innovation) is $1/(1-r)$. There exist parameter pairs with lower stationary variance but a higher response sum.*

Proof. Stationarity gives $v = r^2 v + \sigma^2$. The response sum is the convergent geometric series $\sum_{h \ge 0} r^h$. Choosing $(r, \sigma) = (0.5, 1)$ gives variance $4/3$ and response sum 2; choosing $(0.9, 0.2)$ gives variance $4/19$ and response sum 10. □

This does *not* prove that unconditional tail risk rises in the second process. For Gaussian innovations its unconditional tails contract with variance. Establishing a "machine stability paradox" involving lower ordinary volatility and higher tail losses requires a specified stress distribution, exposure mechanism, and additional evidence. The narrower result is that ordinary volatility alone is an inadequate identifier of feedback amplification.

6 A tractable positive-feedback market model

6.1 A price-adjustment and belief-update specialization

Let $x_t \in \mathbb{R}^d$ be deviations of market prices from a local reference level, and $m_t \in \mathbb{R}^n$ be deviations of adaptive forecasts or decision states. Consider

$$x_{t+1} = ax_t + gBm_t + \varepsilon_{t+1}, \tag{12}$$

$$m_{t+1} = (1-\eta)m_t + \eta C x_t. \tag{13}$$

Here $0 \le a < 1$, $0 < \eta \le 1$, $g \ge 0$, and $B \in \mathbb{R}_+^{d\times n}$, $C \in \mathbb{R}_+^{n\times d}$. The matrix B maps policy-state changes into price pressure; C maps prices into target learning states. The nonnegativity assumption imposes reinforcing responses in the chosen coordinates. It is not a realistic description of all financial strategies.

The market component can be interpreted as a local reduced form of price adjustment under order imbalance. The memory component is an exponential update, not a derivation of optimal behavior or of a specific foundation model. Human adaptive expectations can satisfy the same equations. Machine-specific interpretation requires an empirically validated link from actual agents to B, C, g, and η.

The joint transition matrix is

$$J_+ = \begin{bmatrix} aI_d & gB \\ \eta C & (1-\eta)I_n \end{bmatrix}. \tag{14}$$

A genuinely frozen-policy baseline holds the relevant m deviations at zero and has market transition aI_d. Merely setting $\eta = 0$ in the full augmented system leaves neutral memory eigenvalues at one; that is not the same stability claim as conditioning on a fixed policy.

6.2 An exact stability boundary

Theorem 6.1 (Positive-feedback boundary; model specialization)**.** *Under the assumptions of equations* (12) *and* (13)*, the origin of the deterministic linear joint system is asymptotically stable if and only if*

$$g\rho(BC) < 1 - a. \tag{15}$$

Writing $\nu = \rho(BC)$, its spectral radius is

$$\rho(J_+) = \frac{a + 1 - \eta + \sqrt{(a-1+\eta)^2 + 4g\eta\nu}}{2}. \tag{16}$$

Equality in equation (15) *produces an eigenvalue at one. A strict reversal produces an eigenvalue larger than one.*

The proof in section A.2 is a positive-systems/small-gain argument specialized to this model. The elementary spectral result should not be presented as an original general theorem without a literature-priority review. Its role is to produce explicit, falsifiable consequences and to check a proposed empirical measurement strategy.

Define the model-specific loop ratio

$$\mathcal{L} = \frac{g\rho(BC)}{1-a}. \tag{17}$$

Then $\mathcal{L} < 1$ characterizes stability in this restricted model. The surface $g\rho(BC) = 1 - a$ depends on response structure and market persistence, not merely the fraction of AI participants.

Corollary 6.2 (No universal participation cutoff in this model)**.** *Suppose, as an additional model parameterization, $g = \alpha\ell/q$, where $\alpha \in [0, 1]$ is economically weighted machine participation, $\ell > 0$ is a specified exposure multiplier, and $q > 0$ is normalized depth. If $\nu > 0$, the formal boundary is*

$$\alpha^* = \frac{(1-a)q}{\ell\nu}. \tag{18}$$

If $\alpha^* > 1$, no crossing occurs on the feasible participation interval. The formula is not an empirical identity and does not establish that these factors combine multiplicatively in real markets.

6.3 Learning speed: a useful negative result

For every strictly positive η in the assumed interval, the boundary in equation (15) is unchanged. Update speed changes eigenvalues and adjustment times but does not shift this particular boundary. A claim that faster learning necessarily lowers the instability threshold is therefore false even within a simple reinforcing model. Heterogeneous update rates, delays, nonlinear risk limits, signed feedback, and endogenous depth can change that conclusion; those extensions require fresh analysis.

For the scalar case $B = 1$, $C = \kappa \geq 0$,

$$J_s = \begin{bmatrix} a & g \\ \eta\kappa & 1-\eta \end{bmatrix}, \qquad g\kappa < 1 - a. \tag{19}$$

At $a = 0.4$, $\kappa = 1$, the boundary is $g = 0.6$. Figure 1 plots the analytic eigenvalue formula, not a fitted empirical relationship.




Figure 1: Analytic illustration for $a = 0.4$, $\kappa = 1$. The three update rates share the boundary $g = 0.6$ but yield different growth or decay rates. No AI models were trained to produce this figure.

7 Measurement and causal identification

7.1 Machine autonomy exposure without arbitrary category scores

Rather than assign unvalidated values such as 0.1 to advisory software and 0.7 to execution software, define a decision event and audit who had executable authority. For event e, let $v_e \geq 0$ be a predeclared exposure weight and $d_e \in \{0, 1\}$ indicate machine execution without a

contemporaneous discretionary human approval. For a window W,

$$\mathrm{MAE}_W = \frac{\sum_{e \in W} v_e d_e}{\sum_{e \in W} v_e}. \tag{20}$$

The denominator must be positive, and weights should represent comparable exposure, not arbitrary numbers of messages. Advisory use, order generation, execution authority, and online learning should be reported separately. Net exposure, gross executed exposure, and assets under management answer different questions and should not be mixed.

If authority is unobserved for some events, report an interval: the lower bound treats unknown events as nonautonomous and the upper bound treats them as autonomous. This makes missingness visible rather than assigning undocumented scores. It does not solve measurement error in v_e.

7.2 Behavioral concentration is not provider concentration

Provider concentration and common-cloud dependence are operational quantities. Behavioral concentration instead asks whether agents react along similar directions. Let $r_i \in \mathbb{R}^K$ be a nonzero response vector for agent i on an independently designed panel of controlled perturbations, normalized to unit length after reporting its original response magnitude. With $w_i \geq 0$ and $\sum_i w_i = 1$, define

$$S = \sum_i w_i r_i r_i^\top, \quad \mathrm{ADC} = \lambda_{\max}(S), \quad D_{\mathrm{eff}} = \frac{1}{\mathrm{tr}(S^2)}. \tag{21}$$

Here $\mathrm{tr}(S) = 1$, so ADC is a directional-concentration descriptor. Zero-response agents require a separate reported mass; silently normalizing them is invalid. The perturbation panel, units, weights, and sampling variability all affect the estimate.

There is an important limitation. Two equal-weight agents with responses r, r and two with responses $r, -r$ both yield the same S and $\mathrm{ADC} = 1$. Yet their aggregate signed responses are r and zero, respectively. Thus equation (21) cannot substitute for the signed aggregate response, price-impact direction, or the product BC. Diversity can remove reinforcing feedback, but it can also remove stabilizing behavior. There is no unconditional "more diversity is safer" theorem here.

7.3 An identification impossibility without provenance

Proposition 7.1 (Observational equivalence of decision-maker labels)**.** *Consider two economies with the same initial market-state distribution, the same market transition kernel conditional on aggregate actions, and the same conditional law of aggregate actions given every observable history. The economies can have different assignments of human and machine decision-maker labels. They nevertheless induce the same law for all observable market histories. No estimator using only those histories can consistently distinguish the two label assignments or identify different autonomy shares attached solely to those assignments.*

Proof. The initial observable distributions coincide. If observable histories coincide in distribution through t, the assumed conditional action law and common market transition kernel imply the same distribution for the next observation. Induction establishes equality of all finite-dimensional observable distributions. Any statistic of those observations therefore has the same law in both economies; it cannot converge in probability to two distinct label-dependent constants. □

This is an application of ordinary observational equivalence, not a claim that financial attribution is impossible with richer data. Account-level decision provenance, randomly assigned

architecture, authorized policy-update experiments, or credible external variation can break the equivalence. Historical prices alone do not reveal whether a self-exciting pattern was produced by humans, fixed algorithms, adaptive agents, or a mixture.

7.4 Estimating the response system

The general operator-estimation problem below is broader than the completed scalar experiment. Sections 10–13 provide one restricted solution using signed filled probes and prices; they neither reconstruct every private policy state nor identify AI participation from prices alone.

In a simulator with full state access, estimate J by perturbing each normalized coordinate around a specified operating point and measuring the resulting joint next-state response. Use multiple perturbation sizes to test local linearity and independent random streams to quantify agent stochasticity. Finite differences of a mean response estimate a mean-map derivative, not a pathwise derivative of a discrete sampled action.

In observational data, fitting $z_{t+1} = Jz_t + e_{t+1}$ requires sufficient excitation, a defensible state representation, and restrictions controlling confounding and feedback-induced endogeneity. Hidden policy states typically require a state-space or input–output model. A reduced-form estimate may predict outcomes without identifying architecture-specific mechanisms; the paper must report which claim its design supports.

An uncertainty set $\mathcal{J}$ should reflect estimation uncertainty and relevant model misspecification. There is no distribution-free license to assign a narrow confidence interval to $\rho(J)$ by ignoring dependence, near-defective matrices, hidden states, or selected operating points. A claim of pre-crisis warning additionally requires lead time, false-alarm rates, and a prospectively fixed event definition.

8 Hidden slow learners: the first companion study

This section integrates the results of *Hidden Slow Learners*, the first executed companion to the framework [16]. Its purpose is to distinguish a well-defined stability target from the information available to estimate it. The finite-window construction, its limitations, and its adverse controls are retained; they are not treated as newly observed financial facts.

8.1 Heterogeneous memory and the scalar stability target

Consider the fixed positive linear specialization

$$x_{t+1} = ax_t + \sum_{i=1}^{n} y_{i,t} + \kappa u_t + e_{t+1}, \tag{22}$$

$$y_{i,t+1} = (1 - \eta_i)y_{i,t} + \eta_i q_i x_t, \tag{23}$$

where $0 \le a < 1$, $q_i \ge 0$, $0 < \eta_i \le 1$, and $\kappa > 0$. Positivity refers to transition coefficients, not to signs of realized price deviations or positions. Define $Q = \sum_i q_i$ and $G = Q/(1-a)$. Throughout the new experiments, $S = a + Q$ is the unnormalized stability target and G is used only to index generating configurations. Confusing G with Q changes the threshold.

Proposition 8.1 (Positive heterogeneous-memory boundary)**.** *The joint transition matrix of* (23) *is Schur stable exactly when $S = a + Q < 1$. Equality gives an eigenvalue at one; $S > 1$ gives spectral radius greater than one.*

Proof. The matrix is $J = \begin{bmatrix} a & \mathbf{1}^\top \\ \operatorname{diag}(\eta)q & \operatorname{diag}(1-\eta) \end{bmatrix}$. The lower diagonal block of $I - J$ is positive. Its Schur complement is $1 - a - \sum_i q_i$. The nonsingular M-matrix characterization of a nonnegative

transition matrix establishes the stable case. At equality, $(1, q^\top)^\top$ is an eigenvector. Above the boundary, the function

$$f(\lambda) = \lambda - a - \sum_i \frac{\eta_i q_i}{\lambda - 1 + \eta_i}$$

is negative at one, strictly increasing on $[1, \infty)$, and tends to infinity. It therefore has a root greater than one. This is a specialization of standard positive-system analysis, not a new general stability principle [18]. □

With zero initial adaptive states, the loop-open kernel and unit closed-loop response are

$$k_j = \sum_i q_i \eta_i (1 - \eta_i)^j, \quad \sum_{j=0}^{\infty} k_j = Q, \tag{24}$$

$$h_0 = 1, \quad h_1 = a, \quad h_{t+1} = a h_t + \sum_{j=0}^{t-1} k_j h_{t-1-j}. \tag{25}$$

The kernel sum exists even when the closed loop is unstable. Summing a diverging closed-loop response and calling it Q would be incorrect.

8.2 Exact finite-window ambiguity

Theorem 8.2 (Retained exact construction)**.** *For every positive integer K and $a \in [0, 1)$, there are a stable and an unstable model of* (23) *with the same a, the same impact normalization, and the same number of active memory states, whose kernels agree for $j = 0, \dots, K-1$ and whose price responses agree for $t = 0, \dots, K+1$. Rational nodes and a give rational coefficients.*

Proof. Choose distinct $0 \le r_0 < \cdots < r_K < 1$ and let

$$w_i = \left[\prod_{\ell \neq i} (r_i - r_\ell) \right]^{-1}.$$

Comparing the leading coefficients in polynomial interpolation gives $\sum_i w_i r_i^j = 0$ for $j < K$ and $\sum_i w_i r_i^K = 1$. Partial fractions evaluated at one give

$$\sum_i \frac{w_i}{1 - r_i} = \frac{1}{\prod_i (1 - r_i)} > 0.$$

Set $B_+ = \sum_i \max(w_i, 0)/(1 - r_i)$, $B_- = \sum_i \max(-w_i, 0)/(1 - r_i)$ and $s = 2(1 - a)/(B_+ + B_-)$. Alternating signs imply $B_+ > B_- > 0$. Choose $\eta_i = 1 - r_i$ and $q_i^{\pm} = s \max(\pm w_i, 0)/(1 - r_i)$. The totals have midpoint $1 - a$ and lie on opposite sides of it. Their kernel difference is $s \sum_i w_i r_i^j$, so the stated terms coincide. Equation (25) propagates this equality to the price responses, with first unmatched difference $h^+_{K+2} - h^-_{K+2} = s$. Delete zero weights and split positive weights among identical-rate copies until each model has $K + 1$ active states; splitting changes neither kernel nor stability. Rationality is immediate. □

Equal deterministic observations imply balanced forced-classification error 1/2 on this pair, even after adding identically distributed observation noise. This is a finite-window, increasing-order construction, not a result that every known low-order market remains unidentifiable indefinitely. Under a fixed valid learning-rate floor below one the construction remains possible, but the stability separation can shrink. A floor is useful for bounds, not a guarantee of finite-sample decisiveness arbitrarily near the boundary.

Table 2: Retained readable witness. Four initial price coefficients match exactly.

Quantity	Stable member	Unstable member
a	2/5	2/5
Q	12/65	66/65
$S = a + Q$	0.584615	1.415385
$\rho(J)$	0.757909	1.032345
h_0, h_1	1, 0.4	1, 0.4
h_2, h_3	0.252308, 0.184	0.252308, 0.184
h_4	0.138428	0.159198

Before equal-count splitting, the witness uses rates $(1, 1/2, 1/20)$ with weights $(0, 12/65, 0)$ and $(54/1235, 0, 240/247)$. Displayed decimals are rounded; the equality is rational, not an approximate visual match. A one-rate extrapolation from two exact taps yields

$$\widehat{Q}_{\text{one}} = \frac{k_0^2}{k_0 - k_1} \leq Q.$$

Indeed, with $p_i = q_i\eta_i/k_0$, Jensen's inequality for $r \mapsto 1/(1-r)$ gives the bound. The inequality is strict for heterogeneous active rates. Thus a low one-rate estimate can be false reassurance, not a stability certificate.

8.3 What the first measurement experiment actually assumed

If $\eta_i \geq \underline{\eta} > 0$, $r = 1 - \underline{\eta}$, and $T_H = \sum_{j<H} k_j$, positivity gives

$$T_H \leq Q \leq \min\left\{\frac{T_H}{1 - r^H},\ T_H + \frac{r}{\underline{\eta}} k_{H-1}\right\}. \tag{26}$$

These inequalities follow directly by summing each geometric component and bounding its omitted tail. They are not optimal use of the entire moment sequence.

The first companion ran 112 exact paired constructions, 336 common-shock comparisons, and 21,600 noisy measurement datasets across 108 configurations. Its three-way rule made no wrong confident call in that run, with decision coverage of 82.69% and 66.20% in the lower- and higher-noise conditions at 256 taps. Those measurements were *loop-open kernel responses with known noise standard error*; they were not ordinary price records. The first paper explicitly warned that deconvolving noisy prices would not preserve that noise model. A falsely specified rate floor could label an unstable model stable. These limitations motivate the next two stages rather than disappearing in the integrated manuscript.

9 Full-horizon identification audit and fixed-order limits

The second companion, *Hidden Slow Learners Revisited*, audited the first diagnostic using stronger equal-information alternatives [17]. Its unfavorable comparison for the original method is retained here. A difficult identification problem does not establish superiority of a particular estimator.

9.1 A conventional full-information comparison

All methods received the same noisy normalized kernel vector $\widehat{g}_j$, known common standard error v, and a valid $\underline{\eta}$, where $g_j = k_j/(1-a)$. Neither generating weights, rates, component count nor class label was supplied. A nonnegative least-squares mixture fit used all observed taps. A

second comparator bounded G over positive mixtures consistent with simultaneous confidence intervals, using continuous rate bins to protect off-grid modes. For a feature f and mass w_l in bin B_l, its outer inequalities were

$$\sum_l \min_{\eta \in B_l} f(\eta) w_l \le U_f, \qquad \sum_l \max_{\eta \in B_l} f(\eta) w_l \ge L_f.$$

This belongs to the established set-membership and positive-measure optimization tradition [19, 20]. Stable-model fitting alone would not be an acceptable comparator for detecting instability; stability was not imposed in these fits.

Table 3: Retained full-horizon audit at 256 taps. Each noise condition contains 10,800 vectors. These are the earlier kernel measurements, not the new price experiment.

	Lower noise		Higher noise	
Method	Decisive (%)	Wrong	Decisive (%)	Wrong
Original summary bound	82.69	0	66.20	0
Full-horizon positive point fit	100.00	24	100.00	306
Full-moment positive bounds	88.04	0	76.65	4

The bounds resolved 578 and 1,128 additional vectors respectively, but did not dominate on every realization. Some earlier decisions became model conflicts, and four high-noise decisions were wrong. All four occurred outside the simultaneous confidence event. Across the 82,364 rows on that event, the reported interval contained the true gain and made no wrong confident call. The full audit comprised 86,400 rows over four horizons. Its strongest interpretation is a measurement requirement and benchmark, not an improved original summary diagnostic.

9.2 A fixed-order lower bound in the earlier observation law

For two common-rate models with rates $(1/2, \eta)$ and normalized weights $(0.7, 0.2)$ and $(0.7, 0.4)$, the gains are 0.9 and 1.1. With $\Delta = 0.2$, their kernel means differ by $\Delta\eta(1-\eta)^j$. Under *independent kernel noise* of variance v^2, their squared Mahalanobis distance is

$$d^2_{H,\text{kernel}} = \frac{\Delta^2 \eta\{1-(1-\eta)^{2H}\}}{v^2(2-\eta)}. \tag{27}$$

The equal-prior optimal forced error is $\Phi(-d/2)$, obtained by projecting onto the standardized mean difference. If a rule may abstain, its balanced decision coverage c and unconditional wrong-label probability e obey

$$c \le \min\{1,\, 2e + 2\Phi(d/2) - 1\}. \tag{28}$$

For disjoint stable and unstable decision regions, subtract twice the error from coverage and bound the difference of probabilities by total variation. The Gaussian total variation is $2\Phi(d/2) - 1$. This is a direct specialization of classical two-point testing, not a new general lower-bound method; identification sample-complexity precedents must also be acknowledged [22].

At $\eta = 10^{-5}$, $H = 256$, $v = 0.02/\sqrt{128}$, the oracle error is 49.6394%. An unconditional error target of 5% permits at most 10.7212% coverage on that pair. Because this particular kernel experiment adds equally noisy late taps, its information can saturate. **These numbers and the saturation conclusion must not be transferred unchanged to a different price-measurement protocol.** The price experiment below has a different observation law and a separately calculated lower bound.

10 An observable intervention protocol without hidden-state access

The new research step replaces assumed kernel observations with recorded probe fills and quoted prices. It does not identify the full latent Jacobian or the fraction of trades performed by AI. It estimates an input–output response and asks what that response supports about S under the declared positive-memory class. This change is compatible with established data informativity: a property can sometimes be determined without uniquely recovering every parameter [21].

10.1 Information available to the estimator

In each of R independent episodes, assign one signed pulse $u_r \in \{-\delta, +\delta\}$, balanced across signs and randomized independently of the initial latent states and subsequent disturbances. Record the *filled quantity*, not merely the intended order, and the subsequent quote changes $Y_{r,j} = P_{r,j+1} - P_{r,0}$, $j = 0, \dots, M-1$. Within a linear time-invariant episode,

$$Y_{r,j} = m_j + u_r \beta_j + \varepsilon_{r,j}, \qquad \beta_j = \kappa h_j. \tag{29}$$

The arbitrary common intercept path m_j accommodates the mean no-probe trajectory. The estimator receives only $(u_r, Y_{r,\cdot})$ and a valid externally declared $\underline{\eta}$. It receives neither private states, private aggregate pressures, exact rates, weights, a, κ, nor the disturbance variance. Initial adaptive states need not be zero or observable: in the experiment they are independent Gaussian draws, hidden from the estimator.

For the exact confidence result, episodes have independent identically distributed Gaussian residual vectors $\varepsilon_r \sim N(0, \Sigma)$, independent of assignment, where Σ is unknown and may have arbitrary temporal covariance. This is a finite-window condition; it does not require stationary prices or closed-loop stability. Gaussian initial states, additive flow disturbances and quote errors in the fixed linear simulator imply it. It is not guaranteed by a successful regression on a real market.

10.2 Recovering the response and its uncertainty

Let $v_r = u_r - \bar{u}$ and $D = \sum_r v_r^2 > 0$. Ordinary regression with an intercept gives

$$\widehat{\beta}_j = D^{-1} \sum_r v_r Y_{r,j}, \qquad \widehat{m}_j = \bar{Y}_j - \bar{u}\widehat{\beta}_j, \tag{30}$$

$$\widehat{\Sigma} = \frac{1}{R-2} \sum_r (Y_r - \widehat{m} - u_r \widehat{\beta})(Y_r - \widehat{m} - u_r \widehat{\beta})^\top, \tag{31}$$

$$\widehat{\mathrm{Cov}}(\widehat{\beta}) = \widehat{\Sigma}/D. \tag{32}$$

The covariance is estimated from public price residuals; no oracle covariance is inserted. For balanced pulses, $D = R\delta^2$. Repeating episodes and increasing pulse size change precision, but larger pulses can invalidate linearity and create additional economic exposure.

Theorem 10.1 (Finite-family response uncertainty)**.** *Under* (29) *and the stated independent Gaussian episode contract, let*

$$z = t_{R-2}^{-1}\left(1 - \frac{\alpha}{2M}\right), \qquad L_j = \widehat{\beta}_j - z\sqrt{\widehat{\Sigma}_{jj}/D}, \quad U_j = \widehat{\beta}_j + z\sqrt{\widehat{\Sigma}_{jj}/D}.$$

Then $\mathbb{P}(\beta_j \in [L_j, U_j] \text{ for all } j < M \mid u) \geq 1 - \alpha$. *No temporal independence between price observations or between estimated response coefficients is required.*

Proof. Conditional on the nonconstant design, each response coordinate is a Gaussian regression with two fitted coefficients. Its standardized slope error has a Student-t distribution with $R-2$ degrees of freedom; the residual variance is independent of that coordinate's slope estimate. Each two-sided interval fails with probability α/M. A union bound over the M coordinates yields the result even though these statistics are dependent. In a noiseless coordinate the interval degenerates to its exact coefficient. This is an application of ordinary Gaussian regression inference, not a claim to a new distribution-free method. Exact finite-sample methods under other assumptions already exist, including sign-perturbed sums [25]. □

The event covers all predeclared horizons that use these same coefficients. It is not anytime-valid for an unlimited search over new windows, budgets or operating points. A 95% guarantee applies separately to a declared measurement panel, not simultaneously to the entire collection of thousands of simulation panels. It is also an unconditional wrong-label bound, not a 5% conditional error guarantee among the few cases that receive labels.

10.3 Exact deconvolution is possible; independent noise is not preserved

With exact response coefficients and $\beta_0 > 0$, the unknown impact and direct persistence are recoverable:

$$\kappa = \beta_0, \quad h_j = \beta_j/\beta_0, \quad a = h_1, \quad k_n = h_{n+2} - a h_{n+1} - \sum_{j=0}^{n-1} k_j h_{n-j}. \tag{33}$$

Thus finite loop-open responses can be obtained without observing the adaptive states. The exact claim is algebraic; noisy point estimates require uncertainty propagation. For example,

$$k_0 = \frac{\beta_2}{\beta_0} - \left(\frac{\beta_1}{\beta_0}\right)^2,$$

whose gradient with respect to $(\beta_0, \beta_1, \beta_2)$ is

$$\left(-\frac{\beta_2}{\beta_0^2} + \frac{2\beta_1^2}{\beta_0^3}, -\frac{2\beta_1}{\beta_0^2}, \frac{1}{\beta_0}\right).$$

Even a first-order variance approximation uses the *full* response covariance. Recursive products, division by a weak initial response and dependence across times can amplify uncertainty. Reusing the previous iid-kernel Gaussian endpoints on these estimates would be unjustified. The new pipeline therefore avoids requiring a precise point estimate of every k_n.

11 Positive recurrence bounds directly from uncertain prices

This section constructs an outer feasible set directly from the response intervals, following conventional set-membership logic. The relevant methodological increment in this artifact is the explicit link from randomized price measurements to that set, including unknown persistence and impact. Neither broad novelty nor optimality over all input–output estimators is asserted.

11.1 A response-only convex outer relaxation

The response satisfies

$$\beta_{t+1} = a\beta_t + \int_{\underline{\eta}}^{1} \left[\sum_{j=0}^{t-1} \eta(1-\eta)^j \beta_{t-1-j}\right] d\mu(\eta), \quad \mu = \sum_i q_i \delta_{\eta_i}, \tag{34}$$

with an empty sum at $t = 0$. This equation is homogeneous in the price-impact scale; there is no need to divide a noisy record by an assumed known κ.

Intersect response lower bounds with zero, since the theoretical impulse response is nonnegative. An upper bound below zero is a model conflict. If $L_0 \le 0$, the present implementation remains inconclusive rather than normalizing by a poorly supported impact. Partition $[\underline{\eta}, 1]$ into bins B_l and let $w_l = \mu(B_l) \ge 0$. For $\psi_j(\eta) = \eta(1-\eta)^j$ define exact endpoint/peak bounds

$$\psi_{jl}^- = \min_{\eta \in B_l} \psi_j(\eta), \qquad \psi_{jl}^+ = \max_{\eta \in B_l} \psi_j(\eta).$$

The minimum is at an endpoint; the maximum is at the projection of $1/(j+1)$ onto the bin. Set

$$C_{tl}^- = \sum_{j=0}^{t-1} \psi_{jl}^- L_{t-1-j}, \qquad C_{tl}^+ = \sum_{j=0}^{t-1} \psi_{jl}^+ U_{t-1-j}. \tag{35}$$

Every compatible true model then satisfies the *linear* inequalities

$$aL_t + \sum_l C_{tl}^- w_l \le U_{t+1}, \tag{36}$$

$$aU_t + \sum_l C_{tl}^+ w_l \ge L_{t+1}, \qquad 0 \le a \le 1, \quad w_l \ge 0. \tag{37}$$

Minimize and maximize $a + \sum_l w_l$ over this set to obtain $[S_-, S_+]$. Different terms may attain their bin extrema at different rates and different response endpoints; the relaxation is conservative, not an exact description of all realizations. Refining bins does not by itself remove the looseness of rectangular response uncertainty.

Theorem 11.1 (Observable-data stability interval)**.** *Under the model, a valid rate floor, and the response event in Theorem 10.1, the true S belongs to $[S_-, S_+]$ in exact arithmetic at every declared horizon. Declaring stable if $S_+ < 1$, unstable if $S_- > 1$, and otherwise inconclusive therefore has probability at most α of any wrong confident label within the declared family.*

Proof. On the response event, all true β_t lie in the clipped nonnegative intervals. Positivity of a, the kernel and bin masses makes each lower convolution no greater than its true value and each upper convolution no smaller. Thus the true (a, w) satisfies (37). Its objective is exactly $a + \mu([\underline{\eta}, 1]) = S$, so the LP extremal values enclose it. Proposition 8.1 gives the label implication; the probability statement follows from the simultaneous event. Unknown hidden states affect the observational residual distribution, not the feasibility proof, provided they satisfy the independent episode contract. □

A useful numerical anchor follows from $\beta_2 \ge \underline{\eta}\,\beta_0 Q$:

$$S \le 1 + \frac{U_2}{\underline{\eta} L_0}, \qquad L_0 > 0. \tag{38}$$

The implementation includes this redundant true-model bound, outward feature padding, dual residual repair, primal/dual checks and a 10^{-7} classification margin. Linear-programming bounds are guarded numerically, not formally verified with interval arithmetic. Solver failure and infeasibility are not converted into a favorable label.

11.2 Equal observable-information comparators

The first comparator propagates the same response rectangle through (33), intersects each kernel interval with positivity, and applies (26). It is conservative but repeatedly reuses uncertain quantities, so interval widths can grow sharply. The second is a conventional positive recurrence

least-squares fit using all response coefficients and a 33-node rate grid. It fits $a \in [0, 1]$ and nonnegative weights without imposing $a + Q < 1$.

The point fit uses measured response coefficients on both sides of a regression, creating an errors-in-variables problem. It is not a calibrated certificate, not a strongest possible nonlinear output-error estimator, and not a replacement for the full-horizon kernel audit. The comparison asks whether this explicit measurement protocol can yield valid intervals and what it costs in undecided cases. It does not establish superiority to every conventional identification method. Existing positivity- and gain-informed identification is a necessary comparison literature [23, 24].

12 An account-consistent market environment

To attach the response to economic transactions, the new experiment implements a stylized dealer market rather than feeding the estimator noisy kernel coefficients. It is an excess-demand price-adjustment model with explicit trades and ledgers, not a calibrated exchange or a limit-order book.

12.1 Orders, price formation and adaptive demand

Let $P_t = p^* + x_t$, with the constant reference value $p^* = 100$ dollars. Chartist i holds a private smoothed displacement $m_{i,t}$, with demand $v_{i,t} = \chi_i m_{i,t}$. A fundamentalist submits $v_{F,t} = -\varphi x_t$, a noise trader submits $v_{N,t}$, and the experiment's trader submits u_t. The dealer absorbs their net quantity V_t. Prices and memories update as

$$V_t = \sum_i v_{i,t} + v_{F,t} + v_{N,t} + u_t, \qquad P_{t+1} = P_t + \kappa V_t, \tag{39}$$

$$m_{i,t+1} = (1 - \eta_i) m_{i,t} + \eta_i x_t. \tag{40}$$

Writing $a = 1 - \kappa\varphi$, $q_i = \kappa\chi_i$ and $y_{i,t} = \kappa\chi_i m_{i,t}$ gives (23) exactly. Updates use x_t, not the newly moved x_{t+1}; changing timing changes the response recurrence. Agents have adaptive memory, not trained neural policies or demonstrated utility-optimal behavior.

Empirical order-book research motivates considering a local relation between net pressure, price changes and depth, but does not validate this specific aggregate-demand model or its chosen parameters [26]. In particular, actual order-flow imbalance includes quote and cancellation events; the simple signed trade volume V_t here is not claimed to equal that empirical measure.

12.2 Double-entry accounting and economic scope

Trades execute at the within-step midpoint $P_t^{\text{ex}} = (P_t + P_{t+1})/2$, with half-spread $c = 0.005$ dollars transferred to the dealer. Each nondealer actor with quantity v has changes

$$\Delta N = v, \qquad \Delta C = -v P_t^{\text{ex}} - c|v|.$$

The dealer has the opposite aggregate inventory and cash changes. Thus total shares and cash transfers sum to zero after every step; marking all inventories to one common quote also preserves aggregate marked wealth when net initial shares are zero. The cash variables are ledger changes, not evidence that all actors satisfy capital requirements. Unconstrained credit and short positions, fixed depth, no defaults and no endogenous balance-sheet limits make the primary model a local mechanism test rather than a complete financial economy.

The primary price impact is 0.02 dollars per share and $a = 0.4$, implying $\varphi = 30$ shares per dollar. Chartist elasticities are set from the declared q_i. Background net-flow noise has standard deviation 0.10 shares; quote observation error has standard deviation 0.002 dollars; each initial

private memory has standard deviation 0.01 dollars. The estimator is not told these scales. Time is an abstract model step, not a claimed number of market seconds. No live-market orders, customer records or external financial data are used.

12.3 Experimental design and information firewall

The frozen primary panel uses rates $(0.5, \eta_s)$ with $\eta_s \in \{0.002, 0.02, 0.10\}$ and $G \in \{0.70, 0.95, 1.05, 1.30\}$. Sixty percent of normalized feedback is fast and forty percent slow. The imposed class floor is $\underline{\eta} = \eta_s$; this is public design-side information, not an estimated individual hidden rate. The equality at the floor is a benchmark boundary choice, and off-grid support is separately tested.

For each of 12 configurations, 128 or 1,024 independent episodes use pulses of one or four shares. Forty independent panels per configuration/design give 1,920 panels. Each episode records 66 quote changes. Inference at largest lags 8, 24 and 64 gives 5,760 horizon rows. There are $H + 1$ response coefficients through lag H; the last collected coefficient, lag 65, is unused in these fits but included in the simultaneous confidence family, conservatively. There are 1,105,920 episodes and 72,990,720 quoted-price observations, not that many independent financial markets.

Only a public object with keys `probes` and `prices` crosses into estimation. Analytical responses, latent trajectories, true gains and configuration labels are used by the evaluation layer only. Known noise standard deviations and exact direct persistence are not estimator arguments. Full public response estimates, endpoints and standard errors are saved for every panel, together with generation seeds and raw-record hashes. Four public episode examples and their response covariances are included. All other raw episodes can be regenerated; they are not represented as external market records.

13 Executed observable-data findings

13.1 Response recovery and confidence calibration

The simultaneous response intervals covered all 66 true coefficients in 1,895 of 1,920 panels, or 98.70%, versus a nominal lower coverage of 95%. Estimated neighboring response errors were strongly correlated: the mean absolute adjacent correlation was 0.8497. This supports the decision not to reuse an iid-kernel error model. These are measurements from the declared synthetic experiment, not estimates of correlations in a real exchange.

On all 5,685 horizon rows whose panel satisfied the response event, the output-only recurrence interval contained the true S. It made no wrong confident call anywhere in the 5,760 primary rows, including the 75 rows from the 25 panels outside that event. The observed absence of errors is not proof of a zero-error procedure.

Table 4: New price-only experiment at largest fitted lag 64. Each row contains 480 panels. Parentheses show wrong labels; point fitting always gives a label but has no confidence guarantee.

Episodes	Pulse (shares)	Recurrence bound	Interval deconvolution	Point fit
128	1	0/480 (0)	0/480 (0)	480/480 (101)
128	4	28/480 (0)	0/480 (0)	480/480 (56)
1,024	1	0/480 (0)	0/480 (0)	480/480 (49)
1,024	4	80/480 (0)	0/480 (0)	480/480 (37)

The strongest primary design therefore resolves 16.67%, leaving 83.33% inconclusive. All 80 decisions in that design occur at the fastest allowed slow rate, $\eta_s = 0.10$, and the large-margin gains $G = 0.70$ and 1.30, with 40 correct decisions each. Neither near-boundary gain nor either

slower class is resolved by that design. Across all three nested horizons, the recurrence method makes 256 decisions (176 stable and 80 unstable) and leaves 5,504 rows inconclusive. Nested horizon decisions are not independent replications.

The naive interval-deconvolution comparator remains inconclusive throughout the primary panel. This is evidence of looseness in that particular interval propagation, not a theorem that all deconvolution methods fail. The point estimator makes 1,191 wrong labels across the 5,760 rows. Its apparent 100% decisiveness is therefore not a substitute for a supported stability statement. Nor is this weak point comparator a basis for claiming superiority over the strongest output-error or covariance-aware conventional methods.

13.2 Replication budget and the cost of a useful answer

After inspecting primary results, a separately labeled exploratory extension uses 8,192 and 32,768 episodes, four-share pulses and largest lag 64. Five panels per configuration/budget give 60 panels at each budget. There are 15/60 (25.00%) and 25/60 (41.67%) definite answers, with no wrong labels. At 32,768 episodes all 20 fastest-class panels are resolved, five moderate-rate stable large-margin panels are resolved, and all 20 slowest-class panels remain inconclusive. The extension contributes 2,457,600 simulated episodes but is not pooled with the frozen primary analysis.

These results expose an observation-budget problem, but low decisiveness also reflects conservative bin/rectangle relaxation and discarded covariance geometry. They do not prove that the remaining cases are information-theoretically impossible at these budgets. A full-covariance, positivity-constrained output-error set is an important stronger comparison before attributing all nondecisions to lack of information.

13.3 Assumption failures are not repaired by good price confidence

Table 5: Twenty panels per control, each with 4,096 episodes and four-share pulses. Controls are not part of the primary calibration claim.

Condition	Observed result	Interpretation
Valid reference	20 stable labels; all response bands cover	Consistent with the declared class
False rate floor	20 stable labels for an unstable linear system; all response bands cover	Accurate measured responses do not validate hidden-tail assumptions
Confounded assignment	20 model conflicts; zero response bands cover the causal response	Randomization is part of identification, not decoration
Saturating price impact	20 stable labels; zero bands cover the origin's linear response	A plausible label does not establish linearity or global safety

In the false-floor control, actual rates are $(0.5, 10^{-5})$ but inference is incorrectly told $\underline{\eta} = 0.10$. Weights $(0.42, 0.24)$ give $S = 1.06$. All price-response confidence events hold, yet the true measure is excluded from the allowed support and all 20 outputs are falsely stable. No output-only claim here certifies the rate floor itself.

The confounded control assigns signs using future background flow, deliberately breaking independence. The nonlinear control replaces κV by $\kappa c_0 \tanh(V/c_0)$ with $c_0 = 1$ share. Its Jacobian at the origin retains the linear reference, but finite pulses do not. In an exact noise-free scaling check, initial price response per share is 0.0195935, 0.0152319 and 0.00499665 for pulses of 0.25, 1 and 4 shares. A larger pulse improves linear-model signal-to-noise only while linearity remains valid. Passing feasibility is not a model-validation test; failing amplitude invariance can

flag a problem but cannot certify the remaining assumptions.

13.4 A new lower bound for the actual price-observation family

To separate observation limits from solver conservatism, consider a restricted subexperiment with zero initial states, no flow noise and independent quote noise $N(0, \sigma^2)$. This subexperiment is not the full noisy-dealer panel. For the two models with $a = 0.4$, rates $(0.5, \eta)$ and $q^{(0)} = 0.6(0.7, 0.2)$, $q^{(1)} = 0.6(0.7, 0.4)$, define their observable price responses $\beta^{(0)}, \beta^{(1)}$ as in (29).

Theorem 13.1 (Fixed-budget price-response ambiguity)**.** *With R balanced pulses of magnitude δ, observed through lag H, the exact Gaussian distance is*

$$d^2_{H,\text{price}} = \frac{R\delta^2}{\sigma^2} \sum_{j=0}^{H} (\beta_j^{(1)} - \beta_j^{(0)})^2. \tag{41}$$

The optimal balanced forced-classification error is $\Phi(-d_{H,\text{price}}/2)$, and the abstention bound (28) *holds using this new distance. For fixed $H, R, \delta, \sigma > 0$, the distance tends to zero as $\eta \downarrow 0$, although the two gains remain $G_0 = 0.9$ and $G_1 = 1.1$ and both models have two memory states.*

Proof. Conditional on the known assignments, the stacked observation covariance is $\sigma^2 I$ and each episode's mean difference is $u_r(\beta^{(1)} - \beta^{(0)})$. Summing squared standardized differences gives (41). Projection onto that direction gives the same scalar Gaussian likelihood-ratio calculation as before.

For the limit, let J_0, J_1 be the pressure-coordinate matrices in Proposition 8.1. Their difference has a single entry $\eta\Delta q$, where $\Delta q = 0.12$. A common induced norm bound $\|J_i\| \le M$ can be chosen independently of $\eta \in (0, 1]$. The telescoping identity for powers gives

$$\|J_1^j - J_0^j\| \le jM^{j-1}\eta\Delta q.$$

Since $\beta_j^{(i)} = \kappa e_1^\top J_i^j e_1$, every finite coefficient difference tends to zero and so does the finite sum in (41). The gains do not depend on η. This proves the restricted finite-budget impossibility, not a claim about all possible excitation policies. □

For $R = 1,024$, $\delta = 4$, $\sigma = 0.002$, $H = 64$, and $\kappa = 0.02$, the exact oracle errors are 49.94%, 49.42%, 44.27%, and 7.45% at rates 10^{-7}, 10^{-6}, 10^{-5}, and 10^{-4}. At $\eta = 10^{-5}$ an unconditional 5% wrong-label target permits at most 21.46% balanced decision coverage on this pair. These are newly computed *price-law* examples, not the 49.64% kernel-law number in the previous audit. The limit lets the allowable slowest rate approach zero; it does not hold that rate above one fixed positive floor while simultaneously sending it to zero. Each numerical pair must be assigned a class floor no greater than its actual slow rate. A 100,000-draw likelihood-score Monte Carlo check accompanies the exact calculation. Neither this limit nor the primary low decisiveness establishes a universal crisis-prediction impossibility.

13.5 Accounting, numerical checks and reproduction

Across all primary simulated steps, maximum absolute conservation errors were 3.37×10^{-11} dollars in cash transfers, 3.52×10^{-13} shares and 4.61×10^{-11} dollars in aggregate marked wealth. The largest price displacement was about 1.010 dollars from the artificial 100-dollar reference. These are accounting and implementation checks, not claims of economic realism.

Twenty-two new tests pass, including off-grid feasible-mixture checks, unknown-parameter interface tests, exact response recovery, amplitude scaling and accounting. The previous releases' 29 and 23 tests were rerun and passed; the original 625 scalar and 250 network algebra checks

were also rerun. A separately assembled group-means regression agrees to 1.95×10^{-16} on 48 regenerated panels. Alternative interior-point optimization agrees with the main dual-simplex bounds to 1.30×10^{-12} across 144 comparisons. Maximum primary primal residual was 2.23×10^{-10}; the guarded dual residual was zero to the reported precision. These are internal cross-checks, not independent outside review.

A second full run in a clean output directory regenerated all primary panels, response summaries and comparison rows. Both panel and comparison CSV files match byte for byte; all nine repeated NPZ datasets match array for array. Runtime is recorded separately and is not expected to match. The supplemental archive contains the versioned protocols, source, tests, all result rows, every public response summary, seed manifests, four complete public example datasets and source-paper provenance. The new study uses NumPy 2.3.5 and SciPy 1.17.0; solver options are recorded rather than relying on changing library defaults [27].

14 Auditable memory tails: what a source contract can justify

The v0.4 observation experiment leaves a consequential gap: a short response record cannot validate the minimum learning rate that makes its upper bound finite. We now separate an *implementation-conditioned tail claim*, an *observable linear-gain claim*, and a *finite-horizon operational-risk claim*. They have different assumptions and targets. A successful result for one is not silently promoted to the others. The following studies are new to version 0.5; the earlier studies and their adverse findings remain unchanged.

14.1 A complete channel inventory, not a guessed rate floor

The audited experimental class has the public update rule

$$m_{i,t+1} = (1-\eta_i)m_{i,t} + \eta_i x_t, \qquad x_{t+1} = ax_t + \sum_i q_i m_{i,t} + \lambda u_t + w_{t+1}, \tag{42}$$

with $m_{i,0} = x_0 = 0$, $0 \le a < 1$, $q_i \ge 0$, $\sum_i q_i \le Q_{\max}$, and public $\eta_i \in [\eta_0, 1]$. Here $Q_{\max} = 1$ is enforced by input validation in the released linear source. The rates, reset, update timing, and absence of other feedback channels are architectural disclosures; they are not estimated from price records. The actual q_i, a, and λ are withheld from the estimator.

The release includes a machine-readable contract with source digest, public rates, zero-reset declaration, observation specification and allowed execution regime. Unit tests reject declared changes to the reset, source digest, observation type, or execution regime. In the experiment the contract is issued from the actual public simulation configuration, and the source is available for inspection. This justifies the restriction *within that controlled implementation*, not in an arbitrary proprietary market.

A digest establishes file identity, not completeness, truthful reporting, or secure runtime attestation. A deliberately self-issued contract containing false rates still passes a syntax-and-digest check. This failure is included in the release. An outside application needs authenticated configuration and an independently inspected inventory of every feedback-relevant channel. A manifest alone is not a safety certificate. In particular, a signal-memory reset does not reset account equity, outstanding positions, leverage rules, or other agents.

Proposition 14.1 (Implementation-conditioned tail envelope)**.** *For the nonnegative memory kernel $k_j = \sum_i q_i \eta_i (1-\eta_i)^j$ generated by equation* (42)*, a complete valid contract implies*

$$R_H := \sum_{j=H}^{\infty} k_j = \sum_i q_i (1-\eta_i)^H \le Q_{\max}(1-\eta_0)^H. \tag{43}$$

More generally, for $k_j = CA^jB$, induced-norm bounds $\|A\| \le r < 1$, $\|B\| \le b$ and $\|C\| \le c$ imply $\sum_{j=H}^{\infty} \|k_j\| \le bc\, r^H/(1-r)$.

Proof. Sum each geometric series to obtain the equality in equation (43); nonnegativity and $1-\eta_i \le 1-\eta_0$ give the bound. For the second statement, submultiplicativity gives $\|CA^jB\| \le cbr^j$; summing proves the claim. These are standard geometric-series and induced-norm arguments, not new general stability theorems. □

For $Q_{\max} = 1$ and $H = 64$, the envelopes at $\eta_0 = 0.002, 0.02, 0.1$ are respectively 0.879741, 0.274454, and 0.001179. The slowest contract therefore still permits a large unseen tail. A verified small rate is not equivalent to a useful small tail. If an additional relevant inventory coordinate has unit persistence, the premise $r < 1$ for the complete hidden subsystem is unavailable; a contract for the memory module cannot fill that gap.

14.2 Why the earlier impossibility results still matter

The exact and noisy counterexamples in Sections 8–9 are not contradicted. They concern a less informative observation class. Disclosing the true update architecture and guaranteeing a reset changes the compatible model set. That disclosure has an institutional cost and is not available merely because prices are observed accurately. The distinction between information sufficient for a property and information sufficient for full model recovery is established in data-informativity research [21]; positive side-information is likewise an existing identification tool [23]. Our contribution here is an explicit, executable conditional contract and a documented failure when its scope is misrepresented.

15 Budgeted inference from audited public dynamics

15.1 One terminal innovation per independent episode

Given public rates, exact midprice deviations and a verified reset, the estimator reconstructs

$$m_{i,T-1} = \eta_i \sum_{s=1}^{T-2} (1-\eta_i)^{T-2-s} x_s \tag{44}$$

from prices alone. It never reads the simulator's stored memory. Assume $u_{T-1} = 0$. Each independent episode contributes exactly one regression row,

$$Y_j = x_{j,T_j}, \qquad X_j = (1, x_{j,T_j-1}, m_{j,1,T_j-1}, \dots, m_{j,d,T_j-1}), \quad Y_j = X_j\beta + w_{j,T_j}, \tag{45}$$

where $\beta = (\mu, a, q_1, \dots, q_d)^\top$ and the intercept accommodates a common mean innovation. The endpoint T_j is fixed or randomly assigned *before* observing that episode. It is not selected after a favorable price movement.

Proposition 15.1 (Conditional terminal-row confidence; classical regression)**.** *Suppose episodes are independent, the innovations w_{j,T_j} are independent Gaussian variables with common unknown variance, and each is independent of all pre-terminal regressors and preassigned endpoints. If X has full column rank $p < n$, then for a fixed contrast v,*

$$\frac{v^\top\widehat{\beta} - v^\top\beta}{\widehat{\sigma}\sqrt{v^\top(X^\top X)^{-1}v}} \sim t_{n-p} \quad \textit{conditional on } X. \tag{46}$$

In particular $v = (0, 1, 1, \dots, 1)$ gives a confidence interval for $A_{\mathrm{fb}} = a + \sum_i q_i$, whose threshold is one in the maintained positive linear class.

Proof. Conditional on X, the last innovations are an independent spherical Gaussian vector. The least-squares projection and orthogonal residual projection are independent. The contrast is Gaussian with variance $\sigma^2 v^\top (X^\top X)^{-1} v$, and the residual sum of squares divided by σ^2 is χ^2_{n-p}. Their ratio gives equation (46). No independence claim is made for multiple successive transitions from the same episode; treating those as independent rows would invalidate this proof. □

This is ordinary regression under an explicitly auditable experimental design, not a new superior estimator. Unknown-rate v0.4 recurrence bounds and the present estimator do not receive the same information. The present price observations are exact midquotes rather than the additional sensor-error observations in v0.4. Its initial memory is reset to zero. Consequently, improvement over v0.4 cannot be attributed solely to statistical efficiency.

15.2 Primary budget experiment and negative results

The primary v0.5 panel uses the same twelve (G, η_{slow}) combinations as v0.4: $G \in \{0.7, 0.95, 1.05, 1.3\}$, $\eta_{\text{slow}} \in \{0.002, 0.02, 0.1\}$, a fast rate of 0.5, $a = 0.4$, $\lambda = 0.02$, and $q = 0.6G(0.6, 0.4)$. Gaussian innovation standard deviation is 0.002 dollars. Gains and innovations are not inputs to inference. There are $n \in \{32, 128, 512\}$ independent episodes, lengths $T \in \{16, 64\}$, two probe designs, and twenty replicate panels per cell: 2,880 panels and 645,120 episode trajectories.

The two designs have four shares of within-window gross probe volume: an initial signed four-share impulse or eight half-share orders in four round trips. They do *not* have equal squared input energy or residual inventory. The impulse has energy 16 share-squared and holds four shares at its endpoint; the round trips have energy 2 and return flat, with peak absolute inventory at most half a share. Unwinding the impulse after observation requires another four shares of volume. These economic differences are reported rather than hidden behind a claim of "equal budget." Input design under amplitude and power constraints is established research [28]; neither pattern is claimed optimal.

Across primary panels, 2,758 of 2,880 gain intervals cover the true gain (95.76%); 745 give definite labels and twenty give wrong confident labels. Those are empirical frequencies under per-panel 95% intervals, not simultaneous study-wide coverage. At $T = 64, n = 128$, the impulse resolves 86/240 panels, versus 46/240 for the round trips. At $n = 512$, those counts are 158/240 and 80/240. The round-trip alternative fails as a general accuracy improvement. Its smaller position exposure is a separate property, not proof of equivalent informativeness.

15.3 Held-out endpoint diversification: useful at small budgets, not uniformly

After the primary experiment, a small pilot suggested varying the observation endpoint instead of redistributing the order volume. A fresh-seed follow-up was specified before its execution. Both arms use the same initial four-share impulse and the same audited rates. One arm records 64 transitions per episode. The other assigns equal numbers of episodes to 8, 16, 32 and 64 transitions, shuffled before inspecting prices. Its average record is 30 transitions, with the same maximum of 64. Both arms would require the same four-share post-observation unwind, outside the measurement law.

Each paired dataset is simulated to length 64, but the diversified estimator is given only the assigned prefixes; a test alters all later prices and verifies unchanged inference. There are 720 fresh panel datasets (161,280 episodes), each evaluated in both arms, yielding 1,440 decision rows. This is post-primary held-out confirmation, not external preregistration. The contrasts, model grid and new seeds are released.

Table 6: Held-out endpoint comparison. Each entry uses 240 panels. Wrong calls are included in, not removed from, the definite-call count.

Episodes	Fixed 64: definite	Wrong	Diversified: definite	Wrong
32	26 (10.83%)	0	75 (31.25%)	2
128	86 (35.83%)	0	112 (46.67%)	1
512	159 (66.25%)	1	144 (60.00%)	0

At 32 episodes, 56 previously unresolved paired cases become definite and seven go the opposite way: 49 net additional decisions. At 128, the corresponding counts are 42 and sixteen. At 512, diversification loses fifteen decisions net. Thus the result is a budget-dependent trade-off, not a uniformly dominating detector. The release includes descriptive paired tests; pooling heterogeneous model settings is not a claim of universal statistical superiority. In the original fixed-64 primary experiment, the slowest rate resolves only 4/80 panels at 128 episodes and 15/80 at 512. Architectural disclosure does not remove low signal-to-noise limitations.




Figure 2: Observed decision rates on the held-out paired panel. The crossing is retained: a useful low-budget change does not improve every budget. Error counts appear in table 6.

15.4 A measured tail interval under the stronger audit

When rates are genuinely public, the unseen-tail mass in equation (43) is itself a linear contrast of β. Use $v_H = (0, 0, (1-\eta_1)^H, \ldots, (1-\eta_d)^H)$ in equation (46). Intersect its interval with $[0, Q_{\max}(1-\eta_0)^H]$. An empty intersection is a model conflict, not an interval silently clipped into feasibility. Splitting $\alpha = 0.05$ equally between the gain and tail gives at least 95% joint coverage per panel by a union bound.

This analysis reuses the primary observations; it creates no additional independent market data. For $H = 64$, the joint event holds in 2,796/2,880 panels (97.08%). There are nine model conflicts. At a fixed observation length of 64, the statistical upper bounds below are medians across eighty panels; they are not worst-case bounds for every episode or every institution.

Table 7: Audited tail envelope and median measured upper endpoint for the four-share impulse. Each statistical interval allocates 2.5% error to the tail.

Minimum rate	Analytic envelope	128 episodes	512 episodes
0.002	0.879741	0.788458	0.490520
0.020	0.274454	0.136919	0.103451
0.100	0.001179	0.000674	0.000451

15.5 Assumption violations remain visible

Five eighty-panel controls evaluate deliberately ungated inference. Omitting a slow state produces eighty false stable classifications in eighty panels. Omitting a positive inventory-feedback channel produces three false stable classifications in eighty panels. Noisy regressors and a violated reset produce no wrong labels in their particular runs, but their calibration theorem is still unavailable; absence of observed errors is not proof of robustness. The valid control produces eighty correct unstable classifications. All outcomes, including unhelpful and non-failing controls, are retained. A fit cannot authenticate the architecture that made its confidence statement valid.

16 Binding financial constraints and a different risk target

16.1 A funded transaction model, not just a ledger

Version 0.4 records trades but does not impose binding capital constraints. The new financial experiment contains two memory traders, a fundamentalist, a background-flow trader, a probe account and a dealer. Let C_i, I_i, P and $E_i = C_i + I_i P$ denote cash, shares, midpoint and marked equity. A trade v_i executes at the current midpoint plus a half-spread s paid in the direction of the trade:

$$C_i' = C_i - Pv_i - s|v_i|, \qquad I_i' = I_i + v_i, \quad E_i' = E_i - s|v_i|. \tag{47}$$

The dealer receives the opposite shares and all cash transfers. This leaves total cash and shares unchanged. The price then moves by $\lambda \sum_i v_i$; a declared external repricing may follow.

For previously feasible participants, requested orders are projected onto

$$|I_i'| \le \overline{I}_i, \qquad |I_i'|P \le L_i E_i', \qquad C_i' \ge -\kappa_i E_{i,0}. \tag{48}$$

These constraints include spread costs in post-trade equity. For a fixed trade sign they are linear inequalities in the fill, so the nearest feasible fill along the requested trade direction is computed explicitly. A separate LP verifier checks 500 random cases against this projection. A breach caused by subsequent price marking triggers forced liquidation on the next step. Negative equity is recorded as default; outstanding debt is not erased or replaced with fresh capital.

The dealer also faces inventory, leverage and credit limits. When desired aggregate flow exceeds its capacity, all participant fills are proportionally reduced. If its existing account is already infeasible, the simulated venue halts rather than inventing an unconstrained outside buyer. Existing positions remain on the books. An externally imposed price shock is still recorded. The maximum leverage observed *after* a price move may exceed the execution limit; this is precisely why margin calls exist. The accounting audit distinguishes infeasible newly accepted trades from later marking losses.

Funding–liquidity feedback is established financial theory [3]. Trading under propagator and inequality constraints also has dedicated predecessors [30]. The present simulator is a simple executable validation environment for the measurement distinction. It is not a new liquidity-spiral theory, an exchange order book, or an implementation of those papers' optimal-execution algorithms.

16.2 Primary economic settings and accounting audit

The base initial equities, in account order, are $(100, 100, 600, 300, 600, 2000)$ dollars. Leverage limits are two; credit limits equal initial equity; inventory caps are $(3, 3, 15, 10, 10, 30)$ shares. The ample regime multiplies equity and inventory caps by twenty. The tight regime uses the base values. The unlimited counterfactual ignores execution constraints and may accumulate

insolvent positions; it is a diagnostic counterfactual, not a viable funding arrangement. Positions initially sum to zero.

The primary panel crosses $G \in \{0.7, 1.3\}$, slow rates 0.02/0.1, the three funding regimes, and repricing shocks of zero or minus two dollars at step 16. Each of 24 settings has 20,480 episodes of 64 transitions. The probe buys or sells two shares at step zero and requests the reverse at step eight: four gross requested shares, not a guaranteed full fill. External random tapes are shared across funding counterfactuals. Therefore 491,520 setting-trajectories use 163,840 unique exogenous episode tapes; they must not be counted as 491,520 mutually independent market shocks.

The execution engine modifies 12,388,550 order requests and records 2,240,614 account-step margin calls. These are repeated order/account-step counts, not unique crises. Maximum cash-conservation error is 2.41×10^{-10} dollars, maximum share error 2.34×10^{-12} shares, and maximum fresh-trade constraint residual 3.19×10^{-12}. Thus the financial limits are active, rather than decorative parameters.

16.3 Finite-horizon risk without an unjustified linear certificate

When accounts constrain fills, the dynamics are state-dependent and nonlinear. The audited memory bound still describes that isolated signal module, but not all feedback in the financially constrained system. We therefore do not apply the linear gain interval to certify funded-system stability.

Instead define an episode event B as any account default, a venue halt, or an adaptive trader's peak equity drawdown exceeding 20% of initial equity during 64 transitions. Price dislocation, margin activity, turnover and unfilled orders are reported separately. The endpoint is frozen before the primary experiment. For iid repetitions of a declared scenario distribution, $K_n = \sum_{j=1}^{n} \mathbf{1}_{B_j}$ is binomial regardless of the within-episode nonlinear dynamics. An exact Clopper–Pearson interval bounds p_B [29].

Proposition 16.1 (Planned-budget operational-risk coverage)**.** *At predeclared episode budgets $n \in \{32, 128, 512\}$, construct two-sided exact binomial intervals at error $\alpha/3$ each. Under iid episodes from the same specified scenario law, all three intervals cover p_B with probability at least $1 - \alpha$. This conclusion does not require linearity, a memory-rate floor, or Gaussian observations.*

Proof. Each interval inverts binomial tail tests and has noncoverage probability at most $\alpha/3$. A union bound over the three planned looks gives total noncoverage at most α, without requiring independence across the nested budgets. Arbitrary additional peeking, dependent episodes, a changed scenario distribution, or an event definition chosen after seeing losses is outside the claim. □

The illustrative acceptance threshold $p_B = 5\%$ is a research choice, not a regulatory standard or investment recommendation. At zero events, the upper endpoint is $1 - (\alpha/6)^{1/n}$. Thus 32 quiet episodes are insufficient to establish risk below 5%; 128 can be sufficient. There are 960 setting-panels evaluated at three nested budgets, yielding 2,880 rows. In the primary settings, the realized event frequencies are extreme: twenty settings have zero events and four unlimited-funding shocked settings have an event in every episode. At 128 episodes all panels consequently receive a definite probability-threshold label. This is *not* a difficult near-threshold benchmark, not proof of universal 128-episode practicality, and not a demonstration of zero population risk in the zero-event settings. Exact coverage is separately enumerated on 3,003 (n, p) grid points.

16.4 Dealer stress: locally stable signal feedback is not system safety

The first financial panel activates participant constraints but has no dealer halts. A separately labeled post-primary extension therefore starts the tight-regime dealer with 19 shares and equity 1,000, balanced by positions of minus nine shares in the fundamentalist account and minus ten in the probe account. Cash is adjusted to preserve each initial equity and zero net shares. These positions satisfy the initial constraints. Repricing at step 16 has mean minus two or minus ten dollars and independent standard deviation one. Eight settings each contain 8,192 fresh episodes, totaling 65,536.

Table 8: Preloaded-dealer stress extension. Event rates are synthetic scenario frequencies, not estimates of real-market crisis probabilities. All settings have binding execution limits.

G	Slow rate	Mean repricing	Event rate	Halt rate
0.7	0.02	−2	45.42%	45.42%
0.7	0.10	−2	36.22%	36.22%
1.3	0.02	−2	50.62%	50.62%
1.3	0.10	−2	45.15%	45.15%
0.7	0.02	−10	85.16%	82.59%
0.7	0.10	−10	73.91%	63.94%
1.3	0.02	−10	79.92%	56.60%
1.3	0.10	−10	77.04%	51.75%

For $G = 0.7$, the unconstrained linear quantity is $a + \sum q_i = 0.82 < 1$, yet substantial halt frequencies occur under the stressed dealer balance sheet. This supplies a concrete model-specific counterexample to transferring the signal-stability label to operational financial safety. The difference is not attributed exclusively to artificial intelligence: ordinary adaptive demand and standard funding constraints are enough. Neither the higher-gain nor lower-gain case is uniformly safer across these outcomes. No blanket prescription for capital limits or autonomous-agent adoption follows.

16.5 Verification, reproducibility and the still-open outside gate

The v0.5 tests and the retained earlier suites pass 98 tests in total: 24 new and 74 inherited. A separately coded verifier imports no project modules. It recomputes 4,320 regression decisions with an SVD implementation, checks 24 raw public-path filter reconstructions, recomputes 2,880 binomial rows using a separate exact-interval API, solves 500 fill projections as LPs, recomputes 2,880 tail intervals, and verifies 64 full example ledgers. Maximum alternate-regression difference is below 7.2×10^{-14}; this is a numerical consistency check, not independent scientific review.

A fresh-directory rerun regenerated all scientific data. All 19 scientific CSV files matched byte for byte, and all 566 arrays in 82 data/challenge archives matched exactly in this environment. Runtime metadata was excluded from comparison. The source snapshot used for that rerun and the comparison record are released. The supplement contains public-price challenges, reference answers stored separately, source hashes, environment information and an outside-replication checklist. No outside researcher has reviewed these proofs, reproduced these experiments, authenticated a proprietary runtime, or confirmed novelty. The same assistant's separate code and a clean execution environment are internal cross-checks only. ABIDES offers an established event-driven exchange platform for a later transfer test [15]; it is not claimed to have been used here. The remaining external gate requires another team, a different implementation or venue, realistic data-access and observation-cost assumptions, and a report that can reject the conclusions.

17 Intervention under uncertainty and liquidity feedback

A proposed intervention can reduce order size, slow an update, retain a previously approved policy, route a decision to review, or abstain from a specific action. These are not interchangeable. In particular, freezing learning need not cancel outstanding orders, and abstaining from new positions need not remove existing inventory risk.

Proposition 17.1 (Common-norm robustness; standard sufficient condition)**.** *Let $P \succ 0$, $\|z\|_P = (z^\top P z)^{1/2}$, and let $\|J\|_P$ be the associated induced norm. Suppose all admissible transition matrices satisfy $\|J\|_P \le \gamma < 1$. For any sequence of those matrices and additive disturbances with $\|b_t\|_P \le \bar{b}$, the system $z_{t+1} = J_t z_t + b_t$ satisfies*

$$\|z_T\|_P \le \gamma^T \|z_0\|_P + \bar{b}\frac{1-\gamma^T}{1-\gamma}. \tag{49}$$

A sufficient estimation-aware test is $\left\|\widehat{J}\right\|_P + \epsilon \le \gamma$ when $\left\|J - \widehat{J}\right\|_P \le \epsilon$ holds for every admissible J.

Proof. Submultiplicativity and the triangle inequality give $\|z_{t+1}\|_P \le \gamma \|z_t\|_P + \bar{b}$. Iteration yields the geometric bound. The final sufficient test follows from $\|J\|_P \le \left\|\widehat{J}\right\|_P + \left\|J - \widehat{J}\right\|_P$. □

The common P is essential: separate certificates with incompatible metrics do not certify arbitrary switching. A standard matrix formulation is $J^\top P J \preceq \gamma^2 P$ for every admissible matrix [13]. In a nonlinear setting, analogous derivative bounds must hold throughout an invariant neighborhood; a certificate at one point is insufficient. A probabilistic estimation set yields only a guarantee conditional on its coverage event and assumptions.

17.1 Why abstention is not automatically stabilizing

Consider the scalar positive-feedback model with $a = 0.4$, $\eta = 0.2$, $\kappa = 1$, and baseline $g_0 = 0.45$. Suppose an intervention retains a fraction u of demand sensitivity but depth falls to a fraction $q(u)$ of baseline. The effective scale becomes

$$g(u) = g_0 \frac{u}{q(u)}. \tag{50}$$

At $u = 0.5$ and unchanged depth, $g = 0.225$ and the model is more strongly stable. At $u = 0.5$ and $q(u) = 0.25$, $g = 0.9$ and the model is unstable. These are constructed scenarios, not estimated liquidity elasticities. They show why evaluating abstention only through reduced individual trading ignores an essential equilibrium response.

Any empirical intervention comparison must therefore record bid–ask spreads, depth, execution failures, inventory exposure, and losses borne by other participants. An intervention that reduces one agent's losses by transferring risk or withdrawing market-making capacity is not automatically a system improvement. Operational deployment is outside this manuscript's scope.

18 Executed numerical checks

18.1 Purpose and reproducibility

The computations reported here test agreement between formulas and direct matrix calculations. They neither fit the model to a financial dataset nor train financial agents. Section B contains the exact self-contained Python/NumPy program used for the reported matrix checks. The run used NumPy 2.3.5, double-precision arrays, and seed 20260918 for the network samples. Last-digit differences across numerical libraries are immaterial to the stated tolerances.

Table 9: Computed scalar-model examples. All rows use $a = 0.4$ and $\kappa = 1$. Parameters are illustrative and uncalibrated.

Case	g	η	$\rho(J_s)$	$g\kappa/(1-a)$
Stable feedback	0.300	0.20	0.916228	0.500
Boundary	0.600	0.20	1.000000	1.000
Unstable feedback	0.900	0.20	1.069042	1.500
Same unstable gain, slower learning	0.900	0.05	1.022311	1.500
Same unstable gain, faster learning	0.900	0.80	1.154400	1.500
Baseline before action gate	0.450	0.20	0.960555	0.750
Gate with depth unchanged	0.225	0.20	0.891548	0.375
Gate with depth at one quarter	0.900	0.20	1.069042	1.500

18.2 Verification results

The scalar Cartesian grid comprises five values each of a, η, g, and κ, giving $5^4 = 625$ cases away from the boundary. All direct eigenvalue classifications agree with $g\kappa < 1 - a$. The largest absolute difference between the formula and direct eigenvalue calculations is approximately 2.22×10^{-16}.

The network check uses 250 independently generated nonnegative pairs with $d = 3$ market coordinates and $n = 4$ adaptive states, along with randomized admissible scalar parameters. All classifications agree with equation (15); the largest formula discrepancy is approximately 2.89×10^{-15}. These are numerical consistency tests, not 250 independent market experiments and not evidence of generalization to large language models.

The program also verifies the switching example, the transient-amplification example, and the signed-response concentration counterexample. The switching product has spectral radius 4.486068, corresponding to an asymptotic per-step factor of approximately 2.118034 under periodic alternation. The stable nonnormal example reaches the previously reported gain 8.212429. Both identical and opposite response panels have ADC = 1, despite different aggregate signed responses.

The mathematical proofs, not the finite grid, justify the universal statements within the specified model. The computations provide an implementation check and reproducible illustrations. No confidence interval or significance claim is attached to an exact algebra check.

19 Prospective multi-agent experimental protocol

The following is the retained flagship validation program, not a description of the newly executed dealer pilot. The pilot has adaptive memories and auditable transfers but no trained-agent populations, binding budgets, realistic exchange matching or liquidation. Its completion therefore does not mark these larger tasks complete. **Status: not executed.** This section specifies the experiment needed to test whether the model quantities have useful meaning in richer financial environments. It must be registered or otherwise frozen before inspecting confirmatory outcomes.

19.1 Research hypotheses and their rejection conditions

The "calm but fragile" hypothesis is secondary. It requires jointly measuring ordinary variation and losses under a separately specified shock distribution. A lower volatility statistic coupled with a higher local spectral radius is not itself a measured increase in tail losses.

Table 10: Prospective hypotheses. No row is reported as an established empirical finding.

ID	Hypothesis	Evidence against the proposed claim
H1	A joint response estimate predicts stress amplification beyond ordinary market covariates.	No reproducible incremental prediction on held-out regimes.
H2	Matching measured feedback reduces architecture-specific outcome differences.	Large architecture effects remain after reliable response matching.
H3	Increased reinforcing response alignment increases loss amplification in the specified environment.	Effects disappear under matched depth and exposures, or reverse outside selected cells.
H4	An uncertainty-aware gate improves a predeclared loss–liquidity trade-off.	Apparent benefits rely on disappearing liquidity, oracle information, or shifted losses.
H5	A boundary estimated in one agent family transfers to a held-out family or simulator.	Transfer requires unrestricted refitting or yields unacceptable uncertainty.

19.2 Environment and economic accounting

The first market should contain an exchange, finite cash and inventory balances, explicitly funded positions, and a price-formation mechanism. Every fill transfers inventory and cash between counterparties, with fees and external cash flows separately accounted for. The simulator must reject unfunded or otherwise infeasible actions according to the declared rules. In a leveraged extension, margin calculations and forced liquidation must be implemented and audited.

If public historical order-flow or price data are used for calibration, separate periods for calibration, validation, and stress evaluation are required. Matching a handful of stylized facts is a useful diagnostic but does not prove that a simulator captures crisis mechanisms. Price replays without endogenous market impact cannot test the central feedback hypothesis: the agents must be able to change subsequent market states.

ABIDES is a candidate infrastructure described in prior work [15]; the selected implementation, version, matching rules, and modifications must be recorded. An independent second simulator should use a materially different implementation while preserving the experimental economic contract.

19.3 Agent families and matched baselines

A minimum design should compare adaptive expectation rules, a simple value-learning agent, a more expressive learning policy, and an inference-only language-model policy. Optional online adaptation for an LLM must be operationally defined: weights, external memory, retrieved examples, prompts, or tool policies may update differently. Merely calling an LLM repeatedly is not evidence of online parameter learning.

Each adaptive policy needs a paired baseline with the same architecture, information, constraints, and checkpoint, but the relevant adaptation channel disabled during evaluation. Additional baselines should include nonadaptive rule-based agents, ordinary risk-control feedback, and adaptive expectation agents not described as AI. A human-like rule is not a human-subject benchmark. A claim about replacing human decisions eventually requires actual human evidence or a validated behavioral model with stated limits.

Differences in capital, risk tolerance, signal quality, latency, execution permissions, and available computation should be held fixed where possible and explicitly decomposed where impossible. A language model with richer information and a longer decision budget is not a clean architecture-only comparison with a small tabular learner.

19.4 Factor design and compute discipline

Begin with a small mechanism-identification pilot. A proposed affordable pilot crosses three participation levels, three response-sharing conditions, three update schedules, and two depth regimes: $3 \times 3 \times 3 \times 2 = 54$ cells. Ten independent market seeds per cell would require 540 trajectories per paired policy condition. These are planning choices, not a power calculation or completed run count.

Use the pilot only to identify implementation failures, estimate variance, and choose financially meaningful outcome scales. Confirmatory seeds, shock paths, and held-out architectures must then be fresh. A proposed second stage expands only the dimensions needed to distinguish competing mechanisms. A large six-dimensional grid or 10,000-agent population should not precede basic accounting validation and estimator recovery.

Avoid treating thousands of ticks within one market run as independent replications. The independent unit is generally the market episode or another justified cluster. Paired shock paths can improve precision, but they do not remove dependence within episodes or make different agents in the same market independent samples.

19.5 Shock families and timing

Predeclare shocks to fundamentals, depth, funding requirements, information quality, update synchronization, and decision-service availability. Apply information-corruption scenarios only inside an isolated, authorized simulation. A shared model change should be tested both synchronously and asynchronously, and compared with an equally large change to a non-AI policy.

Hold shock realizations paired across treatment and baseline where the comparison requires identical external conditions. Randomize shock timing within a predeclared range to reduce phase-specific artifacts. Stress amplitudes must be reported in economically interpretable units as well as normalized model units. There is no presumption that one calendar-time horizon applies to both an exchange and a fund-redemption environment.

19.6 Primary outcomes and statistical analysis

For a price-forming environment, a useful primary outcome is a predeclared, horizon-limited cumulative price dislocation from a simulated fundamental reference, normalized by the scale of the initiating shock. Report the unnormalized numerator and denominator, and avoid ratios near a zero denominator. In an empirical market, the fundamental reference is not observed directly and requires a separate identification argument.

Secondary outcomes should include liquidation losses, execution shortfall, spread, depth, order imbalance, inventory concentration, and recovery time. Distributional tail loss is meaningful only after defining whose loss is measured and over what shock distribution. Mark-to-market wealth transfers should not be mislabeled aggregate social losses. Deadweight liquidation costs, default shortfalls, and real-economy outcomes are distinct quantities.

Compare a baseline predictor using volatility, depth, spreads, leverage, and ordinary order-flow statistics with an augmented predictor that also uses the proposed feedback variables. Evaluate temporal and architecture-held-out prediction with uncertainty, calibration, and economic effect sizes. If the outcome is a distress event, report lead time and false alarms rather than only an area-under-curve statistic. Thresholds and model-selection rules must be fixed without access to the held-out outcomes.

Use cluster-aware uncertainty estimates or independent-run resampling, declare the multiple-testing family, and report failed and null conditions. A practical power analysis should use pilot variance and a justified smallest effect of interest, not a universal “30 seeds” rule.

19.7 Boundary estimation and terminology

A sharp-looking heatmap is not proof of a phase transition. First test whether a continuous, nonlinear, or threshold model better describes held-out outcomes. Distinguish a local eigenvalue crossing from a finite-sample increase in crisis frequency and from a true large-population phase transition. A statistical-physics claim would require an appropriate limiting sequence, scaling analysis, and finite-size evidence.

Report a region of uncertainty around any fitted boundary. When the estimator cannot distinguish stable and unstable mechanisms under realistic observation noise, that limitation is a result. A model-conditioned warning that is frequently indeterminate may still be scientifically useful, but it should not be marketed as a universal instability detector.

20 Prospective empirical validation

Status: not executed; no partner access is claimed. The crucial bottleneck is observation of decision provenance and adaptation, not simply downloading more price histories. An empirical dataset would ideally record anonymized decision or account identifiers, timestamps, execution authority, policy versions, update timing, exposure limits, and market outcomes. Such records require lawful access, institutional cooperation, and appropriate privacy controls.

A partner-assisted study could exploit an authorized staggered rollout or a preplanned randomized change to update scheduling, provided risk controls and research oversight permit it. A model-provider outage or update is not automatically exogenous: exposure may differ systematically across institutions, and the event may coincide with other market information. A difference-in-differences or event-study label does not remove those problems. The identification argument must specify the assignment mechanism, comparison group, anticipation, spillovers, and relevant confounders.

An initial empirical contribution could be measurement validation rather than crisis forecasting. For example, compare response estimates obtained from controlled internal replay or paper trading with responses around authorized small operational changes. Test whether provider labels predict actual signed behavioral similarity, and whether policy update logs distinguish learning from ordinary signal refresh. These questions can reveal whether the proposed state variables are observable enough to support the larger program.

Shadow evaluation permits predictions and alerts to be recorded without authorizing trades. It is a possible stage before intervention research, not a substitute for causal validation. Predictions must be timestamped and evaluated against later outcomes under frozen scoring rules. Where access is unavailable, the paper should remain a simulation or theoretical contribution and restrict its conclusions accordingly.

Cross-domain extension requires separate validation. A limit-order-book price perturbation is not the same object as a depositor's redemption incentive or a lender's credit supply response. A genuine unifying contribution would show which state transformations and feedback quantities remain meaningful across those settings, where the mapping fails, and what institutional variables cannot be abstracted away.

21 Limitations, responsible use, and wider significance

21.1 Scientific limitations

The original tractable network model uses a common first-order learning rate; the integrated scalar studies extend it to heterogeneous first-order rates. Both retain a fixed reference point and nonnegative response coefficients. It omits endogenous innovation in strategies, strategic

deception, discontinuous liquidation rules, endogenous entry and exit, and general-equilibrium wealth effects. Its spectral boundary is neither an asset-pricing theorem nor a universal condition for crises. Some instability modes may be damped by limits, while finite disturbances can cause defaults even around a locally stable equilibrium.

The complete joint state may be inaccessible for modern agents. Hidden memory, discrete version changes, stochastic sampling, and proprietary risk overlays can undermine smooth finite-dimensional approximations. Estimated feedback may be highly uncertain exactly where extreme events matter. Identifying a persistent empirical feedback coefficient does not identify an economically optimal intervention.

The original algebra checks and all subsequent measurement and funded-market experiments are uncalibrated to a real exchange. The v0.5 funded model introduces binding financial limits, but its source-aware linear interval is deliberately not applied across those nonlinear limits. A large number of repeated synthetic episodes does not supply external validity. Independent identically distributed Gaussian episodes, fixed parameters, exogenous filled pulses and a valid positive learning-rate floor are substantive assumptions. A repeatable episode is natural in simulation but not automatically obtainable from a single evolving market. Selecting windows after observing stress, using endogenous fills as if randomly assigned, or carrying an invalid floor into the solver breaks the argument.

The response rectangle discards covariance geometry and the recurrence inequalities over-approximate compatible models. Some inconclusive outcomes reflect this conservatism, not a proven information limit. An equally informed full-covariance output-error estimator or set should be tested before any broad efficiency claim. A true fixed-step instability may be limited by nonlinearities and capital restrictions in a different model, while stable prices do not prevent funded agents from defaulting.

The results provide no evidence of a global machine-participation threshold, real-market crisis prediction, architecture-independent transfer, or the superiority of an abstention intervention. They also do not establish a new scientific paradigm. Any submission must communicate this evidence boundary in the abstract as well as the methods.

21.2 Research ethics and operational boundaries

All agent-interaction and information-corruption experiments should remain in controlled environments unless separately authorized. No experiment proposed here requires placing deceptive orders, manipulating public markets, or using customer data without permission. Human-subject work and sensitive institution-level records require relevant review, consent or lawful basis, data minimization, and secure handling.

Publication should document model versions, datasets, licenses, prompts that may legally be shared, code changes, and observed failure modes. Public generated explanations may be studied as outputs, but should not be treated as verified internal reasoning or a causal account of an agent's decision. No claim depends on access to private model reasoning.

21.3 What would make the contribution globally useful

The potential value is a measurement and validation framework that helps institutions understand interactions among decision systems, rather than another predictor of asset prices. To support wider use, the framework would need reliable estimation from realistic observations, added value over existing risk measures, transfer across relevant architectures and institutions, and evidence about intervention costs and spillovers. The FSB's monitoring work and its 2026 consultation on responsible adoption provide institutional context for such questions, not endorsement of this manuscript [11, 12].

A globally relevant result need not claim that all financial laws have changed. A precisely demonstrated failure of an existing diagnostic, together with a better measurable replacement and clearly delimited applicability, could materially advance the field. Conversely, evidence that conventional feedback and liquidity models already explain the alleged machine transition would be an important correction to exaggerated claims.

22 Conclusion

The defensible question is not whether finance loses its familiar principles when AI becomes prevalent. It is which feedback properties can be established from available observations when adaptive decision rules interact with price formation. The original framework requires the complete market–learning state for local analysis, distinguishes asymptotic stability from transient and switching risk, and rejects provider diversity or individual abstention as automatic safety certificates.

The companion studies strengthen the measurement question while correcting the initial diagnostic claim. Exact finite windows can conceal opposite stability classes; fixed-order noisy examples can remain hard to distinguish. Yet conventional full-moment identification extracts more useful information than the original summary bound. Thus neither a vivid counterexample nor a favorable weak-baseline result justifies claiming a universally better estimator.

The new study closes a narrower missing link: randomized filled-order quantities and quoted prices can recover the relevant response without accessing private states, and their uncertainty can be propagated into a conditional stability interval. This is demonstrated in a transaction- and ledger-consistent synthetic dealer model. The strongest primary design resolves only 16.67% of panels. A false rate floor produces false stability even when the measured response intervals are accurate. A price-specific lower bound, distinct from the earlier kernel law, explains one genuine finite-budget obstruction without attributing every inconclusive case to impossibility.

Version 0.5 makes further model-conditioned progress. A truthful implementation contract bounds the isolated memory tail; a terminal-row design estimates gain and tail contrasts from observable prices without reading private states. Preassigned diverse endpoints improve low-budget decisions on held-out synthetic panels but do not uniformly dominate a fixed endpoint. Binding limits and preloaded dealer stress show why the linear signal certificate cannot serve as a blanket financial-safety claim. A different, finite-horizon probability target remains statistically measurable under explicit independent-scenario assumptions.

The resulting direction is a separation of guarantees, not a completed universal detector. Architectural audit, observed statistical uncertainty and operational financial risk must each be established at their own level. The next external requirements are truthful complete-state provenance, a calibrated observation and funding environment, an appropriately strong equal-information comparator for each target, outside proof and novelty review, and an independent team's reproduction. A global safety framework requires institutional evidence and validated economic outcomes, not simply a larger manuscript.

Data, code, and disclosure statement

No empirical financial dataset, human-subject dataset or proprietary institutional record was used. Original algebra results come from Appendix B. Two previous synthetic studies are attributed and their original PDFs, TeX files and result summaries preserved in the supplement. The v0.4 price-only study was executed for the previous integration; its code, protocols, seeds, summary observations, all decision rows and example raw observations are released. Full raw records outside the examples are regenerated from recorded seeds, not claimed to be included.

The full primary run reproduced byte-identical comparison and panel CSV files in a clean output directory on this environment. The v0.5 supplement adds source-audited regression, measured tails, endpoint-budget comparisons and funded-market studies, with all terminal regression rows, per-episode financial outcomes, selected complete price paths and source-based regeneration. Rich trained-agent and real-institution experiments remain unexecuted.

The manuscript was developed with AI assistance from the user's concept note and three project manuscripts. Prospective named authors must independently verify its mathematics, source attribution and empirical scope and take responsibility for submission. No author identity, institutional affiliation, funding award, ethics approval, data partnership, external reviewer, or endorsement is asserted. Internal code cross-checks and clean reruns are not independent outside replication.

References

[1] W. Brian Arthur, John H. Holland, Blake LeBaron, Richard Palmer, and Paul Tayler. Asset Pricing Under Endogenous Expectations in an Artificial Stock Market. Santa Fe Institute Working Paper 96-12-093, 1996. https://www.santafe.edu/research/results/working-papers/asset-pricing-under-endogenous-expectations-in-an-.

[2] William A. Brock and Cars H. Hommes. Heterogeneous beliefs and routes to chaos in a simple asset pricing model. *Journal of Economic Dynamics and Control*, 22(8–9):1235–1274, 1998. https://doi.org/10.1016/S0165-1889(98)00011-6.

[3] Markus K. Brunnermeier and Lasse Heje Pedersen. Market Liquidity and Funding Liquidity. *The Review of Financial Studies*, 22(6):2201–2238, 2009. https://doi.org/10.1093/rfs/hhn098.

[4] Emilio Calvano, Giacomo Calzolari, Vincenzo Denicolò, and Sergio Pastorello. Artificial Intelligence, Algorithmic Pricing, and Collusion. *American Economic Review*, 110(10):3267–3297, 2020. https://doi.org/10.1257/aer.20190623.

[5] Juan C. Perdomo, Tijana Zrnic, Celestine Mendler-Dünner, and Moritz Hardt. Performative Prediction. *Proceedings of Machine Learning Research*, 119:7599–7609, 2020. https://proceedings.mlr.press/v119/perdomo20a.html.

[6] Adhyyan Narang, Evan Faulkner, Dmitriy Drusvyatskiy, Maryam Fazel, and Lillian J. Ratliff. Multiplayer Performative Prediction: Learning in Decision-Dependent Games. *Journal of Machine Learning Research*, 24(202):1–56, 2023. https://jmlr.org/papers/v24/22-0131.html.

[7] Gabriele Farina and Juan Carlos Perdomo. The Stability of Online Algorithms in Performative Prediction. arXiv:2602.24207v2, 3 June 2026. Preprint. https://arxiv.org/abs/2602.24207v2.

[8] Kartik Anand, Sophia Kazinnik, Agnese Leonello, and Ettore Panetti. Ex Machina: financial stability in the age of artificial intelligence. European Central Bank Working Paper Series, No. 3225, 2026. https://doi.org/10.2866/4103076.

[9] Jean-Edouard Colliard, Thierry Foucault, and Stefano Lovo. Algorithmic Pricing and Liquidity in Securities Markets. *The Review of Financial Studies*, hhag010, 2026. https://doi.org/10.1093/rfs/hhag010.

[10] Financial Stability Board. The Financial Stability Implications of Artificial Intelligence. 14 November 2024. https://www.fsb.org/uploads/P14112024.pdf.

[11] Financial Stability Board. Monitoring Adoption of Artificial Intelligence and Related Vulnerabilities in the Financial Sector. 10 October 2025. https://www.fsb.org/2025/10/monitoring-adoption-of-artificial-intelligence-and-related-vulnerabilities-in-the-financial-sector/.

[12] Financial Stability Board. Sound Practices for Responsible Adoption of Artificial Intelligence (AI): Consultation report. 10 June 2026. This reference identifies the consultation version, not a legal requirement. https://www.fsb.org/2026/06/sound-practices-for-responsible-adoption-of-artificial-intelligence-ai-consultation-report/.

[13] Stephen Boyd, Laurent El Ghaoui, Eric Feron, and Venkataramanan Balakrishnan. *Linear Matrix Inequalities in System and Control Theory*. SIAM, 1994. https://web.stanford.edu/~boyd/lmibook/.

[14] Hassan K. Khalil. *Nonlinear Systems*. Third edition. Prentice Hall, 2002. https://www.egr.msu.edu/~khalil/NonlinearSystems/.

[15] David Byrd, Maria Hybinette, and Tucker Hybinette Balch. ABIDES: Towards High-Fidelity Market Simulation for AI Research. arXiv:1904.12066, 2019. This reference identifies the preprint version. https://arxiv.org/abs/1904.12066.

[16] *Hidden Slow Learners: Finite-Horizon Limits and Rate-Aware Certificates for Adaptive-Market Stability.* Unpublished project research artifact, 18 September 2026, 15 pages. Supplied as Hidden_Slow_Learners_Paper.pdf; original source and selected machine-readable results preserved in the supplement. Not an external or peer-reviewed source.

[17] *Hidden Slow Learners Revisited: Full-Horizon Positive Identification and Limits of Stability Measurement.* Unpublished project research artifact, 18 September 2026, 13 pages. Supplied as Full_Horizon_Identification_Audit.pdf; original source and selected machine-readable results preserved in the supplement. Not an external or peer-reviewed source.

[18] Anders Rantzer. Scalable control of positive systems. *European Journal of Control*, 24:72–80, 2015. https://doi.org/10.1016/j.ejcon.2015.04.004.

[19] Robert L. Kosut, Ming K. Lau, and Stephen P. Boyd. Set-Membership Identification of Systems with Parametric and Nonparametric Uncertainty. *IEEE Transactions on Automatic Control*, 37(7):929–941, 1992. https://web.stanford.edu/~boyd/papers/set_member_id.html.

[20] Dimitris Bertsimas and Ioana Popescu. Optimal Inequalities in Probability Theory: A Convex Optimization Approach. *SIAM Journal on Optimization*, 15(3):780–804, 2005. https://doi.org/10.1137/S1052623401399903.

[21] Henk J. van Waarde, Jaap Eising, Harry L. Trentelman, and M. Kanat Camlibel. Data informativity: a new perspective on data-driven analysis and control. *IEEE Transactions on Automatic Control*, 65(11):4753–4768, 2020. https://arxiv.org/abs/1908.00468.

[22] Yassir Jedra and Alexandre Proutiere. Sample Complexity Lower Bounds for Linear System Identification. arXiv:1903.10343, 2019. Preprint version consulted. https://arxiv.org/abs/1903.10343.

[23] Mohammad Khosravi and Roy S. Smith. Regularized Identification with Internal Positivity Side-Information. arXiv:2111.00407, 2021. Verified preprint version consulted. https://arxiv.org/abs/2111.00407.

[24] Mohammad Khosravi and Roy S. Smith. Kernel-based Impulse Response Identification with Side-Information on Steady-State Gain. arXiv:2111.00409, 2021. Preprint version consulted. https://arxiv.org/abs/2111.00409.

[25] Balázs Cs. Csáji, Marco C. Campi, and Erik Weyer. Sign-Perturbed Sums: A New System Identification Approach for Constructing Exact Non-Asymptotic Confidence Regions in Linear Regression Models. *IEEE Transactions on Signal Processing*, 63(1):169–181, 2015. https://doi.org/10.1109/TSP.2014.2369000; author manuscript: https://arxiv.org/abs/1807.08216.

[26] Rama Cont, Arseniy Kukanov, and Sasha Stoikov. The Price Impact of Order Book Events. *Journal of Financial Econometrics*, 12(1):47–88, 2014. https://doi.org/10.1093/jjfinec/nbt003.

[27] SciPy developers. SciPy API reference: linprog, HiGHS dual-simplex and interior-point methods. Official documentation; accessed 18 September 2026. Tested version: SciPy 1.17.0. https://docs.scipy.org/doc/scipy/reference/optimize.linprog-highs-ds.html.

[28] Ian R. Manchester. Input Design for System Identification via Convex Relaxation. arXiv:1009.5614, 2010. https://arxiv.org/abs/1009.5614.

[29] C. J. Clopper and E. S. Pearson. The Use of Confidence or Fiducial Limits Illustrated in the Case of the Binomial. *Biometrika*, 26(4):404–413, 1934. doi:10.1093/biomet/26.4.404.

[30] Eduardo Abi Jaber, Nathan De Carvalho and Huyên Pham. Trading with propagators and constraints: applications to optimal execution and battery storage. arXiv:2409.12098, 2024. https://arxiv.org/abs/2409.12098.

A Proofs and technical qualifications

A.1 Local stability and the limits of linearization

For the stable part of Proposition 5.1, choose $\gamma \in (\rho(J^*), 1)$. Finite-dimensional matrix theory provides an equivalent vector norm with $\|J^*\| < \gamma$. Continuity of $D\Phi$ provides a convex neighborhood of z^* and $\widetilde{\gamma} < 1$ such that $\|D\Phi(z)\| \le \widetilde{\gamma}$ throughout that neighborhood. The mean-value integral yields

$$\|\Phi(z) - z^*\| \le \widetilde{\gamma} \|z - z^*\| . \tag{51}$$

A sufficiently small norm ball is invariant; iteration gives exponential decay. The unstable part is the standard discrete-time linearization instability result: a derivative eigenvalue outside the closed unit disk produces a locally expanding direction and rules out Lyapunov stability for a continuously differentiable map. No conclusion is asserted from an eigenvalue on the unit circle alone. The result concerns the fixed autonomous map and its fixed point, not an arbitrary sequence of re-estimated Jacobians.

A.2 Proof of the positive-feedback boundary

Let $\nu = \rho(BC)$ and define

$$r_+ = \frac{a + 1 - \eta + \sqrt{(a - 1 + \eta)^2 + 4g\eta\nu}}{2}. \tag{52}$$

When $g\nu > 0$, Perron–Frobenius theory supplies $v \ge 0$, $v \ne 0$, with $BCv = \nu v$. Then $Cv \ne 0$ and

$$w = \frac{\eta}{r_+ - 1 + \eta} Cv \tag{53}$$

satisfies $J_+(v, w)^\top = r_+(v, w)^\top$. Hence r_+ is an eigenvalue.

To show that no eigenvalue has greater modulus, let (v, w) be a nonzero eigenvector with eigenvalue λ. Eigenvalues equal to a or $1-\eta$ have modulus at most r_+. For the others, eliminating w gives

$$BCv = \frac{(\lambda - a)(\lambda - 1 + \eta)}{g\eta} v. \tag{54}$$

If $|\lambda| > r_+$, then $|\lambda| > \max(a, 1 - \eta)$ and

$$|(\lambda - a)(\lambda - 1 + \eta)| \ge (|\lambda| - a)(|\lambda| - (1 - \eta)) \tag{55}$$

$$> (r_+ - a)(r_+ - (1 - \eta)) = g\eta\nu. \tag{56}$$

This contradicts the spectral-radius bound on eigenvalues of BC. Thus $\rho(J_+) = r_+$. If $g = 0$, the matrix is block triangular. If $\nu = 0$ and $g > 0$, the same elimination excludes every eigenvalue outside $\{a, 1 - \eta\}$, so the formula reduces to $\max(a, 1 - \eta)$ and remains valid.

Finally, $r_+ < 1$ is equivalent to

$$\sqrt{(a - 1 + \eta)^2 + 4g\eta\nu} < 1 - a + \eta. \tag{57}$$

The right side is positive. Squaring and simplifying yields $g\nu < 1 - a$ because $\eta > 0$. Equality and strict reversal follow identically. For a finite-dimensional constant linear system, all eigenvalues inside the unit disk are equivalent to asymptotic stability. This proves theorem 6.1.

A.3 What the boundary does not imply

A positive real eigenvalue passing through one identifies loss of local linear stability in the specified model. It does not determine the nonlinear attractor, whether prices crash or grow, whether an institution defaults, or whether a finite disturbance remains inside the modeled region. A nonlinear extension could saturate or switch into another regime. An observed financial crisis can also occur without this crossing, for example when an external shock overwhelms solvency buffers.

The result uses a single persistence scalar a and a common η. Allowing asset-specific persistence, asymmetric learning rates, delayed observation, or signed response matrices removes the simple formula unless further structure is proved. A claimed universal surface in six aggregate variables would need to show that the omitted state is either irrelevant, bounded, or measured. The current theorem does not establish such sufficiency.

A.4 Stochastic and nonlinear robustness

For a nonlinear map Φ_t with a common reference point, suppose the induced P-norm of every derivative on a convex ball of radius r is at most $\gamma < 1$. Then the same Lipschitz argument yields the disturbance bound in equation (49). If $\bar{b} \leq (1-\gamma)r$ and the initial state is inside the ball, that ball is invariant. With an evolving reference point, its motion must appear as an additional disturbance; ignoring that drift changes the claim.

If an estimated uncertainty set covers the actual matrices with probability at least $1-\delta$ over the relevant horizon, the robust bound holds on that coverage event. Marginal per-time coverage does not automatically imply simultaneous horizon coverage. Model updates, adaptive sampling, and post-selection can invalidate a naive confidence statement. These statistical issues are work remaining, not solved by the deterministic norm inequality.

B Executable reproduction of the numerical checks

Copy the following listing into `verify_math.py` and run it with Python 3 and NumPy. The program has no network access, downloads no financial data, and trains no models. All numerical parameters and random seeds are explicit. It prints the values reported in section 18 and stops with an assertion error if an algebraic check fails.

```
"""Deterministic algebra checks for the Machine Markets working paper.
These are NOT calibrated markets, agent experiments, or empirical evidence.
Requires Python 3 and NumPy. Run: python verify_math.py
"""
import json
import numpy as np


def spectral_radius(matrix):
    matrix = np.asarray(matrix, dtype=float)
    if matrix.ndim != 2 or matrix.shape[0] != matrix.shape[1]:
        raise ValueError("Expected a square matrix")
    if not np.isfinite(matrix).all():
        raise ValueError("Nonfinite matrix entry")
    return float(np.max(np.abs(np.linalg.eigvals(matrix))))


def scalar_matrix(a, g, eta, kappa=1.0):
    if not (0 <= a < 1 and 0 < eta <= 1 and g >= 0 and kappa >= 0):
        raise ValueError("Parameters violate the proposition assumptions")
    return np.array([[a, g], [eta * kappa, 1 - eta]])
```

```
22
23
24  def rho_formula(a, g, eta, kappa=1.0):
25      return float((a + 1 - eta + np.sqrt((a - 1 + eta)**2
26                   + 4 * g * eta * kappa)) / 2)
27
28
29  def main():
30      rows = []
31      for label, g, eta in [
32          ("stable feedback", 0.30, 0.20),
33          ("boundary", 0.60, 0.20),
34          ("unstable feedback", 0.90, 0.20),
35          ("same unstable gain, slower learning", 0.90, 0.05),
36          ("same unstable gain, faster learning", 0.90, 0.80),
37          ("baseline before action gate", 0.45, 0.20),
38          ("gate, depth unchanged", 0.225, 0.20),
39          ("gate, depth reduced to one quarter", 0.90, 0.20),
40      ]:
41          radius = spectral_radius(scalar_matrix(0.4, g, eta))
42          assert abs(radius - rho_formula(0.4, g, eta)) < 1e-12
43          rows.append(dict(case=label, a=0.4, g=g, eta=eta, kappa=1.0,
44                           radius=radius))
45
46      # A deterministic Cartesian grid, not a Monte Carlo experiment.
47      scalar_checks = 0
48      max_error = 0.0
49      for a in [0.1, 0.3, 0.5, 0.7, 0.9]:
50          for eta in [0.05, 0.2, 0.5, 0.8, 1.0]:
51              for g in [0.07, 0.17, 0.37, 0.67, 1.07]:
52                  for kappa in [0.15, 0.45, 0.85, 1.25, 1.75]:
53                      radius = spectral_radius(scalar_matrix(a, g, eta, kappa))
54                      max_error = max(max_error,
55                          abs(radius - rho_formula(a, g, eta, kappa)))
56                      assert abs(g * kappa - (1 - a)) > 1e-8
57                      assert (radius < 1) == (g * kappa < 1 - a)
58                      scalar_checks += 1
59
60      # Independent network formula checks with a fixed seed.
61      rng = np.random.default_rng(20260918)
62      network_checks = 0
63      max_network_error = 0.0
64      for _ in range(250):
65          d, n = 3, 4
66          B = rng.uniform(0, 1, (d, n)) / n
67          C = rng.uniform(0, 1, (n, d)) / d
68          a = float(rng.uniform(0.05, 0.95))
69          eta = float(rng.uniform(0.05, 1.0))
70          g = float(rng.uniform(0.01, 4.0))
71          J = np.block([[a*np.eye(d), g*B],
72                        [eta*C, (1-eta)*np.eye(n)]])
73          nu = spectral_radius(B @ C)
74          radius = spectral_radius(J)
75          pred = rho_formula(a, g, eta, nu)
76          max_network_error = max(max_network_error, abs(radius - pred))
77          assert abs(radius - pred) < 1e-10
78          assert abs(g*nu - (1-a)) > 1e-8
79          assert (radius < 1) == (g*nu < 1-a)
80          network_checks += 1
81
82      # Frozen eigenvalues do not certify an arbitrarily switched system.
83      J1 = np.array([[0.5, 2.0], [0.0, 0.5]])
84      J2 = J1.T
```

```
    switch_radius = spectral_radius(J2 @ J1)
    assert spectral_radius(J1) == 0.5
    assert spectral_radius(J2) == 0.5
    assert switch_radius > 1

    # Stable eigenvalues can coexist with large finite-horizon gain.
    J = np.array([[0.8, 4.0], [0.0, 0.8]])
    gains = [float(np.linalg.norm(np.linalg.matrix_power(J, h), 2))
             for h in range(51)]
    peak_h = int(np.argmax(gains))
    assert spectral_radius(J) < 1 and max(gains) > 8

    # A Gram concentration score loses the direction of action alignment.
    r = np.array([1.0, 0.0])
    same = np.stack([r, r])
    opposite = np.stack([r, -r])
    def adc(R):
        return float(np.linalg.eigvalsh(R.T @ R / len(R))[-1])
    assert adc(same) == adc(opposite) == 1.0
    assert np.linalg.norm(same.mean(axis=0)) == 1.0
    assert np.linalg.norm(opposite.mean(axis=0)) == 0.0

    out = dict(scalar_cases=rows, scalar_grid_checks=scalar_checks,
               max_scalar_formula_error=max_error,
               network_checks=network_checks,
               max_network_formula_error=max_network_error,
               switching_product_radius=switch_radius,
               switching_per_step_growth=np.sqrt(switch_radius),
               nonnormal_radius=0.8, nonnormal_peak_h=peak_h,
               nonnormal_peak_gain=max(gains),
               concentration_same=adc(same),
               concentration_opposite=adc(opposite),
               numpy_version=np.__version__)
    print(json.dumps(out, indent=2))

if __name__ == "__main__":
    main()
```

C Source provenance and revisions to the supplied concept note

The user-supplied document *Pasted markdown.md* is the conceptual basis of this manuscript. It proposes the title, the market–learning feedback question, six organizing dimensions, critical-regime analysis, and a long-term ambition extending beyond trading. It is a planning document, not an empirical source. The table below explicitly separates retained framing from changes introduced during drafting and literature verification.

Table 11: Transparent changes from the concept note.

Concept-note element	Treatment in this manuscript
Human-to-machine market transition	Retained as the motivating question; no assertion that accounting or all classical finance becomes invalid.
Joint evolution of market and policy	Retained, while explicitly acknowledging adaptive-expectations and performative-prediction precedents.
Partial feedback product	Replaced by the full augmented Jacobian, including direct persistence and policy-state dynamics.
Machine-market criticality	Retained as a descriptive local label; supplemented with transient gains, time-varying products, and robustness qualifications.
Arbitrary autonomy scores	Replaced by event-level execution-authority measurement, exposure weights, and missingness bounds.
Weighted concentration index	Replaced by an explicit response-panel descriptor plus a counterexample showing why concentration alone is insufficient.
Candidate “laws”	Reclassified as hypotheses or model-conditioned results. Update speed and volatility receive explicit counterexamples to universal claims.
Universal AI participation threshold	Replaced by a conditional surface in a solvable positive-feedback model; no universal percentage is claimed.
Act/freeze/abstain safety idea	Retained as a prospective comparison; liquidity withdrawal and remaining inventory risk are modeled as possible failure channels.
Large multi-agent experiment	Retained as future work. This integration adds a separate small dealer measurement pilot, not the proposed trained-agent market experiment.
2025–2026 source links	Only independently checked primary-source references used in the text were retained. Other concept-note links are not treated as established evidence here.
Paradigm-level ambition	Retained as an eventual evidence standard, not as a current quality rating or promised outcome.

The mathematical examples and executed matrix checks were developed for this draft and were not reported findings in the concept note. The 2026 ECB working paper is cited by its verified working-paper version; the surrounding Research Bulletin uses an earlier-year citation to its predecessor. The present reference deliberately identifies the version consulted rather than silently combining versions.

D Evidence contract for a completed flagship paper

A final empirical manuscript should replace the prospective sections only when the corresponding evidence exists. The following is an acceptance contract for the research program, not a list of results already achieved.

Theoretical increment. Identify and defend at least one result that is not merely a standard local-stability theorem under new names. Possible targets include partial-observation identification bounds, statistically valid finite-horizon certificates under endogenous adaptation, or a causal decomposition that separates adaptive-policy feedback from ordinary liquidity feedback. The choice should follow a nearest-neighbor literature review.

Mechanism evidence. Recover known parameters in a synthetic system before interpreting estimates from a market simulator. Then show that interventions on the proposed feedback channel, with capital, information, and market design controlled, change the specified financial outcome as predicted. Include alternative explanations and conditions in which the hypothesis fails.

Predictive and economic relevance. Demonstrate added value beyond conventional observables on genuinely held-out conditions. Report uncertainty, false alarms, lead time, and financially meaningful effect sizes. Do not select the only successful architecture, asset, shock, or seed after seeing results.

Transfer and falsification. Test a held-out agent family and an independently implemented environment. Map failure regions. A second financial domain is desirable for a broad framework, but not permission to weaken the first domain's identification. Universal laws require much more than success on two datasets.

Responsible intervention evidence. Evaluate feasible interventions using only information available at the decision time. Include liquidity, execution costs, inventory exposure, externalities, and the conditions under which a proposed gate cannot certify anything. An oracle controller is a diagnostic upper benchmark, not a deployable competitor.

External validation and independent reproduction. Establish whether the quantities can be measured with realistic institutional data, or delimit the work to simulation. Release reproducible materials where permitted, obtain independent verification, and distinguish peer-reviewed acceptance from subsequent scientific adoption. Community use and durable explanatory power, not a preassigned score, determine whether a contribution becomes paradigm forming.

Completion statement. This version completes the integrated framework, companion-study synthesis and a reproducible observable-price measurement pilot under explicit assumptions. It does not complete the flagship scientific program. The original Word roadmap is historical planning material, not a current completion checklist; the integration ledger and supplement documents state which measurement tasks are now done and which experimental and external-validation gates remain open.

E Integration ledger, information contract and reproduction

This manuscript updates the original 24-page paper rather than concatenating the three PDFs. The general framework, intervention cautions and future validation program remain. The two companion findings are integrated with their adverse results intact. The new measurement study is separately identified.

Table 12: Source-to-result integration map.

Source	Material retained or added
Original 24-page framework	Joint Jacobian; local, transient and switching risk; positive network boundary; autonomy and concentration cautions; liquidity-sensitive interventions; 875 algebra checks; prospective programs.
First 15-page companion	Heterogeneous-memory boundary; exact paired construction and proof; readable witness; slow-tail bounds; original measurement counts and false-floor failure. See Section 8.
Second 13-page companion	Full-horizon conventional comparison; 4 wrong confident calls retained; 82,364 covered rows; fixed-order kernel-observation limit and explicit observation-law restriction. See Section 9.
New research for this version	Filled-probe/price-only protocol; unknown-covariance uncertainty; positive recurrence bounds; hidden-state firewall; ledger-consistent dealer test; 1,920 primary panels; budget and failure controls; price-law lower bound; clean internal rerun.
Not established	Trained-agent transfer, realistic binding capital and order books, observed-market accuracy, optimal active design, universal estimator superiority, outside proof review, exhaustive novelty confirmation or independent external reproduction.

E.1 Notation and observation laws must not be silently merged

The general framework uses u_t for agent decisions; in the scalar measurement experiment it denotes the external signed probe. The new κ is dollars of price impact per share; it is not the generic normalized cross-response appearing in the original algebra examples. New scalar $Q = \sum_i q_i$ is feedback mass, $G = Q/(1-a)$ is normalized gain, and $S = a + Q$ is the stability objective. The new linear-programming label threshold is $S = 1$.

The older audit observes normalized loop-open $g_j = k_j/(1-a)$ with declared noise precision. The new study observes price responses $\beta_j = \kappa h_j$ through randomized regression, with precision estimated from prices. The old and new sample counts, error formulas and decisive fractions refer to different experiments. Neither their errors nor their effectiveness should be pooled into one headline result.

E.2 What is released

The supplement's `src/market.py` contains the simulator and evaluation-only analytical response; `src/observable.py` takes the public observations for inference. `run_study.py` creates the primary panel; `run_extensions.py` creates explicitly exploratory and adverse controls; `verify_release.py` performs internal alternate-calculation checks. `configs/models.json` and the protocol document specify generating configurations and fixed seed construction. Configuration labels never enter the inference function.

`results/comparison.csv` contains all 5,760 primary decisions and bounds. `results/panels.csv` records seeds, exact public-record hashes, accounting checks and the evaluation-only response coverage indicator. `data/public_panel_statistics.npz` stores every measured response estimate, lower/upper endpoint and standard error. Four complete `public_example_*.npz` files contain only probes and prices. Separately named covariance/example files include evaluation truth and must not be supplied to inference. Not every raw episode is stored; all are reconstructible from seeds using the declared environment.

The original manuscripts and selected old result summaries are kept unmodified under `provenance/`. The complete prior archives remain separate source releases, not silently folded into the new experiment's counts. SHA-256 manifests identify released files. No font files, credentials, private records or external account access are required.

E.3 Reproduction commands

From the unpacked supplement, install the version-pinned dependencies in an isolated Python environment. The primary runner writes to a new directory so the delivered result files remain unchanged.

```
python -m pip install -r requirements.txt
python -m pytest -q tests
python run_study.py --out rerun_primary
python run_extensions.py
python verify_release.py
pdflatex -interaction=nonstopmode -halt-on-error \
  -output-directory=paper paper/Machine_Markets_Integrated_Research_Paper.tex
# Repeat the same pdflatex command to resolve cross-references.
```

The extension script writes into the current release folder; copy that folder before rerunning if preserving byte-for-byte delivered results. The primary full rerun produced identical panel and comparison CSVs and identical arrays in all repeated NPZ files in this environment. Floating-point details on other platforms may differ; the scientific tests and declared tolerances, not one bit pattern, are the portable contract. Internal reruns and alternate solvers are not outside replication.

E.4 Version 0.4 gates and the v0.5 response

Version 0.4 identified the following gates. A realistic observation study should predeclare a budget in episodes, elapsed time, filled volume and inventory exposure; justify the learning-rate floor or replace it with a defensible tail class; use a model check beyond LP feasibility; and compare an equally informed full-covariance output-error method. Dependent episodes, changing latent states and partial fills require a revised identification and uncertainty argument. A longer single market trace must not simply be relabeled as thousands of independent episodes.

Version 0.5 implements funded positions and binding inventory, credit and leverage limits, including dealer-capacity reductions. It does not close the requirements for calibrated endogenously changing liquidity, richer objectives, or matched trained-AI versus non-AI adaptive baselines. A reviewer should challenge the proofs and closest predecessors before the paper claims original priority. An external team should reproduce at least one complete observation panel from the public interface alone. The source audit and synthetic financial implementation make some of these requirements testable in this release, but independent external reproduction, institutional applicability and original-priority review remain open. Synthetic sample size does not close them.

F Version 0.5 evidence and reproduction contract

The main manuscript preserves the original framework and both companion conclusions. Sections 14–16 are new. Primary, post-primary pilot, held-out confirmation, and dealer-stress extension are distinguished in the protocol files. No experiment is described as externally preregistered.

F.1 Data lineage and counts

The v0.5 primary linear study contains 2,880 panels and 645,120 independent episode rows. Its tail reanalysis uses the same rows. Endpoint confirmation uses 720 fresh datasets and 161,280 episodes, evaluated twice for 1,440 paired decision rows. The financial primary uses 491,520 setting-trajectories but only 163,840 unique exogenous tapes because three funding regimes share each tape. Its 2,880 probability rows use nested episode budgets, not new data at every look. The preloaded-dealer extension adds 65,536 paths; the five assumption controls use 400 panels of 512 episodes. These are synthetic experimental counts, not counts of real institutions or independent crises.

F.2 Executable information separation

Files under `src/inference.py` accept public prices or reconstructed terminal rows and public rates. They do not accept the true q_i, noise variance, simulator memory, hidden equity state, or target label. Public records include probe schedules and preassigned endpoints where relevant. Source-truth parameters are used only by generators and post-estimation evaluators. Configuration disclosure is a maintained audit input, not a fact inferred from short prices. The standalone verifier uses SVD regression, explicit convolution, exact binomial intervals and LP order projection without project inference imports.

F.3 Portable rerun

From the new package root, the following commands rebuild the new studies. The finance runner checkpoints after eight newly computed settings; three invocations complete all 24. It rejects stale checkpoints when the financial source hash changes. To force a fresh run, use a clean copied directory, not an output folder containing old checkpoints.

```
python -m pip install -r requirements.txt
export OPENBLAS_NUM_THREADS=1
export OMP_NUM_THREADS=1
python -m pytest -q tests
python scripts/run_linear.py
python scripts/run_finance.py --max-new 8
python scripts/run_finance.py --max-new 8
python scripts/run_finance.py --max-new 8
python scripts/run_followup.py
python scripts/run_controls.py
python scripts/measure_tail.py
python scripts/prepare_replication.py
python replication/verify_without_project_imports.py
pdflatex -interaction=nonstopmode -halt-on-error \
  -output-directory=paper paper/Machine_Markets_Audited_Integrated_Paper.tex
# Run the same pdflatex command again for cross-references.
```

The PDF and TeX are self-contained; reproducing research calculations does not require LaTeX. A clean-directory rerun and the final release record document the executed checks. Floating-point tolerances are part of the external contract; cross-platform bit identity is not promised.

F.4 External-review acceptance checklist

An outside reviewer should independently reconstruct the filters and final-row independence argument; challenge completeness of the declared audit boundary; check the geometric tail bound and the two-point predecessors; evaluate observation error and unknown initial states; inspect dealer and liquidation mechanics; compare fair budgets including inventory unwind; and rerun at least one observation panel in a separate implementation. A source digest from an untrusted issuer is not sufficient evidence. Passing the shipped tests is not proof of scientific novelty or external economic validity. The release's status for outside replication is explicitly `pending`, with no reviewer or institution attributed.