FedQPNT: Attack-Resilient Vehicle Navigation with Quantum Inertial Aiding, Federated Attack Detection and Continuous GNSS Trust

Review 3 Report

Project basket: Novelty project (journal paper draft + patent claim draft)

Team name: [Team name]

Members: [Member names and register numbers]

Guide: [Guide: Professor name]

Course / Slot: [Course code / Slot]

Department: [Department, University]

October 2026

Abstract

Global Navigation Satellite System (GNSS) spoofing and jamming threaten autonomous vehicles and unmanned aerial vehicles. We present FedQPNT, which fuses an inertial measurement unit, GNSS and a cold-atom accelerometer (CAI) in an error-state Kalman filter. A learned detector drives a continuous, asymmetric trust law with evidence-bounded exclusion, and detector parameters are aggregated across a fleet by a robust federated-learning (FL) aggregator. The CAI noise model is calibrated to real laboratory data; platform, GNSS observables and attacks are simulated. We report a pre-registered evaluation on 30 unseen seeds per scenario at two inertial grades, with a Holm-corrected confirmatory family of eight tests. FedQPNT detects attack onset significantly earlier than a detect-and-exclude baseline (median paired difference 0.5 s, Holm-adjusted $p = 0.004$); the accompanying position-error test was not significant. It adds no measurable cost in nominal operation or under jamming. Against a displaced meaconer it lowers attack-window horizontal error relative to the baseline at both grades and to the undefended filter at the MEMS grade, and it cuts median clock error about eight-fold (634 versus 5220 ns). Trust cycling stayed at or below 29 cycles per hour (proven bound: 223), and a four-hour mission showed no drift. The evaluation also characterises where GNSS exclusion does not pay: for small-offset spoofs an inertial coast drifts further than the spoof displaces, and the re-admission dwell dominates post-attack error. The CAI and federated learning showed no measurable effect in this configuration (hypotheses H2–H4 not supported).

Contents

Abstract **i**

1 Introduction **1**

1.1 Motivation 1

1.2 Problem statement and gap 1

1.3 Objectives 1

1.4 Contributions 2

1.5 Report organisation 2

2 Related Work **3**

2.1 Federated learning for GNSS security 3

2.2 Adaptive and fault-tolerant sensor fusion and trust 3

2.3 Quantum inertial sensing for navigation 3

2.4 Quantum federated learning (distinguished from quantum sensing) 4

2.5 GNSS spoofing and jamming signatures 4

2.6 Comparison 4

3 Methodology **4**

3.1 System and threat model 5

3.2 Sensor models 6

3.3 Fusion filter 7

3.4 Learned detector 8

3.5 Trust engine 9

3.6 Federated learning 11

3.7 Evaluation protocol 12

4 Experimental Results **14**

4.1 Setup 14

4.2 Confirmatory family 14

4.3 Safety principle 15

4.4 Headline comparison 15

4.5 Illustrative single-seed demonstration 17

4.6 Trust chattering and long-duration stability 17

4.7 Quantum aiding: a null result 18

4.8 Fleet experiments and federated learning: a null result 18
4.9 Other scenarios 18
4.10 Discussion 19

5 Conclusions **20**
5.1 Summary 20
5.2 Limitations 20
5.3 Future work 21

References **25**

1 Introduction

1.1 Motivation

Positioning, navigation and timing (PNT) for autonomous vehicles and UAVs depends heavily on GNSS, a signal that is inexpensive to spoof or jam and whose loss or manipulation directly threatens safety. In plain terms, a spoofer broadcasts a fake satellite signal so that the receiver believes it is somewhere else, or at another time; a jammer drowns the real signal in noise. A vehicle that trusts GNSS blindly follows the fake signal, while a vehicle that distrusts it too readily must navigate on inertial sensors alone, whose error grows with time.

A wide literature addresses parts of this problem: federated learning has been used to detect GNSS spoofing across a fleet without centralizing raw sensor data [23, 7, 26, 30, 46]; classical and learned adaptive filters re-weight or exclude GNSS when it disagrees with inertial propagation [28, 5, 6, 38, 33, 31]; and cold-atom interferometers (CAIs) have been proposed and increasingly demonstrated as inertial sensors whose bias is orders of magnitude below that of classical accelerometers [44, 11]. Separately, quantum-enhanced and quantum federated learning have been studied as a way to speed up or secure the *learning computation* itself [15, 8, 9]. To date, however, these threads have not been combined: no verified prior work couples (a) a physical quantum inertial sensor, (b) fleet-wide federated learning of an attack detector, and (c) a continuous, attack-adaptive trust law that keeps this detector's output as a smoothly varying confidence rather than a switch.

1.2 Problem statement and gap

No verified reference in our bibliography (Section 2, Table 1) implements federated learning together with a physical quantum inertial sensor, and among the FL-based GNSS-defense papers we could verify, all use a binary detect-and-exclude action rather than a continuously varying trust weight. Conversely, the continuous/adaptive-trust literature either has no federated learning component or, when described as "federated", uses the classical multi-sensor "federated filter" sense of the term (master/local filter fusion within one platform) [31]. The specific, scoped gap addressed is therefore: *a closed loop in which an FL-trained, fleet-shared spoofing/jamming detector drives a continuous, evidence-bounded, per-sensor trust weight that gates a quantum-aided navigation filter, with the quantum sensor's own noise and fault behaviour calibrated to real laboratory data rather than assumed.*

1.3 Objectives

The project has four objectives, each stated as a falsifiable hypothesis before any test result was seen (Section 3.7):

- H1: continuous trust improves on a binary detect-and-exclude baseline (Baseline A) in attack-window position error and detection latency;
- H2: fleet-shared learning improves on single-node learning for an attack family the node has not experienced;
- H3: quantum aiding improves detection latency for gradual spoofing;
- H4: fleet-shared learning improves detection by a cold-start node.

1.4 Contributions

- A system architecture in which a single 15-state loosely-coupled error-state Kalman filter is shared, unmodified, across every baseline and ablation, so that comparisons isolate the contribution of each mechanism rather than confounding it with implementation differences (Section 3).

- A continuous, asymmetric trust law with evidence-bounded exclusion (a bounded distrust time, a shadow probe that tests returning GNSS against the coasting state without applying it, and separate position and clock trust weights) that couples a learned, federated detector to the measurement covariances via a bounded inflation $R_{\text{eff}} = R/\max(w, w_{\min})$, with trust cycling bounded at 223 cycles per hour independently of the timing of the evidence.

- TRIM-NB-R, a trust-aware robust federated aggregator combining norm clipping, coordinate-wise trimmed-mean/median aggregation, and a cosine-similarity reputation score with quarantine; the round-3 evaluation does not include an AUC-based poisoning comparison, so its robustness benefit is specified but not evaluated here.

- A quantum inertial sensor model whose noise density, per-interrogation-time noise scaling and bursty fault process are calibrated from real cold-atom interferometer shot data [11], together with an explicitly reported operating limit (rigid-mode contrast loss above $\Omega_c \approx 17\,\text{mrad/s}$).

- A pre-registered, mechanism-class baseline taxonomy (A: FL detect-and-exclude; B-bin: single-node detect-and-switch; B-cont: single-node continuous trust; B′: classical innovation-based adaptive filter) and four hypotheses H1–H4, reported whatever their outcome.

1.5 Report organisation

Section 2 surveys related work. Section 3 gives the threat model, sensor models, fusion filter, detector, trust engine, federated learning and the evaluation protocol. Section 4 reports the experimental results. Section 5 concludes with limitations and future work.

2 Related Work

2.1 Federated learning for GNSS security

Several recent papers apply federated learning to GNSS spoofing or jamming detection so that a fleet of vehicles can share a detector without centralizing raw trajectory data. Khan et al. [23] have each vehicle localize itself from dead-reckoning-style signals, compare this against GNSS, and aggregate the resulting mismatch-based weights at a roadside unit, where a global support-vector machine is trained by FL; they report 99% accuracy on CARLA-simulated trajectories. Chai et al. [7] similarly use federated learning to identify spoofing and jamming signals for UAVs, and Namagembe et al. [30] propose a machine-learning GPS spoofing detection and mitigation scheme for UAVs. Zhou et al. [46] propose spatial-temporal federated transfer learning for cooperative positioning, which targets accuracy under heterogeneous data rather than adversarial spoofing. Closest to our robust-aggregation component is G^{2}FL [26], a robust FL scheme for GNSS spoofing detection under Byzantine or poisoned clients. In every one of these papers the FL-trained detector's output drives a *binary* decision at the node; none couples the detector to a continuously varying trust weight on the fusion filter's measurement covariance, and none uses a physical quantum sensor.

2.2 Adaptive and fault-tolerant sensor fusion and trust

Re-weighting or excluding a sensor based on its own innovation statistics predates federated learning by decades. Mehra [28] introduced innovation-based adaptive estimation for Kalman filters, the basis of our B′ baseline. Carlson's federated filter [5, 6] decomposes a navigation filter into local filters per sensor feeding a master filter; this is the classical, single-platform sense of "federated". Ren et al. [38] demonstrate adaptive fusion of camera, GNSS and IMU for autonomous driving, which we use as the representative of the single-node continuous-weighting class (B-cont). Pardhasaradhi and Cenkeramaddi [33] detect GPS spoofing on a drone via distributed radar tracking and switch to the radar track once spoofing is flagged, the representative of our detect-and-switch class (B-bin). Negru et al. [31] integrate GNSS, IMU, camera and barometer with local extended Kalman filters feeding a gated-recurrent-unit master filter; despite the word "federated" in its title, this is the Carlson-style federated *filter* inside a single UAV, not federated learning across clients. A companion paper [32] studies UWB-aided navigation in degraded GNSS. None of this group's mechanisms is trained or shared across a fleet, and none uses a physical quantum sensor.

2.3 Quantum inertial sensing for navigation

Cold-atom interferometers measure acceleration or rotation via atom-interferometric phase, giving an absolute output whose bias is set by atomic constants rather than by the drift of a mechanical proof mass. Wright et al. [44] review cold-atom inertial sensors for naviga-

tion, including dead time, dynamic range and size/weight/power challenges on a moving platform. d'Armagnac de Castanet et al. [11] report a three-axis hybrid cold-^{87}Rb atom interferometer operated at arbitrary orientations and rotation rates, providing per-shot population-ratio residuals at several interrogation times and a measured contrast-versus-rotation-rate law. We use this dataset [12] directly to calibrate our simulated CAI's noise density, its per-interrogation-time scaling and a Gilbert–Elliott bursty-outlier channel. Neither work addresses fleet-wide learning or GNSS attack robustness.

2.4 Quantum federated learning (distinguished from quantum sensing)

A separate line of work applies quantum *computation* to the federated learning process itself. Hazarika et al. [15] propose quantum-enhanced FL for vehicular networks; Chehimi et al. [8, 9] lay architectural foundations for quantum FL over quantum networks, including quantum data. These address the learning substrate and communication channel, not inertial or positioning sensors, and none targets GNSS spoofing or jamming. We cite them to pre-empt a mistaken reading of "quantum federated learning for navigation" as prior work equivalent to ours.

2.5 GNSS spoofing and jamming signatures

Psiaki and Humphreys [34] survey spoofing mechanisms and detection, including capture-and-carry-off dynamics and the vulnerability of a receiver at re-acquisition after an outage; Humphreys et al. [19] assess the practical threat. Radoš et al. [37] report field-measured signatures we rely on, including the collapse of cross-satellite C/N0 correlation under single-antenna spoofing (from -0.76 clean to 0.99 spoofed). Borhani-Darian et al. [3] classify spoofing from the cross-ambiguity function, a lower, pre-tracking level than our raw-observable level, and Tariq and Ahanger [41] fuse Kalman filtering with ensemble and transformer models for BeiDou spoofing across a UAV swarm (about 99% detection accuracy reported; the often-quoted 97% figure is a mission-success rate). Together these motivate our attack simulator and detector feature set.

2.6 Comparison

Table 1 positions FedQPNT against the verified related systems on the four properties it combines.

3 Methodology

This section condenses the specification of the reference simulator. Parameters are tagged by provenance: *measured* (fitted to the real cold-atom data of [11]), *datasheet*, or *assumed*

Table 1: Comparison of related systems. "FL?" = detector trained/aggregated across distributed clients (not the single-platform "federated filter"). "Quantum?" = physical quantum sensor (not quantum-enhanced computation). "Adaptive trust?" = continuously varying, not binary, trust during an attack. "Attack-tested?" = evaluated under an explicit attack scenario in the cited paper.

System / paper	FL?	Physical quantum sensor?	Adaptive (continuous) trust?	Attack-tested?
Khan et al. 2025 [23]	Yes	No	Not stated (detection only)	Yes (spoofing)
Chai et al. 2025 [7]	Yes	No	No (classification only)	Yes (spoofing/jamming)
G^{2}FL, Liu et al. 2026 [26]	Yes (robust)	No	No	Yes (spoofing, Byzantine)
Negru et al. 2024 [31]	No (federated *filter*)	No	Continuous (GRU master filter)	No (degraded GNSS)
Pardhasaradhi & Cenkeramaddi 2022 [33]	No	No	No (detect-and-switch)	Yes (spoofing)
Hazarika et al. 2025 [15]	Yes	No (quantum compute)	No	No
Chehimi et al. 2023 [8]	Yes (quantum FL)	No	No	No
Tariq & Ahanger 2026 [41]	No (multi-model fusion)	No	Partial (ensembling)	Yes (BeiDou spoofing)
FedQPNT (this work)	**Yes**	**Yes (real-data-calibrated)**	**Yes (continuous, evidence-bounded exclusion)**	**Yes (15-scenario matrix)**

(a design value that is swept or stress-tested rather than claimed).

3.1 System and threat model

The system is a fleet of N independent nodes (ground vehicles or UAVs) running the same code. Every node is split into an *Environment* half (ground-truth trajectory, sensor models, GNSS signal generation and attacks) and an *Agent* half (GNSS receiver, fusion filter, trust engine, learnable detector and FL client). Only sensor outputs cross from Environment to Agent; ground truth and the per-tick attack label never do, enforced by construction and by an automated static-analysis guard. A node runs a 100 Hz global tick. Nodes exchange only federated-learning model updates with a server on a fixed round schedule; navigation never blocks on a fresh global model, so a node that has lost communications keeps navigating with its last detector.

The attacker acts only on the GNSS signal, at the raw-observable level (per-satellite pseudorange, pseudorange rate, C/N0, lock state, AGC), never on the IMU, the quantum sensor or the inter-node channel. Five attack families are modelled: (i) gradual ("drift-in") spoofing, in which a single-antenna spoofer captures the tracking loops and drags

the measurements toward a fake trajectory; (ii) meaconing (record-and-rebroadcast), a common-mode clock/delay shift across all satellites; (iii) abrupt spoofing, which forces a loss of lock and a position jump on re-lock; (iv) continuous-wave and wideband jamming; and (v) combined jam-then-spoof, the classic window in which a receiver is most vulnerable [34]. The single-antenna signature (common-mode C/N0 fluctuation, loss of elevation dependence) follows field statistics [37]. In the FL threat surface a fraction f of nodes may be Byzantine (sign-flip, Gaussian, label-flip or "A Little Is Enough" updates); the self-reported sample count is untrusted.

No raw sensor stream, trajectory or attack label ever leaves a node. The only object sent to the server is a `ModelUpdate`: a detector weight delta (1010 parameters, about 4 kB), feature-normalisation statistics and scalar training metrics. Trust-law hyperparameters and the filter are fixed, identical across all compared methods, and tuned once on disjoint tuning seeds before any test result was examined.

3.2 Sensor models

Classical IMU. Each axis follows an IEEE Std 952-style error budget [20]: constant turn-on bias, a first-order Gauss–Markov bias-instability process, white noise, scale-factor and misalignment errors, quantisation and saturation (GM1 standard deviation $\sigma_{\mathrm{GM}} = B/0.664$ [21]). Two grades are reported separately (Table 2), following ADIS16470-class and HG1700-class parts [1, 18].

Table 2: IMU grades. "D" = datasheet figure, "A" = assumed. Both run at 100 Hz.

Parameter	Industrial MEMS	Tactical
Gyro in-run bias stability	8°/h (D)	1°/h (D)
Gyro angular random walk	$0.34^\circ/\sqrt{\mathrm{h}}$ (D)	$0.125^\circ/\sqrt{\mathrm{h}}$ (D)
Accel in-run bias stability	$13\,\mu$g (D)	$30\,\mu$g (A)
Accel white-noise density	$25\,\mu\mathrm{g}/\sqrt{\mathrm{Hz}}$ (A)	$15\,\mu\mathrm{g}/\sqrt{\mathrm{Hz}}$ (A)
Bias correlation time τ_c	200 s (A)	300 s (A)
Accel turn-on bias	10 mg (A)	2 mg (A)
Gyro turn-on bias	0.1°/s (A)	0.01°/s (A)
Scale factor / misalignment	500 ppm / 0.3 mrad (A)	100 ppm / 0.1 mrad (A)

GNSS receiver. A synthetic Walker-like GPS almanac with a 10° elevation mask gives eight to nine visible satellites. Per satellite the simulator generates pseudorange, pseudorange rate, C/N0 (38 to 48 dB Hz from low elevation to zenith, assumed) and AGC. The pseudorange error combines code thermal noise, a Gauss–Markov ionospheric residual, tropospheric delay and multipath [22]. A position/velocity/clock fix is solved by weighted least squares [29] followed by a snapshot residual-based RAIM statistic [35], at 1 Hz by default.

Cold-atom accelerometer (CAI). The CAI is a Mach–Zehnder light-pulse interferometer with phase $\phi = k_{\mathrm{eff}}\, a\, T^2$, $k_{\mathrm{eff}} = 1.61 \times 10^7$ rad/m for ^{87}Rb. The fringe is observed

modulo 2π, so the model resolves the fringe order with a classical companion accelerometer as in hybrid matter-wave/classical sensors [10, 42, 44]. The primary (FIELD) grade is anchored to real shot data [11, 12] through four fitted elements (Table 3): a robust per-shot noise $\sigma_{\text{shot}} = 5.60\,\mu g$ at $2T = 20\,\text{ms}$ (bootstrap 95% CI $[5.04, 6.40]\,\mu g$, $n = 491$ shots), interpolated across interrogation times and deliberately not scaled as $1/T^2$; a two-state Gilbert–Elliott bursty-outlier channel with 9.0% outlier probability and 65.9% persistence (7.4× more adjacency than independence); a contrast loss $C = C_0 \exp(-(\Omega_\perp/\Omega_c)^2)$ with $C_0 = 0.394$, $\Omega_c = 48.2\,\text{mrad/s}$ at $2T = 12\,\text{ms}$, scaled as $1/T^2$ to $17.3\,\text{mrad/s}$ at $T = 10\,\text{ms}$ (physics-derived, unverified away from the measured point); and a cycle time of 1.548 s. The sample is *not* flagged invalid during an outlier burst: the sensor is silently wrong, as a real instrument would be, so the trust engine, not a validity flag, must catch it.

Table 3: CAI FIELD-grade parameters. M = measured from [11, 12], A = assumed.

Quantity	Value	Basis
Interrogation time $2T$	20 ms	M
Cycle time	1.548 s	M
Shot noise σ_{shot}	$5.60\,\mu$g	M
Outlier rate / persistence	9.0% / 65.9%	M
Contrast C_0, Ω_c (T=6 ms)	0.394, 48.2 mrad/s	M
Ω_c at T=10 ms	17.3 mrad/s	$1/T^2$ scaling
Contrast threshold; range	0.08; $2g$	A
Slow bias residual (GM1)	$3\,\mu$g, τ_c=300 s	A

3.3 Fusion filter

All methods share one loosely coupled 15-state error-state extended Kalman filter (ESKF) with error state $\delta x = [\delta p,\ \delta v,\ \psi,\ \delta b_a,\ \delta b_g] \in \mathbb{R}^{15}$ [39]. Process noise follows the IMU configuration. The initial roll/pitch uncertainty is

$$\sigma_{\text{tilt}} = \max\Big(1\,\text{mrad},\ \sigma_{b_a,0}/g\Big), \tag{1}$$

since an accelerometer turn-on bias tilts the levelling by about $\sigma_{b_a,0}/g$. The covariance propagation also carries the second moment of the neglected second-order attitude term $d_2 = \frac{1}{2}\,\psi \times (\psi \times f_n)$, a one-signed vertical velocity error growing with tilt squared; without it the coast covariance is over-confident and returning GNSS is never re-admitted. The term has no tuning constant and is part of the shared core.

GNSS update. The fix enters as a six-dimensional position/velocity update with

$$R_{\text{g}} = \kappa_R\,\text{blkdiag}\Big(\Sigma_p^{\text{fix}},\ \Sigma_v^{\text{fix}}\Big), \qquad \kappa_R = 60, \tag{2}$$

where κ_R compensates the time-correlated error (ionosphere, troposphere, multipath) that a loosely coupled fix treats as white. It is set once on tuning seeds, identically for every method, so that nominal horizontal ANEES is close to one.

CAI update. The CAI enters as a direct observation of the classical accelerometer bias: over the sample's response window the innovation $\nu_{\mathrm{q}} = \bar{f}_{\mathrm{Q}} - \bar{f}_{\mathrm{IMU}} \approx \delta b_a + (\text{CAI noise})$, in which gravity, attitude and trajectory cancel, with

$$R_{\mathrm{q}} = \mathrm{diag}(\sigma^2_{\mathrm{shot}}) + \frac{\mathrm{VRW}^2}{T_W} I + \sigma^2_{\mathrm{win}} I, \qquad \sigma_{\mathrm{win}} = 10^{-5} g \text{ (assumed)}. \tag{3}$$

Trust coupling and gating. For a sensor s with trust weight $w_s \in [w_{\min}, 1]$, trust enters only through the effective covariance and an exclusion rule,

$$R_{\mathrm{eff},s} = \frac{R_s}{\max(w_s,\, w_{\min})}, \qquad \text{skip the update if } w_s < w_{\mathrm{excl}}, \tag{4}$$

with $w_{\min} = 0.02$, $w_{\mathrm{excl}} = 0.05$ (assumed). A χ^2 gate at level 10^{-4} is part of the shared core and is applied *softly*: an update whose normalised innovation squared exceeds the gate has its covariance scaled so its effective NIS equals the gate (a Huber-type robust update), because a hard gate drops a slowly dragged fix once it leaves the χ^2 region, after which inertial coasting diverges. Only the deliberately gate-free "undefended" reference lacks the gate.

Clock filter. Timing is estimated by a standalone two-state Kalman filter on clock bias and drift, with TCXO oscillator spectral densities $q_b = \frac{1}{2} c^2 h_0 \approx 9.0 \times 10^{-3}\,\mathrm{m}^2/\mathrm{s}$ and $q_d = 2\pi^2 c^2 h_{-2} \approx 3.6 \times 10^{-2}\,(\mathrm{m/s})^2/\mathrm{s}$ [4, 24, 36]. The filter is aided by the fix's clock estimates, with trust applied as in Eq. (4) through a separate clock weight w_{clk}; below w_{excl} it holds over on the oscillator model. The simulated truth clock uses the same TCXO values, so the timing results are model-consistent by construction.

3.4 Learned detector

At each GNSS epoch a causal extractor produces a 15-dimensional feature vector from the fix and the filter's *nominal-R* pre-correction innovations (so a feature cannot depend on its own trust output): position and velocity NIS per degree of freedom, the RAIM statistic, mean C/N0 and its cross-satellite spread, C/N0 rate, AGC, clock-bias and clock-drift jumps against a constant-drift prediction, WLS residual rms, change in satellite count, a Page CUSUM, an outage indicator, the mean pairwise C/N0 correlation over a 20-epoch window and the slope of C/N0 on elevation. The last two encode the single-antenna signature [37]. The vector is normalised and expanded to a 60-dimensional input with short and long exponential moving averages and a difference term.

The detector is a multilayer perceptron $60 \to 16\,(\tanh) \to 2\,(\mathrm{sigmoid})$ with a spoofing head and a jamming head (1010 parameters), Platt-calibrated on held-out tuning missions so that the trust engine consumes calibrated probabilities [14]; the output is $p = \max(p_{\mathrm{spoof}}, p_{\mathrm{jam}})$. Training is supervised with ground-truth labels joined to the feature stream offline, outside the agent's import graph, the same supervision used by the FL

detectors we compare against [23, 7]; no label reaches a node at deployment. The training mix covers six attack families plus clean missions. The detector used for the primary results (v5) was retrained after the covariance corrections changed three features.

3.5 Trust engine

The trust engine turns the calibrated probability p and a set of physical evidence into continuous per-sensor weights: a position weight w_{pos} (GNSS position/velocity update), a clock weight w_{clk}, a quantum weight and an IMU weight. The law described here is the one frozen at git tag `core-freeze-6`; it was revised several times on tuning seeds before the freeze, and each revision is a disclosed design iteration made before any test-seed run.

Smoothing, target and ramp. The probability is smoothed and mapped to a target weight,

$$\bar{p}_j = \bar{p}_{j-1} + \beta_j(p_j - \bar{p}_{j-1}), \qquad \beta_j = 1 - e^{-\Delta t_j/\tau_p},\ \tau_p = 0.5\,\mathrm{s}, \tag{5}$$

$$w_j^\star = w_{\min} + (1 - w_{\min})\,\mathrm{clip}\Big(\frac{\theta_{\mathrm{hi}} - \bar{p}_j}{\theta_{\mathrm{hi}} - \theta_{\mathrm{lo}}}, 0, 1\Big), \qquad \theta_{\mathrm{lo}} = 0.2,\ \theta_{\mathrm{hi}} = 0.8, \tag{6}$$

and a hysteretic detection flag D is set when $\bar{p} \geq 0.6$ holds for 0.5 s and cleared when $\bar{p} \leq 0.3$ holds for 5 s. The weight falls fast and rises slowly,

$$w \leftarrow w + \Big(1 - e^{-\Delta t/\tau}\Big)(w^\star - w), \qquad \tau = \begin{cases} \tau_d = 0.5\,\mathrm{s} & w^\star < w, \\ \tau_r = 10\,\mathrm{s}, \text{ only if the recovery gate is open} & w^\star > w, \end{cases} \tag{7}$$

where the gate requires $D = 0$, a clean dwell of 10 s and consistent position innovations. A first fix after an outage longer than 5 s is capped at $w = 0.5$ unless it is consistent with the coasting state.

Bounded exclusion: TRUST, DISTRUST and PROBE. A recursion alone has no bound on time spent excluded: a chronically mis-firing detector could pin the weight at its floor and let free-inertial error grow without limit. Each law instance is therefore a three-state machine (Table 4). Because DISTRUST can only be left through PROBE, successive entries into DISTRUST are separated by at least 70 s by construction. From the ramp time constant and the 0.5 and 0.9 crossings every trust cycle lasts at least $L = 16.094$ s, so

$$N_{\mathrm{cyc}} \leq \lfloor 3600/16.094 \rfloor = 223 \text{ per hour}, \tag{8}$$

without any assumption on the timing of the evidence (133 per hour on a regular 1 Hz grid).

Physical spoof evidence. A set of rule-based signatures independent of the learned detector complements it: (i) a position jump test comparing the change of the GNSS fix

Table 4: The three trust states.

State	What happens	Exit
TRUST	Weight follows Eq. (7); GNSS is used, down-weighted by R_{eff}.	Detection flag D set $\rightarrow$ DISTRUST.
DISTRUST	Weight driven toward the floor; GNSS excluded, filter coasts on inertial and CAI.	After $T_{\text{ex}} = 60\,\text{s} \rightarrow$ PROBE (the only exit).
PROBE	Duration 10 s; reported weight 0.3; fixes are evaluated in shadow but *not* applied.	Pass (probe statistic within bound and no physical spoof evidence) $\rightarrow$ TRUST, with the learned detector suppressed for 120 s; otherwise back to DISTRUST for another 60 s.

over one epoch with the change of the filter's own pre-correction estimate,

$$d_k^\top \left(\Sigma_{p,k} + \Sigma_{p,k-1} + \sigma_{\text{ins}}^2 I_3\right)^{-1} d_k > \chi^2_{3,0.999} \approx 16.27, \qquad \sigma_{\text{ins}} = 0.05\,\text{m}; \tag{9}$$

(ii) a clock jump normalised by the *predicted* innovation standard deviation over the gap (so ordinary oscillator holdover after an outage is not a false alarm); (iii) cross-satellite C/N0 correlation; and (iv) a C/N0 bump signature of a meaconing power advantage.

Shadow probe. During PROBE the filter evaluates each returning fix against the coasting state but applies no GNSS update, so a persisting spoof cannot pull the state while the decision is taken (a probe that applied fixes at partial trust was found on tuning data to drag the state onto a persisting spoof). With the coasting covariance P^- and the receiver's reported covariance,

$$\text{NIS}_s = \nu_s^\top \left(H P^- H^\top + \text{blkdiag}(\Sigma_p^{\text{fix}}, \Sigma_v^{\text{fix}})\right)^{-1} \nu_s, \tag{10}$$

approximately χ^2_6 under nominal conditions. The probe is accepted when the mean NIS stays below a per-grade bound (default $\chi^2_{6,0.99} = 16.81$; pre-registered replacement by the clean 99th percentile gives 25.07 at the MEMS grade and 6.74 at the tactical grade, calibrated on clean tuning data only) and the C/N0 signatures were silent.

Position/clock trust split. A single GNSS weight forced a co-located meaconer, which appears as a clock-bias jump with an undisturbed position innovation, to cost the position solution its updates as well. The frozen engine therefore runs two independent instances of the three-state law (Table 5): the position law drives w_{pos} and the clock law drives w_{clk}. The learned detector and the single-antenna signatures drive both laws; the position jump only the position law; the clock jump only the clock law.

Table 5: Routing of evidence to the position and clock laws (x_8, x_9: normalised clock jumps).

Item	Position law	Clock law
Position jump, Eq. (9)	drives	—
Clock jump, $x_8, x_9 \geq 5$	—	drives
C/N0 cross-satellite and bump events	drives	drives
Detector output p	drives	drives
Probe statistic	mean $\mathrm{NIS}_s \leq \bar{\nu}_{\mathrm{grade}}$	mean $x_8^2 + x_9^2 \leq \chi^2_{2,0.99}$
Reacquisition cap	waived if consistent	always kept

Quantum and inertial trust. The quantum weight is rule-based: its evidence combines the fringe contrast, a NIS consistency test on the CAI innovation and a two-sided Page CUSUM, so a silently wrong CAI sample is down-weighted by the same covariance-inflation mechanism. The IMU weight is the floor when a sample is missing or saturated and one otherwise.

3.6 Federated learning

The only trained object is the detector. Rounds are bulk-synchronous with period 60 s; a live node trains for 2 epochs (SGD, learning rate 0.05, batch 64) on a replay buffer of oracle-labelled samples and uploads its weight delta, normalisation statistics and scalar metrics (a leakage guard rejects anything else). Communications are simulated with a log-normal delay (median 0.2 s), a 1 Mbit/s serialisation term and a Gilbert–Elliott loss channel. A node installs a received global model at its next GNSS epoch and its trust state is never reset by a model swap.

FedAvg [27] aggregates with weights $n_i(1 + s_i)^{-1/2}$ (n_i self-reported sample count, s_i staleness; updates staler than 3 rounds are discarded, and a round is skipped unless at least half the live nodes report). TRIM-NB-R combines norm clipping [40] with a coordinate-wise trimmed mean [45]:

$$\tilde{\Delta}_i = \Delta_i \min\Big(1,\ \frac{c \cdot \mathrm{median}_j \|\Delta_j\|}{\|\Delta_i\|}\Big), \qquad c = 2, \tag{11}$$

$$\Delta = \begin{cases} \mathrm{TrimMean}_{\beta=0.2}\Big(\{(1+s_i)^{-1/2}\tilde{\Delta}_i\}\Big) & N_{\mathrm{live}} \geq 5 \\ \mathrm{Median}\Big(\{(1+s_i)^{-1/2}\tilde{\Delta}_i\}\Big) & N_{\mathrm{live}} < 5, \end{cases} \tag{12}$$

$$r_i \leftarrow \rho r_i + (1-\rho)\max\Big(0, \cos(\tilde{\Delta}_i, \Delta)\Big), \qquad \rho = 0.8, \tag{13}$$

$$\theta_g \leftarrow \theta_g + \Delta. \tag{14}$$

A node whose reputation stays below 0.2 for three consecutive rounds is quarantined for ten rounds. The sample count never enters the robust aggregator, since it is exactly what a poisoning node can misreport. FedProx [25] is implemented but, with the frozen $\mu = 0$, coincides with FedAvg and is not evaluated. Simulated poisoning includes sign flip, Gaussian noise, label flip and "A Little Is Enough" [2].

Every FL method and the local-only baselines start from the same θ_0, pretrained on a disjoint seed range with a restricted family set that excludes the abrupt-spoof family used as the "novel" family in H2 and H4, so that the family is unseen by θ_0 and by the target node but present in its peers' data. Before any H2 or H4 run an FL sanity check requires FedAvg and TRIM-NB-R on IID nodes to reach at least 0.95× the AUC of a centrally trained detector.

3.7 Evaluation protocol

Scenarios. Fifteen scenarios (seventeen registry entries) exercise the system along axes independent of the hypotheses (Table 6). All use the FIELD-grade CAI and a ground vehicle unless stated. S2-DM, a displaced meaconer (a common-mode delay with position displacement up to 500 m), is held out of detector training; S6-coast is an exploratory 180 s forced-outage test of the CAI's coasting contribution.

Table 6: Scenario matrix (attack severity; onset and duration in seconds).

ID	Scenario	Nodes	Dur. (s)	Attack
S1	Nominal	1	600	none
S2	Gradual spoofing, low/medium/high	1	600	drift; 0.3/0.6/0.9; 60; 300
S2-DM	Displaced meaconer	1	600	up to 500 m; 0.6; 60; 300
S3	Sudden jamming	1	300	wideband; 1.0; 60; 60
S4	Jam-then-spoof at reacquisition	1	400	jam 60–100 s, then drift 0.6
S5	Node failure / delayed FL updates	10	600	none (30% failure)
S6	Long CAI bias drift	1	14 400	drift; 0.05; 600; open
S6-coast	CAI coasting envelope	1	–	forced outage 180 s
S7	Trust chattering	1	3600	drift toggled, period 2–60 s
S8	Cold-start node at $T/2$	5	600	drift; 0.6; 330; 120
S9	Communication dropouts	5	600	none (loss sweep)
S10	Sample-rate mismatch	1	300	none
S11	Extreme noise (filter not told)	1	300	abrupt; 1.0; 60; 60
S12	Model poisoning (f=20%, 40%)	10	600	none (poisoning)
S13	Recovery after attack	1	300	abrupt; 0.8; 60; 60
S14	Multi-hour stability	1	14 400	none
S15	Attack on 30% of fleet	10	600	drift; 0.6; 60; 300

Methods and baselines. Baselines are *mechanism classes*, not re-implementations of specific papers, each defined by a configuration difference over one shared code path (same sensors, paired noise realisations, filter with soft gate, features, detector architecture, θ_0 and tuning budget) (Table 7). B-cont is the strongest single-node competitor (the FedQPNT law with a local-only detector) and isolates the federation contribution exactly.

Hypotheses and metrics. H1–H4 are as in Section 1.3. The pre-registered primary metrics are attack-window horizontal RMSE, $\mathrm{RMSE}_h(P_{\mathrm{att}})$, and onset detection latency; all others are exploratory. With $e_h(t) = \|\hat{p}_{EN}(t) - p_{EN}(t)\|_2$, $\mathrm{RMSE}_h(P) = \sqrt{\mathrm{mean}_{t\in P}\, e_h^2}$ over the attack window P_{att} or the post-attack window. Detection latency is the time from onset until the trust alarm holds for 1 s (misses are censored). Clock error RMSE_t

Table 7: Methods. FL = federated detector, Local = single node from the same θ_0.

Method	Detector	Trust action	Aggregator
FedQPNT	FL	continuous three-state law	TRIM-NB-R
A [23, 7]	FL	w=1 if p<0.5 else 0 (memoryless)	TRIM-NB-R
B-bin [33]	Local	detect, exclude, coast until recovery gate passes	—
B-cont [38]	Local	the FedQPNT law	—
B′ [28]	—	earlier continuous law, innovation-based, no probe	—
−quantum	FL	continuous law, CAI off	TRIM-NB-R
Fixed trust	FL	$w \equiv 1$, gate on	TRIM-NB-R
Undefended	FL	$w \equiv 1$, *gate off*	TRIM-NB-R

is reported in nanoseconds, since meaconing is chiefly a timing attack. Trust behaviour is summarised by the number of trust cycles per hour and the alarm fraction.

Safety principle. A defended method must never be substantially worse than the undefended reference, pre-registered as

$$\mathrm{RMSE}_h^{\mathrm{def}}(P_{\mathrm{att}}) \le \mathrm{RMSE}_h^{\mathrm{undef}}(P_{\mathrm{att}}) + 3\sigma_{\mathrm{nom}}, \tag{15}$$

where σ_{nom} is the across-seed standard deviation of the undefended method's nominal horizontal error (a noise floor). Failures are reported as measured and are not tuned away.

Statistics and seed protocol. Each scenario–method cell uses 30 test seeds, paired across methods by seed-indexed random streams so that sensor and attack noise are identical between methods. The primary test is the two-sided Wilcoxon signed-rank test on paired differences [43]; effect sizes are Hodges–Lehmann (HL) medians of paired differences [16] with 95% BCa bootstrap intervals [13]. Holm–Bonferroni [17] controls the family-wise error over a confirmatory family of eight tests with fixed $m = 8$: H1 (position error and latency vs. Baseline A), H2 and H4 (detection probability and onset latency vs. B-cont), and H3 (latency with and without the CAI, both grades). Seed ranges are disjoint by purpose and fixed in advance: pretraining 400–449, tuning 500–599 (detector training, Platt calibration, held-out checks), and test seeds 10060–10089 (and 10090–10099 for the H2/H4 fleet experiment), each used once behind a gate that refuses test seeds unless the code tree is clean and frozen. The core for the primary results is tag `core-freeze-6`.

Two earlier test rounds on disjoint seeds exposed implementation defects (coast-covariance consistency, federated staleness bookkeeping, normaliser estimation) and informed which defects were investigated; these were corrected on tuning data only, and the results reported here are from a fresh, pre-registered round on unused seeds.

4 Experimental Results

4.1 Setup

All results come from a single pre-registered round on the code at tag `core-freeze-6`: test seeds 10060–10089 ($n = 30$ per scenario–method cell; 5,340 of 5,340 runs completed) and, for the H2/H4 fleet experiment, seeds 10090–10099 ($n = 10$). The nominal noise floor of the safety rule is $\sigma_{\text{nom}} = 1.098\,\text{m}$ (industrial MEMS) and $1.117\,\text{m}$ (tactical), so $3\sigma_{\text{nom}} = 3.29$ and $3.35\,\text{m}$. Cells report the median over seeds unless stated. The alarm fraction is the fraction of epochs outside the attack label in which the trust alarm is active, so it includes the post-attack exclusion dwell. In the single-node scenarios the FedQPNT arm uses the frozen supervised detector and no federation rounds (a single node has no peers), so those comparisons test the continuous trust law and the quantum-aided filter; federated learning enters only in the fleet experiments (S5, S8, S9, S12, S15, H2, H4). Verdicts are paired HL differences with 95% BCa intervals; "better"/"worse" means that the interval excludes zero, and these descriptive verdicts are not part of the Holm family. Both IMU grades are always reported.

4.2 Confirmatory family

Table 8 lists the eight pre-registered tests. One rejects after Holm correction: the latency of attack-onset detection (H1, S2-medium, MEMS), where FedQPNT detects the onset a median 0.5 s earlier than Baseline A (raw $p = 4.65 \times 10^{-4}$, Holm $p = 3.72 \times 10^{-3}$; both medians 1 s on a 1 Hz detector clock). The H1 position-error test was *not* significant (raw $p = 0.271$, Holm $p = 1$; HL +85.3 m, 95% CI $[-59.7, 235]$), so H1 is supported on latency only. H2, H3 and H4 are not supported: every paired difference is exactly zero ($p = 1$). In the H2/H4 experiments both arms detect all abrupt-spoof events at the onset epoch (P_D@10 s = 1, latency 0 s, no censored events), and in S6 both CAI arms have identical effective latency at both grades. These primary metrics are therefore at a ceiling or floor and cannot separate the arms.

Table 8: Confirmatory family (paired Wilcoxon, Holm with fixed $m = 8$). HL: paired Hodges–Lehmann difference, FedQPNT − comparator (m for RMSE, s for latency), 95% BCa CI. "Rej.": rejected at the Holm-adjusted 0.05 level.

Hyp.	Metric	Setting	n	raw p	Holm p	HL	95% CI	Rej.
H1	$\text{RMSE}_h(P_{\text{att}})$ vs. A	S2-med, MEMS	30	0.27	1	85.3	[−59.7, 235]	no
H1	$\text{latency}_{\text{on}}$ vs. A	S2-med, MEMS	30	4.65×10^{-4}	3.72×10^{-3}	−0.5	[−1, −1]	yes
H2	P_D@10 s vs. B-cont	abrupt fleet	10	1	1	0	[0, 0]	no
H2	onset latency vs. B-cont	abrupt fleet	10	1	1	0	[0, 0]	no
H3	$\text{latency}_{\text{eff}}$, CAI vs. −CAI	S6, MEMS	30	1	1	0	[0, 0]	no
H3	$\text{latency}_{\text{eff}}$, CAI vs. −CAI	S6, tactical	30	1	1	0	[0, 0]	no
H4	P_D@10 s vs. B-cont	cold-start fleet	10	1	1	0	[0, 0]	no
H4	onset latency vs. B-cont	cold-start fleet	10	1	1	0	[0, 0]	no

4.3 Safety principle

Table 9 gives the outcome of Eq. (15) (mean attack-window maximum horizontal error, defended minus undefended, against the bound $3\sigma_{\text{nom}}$; the S1 row uses the nominal-window maximum). The principle holds in nominal operation (S1) and under jamming (S3) at both grades, and for the displaced meaconer at the MEMS grade (S2-DM margin -60.1 m; the HL CI $[-686, 578]$ includes zero). It fails for the tactical grade on S2-DM (margin 522 m), for every gradual-spoof severity (margins 1.75–2.87 km), for jam-then-spoof (S4, 1.04 and 1.50 km), for the four-hour drift spoof (S6, 47.4 and 6.81 km) and for every chattering variant (S7). These failures are reported as measured and were not tuned away. Recovery after jamming is not slowed: in S3 the median recovery time is 3 s with FedQPNT versus 3 s undefended at the MEMS grade and 0 s versus 1 s at the tactical grade. The signature-strength sweep of the safety protocol was not part of the round-3 test campaign.

Table 9: Safety principle: margin is mean defended minus mean undefended maximum horizontal error (m); bound $3\sigma_{\text{nom}} = 3.29$ m (MEMS), 3.35 m (tactical). p is the S7 toggle period in seconds.

	Industrial MEMS		Tactical	
Scenario	Result	Margin	Result	Margin
S1	PASS	−0.00223	PASS	−0.0196
S2-low	FAIL	2,260	FAIL	2,870
S2-med	FAIL	1,990	FAIL	2,560
S2-high	FAIL	1,750	FAIL	2,230
S2-DM	PASS	−60.1	FAIL	522
S3	PASS	−0.00684	PASS	0.682
S4	FAIL	1,040	FAIL	1,500
S6	FAIL	47,400	FAIL	6,810
S7, p=2	FAIL	29.1	FAIL	10.9
S7, p=5	FAIL	26.1	FAIL	165
S7, p=10	FAIL	122	FAIL	51,200
S7, p=20	FAIL	144	FAIL	15,600
S7, p=60	FAIL	202	FAIL	65,900

4.4 Headline comparison

Tables 10 and 11 compare FedQPNT (FQ) with the undefended filter (UD) and Baseline A (BA). The pattern separates cleanly into scenarios in which FedQPNT costs nothing or helps, and scenarios in which it is worse.

Nominal operation and jamming (S1, S3). FedQPNT is equal to the undefended filter in nominal horizontal error at the MEMS grade (2.91 versus 2.90 m) and marginally better at the tactical grade (HL -0.036 m, CI $[-0.072, -0.006]$); the alarm fraction is 0 in all arms. Its clock error is marginally worse (10.4 versus 10.0 ns). The S1 acceptance criteria pass on horizontal error relative to fixed trust (median ratio 0.997 MEMS, 0.991 tactical; bound 1.05), false alarms (0/h), position ANEES (0.84 and 0.94, band $[0.5, 2]$) and mean GNSS weight (0.975), but the total variation of the GNSS weight (12.5 and

12.6 per hour against a bound of 1) fails. Under jamming (S3) attack-window error is equal to the undefended and Baseline A arms at both grades.

Displaced meaconer (S2-DM). At the MEMS grade the attack-window horizontal error is lower than undefended (median 943 versus 1,340 m; HL −471 m, CI [−743, −202]) and than Baseline A (2,150 m; HL −5,020 m). At the tactical grade it is indistinguishable from undefended and lower than Baseline A (3,010 m). Clock error falls from 5,220 ns undefended to 634 ns (HL −4,570 ns, CI [−5,180, −4,180]), and is also lower than Baseline A (1,220 and 2,230 ns). The cost is paid after the attack: post-attack horizontal error is higher than both comparators (1,310 versus 859 undefended and 268 m Baseline A at the MEMS grade), and the alarm fraction is 0.169 versus 0.021 undefended and 0.0027 Baseline A.

Gradual spoofing (S2). Here FedQPNT is worse than the undefended filter in the attack window at both grades (medium severity, MEMS: 760 versus 254 m; tactical: 973 versus 254 m) and equal to Baseline A at the MEMS grade for all three severities. Post-attack error is much larger than for either comparator (medium, MEMS: 1,120 versus 189 m undefended and 5.69 m Baseline A), and the alarm fraction is 0.164 versus 0. Detection is nevertheless faster than both comparators by 0.5–1 s at all severities and grades.

Jam-then-spoof (S4) and the four-hour drift spoof (S6). In S4 FedQPNT detects the attack at a median 42 s against 61 s for both comparators (HL −19.5 s), but its attack-window error (461 and 638 m) exceeds the undefended filter (137 m) and Baseline A. In S6 the attack-window error is 16,200 m (MEMS) and 2,680 m (tactical) against 438 m undefended, and clock error is 3,790 versus 11.6 ns. Detection is as quick as or quicker than the undefended filter (1 s median), but here detection does not translate into lower error.

Table 10: Horizontal error RMSE_h (m), median over 30 seeds. FQ: FedQPNT; UD: undefended; BA: Baseline A. Verdict (B: FQ better; W: worse; =: CI includes zero) is FQ against UD/BA. The S1 entry is the nominal-window RMSE_h. S6 has no Baseline A arm.

		Attack window				Post-attack			
Scen.	Grade	FQ	UD	BA	vs UD/BA	FQ	UD	BA	vs UD/BA
S1	MEMS	2.91	2.9	2.9	=/=	–	–	–	–
	Tact.	2.9	2.96	2.95	B/B	–	–	–	–
S2-med	MEMS	760	254	623	W/=	1,120	189	5.69	W/W
	Tact.	973	254	569	W/W	1,310	191	5.76	W/W
S2-DM	MEMS	943	1,340	2,150	B/B	1,310	859	268	W/W
	Tact.	1,050	1,340	3,010	=/B	1,420	887	296	W/W
S3	MEMS	14.3	14.4	14.4	=/=	2.58	2.6	2.6	B/B
	Tact.	21.1	21.1	21.1	=/=	2.42	2.43	2.42	B/B
S4	MEMS	461	137	227	W/W	1,430	165	5.45	W/W
	Tact.	638	137	104	W/W	1,790	167	5.31	W/W
S6	MEMS	16,200	438	–	W/–	24,600	268	–	W/–
	Tact.	2,680	438	–	W/–	3,840	268	–	W/–

Table 11: Detection latency (s from onset) and clock error RMSE_t (ns), median over 30 seeds; notation as in Table 10. S1 has no attack, so no latency is defined.

		Detection latency				Clock RMSE_t			
Scen.	Grade	FQ	UD	BA	vs UD/BA	FQ	UD	BA	vs UD/BA
S1	MEMS	–	–	–	–	10.4	10	10	W/W
	Tact.	–	–	–	–	10.4	10	10	W/W
S2-med	MEMS	1	1	1	B/B	743	10.5	412	W/W
	Tact.	1	1	1	B/B	743	10.5	412	W/W
S2-DM	MEMS	1	1	1	=/=	634	5,220	1,220	B/B
	Tact.	1	1	1	=/=	634	5,220	2,230	B/B
S3	MEMS	62	62	62	=/=	29.4	29.3	29.3	W/W
	Tact.	62	62	62	=/=	29.4	29.3	29.3	W/W
S4	MEMS	42	61	61	B/B	748	17.3	231	W/W
	Tact.	42	61	61	B/B	748	17.3	231	W/W
S6	MEMS	1	1	–	B/–	3,790	11.6	–	W/–
	Tact.	1	1	–	B/–	3,790	11.6	–	W/–

4.5 Illustrative single-seed demonstration

Figure 4 shows one live run of the displaced-meaconer scenario (S2-DM, industrial MEMS) on a *tuning* seed (531), with FedQPNT, the undefended filter and Baseline A. It is an illustration of the mechanism, not evidence: it is a single seed, outside the pre-registered test set, and its numbers differ from the 30-seed medians above. In the run the attack begins at 60 s and lasts 300 s. The detector flags the signal within about 2 s and the position trust drops to its floor; the filter then coasts on the inertial and quantum accelerometer. Every roughly 70 s the engine briefly enters PROBE and rejects the still-fake GNSS; after the attack ends one probe passes and GNSS is re-admitted at $t = 411$ s, snapping the error back to about a metre. Attack-window RMSE is 592 m for FedQPNT, 2,371 m undefended and 612 m for Baseline A, and clock RMSE is 1,652, 7,655 and 760 ns respectively. On this seed the simple detect-and-exclude Baseline A is similar to FedQPNT in position and better in clock error; the clear gain is against the undefended receiver, and the re-admission dwell visibly delays the recovery of FedQPNT relative to Baseline A (which recovers at about 360 s).

4.6 Trust chattering and long-duration stability

Across the ten S7 variants (toggle periods 2 to 60 s, both grades) the maximum number of trust cycles per hour observed in any run was 4 for $p \leq 5$ s, 1 for $p = 10$ and 20 s, and 29 (MEMS) and 13 (tactical) for $p = 60$ s, all within the proven bound of 223 per hour (and the 133 per hour regular-grid figure). Bounded chattering does not imply small error: FedQPNT is worse than undefended on attack-window horizontal error in all S7 variants (Table 9), and on the tactical grade rapid toggling accumulates long exclusion; a pure blackout gives the same result.

In the four-hour nominal mission (S14) the median horizontal RMSE of the last hour is 0.786 (MEMS) and 0.840 (tactical) of the first hour (criterion ≤ 1.2), i.e. there is no slow drift; the median RMSE_h is 2.98 m and 2.90 m, the alarm fraction is 0, every run is finite and positive-definite, and the false-alarm rate is 0.067 per hour (criterion ≤ 1).

The registry marks S14 "not evaluable" overall because its covariance-growth leg is not emitted by the runner.

4.7 Quantum aiding: a null result

In the exploratory 180 s forced-outage test the CAI did not reduce the maximum coasting error (Fig. 5). The median ratio of the maximum error without and with the CAI is 1.006 at the MEMS grade (mean maximum error 513.4 m without and 521.4 m with the CAI; HL CI $[-11.7, 20.9]$) and 0.986 at the tactical grade (106.1 versus 104.6 m); the 2.1–3.4× envelope seen on tuning seeds was not reproduced. The confirmatory H3 test shows identical effective detection latency with and without the CAI at both grades (Table 8).

4.8 Fleet experiments and federated learning: a null result

Functional federation. Fleet nodes install the global model: in the abrupt H2 experiment FedQPNT nodes installed it in 9.6 of 10 rounds on average, against 8.0 for B-cont. In S5 (node failures and delayed updates) no run deadlocked or aborted and 5.93 rounds per run were gracefully skipped; in S8 a cold-start node received the global model within two rounds of joining in every run. In S15 (simultaneous attack on 30% of a ten-node fleet) the detection probability over attacked nodes is 1.000, the attacked-node attack-window error is 935 ± 115 m (mean, 95% CI), the false-alarm rate on unattacked nodes is 0 per hour, and no quarantine occurred. The clean-window error and alarm rate in S12 (sign-flip poisoning at $f = 20\%$ and 40%) are identical to the clean-fleet arm (2.79 ± 0.14 m, 0 false alarms per hour). The AUC-based legs of S5, S9 and S12 are undefined because those scenarios contain no attack, so the poisoning robustness of TRIM-NB-R against FedAvg is *not* evaluated in this round.

H2 and H4 (abrupt spoof, $n = 10$). At the pre-registered per-arm threshold both FedQPNT and B-cont detect every event at the onset epoch (P_D@10 s $= 1$, latency 0 s, no censored events), so the paired tests are degenerate. The secondary onset-window AUC is near chance for both arms: H2, 0.505 versus 0.507; H4, 0.526 versus 0.501 (uncorrected paired $p = 0.006$, exploratory, outside the Holm family). Per-seed values range from 0.20 to 0.89 in both arms (Fig. 6), and the H4 mean difference of +0.025 is small against that spread; we do not interpret it as a detection benefit.

4.9 Other scenarios

For the sample-rate-mismatch scenarios (S10) the position ANEES lies in the band $[0.5, 2]$ at GNSS rates of 1 and 2 Hz and outside it at 5 Hz (3.26–3.47) and 10 Hz (6.40–6.62). In the extreme-noise scenario (S11) the filter locks out GNSS, so its error is far above raw GNSS (median ratio 5,494 MEMS, 1,823 tactical; criterion ≤ 1.5). In the recovery scenario (S13) no run recovers within 60 s at either grade; at the MEMS grade 20 of 30

runs recover within 180 s and at the tactical grade none do, so the pre-registered recovery bounds fail.

4.10 Discussion

When trust-based exclusion pays. The measured benefits are concentrated where excluding GNSS removes a large, sustained error. Against the displaced meaconer FedQPNT lowers attack-window horizontal error relative to Baseline A at both grades and relative to the undefended filter at the MEMS grade, and reduces median clock error about eight-fold (634 versus 5,220 ns). It detects attack onset earlier than a binary detect-and-exclude baseline (by 0.5 to 1 s in gradual-spoof scenarios and by 19.5 s in jam-then-spoof), at no cost in nominal operation or under jamming; trust cycles at most 29 times per hour against a proven bound of 223, and a four-hour mission shows no drift.

When it does not. Against ordinary drifting spoofs (S2) and the jam-then-spoof, long-drift and toggling scenarios (S4, S6, S7), FedQPNT's horizontal error is larger than that of the undefended filter, so the safety principle fails. Two mechanisms are consistent with this. First, when the spoof offset is small the inertial coast drifts further than the spoof displaces the position: at the MEMS grade the undefended filter that simply follows the spoof (127 to 381 m across S2 severities) is below the coast error of an excluding filter (730 to 770 m). Second, post-attack error is dominated by the designed 60 s re-admission dwell. The tactical grade should coast better yet is not better here, so the coast floor alone does not explain the loss; a plausible but untested contributor is residual over-confidence of the attitude and accelerometer-bias states during long coasts. We read the results as characterising the regime in which exclusion pays rather than as a uniform improvement over not defending.

CAI and federated learning showed no measurable effect here. Three untested hypotheses are offered. (i) The rigid-mode CAI loses contrast above $\Omega_c \approx 17\,\mathrm{mrad/s}$, so its aiding is intermittent in manoeuvring motion, and its bias observation may add little to a filter whose coast error is dominated by tilt. (ii) The rule-based physical evidence, not the learned detector, may drive detection at the tested severities, making latency insensitive to both the CAI and the federated model; the primary metric is at its ceiling, so a harder setting is needed to separate the arms. (iii) The experiments are simulation-only and use ten live seeds for the fleet tests. The null results are results about this configuration; they are not evidence that quantum aiding or fleet learning cannot help.

5 Conclusions

5.1 Summary

We have presented FedQPNT, a system architecture that closes the loop between a learned, fleet-shared attack detector, a continuous and evidence-bounded per-sensor trust law, and physical quantum inertial aiding whose noise and fault behaviour is calibrated against real laboratory data, and we have evaluated it in a pre-registered round of 5,340 simulated runs on unseen seeds. The evidence supports a specific and bounded set of conclusions. The continuous trust law detects attack onset significantly earlier than a detect-and-exclude baseline (median 0.5 s, Holm-adjusted $p = 0.004$), adds no measurable cost in nominal operation or under jamming, cycles trust at most 29 times per hour against a proven bound of 223, remains stable over four hours, and, against a displaced meaconer, lowers attack-window horizontal error relative to the baseline and cuts median clock error about eight-fold.

The study did *not* show that the cold-atom accelerometer improves coasting or detection (coasting-error ratio 1.006 and 0.986; H3 null), that federated learning improves abrupt-spoof detection (H2 and H4 null, with the primary metric at its ceiling), or that FedQPNT reduces position error under ordinary drifting spoofs, where its error exceeded that of the undefended filter at both IMU grades and the safety principle failed; the position-error component of H1 was not significant. These outcomes delimit the regime in which GNSS exclusion pays: large or timing-corrupting offsets.

5.2 Limitations

- **No position benefit under ordinary spoofing.** In S2, S4, S6 and S7 the attack-window error exceeds that of the undefended filter at both grades; post-attack error is raised by the 60 s re-admission dwell.
- **No measured benefit from the CAI or from federated learning**; single-node results involve no federation, the fleet tests use $n = 10$ seeds, and TRIM-NB-R's robustness against FedAvg was not evaluated.
- **Signature-strength envelope.** Detection of a drifting single-antenna spoofer relies on its C/N0 signature strength $s \gtrsim 0.5$, an explicit operating assumption; a signature-free multi-antenna spoofer is outside the threat model, and the sweep was not run in the round-3 campaign.
- **A consistency-matched adversary can pass the shadow probe.** An offset kept inside the coasting uncertainty is consistent with the coasting state; the bound is looser at the MEMS grade.
- **Clock-only evidence is weak just after a long outage**, since the oscillator uncertainty is large (about 263 m after 180 s; a 750 m replay step is only about 2.9σ).

- **The filter may remain over-confident in attitude and accelerometer bias.** The round-3 campaign measured position ANEES only (0.84 and 0.94); the earlier bias-NEES figure (about six times nominal on tuning seeds) was not re-measured.
- **Simulation-only evaluation.** Only the CAI noise model is calibrated to real laboratory data; trajectories, GNSS signals, receiver and clock are simulated, and the truth clock shares the filter's model, so timing results are model-consistent by construction.
- **Rigid-mode quantum aiding is intermittent in manoeuvres**, with a rotation-rate tolerance of about 17 mrad/s against about 0.3 rad/s in an ordinary vehicle turn.
- **Scoped novelty.** G^{2}FL [26] already provides robust FL for GNSS spoofing; the contribution is the closed loop of FL detector, continuous bounded trust and quantum aiding, not robust aggregation alone.

5.3 Future work

The results point to four directions: (i) harder detection settings (lower-severity or signature-free families, stricter latency metrics) that can separate the federated and local arms, together with an AUC-based poisoning comparison of TRIM-NB-R against FedAvg; (ii) filter consistency during long coasts, including re-measuring attitude and bias NEES and a coupled or tightly coupled formulation, which bears on both the coast error and the unexplained tactical-grade result; (iii) shortening or adapting the re-admission dwell, to reduce post-attack error without losing the evidence-bounded property; and (iv) a quantum sensor mode that tolerates vehicle rotation rates (inertial-pointing), and ultimately a real-data or hardware-in-the-loop evaluation.

References

[1] Analog Devices. ADIS16470: Wide dynamic range, miniature MEMS IMU data sheet (Rev. C). `https://www.analog.com/media/en/technical-documentation/data-sheets/ADIS16470.pdf`. Accessed 2026-10-03.

[2] Moran Baruch, Gilad Baruch, and Yoav Goldberg. A little is enough: Circumventing defenses for distributed learning. arXiv preprint arXiv:1902.06156, 2019. arXiv/proceedings preprint (NeurIPS 2019).

[3] P. Borhani-Darian, H. Li, P. Wu, and P. Closas. Detecting GNSS spoofing using deep learning. *EURASIP Journal on Advances in Signal Processing*, 2024(1):14, 2024.

[4] R. G. Brown and P. Y. C. Hwang. *Introduction to Random Signals and Applied Kalman Filtering*. Wiley, 4th edition, 2012.

[5] N. A. Carlson. Federated filter for fault-tolerant integrated navigation systems. In *IEEE PLANS '88*, 1988.

[6] N. A. Carlson. Federated square root filter for decentralized parallel processors. *IEEE Transactions on Aerospace and Electronic Systems*, 26(4):517–525, 1990.

[7] Y. Chai, M. Liu, and M. Li. Navigation spoofing and jamming signals identification of UAV based on federated learning. *IEEE Internet of Things Journal*, 2025.

[8] M. Chehimi, S. Y.-C. Chen, W. Saad, D. Towsley, and M. Debbah. Foundations of quantum federated learning over classical and quantum networks. *IEEE Network*, 2023. Published online 2023. Survey of QFL network architectures; not GNSS clock sync or positioning.

[9] M. Chehimi and W. Saad. Quantum federated learning with quantum data. In *2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2022.

[10] Pierrick Cheiney, Lauriane Fouché, Simon Templier, Fabien Napolitano, Baptiste Battelier, Philippe Bouyer, and Brynle Barrett. Navigation-compatible hybrid quantum accelerometer using a Kalman filter. *Physical Review Applied*, 10(3):034030, 2018.

[11] Q. d'Armagnac de Castanet, C. Des Cognets, R. Arguel, S. Templier, V. Jarlaud, V. Menoret, B. Desruelle, P. Bouyer, and B. Battelier. Atom interferometry at arbitrary orientations and rotation rates. *Nature Communications*, 15:6406, 2024.

[12] Q. d'Armagnac de Castanet, C. Des Cognets, R. Arguel, S. Templier, V. Jarlaud, V. Menoret, B. Desruelle, P. Bouyer, and B. Battelier. Atom interferometry at arbitrary orientations and rotation rates – dataset, 2024. Zenodo, CC-BY-4.0.

[13] B. Efron. Better bootstrap confidence intervals. *Journal of the American Statistical Association*, 82:171–185, 1987.

[14] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. arXiv preprint arXiv:1706.04599, 2017. arXiv/proceedings preprint (ICML 2017).

[15] B. Hazarika, K. Singh, O. A. Dobre, C.-P. Li, and T. Q. Duong. Quantum-enhanced federated learning for metaverse-empowered vehicular networks. *IEEE Transactions on Communications*, 2025. Published online 2024. Quantum-enhanced computation for FL, not a physical quantum sensor.

[16] J. L. Hodges and E. L. Lehmann. Estimates of location based on rank tests. *Annals of Mathematical Statistics*, 34:598–611, 1963.

[17] S. Holm. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 6:65–70, 1979.

[18] Honeywell Aerospace. HG1700 inertial measurement unit (product page and brochure). https://www.honeywellaerospace.com/us/en/products-and-services/products/navigation-and-sensors/inertial-measurement-units/hg1700-inertial-measurement-unit, 2025. Accessed 2026-10-03.

[19] T. E. Humphreys, B. M. Ledvina, M. L. Psiaki, B. P. O'Donnell, and P. M. Kintner. Assessing the spoofing threat. In *Proceedings of the ION GNSS 2008*, 2008. No DOI available; catalogue check pending.

[20] IEEE. IEEE standard specification format guide and test procedure for single-axis interferometric fiber optic gyros. IEEE Std 952-1997, 1997.

[21] Juan Jurado, Christine M. Schubert Kabban, and John Raquet. A regression-based methodology to improve estimation of inertial sensor errors using Allan variance data. *NAVIGATION*, 66(1):251–263, 2019.

[22] E. D. Kaplan and C. J. Hegarty, editors. *Understanding GPS/GNSS: Principles and Applications*. Artech House, 3rd edition, 2017. No DOI available; catalogue check pending.

[23] M. M. Khan, M. Kamal, M. Shabbir, and S. Alahmari. Enhancing autonomous vehicle security: Federated learning for detecting GPS spoofing attack. *Transactions on Emerging Telecommunications Technologies*, 36(4):e70138, 2025.

[24] T. Krawinkel and S. Schön. Improved high-precision GNSS navigation with a passive hydrogen maser. *NAVIGATION (Journal of the Institute of Navigation)*, 2021.

[25] Tian Li, Anit Kumar Sahu, Manzil Zaheer, Maziar Sanjabi, Ameet Talwalkar, and Virginia Smith. Federated optimization in heterogeneous networks. arXiv preprint arXiv:1812.06127, 2018. arXiv/proceedings preprint (MLSys 2020).

[26] S. Liu, W. Liu, A. Hussain, and P. Papadimitratos. G^2FL: Robust federated learning for GNSS spoofing detection. In *2026 IEEE ICC Workshops*, 2026.

[27] H. Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Agüera y Arcas. Communication-efficient learning of deep networks from decentralized data. arXiv preprint arXiv:1602.05629, 2016. arXiv/proceedings preprint (AISTATS 2017).

[28] R. K. Mehra. On the identification of variances and adaptive kalman filtering. *IEEE Transactions on Automatic Control*, 15(2):175–184, 1970.

[29] P. Misra and P. Enge. *Global Positioning System: Signals, Measurements, and Performance*. Ganga-Jamuna Press, 2nd edition, 2006. No DOI available; catalogue check pending.

[30] C. O. Namagembe, M. Ibrahim, M. A. Rahman, and P. Pillai. Machine learning-based GPS spoofing detection and mitigation for UAVs. *Computers, Materials & Continua*, 86(2), 2026.

[31] S. A. Negru, P. Geragersian, I. Petrunin, and W. Guo. Resilient multi-sensor UAV navigation with a hybrid federated fusion architecture. *Sensors*, 24(3):981, 2024. Classical federated-filter (EKF + GRU master filter) architecture, NOT federated learning across clients (D-013).

[32] S. A. Negru, P. Geragersian, I. Petrunin, and W. Guo. UWB-aided hybrid navigation system in degraded GNSS environments. In *ION GNSS+ 2024, Proceedings of the 37th International Technical Meeting*, 2024.

[33] B. Pardhasaradhi and L. R. Cenkeramaddi. GPS spoofing detection and mitigation for drones using distributed radar tracking and fusion. *IEEE Sensors Journal*, 22(11):11122–11134, 2022.

[34] M. L. Psiaki and T. E. Humphreys. GNSS spoofing and detection. *Proceedings of the IEEE*, 104(6):1258–1270, 2016.

[35] Sam Pullen and Mathieu Joerger. GNSS integrity and receiver autonomous integrity monitoring (RAIM). In *Position, Navigation, and Timing Technologies in the 21st Century*, pages 591–617. Wiley, 2020.

[36] W.-J. Qin, X. Wang, H. Su, Z. Zhang, X. Li, and X. Yang. The benefits of receiver clock modelling in satellite timing. *Sensors*, 21(2):466, 2021.

[37] K. Radoš, M. Brkić, and D. Begušić. Recent advances on jamming and spoofing detection in GNSS. *Sensors*, 24(13):4210, 2024.

[38] W. Ren, K. Jiang, X. Chen, T. Wen, and D. Yang. Adaptive sensor fusion of camera, GNSS and IMU for autonomous driving navigation. In *2020 4th CAA International Conference on Vehicular Control and Intelligence (CVCI)*, 2020.

[39] Joan Solà. Quaternion kinematics for the error-state Kalman filter. arXiv preprint arXiv:1711.02508, 2017. arXiv preprint.

[40] Ziteng Sun, Peter Kairouz, Ananda Theertha Suresh, and H. Brendan McMahan. Can you really backdoor federated learning? arXiv preprint arXiv:1911.07963, 2019. arXiv preprint.

[41] U. Tariq and T. A. Ahanger. Multi-model fusion for robust detection and resilient mitigation of BeiDou spoofing in decentralized UAV swarm systems. *PeerJ Computer Science*, 2026. Fusion via per-model ensembling, not consensus; approx. 99% detection accuracy, >97% mission-success rate (D-013).

[42] Simon Templier, Pierrick Cheiney, Quentin d'Armagnac de Castanet, Baptiste Gouraud, Henri Porte, Fabien Napolitano, Philippe Bouyer, Baptiste Battelier, and

Brynle Barrett. Tracking the vector acceleration with a hybrid quantum accelerometer triad. *Science Advances*, 8(45):eadd3854, 2022.

[43] F. Wilcoxon. Individual comparisons by ranking methods. In *Breakthroughs in Statistics*, pages 196–202. Springer, 1992. Reprint of Biometrics Bulletin, 1945.

[44] M. J. Wright, L. Anastassiou, C. Mishra, J. M. Davies, A. M. Phillips, S. Maskell, and J. F. Ralph. Cold atom inertial sensors for navigation applications. *Frontiers in Physics*, 10:994459, 2022.

[45] Dong Yin, Yudong Chen, Kannan Ramchandran, and Peter Bartlett. Byzantine-robust distributed learning: Towards optimal statistical rates. arXiv preprint arXiv:1803.01498, 2018. arXiv/proceedings preprint (ICML 2018).

[46] Xu Zhou, Qing Yang, Qiang Liu, Wei Liang, Kai Wang, Zhen Liu, Jianfeng Ma, and Qun Jin. Spatial–temporal federated transfer learning with multi-sensor data fusion for cooperative positioning. *Information Fusion*, 2024. Published online 2023.




Figure 1: Safety principle: HL difference in maximum horizontal error, defended minus undefended, with 95% BCa CI (symlog axis); dotted lines mark $3\sigma_{\text{nom}}$.




Figure 2: Clock RMSE under the displaced meaconer (S2-DM): mean and 95% CI over 30 seeds.




Figure 3: Attack-window RMSE$_h$ (mean and 95% CI over 30 seeds, log scale) for FedQPNT, the undefended filter and Baseline A, per scenario and IMU grade.




Figure 4: Single-seed demonstration (tuning seed 531, industrial MEMS, S2-DM): horizontal error (top), FedQPNT trust weight and TRUST/DISTRUST/PROBE state (middle) and clock error (bottom). Illustrative only; not part of the confirmatory evaluation.




Figure 5: Maximum horizontal coasting error in a 180 s GNSS outage with and without the CAI: mean and 95% CI over 30 seeds, per IMU grade.




Figure 6: Per-seed onset-window AUC ($N = 10$ s), FedQPNT versus B-cont, for H2 and H4 ($n = 10$ seeds each); p is the uncorrected paired Wilcoxon value.