

CYPHERROLL: A PROVABLY FAIR WEB3 CRYPTO CASINO WITH HYBRID OFF-CHAIN EXECUTION AND NON-CUSTODIAL ON-CHAIN SETTLEMENT

PROJECT REPORT

Submitted by

PRATYUSH KIRAN RATH

Regd. No.: 250301120001

SAMARPIT BISWAL

Regd. No.: 250301120012

in partial fulfillment for the award of the degree of

BACHELOR OF TECHNOLOGY

in

COMPUTER SCIENCE AND ENGINEERING



**Centurion
UNIVERSITY**

*Shaping Lives...
Empowering Communities...*

**SCHOOL OF ENGINEERING AND TECHNOLOGY BHUBANESWAR CAMPUS
CENTURION UNIVERSITY OF TECHNOLOGY AND MANAGEMENT ODISHA**

October, 2026

**CENTURION UNIVERSITY OF TECHNOLOGY AND
MANAGEMENT ODISHA**

School of Engineering and Technology, Bhubaneswar Campus

BONAFIDE CERTIFICATE

This is to certify that the project report entitled “**CypherRoll: A Provably Fair Web3 Crypto Casino with Hybrid Off-Chain Execution and Non-Custodial On-Chain Settlement**” submitted by **PRATYUSH KIRAN RATH** (Regd. No.: **250301120001**) and **SAMARPIT BISWAL** (Regd. No.: **250301120012**) in partial fulfillment of the requirements for the award of the degree of **Bachelor of Technology in Computer Science and Engineering** is a bonafide record of work carried out under proper academic guidance and supervision.

Project Supervisor

Sunny Singh

Department of CSE

Centurion University, Odisha

Head of the Department

Department of CSE

Centurion University, Odisha

DECLARATION

We, **Pratyush Kiran Rath** (Regd. No.: **250301120001**) and **Samarpit Biswal** (Regd. No.: **250301120012**), students of Bachelor of Technology in Computer Science and Engineering at Centurion University of Technology and Management, Odisha, hereby declare that the project entitled “**CypherRoll: A Provably Fair Web3 Crypto Casino with Hybrid Off-Chain Execution and Non-Custodial On-Chain Settlement**” represents original engineering and development work undertaken by us.

All materials, smart contracts, cryptographic libraries, and technical specifications referenced throughout this work have been properly credited and documented. We further confirm that this report has not been submitted previously to this or any other institution for the award of any degree or diploma.

Pratyush Kiran Rath

Regd. No.: 250301120001

Department of CSE

Centurion University, Odisha

Samarpit Biswal

Regd. No.: 250301120012

Department of CSE

Centurion University, Odisha

ACKNOWLEDGEMENT

We would like to express our profound gratitude and deep regards to our project guide, **Sunny Singh**, Department of Computer Science and Engineering, for his exemplary guidance, invaluable technical insights, and constant encouragement throughout the architecture and development of the CypherRoll platform.

We are immensely obliged to the Head of the Department, Department of Computer Science and Engineering, and the administration of the School of Engineering and Technology, Centurion University of Technology and Management, Odisha, for providing the necessary facilities, computing infrastructure, and academic ecosystem to carry out this research and engineering initiative.

We also extend our sincere appreciation to the open-source Ethereum, Web3, and Solana developer communities whose open protocols, smart contract libraries, and cryptographic primitives laid the foundation for this platform.

Finally, we express our heartfelt gratitude to our families and friends for their continuous moral support and encouragement throughout our academic journey.

Pratyush Kiran Rath

Regd. No.: 250301120001

Department of CSE

Centurion University, Odisha

Samarpit Biswal

Regd. No.: 250301120012

Department of CSE

Centurion University, Odisha

ABSTRACT

CypherRoll is a Web3-oriented online gaming platform designed around a hybrid execution model that separates responsive real-time game execution from blockchain-based non-custodial settlement. The project combines a modern Next.js and React application layer with Three.js/WebGL 3D hardware-accelerated visualization, wallet-based cryptographic authentication, cryptographic provable fairness, Supabase-backed relational persistence and real-time state synchronization, and an EVM escrow-vault smart contract component. The application implements two principal games—CypherDice and CypherCrash—along with a vault/cashier interface, live betting feed, community communication, support workflows, and an independent provably-fair verification interface.

The core cryptographic fairness mechanism employs a cryptographically secure server seed, a SHA-256 commitment published prior to bet placement, a player-controlled client seed, and a strictly incrementing nonce. HMAC-SHA256 deterministically derives game outcomes, allowing the revealed server seed and recorded inputs to be independently verified by players. The platform incorporates deterministic statistical testing, atomic wager balance mutations under concurrency, wallet signature authentication (Sign-In with Ethereum - EIP-4361 and Solana Wallet Adapter), real-time event broadcasting, and cryptographic withdrawal authorization via EIP-712 structured signatures.

The system architecture is structured as a three-tier hybrid model: presentation layer, application and game execution layer, and persistence/settlement layer. This decoupling addresses the latency and high gas-cost bottlenecks of executing high-frequency game state transitions directly on-chain, while preserving the cryptographic auditability and non-custodial security guarantees of decentralized ledgers.

Keywords: Web3, Provably Fair Gaming, HMAC-SHA256, SHA-256, Blockchain, Smart Contracts, Next.js, Three.js, WebGL, Supabase, MetaMask, EVM, Solana, CypherDice, CypherCrash.

TABLE OF CONTENTS

Chapter No.	Chapters	Page No
1	Introduction	01–03
2	Objectives of the Project	04–05
3	Existing System	06–08
4	Proposed System	09–12
5	System Requirements	13–16
6	System Design	17–19
7	Module Description	20–22
8	Implementation Details	23–25
9	Testing and Results	26–28
10	Conclusion	29–30
	Reference	31–32

CHAPTER 1

INTRODUCTION

1.1 Background and Overview of Web3 Gaming

Web3 applications introduce user-controlled non-custodial wallets, blockchain settlement, and cryptographic identity primitives into conventional web workflows. In modern digital wagering and prediction platforms, however, purely on-chain execution models introduce substantial block confirmation delays (such as 12-second block intervals on Ethereum Mainnet) and prohibitive gas transaction fees that conflict with fast-paced, interactive consumer gameplay.

The CypherRoll platform resolves this fundamental tension through a state-of-the-art **3-Tier Hybrid Web3 Architecture**. In this design, high-frequency game execution and interactive 3D WebGL rendering are handled efficiently within the browser and application layer, while value custody and capital settlements are anchored to decentralized blockchain escrow contracts. This guarantees that players experience sub-second responsiveness without forfeiting decentralized custody or mathematical fairness.

1.2 Motivation of the Study

The CypherRoll project is driven by four primary software engineering and architectural imperatives:

1. **Verifiable Mathematical Fairness:** Replacing centralized, opaque random number generators (“black-box RNGs”) with verifiable, deterministic commit-reveal cryptographic hashing protocols.
2. **Low-Latency Interactive Gameplay:** Eliminating gas-fee frictions and transaction wait-times from individual gaming rounds by maintaining off-chain state execution backed by Three.js 60 FPS WebGL graphics.
3. **Non-Password Cryptographic Wallet Identity:** Transitioning from vulnerable email/password accounts and intrusive KYC document harvesting to decentralized cryptographic wallet signatures via Sign-In with Ethereum (SIWE – EIP-4361) and Solana Wallet Adapter.
4. **Auditable Non-Custodial Capital Settlement:** Preventing operator solvency failures, commingling of player funds, and arbitrary withdrawal lockouts through smart contract escrow vaults deployed across EVM Layer-2 rollups.

1.3 Problem Statement

Traditional online gambling systems operate as centralized black boxes where server-side random number generation, player ledger databases, and treasury funds are held entirely by a single corporate operator. This centralized paradigm suffers from three critical industry-wide flaws:

- **Opaque and Unauditable Randomness:** Players have no mathematical mechanism to verify whether a dice roll, roulette spin, or multiplier crash was authentically random or algorithmically altered to maximize operator profit.
- **Custodial Counterparty Vulnerability:** Players must deposit funds directly into custodial operator accounts, leaving them completely vulnerable to insolvency, internal embezzlement, and frozen withdrawals.
- **Scalability Constraints of Pure On-Chain DApps:** Existing fully on-chain casinos execute every single wager as an individual blockchain transaction, resulting in exorbitant gas fees and multi-second latencies that make real-time gaming unviable.

1.4 Scope and Boundaries of the Project

The scope of the CypherRoll project encompasses the end-to-end design, implementation, and empirical validation of a full-stack Web3 wagering application:

- Modern frontend application engineering using Next.js 14, TypeScript, Tailwind CSS, and Framer Motion.
- High-fidelity hardware-accelerated 3D WebGL rendering for **CypherDice** and **CypherCrash** built with Three.js and Draco-compressed GLB asset pipelines, complete with automatic canvas fallbacks for non-WebGL devices.
- Cryptographic Provably Fair Engine using HMAC-SHA256 with SHA-256 pre-committed server seeds, user-selected client seeds, and sequential nonces.
- Solidity Non-Custodial Smart Contract Escrow Vault (`CypherRollVault.sol`) deployed across EVM networks (Ethereum Sepolia and Base Sepolia testnets) with EIP-712 structured signature withdrawal authorization.
- Relational persistence and real-time state synchronization through Supabase PostgreSQL, incorporating atomic balance mutations, row-level security, and a live global betting feed.
- Automated AML/OFAC sanctions compliance screening, client-side PoW rate-limiting, and Kelly Criterion bankroll solvency controls.

1.5 Key Contributions of the System

The primary contributions of this project include:

1. Designing and executing a provably fair cryptographic protocol that allows players to independently verify round outcomes in real-time or posthumously using open mathematical formulas.
2. Developing a dual-chain Web3 authentication interface supporting EVM wallets (MetaMask, Coinbase Wallet, Rainbow) and Solana wallets (Phantom) under a unified session abstraction.
3. Demonstrating an enterprise-grade Layer-2 settlement model achieving sub-cent gas fees and non-custodial escrow protection on Base Sepolia.

1.6 Organization of the Report

The remainder of this report is organized into ten chapters aligned with academic guidelines: Chapter 2 details the project objectives; Chapter 3 evaluates existing gaming architectures; Chapter 4 presents the proposed hybrid system; Chapters 5 through 8 provide the system requirements, architectural design, module breakdown, and implementation details; Chapter 9 presents testing and experimental results; and Chapter 10 concludes the report with future directions.

CHAPTER 2

OBJECTIVES OF THE PROJECT

2.1 Introduction

The success of the CypherRoll platform depends on clearly articulated software engineering, cryptographic, and architectural objectives. These objectives systematically address the structural vulnerabilities of centralized online gaming through decentralized smart contract settlement, provably fair commit-reveal mathematics, hardware-accelerated 3D WebGL rendering, and secure off-chain state computation.

2.2 Primary Objective

The overarching objective of the CypherRoll project is to design, construct, and empirically validate an enterprise-grade, provably fair Web3 gaming platform with a 3-tier hybrid architecture. The platform decouples fast, interactive browser gameplay from immutable, non-custodial smart contract settlements, guaranteeing that neither the casino operator nor the player can manipulate game outcomes.

2.3 Specific Technical Objectives

The specific technical objectives formulated to achieve this system comprise:

1. **Implement Deterministic Cryptographic Provable Fairness:** Construct a mathematical commit-reveal fairness engine using HMAC-SHA256. The system ensures that a 256-bit server seed is cryptographically committed (via SHA-256) prior to any wager placement, and combined with a player-selected client seed and monotonic nonce to generate tamper-proof dice outcomes and crash points.
2. **Develop a Non-Custodial Smart Contract Escrow Vault:** Design, implement, and deploy a Solidity escrow contract (`CypherRollVault.sol`) on Ethereum Sepolia and Base Sepolia. The contract enforces trustless segregation of player balances and processes withdrawals only upon validating cryptographically authorized EIP-712 structured operator signatures.
3. **Integrate Zero-KYC Multi-Chain Wallet Authentication:** Implement gasless, passwordless cryptographic authentication supporting both EVM wallets via Sign-In with Ethereum (SIWE – EIP-4361) and Solana wallets via the Solana Wallet Adapter, establishing authenticated sessions without requiring user identity disclosures.

4. **Build High-Performance 3D WebGL Game Environments:** Engineer interactive Three.js 3D rendering pipelines for **CypherDice** and **CypherCrash**, incorporating 60 FPS physics lerping, dynamic lighting, camera shake effects, and Draco-compressed GLB assets, with automatic 2D HTML5 canvas fallbacks for devices without WebGL acceleration.
5. **Ensure High-Concurrency Atomic Balance Management:** Construct an ACID-compliant PostgreSQL transaction ledger using Supabase, employing row-level database locks (SELECT FOR UPDATE) to guarantee atomic wager balance debits and winnings credits under concurrent user sessions.
6. **Deploy Real-Time Global Telemetry and Communication:** Implement a low-latency WebSocket communication layer using Supabase Realtime to broadcast live betting results, active player counts, and interactive community trollbox messages across all connected clients.
7. **Enforce Dynamic Solvency Controls (Kelly Criterion):** Integrate mathematical risk boundaries that dynamically cap maximum player wagers and potential payouts to $\leq 1\%$ of the total available escrow vault reserves, preventing bankroll exhaustion during anomalous winning streaks.
8. **Integrate Regulatory AML Screening and Replay Protection:** Incorporate automated OFAC/AML sanctions screening oracles to detect and quarantine high-risk cryptocurrency addresses, coupled with client-side PoW rate-limiting and deadline-enforced nonces to defend against replay and Sybil attacks.

2.4 Conclusion of the Chapter

This chapter established the primary and specific technical objectives guiding the CypherRoll architecture. By formulating measurable targets across cryptography, smart contracts, Web3 identity, and 3D rendering, these objectives define the structural criteria against which the system is developed and evaluated.

The following chapter reviews existing centralized and decentralized gaming architectures and examines their structural limitations.

CHAPTER 3

EXISTING SYSTEM

3.1 Introduction

The current online gambling and crypto casino sector is overwhelmingly dominated by centralized web platforms such as Stake.com, Roobet, and traditional online casinos licensed in offshore jurisdictions. These systems allow users to create accounts, deposit cryptocurrencies or fiat currencies into hot wallets managed by the casino company, and wager across various digital casino games. However, they lack a decentralized, trustless architecture, forcing players to rely on blind faith in the operator's integrity.

Most existing solutions claim to provide fair odds, but the algorithms generating the random numbers remain proprietary and hosted on private servers. As a result, these systems fail to provide transparent, tamper-proof guarantees of mathematical fairness. This architectural centralization fundamentally weakens user trust and leaves players exposed to severe financial and data security risks.

3.2 Features of the Existing System

The existing centralized online casinos provide standard functionalities for user engagement and wagering:

- **User Registration and Accounts:** Platforms require players to register using an email address, password, or third-party OAuth account (Google, Facebook).
- **Centralized Custodial Banking:** Players deposit cryptocurrency (Bitcoin, Ethereum, USDT) into custodial deposit addresses generated by the casino. Balances are held directly by the company rather than in smart contract escrow.
- **Proprietary Game Loops:** Games such as dice, roulette, slots, and crash are rendered using standard 2D web canvases or pre-rendered sprite animations driven by private server-side random number generators.
- **Gamification and Retention Features:** Existing systems incorporate VIP tier ladders, daily bonus wheels, rakeback rewards, and live trollbox chat rooms to maximize user engagement.

3.3 Challenges in the Existing System

One of the major challenges in the existing system is the total lack of cryptographic verifiability. Because users cannot independently audit the private server seed or the internal RNG

before placing their wagers, operators can manipulate roll results to favor the house during high-stakes rounds without leaving an auditable trail.

Another critical challenge is the complete absence of fund custody. When players transfer funds to centralized casinos, they surrender legal and cryptographic ownership of their assets. Numerous instances of platform insolvencies, frozen withdrawals, and sudden account closures demonstrate that centralized custody poses unacceptable counterparty risk.

Furthermore, existing systems subject users to invasive Know Your Customer (KYC) identity verification procedures. Players are routinely forced to upload government passports, national IDs, and proof of address before being permitted to withdraw winnings. This exposes user identities to severe data breach risks and privacy violations.

3.4 Workflow of the Existing System

The typical workflow of existing centralized gambling systems proceeds through the following sequence:

1. The user visits the platform and completes an account registration form providing email and password credentials.
2. The platform creates a custodial wallet address for the user and requests a cryptocurrency deposit.
3. Once the blockchain transaction confirms, the platform's private database increments the user's virtual balance.
4. The user selects a game and clicks "Bet". A request is transmitted to the casino's private server.
5. The server executes a closed-source RNG function, determines whether the user won or lost, updates the database balance, and returns the animation response to the frontend.
6. When the user attempts to withdraw their balance, the request is routed to a human or automated compliance team. The platform may demand identity verification documents (KYC) and holds discretion over whether to approve or cancel the payout.

3.5 Limitations of the Existing System

The existing system suffers from several structural limitations:

- **Counterparty and Insolvency Risk:** Player assets are commingled with the company's operating capital, creating high risk of total loss if the platform becomes insolvent.
- **Absence of Mathematical Proof:** No mathematical proof of fairness is available in real time; audit certifications are static, periodic, and issued by paid third-party testing agencies.

- **Arbitrary Account Confiscation:** Terms of service grant operators unilateral authority to void bets, freeze balances, or deny payouts at their sole discretion.
- **Primitive 2D Graphics:** Most crypto gaming sites rely on simplistic 2D charts and low-frame-rate canvas animations, lacking modern hardware acceleration.

3.6 Need for a New System

The challenges and limitations of the existing centralized ecosystem highlight the critical need for a modern, blockchain-anchored gaming platform. A system that integrates cryptographic provable fairness with non-custodial smart contracts can eliminate counterparty risk, prevent game tampering, and guarantee self-custodial ownership of assets.

Such a platform must enable gas-free, zero-KYC wallet authentication, deliver 60 FPS 3D WebGL graphics, and support instant, cryptographically signed withdrawals. CypherRoll is engineered from the ground up to address these needs by introducing a hybrid Web3 architecture for online gaming.

3.7 Conclusion of the Chapter

This chapter analyzed the existing centralized gambling systems, outlining their workflow, key features, and fundamental operational limitations. It clearly demonstrated the acute need for an authentic, provably fair, and non-custodial gaming architecture.

The next chapter will present the proposed CypherRoll system, describing its high-level overview, key features, working methodology, and operational feasibility.

CHAPTER 4

PROPOSED SYSTEM

4.1 Introduction

To overcome the severe limitations and vulnerabilities of centralized gaming platforms, the CypherRoll system proposes a hybrid Web3 gaming architecture that integrates cryptographic provable fairness with non-custodial smart contracts. The proposed system is designed to provide a secure, transparent, and mathematically tamper-proof environment for playing interactive 3D casino games.

Unlike traditional platforms, CypherRoll ensures that users retain sovereignty over their assets and identity. Game randomness is cryptographically predetermined using an open HMAC-SHA256 commit-reveal protocol, while deposits and withdrawals are governed by an on-chain Solidity escrow vault (`CypherRollVault.sol`) deployed across EVM networks such as Base Sepolia and Ethereum Sepolia.

4.2 Overview of the Proposed System

CypherRoll is a web-based decentralized application that allows players to connect their Web3 wallets (such as MetaMask or Phantom), deposit funds into a non-custodial smart contract escrow, and participate in arcade games including CypherDice, CypherCrash, Mines, and Plinko.

The architecture decouples fast real-time game rendering and outcome generation from durable on-chain financial settlement. When a user places a wager, the game outcome is computed deterministically in less than one millisecond off-chain using the player's client seed and the server's pre-committed seed hash. The 3D WebGL engine immediately renders the physics-driven simulation at 60 FPS. Once a player wishes to withdraw, the backend generates an EIP-712 cryptographic signature, empowering the player to claim their balance directly from the smart contract on-chain.

4.3 Key Features of the Proposed System

The proposed CypherRoll system incorporates several state-of-the-art features:

- **Cryptographic Provable Fairness:** The system implements a 100% transparent commit-reveal protocol based on HMAC-SHA256. The server commits to a secret seed via its SHA-256 hash before bets are placed. The user can customize their client seed, guaranteeing that neither party can manipulate the roll.

- **Non-Custodial Escrow Vault** (`CypherRollVault.sol`): Treasury assets are secured within an immutable Solidity contract supporting native ETH and standard ERC-20 tokens (e.g., USDC). Withdrawals require valid cryptographic signatures from the casino operator, preventing unauthorized fund drains.
- **Zero-KYC Authentication via SIWE (EIP-4361)**: Users log in by signing a cryptographic challenge message using their private key in MetaMask. This provides instant, passwordless authentication without collecting personal information or incurring gas fees.
- **Cinematic 3D WebGL Gaming**: Games are rendered using Three.js with realistic lighting, dynamic camera shakes, particle thruster plumes, and Draco-compressed 3D models running smoothly at 60 frames per second.
- **Automated AML and OFAC Sanctions Screening**: An integrated security oracle automatically screens connecting addresses against sanctioned entity lists and high-risk mixers, quarantining illicit funds while protecting ordinary user privacy.
- **Kelly Criterion Dynamic Treasury Guard**: The maximum profit allowed for any single wager is mathematically capped at $\leq 1\%$ of total vault reserves, ensuring long-term bankroll solvency.

4.4 Working of the Proposed System

The operational lifecycle of the CypherRoll system proceeds as follows:

1. **Wallet Connection and Authentication**: The player connects MetaMask via RainbowKit. The platform issues a challenge nonce via `GET /api/auth/nonce`. The player signs the challenge message in MetaMask, and `POST /api/auth/verify` validates the signature, issuing an authenticated session cookie.
2. **Vault Deposit**: The player deposits ETH or USDC into `CypherRollVault.sol`. The contract emits a `Deposited` event. The player submits the transaction hash to `/api/cashier/verify-deposit`, where Viem inspects the on-chain receipt and credits the ledger balance atomically in Supabase.
3. **Wagering and Provably Fair Execution**: The player configures their wager and target odds. The server computes:

$$\mathcal{H} = \text{HMAC-SHA256}(S_{\text{srv}}, S_{\text{cli}} : N)$$

The outcome is mapped deterministically to a dice roll or crash multiplier. The Three.js 3D canvas animates the roll, and the player's balance updates in the ACID ledger with row-level locks.

4. **Cryptographic Withdrawal (EIP-712):** When the user clicks withdraw, `POST /api/cashier/withdraw` validates their balance and emits an EIP-712 typed signature voucher signed by the casino operator.
5. **On-Chain Settlement:** The user submits the operator-signed withdrawal voucher directly to `CypherRollVault.sol` via MetaMask, triggering autonomous token release straight into the player's wallet.

4.5 Advantages of the Proposed System

The proposed system offers substantial advantages over legacy platforms:

- **Elimination of Fraud and Manipulation:** Mathematical commit-reveal algorithms make it impossible for the casino to alter odds or outcomes retroactively.
- **Self-Custody and Security:** Funds reside in an on-chain smart contract rather than an opaque corporate bank account, eliminating insolvency and exit scam risks.
- **High-Speed Interactivity:** Off-chain computation delivers instantaneous game feedback without requiring players to wait for blockchain block confirmations for every roll.
- **Privacy Preservation:** Players authenticate cryptographically via their Web3 wallet without surrendering personal identity documents or undergoing invasive KYC procedures.

4.6 Feasibility of the System

Technical Feasibility The CypherRoll system is technically feasible as it leverages well-established, industry-standard technologies. Next.js 14 provides a robust full-stack framework; Three.js provides mature, hardware-accelerated 3D graphics; and Viem, Wagmi, and Solidity offer enterprise-grade Web3 development tooling. All cryptographic protocols (HMAC-SHA256, EIP-712, EIP-4361) are mathematically proven and supported by widespread libraries.

Economic Feasibility Economically, the system is exceptionally cost-effective. By deploying the escrow vault on Layer-2 networks (Base Sepolia and Base Mainnet), transaction gas fees for deposits and withdrawals are reduced by over 99.8% compared to Ethereum Layer-1. During testing and grading, the platform operates completely free of charge on public testnets using faucets.

Operational Feasibility Operationally, the system is intuitive and user-friendly. Users familiar with Web3 browser extensions like MetaMask can onboard and play within seconds. The intuitive Cashier modal, clear provably fair seed inspectors, and real-time live bet tickers ensure high accessibility and operational clarity.

4.7 Conclusion of the Chapter

This chapter outlined the proposed CypherRoll system, including its architectural overview, key features, working methodology, advantages, and technical, economic, and operational feasibility. The proposed architecture solves the fundamental challenges of centralized gambling by introducing cryptographic fairness and non-custodial smart contract security.

The next chapter will detail the hardware, software, functional, and non-functional system requirements necessary for implementing and running the platform.

CHAPTER 5

SYSTEM REQUIREMENTS

5.1 Introduction

System requirements define the essential hardware, software, and operational conditions necessary for the successful design, implementation, deployment, and testing of the CypherRoll platform. These requirements ensure that the system executes efficiently, maintains data integrity and cryptographic security, and delivers a responsive, lag-free user experience. The requirements are categorized into hardware, software, functional, and non-functional specifications.

5.2 Hardware Requirements

The CypherRoll system is a web-based decentralized application built on modern web standards, and therefore it does not require specialized server hardware for end users. The minimum and recommended hardware specifications comprise:

Client-Side Hardware Requirements:

- **Processor:** Dual-core Intel Core i3 / AMD Ryzen 3 or higher (ARM-based Apple M1/M2/M3 fully supported).
- **Memory (RAM):** Minimum 4 GB of system RAM (8 GB recommended for optimal 60 FPS 3D WebGL rendering).
- **Graphics Card (GPU):** Integrated graphics (Intel UHD / Iris Xe / AMD Radeon Vega) or dedicated GPU supporting WebGL 2.0 and hardware-accelerated canvas compositing.
- **Storage:** At least 1 GB of available disk space for browser caches, local state, and Web3 extension storage.
- **Network Connectivity:** Stable internet broadband connection (minimum 2 Mbps) for real-time WebSocket communication and JSON-RPC node calls.

Development and Server-Side Hardware Requirements:

- **Processor:** Quad-core 2.4 GHz 64-bit x86/ARM processor.

- **Memory (RAM):** Minimum 8 GB RAM (16 GB recommended for running concurrent Next.js dev servers, Blender asset pipelines, and local testnet nodes).
- **Storage:** Minimum 20 GB of free solid-state storage (SSD) for dependencies, compiled build artifacts, and database ledgers.

5.3 Software Requirements

The software requirements encompass all programming environments, operating systems, frameworks, and developer toolkits utilized in building and operating CypherRoll:

- **Operating System:** Compatible across Windows 10/11 64-bit, macOS 12+ (Monterey, Ventura, Sonoma), and Ubuntu Linux 20.04+ LTS.
- **Runtime Environment:** Node.js version 18.x or 20.x LTS alongside the npm package manager.
- **Frontend Framework:** Next.js 14 (App Router) with React 18, TypeScript 5.4, and Tailwind CSS 3.4.
- **3D Graphics Library:** Three.js (v0.164.1) with Draco mesh decompression libraries.
- **Web3 and Blockchain Libraries:** Wagmi (v2.8.6), Viem (v2.10.8), RainbowKit (v2.1.2), and Solana Web3.js (v1.91.8).
- **Smart Contract Development:** Solidity compiler (pragma ^0.8.24) with Remix IDE / Hardhat / Foundry for contract compilation and testing.
- **Database and Storage:** Supabase PostgreSQL 16 with Row-Level Security (RLS) and real-time WebSocket Pub/Sub subscriptions.
- **Web Browser and Wallet Extension:** Modern Chromium-based browser (Google Chrome, Brave, Microsoft Edge, Firefox) equipped with the MetaMask Web3 wallet extension.

5.4 Functional Requirements

Functional requirements specify the direct capabilities, workflows, and operations the CypherRoll system must execute:

1. **Wallet Authentication:** The system must permit users to connect their MetaMask or Phantom wallet and authenticate using cryptographic message signing (SIWE - EIP-4361) without passwords or gas fees.
2. **Interactive 3D Game Environments:** The system must render interactive 3D WebGL game environments for CypherDice and CypherCrash with physical dice rolling and rocket flight synchronized with game state.

3. **Provably Fair Outcome Generation:** The system must generate game results using HMAC-SHA256 based on the pre-committed server seed, user client seed, and sequential nonce, enabling independent post-game verification.
4. **Vault Deposit Management:** The system must provide multi-network deposit addresses (Base, Arbitrum, Solana) and allow players to submit transaction hashes for on-chain receipt verification and balance crediting.
5. **EIP-712 Withdrawal Authorization:** The system must process player withdrawal requests and emit cryptographically signed EIP-712 vouchers for autonomous on-chain redemption against `CypherRollVault.sol`.
6. **Seed Rotation and Inspection:** Players must be able to view their active server seed hash, generate new client seeds, and rotate their seed pair to reveal historical server seeds for auditability.
7. **Live Telemetry and Bet Tickers:** The system must display an infinite real-time marquee tracking live bets, multipliers, and payouts across all active platform games.

5.5 Non-Functional Requirements

Non-functional requirements define the quality attributes, performance criteria, and security benchmarks of the platform:

- **High Security:** The system must protect against reentrancy attacks, replay nonces, front-running, and double-crediting. All SQL balance updates must execute under strict ACID row-level locking.
- **Low Latency and High Responsiveness:** The backend game outcome calculation must complete in $< 1.0\text{ms}$. The 3D WebGL render loop must sustain a steady 60 frames per second (16.6ms frame time).
- **Scalability:** The stateless Next.js API architecture must support concurrent user scaling, handling horizontal worker distribution behind reverse proxies.
- **Reliability and Solvency:** The system must enforce dynamic Kelly Criterion bet capping ($\leq 1\%$ vault reserves) to ensure mathematical platform solvency at all times.
- **Usability and Accessibility:** The interface must offer an intuitive, responsive OLED cyberpunk design with clear error feedback and full cross-browser compatibility.

5.6 Conclusion of the Chapter

This chapter outlined the comprehensive hardware, software, functional, and non-functional requirements necessary for developing and operating the CypherRoll platform. These criteria

provide the technical baseline for constructing a secure, robust, and high-performance Web3 gaming system.

The next chapter will delve into the system design, detailing the architectural decomposition, component diagrams, data flows, database schemas, and security measures.

CHAPTER 6

SYSTEM DESIGN

6.1 Introduction

System design defines how the CypherRoll platform is structured and how its constituent frontend, backend, database, and blockchain components interact to deliver seamless, tamper-proof gaming functionality. The system follows a modular, layered 3-tier hybrid architecture that synthesizes high-performance client rendering, off-chain provably fair outcome generation, and on-chain non-custodial smart contract settlement.

6.2 Architecture Overview

The CypherRoll platform is built using a multi-layer architecture consisting of three primary tiers: the presentation layer, the application/logic layer, and the persistence and consensus settlement layer.

Figure 6.1: CypherRoll 3-Tier Architecture High-Level Design




Figure 1: Architectural Blueprint of CypherRoll

The presentation layer is developed using Next.js 14, React, and Three.js. It allows users to connect their Web3 wallets, inspect provably fair seeds, configure wagers, and experience hardware-accelerated 3D WebGL animations.

The application layer comprises Next.js API Routes and cryptographic Node.js modules. It handles SIWE authentication, verifies on-chain deposit transactions, computes deterministic outcomes, and signs EIP-712 withdrawal authorizations.

The blockchain and settlement layer comprises the Solidity smart contract (CypherRollVault.sol) deployed across Ethereum Sepolia and Base Sepolia, enforcing non-custodial custody and autonomous fund release upon cryptographic signature verification.

6.3 Component Design

The system is composed of several interconnected components:

- **Frontend Component:** Provides the interactive 3D canvas, responsive betting HUD, wallet dropdown, and modal dialogs (Cashier, Provably Fair, VIP).
- **Backend Processing Component:** Acts as the secure coordinator, validating incoming client requests, computing HMAC hashes, and interacting with the database.
- **Smart Contract Escrow Component:** Defines the non-custodial rules for asset deposits, reserves tracking, and EIP-712 signature verification.
- **External Oracle Component:** Screens wallet addresses for OFAC sanctions compliance and queries public RPC nodes for on-chain receipt confirmation.

6.4 Data Flow

The data flow begins when a user connects their MetaMask wallet and signs a SIWE challenge message. The verified wallet address initializes a player profile in the database. When the user deposits ETH or USDC into CypherRollVault.sol, the frontend captures the transaction hash and sends a verification request to the backend.

The backend queries the EVM RPC node using Viem to confirm on-chain execution. Upon confirmation, the backend credits the player's balance. When the player places a bet, the backend computes the deterministic outcome via HMAC-SHA256, deducts the wager or credits the payout atomically, and streams the result to the 3D WebGL renderer. When a withdrawal is requested, the backend emits an EIP-712 voucher allowing the user to claim tokens directly from the smart contract.

6.5 Database Design

The relational database is architected in PostgreSQL 16 (via Supabase) to preserve an immutable financial audit trail. It includes four core tables:

- **users:** Stores player wallet addresses, primary chain type, active balance, VIP tier, and rakeback totals.
- **transactions:** Tracks deposits and withdrawals, recording wallet, amount, transaction hash, status, and network.
- **bets:** Records every wager, game type, wager amount, multiplier, payout, and associated seed references.
- **seeds:** Preserves active and rotated server seeds, pre-committed hashes, client seeds, and sequential nonces.

6.6 System Workflow

The system workflow starts with user authentication through MetaMask. Once authenticated, the user can deposit funds via the Cashier modal, choose an arcade game (CypherDice or CypherCrash), customize their client seed, and place bets. The backend executes the bet in under 1ms and renders the result in 3D. The user can continuously track their statistics, view live global bet tickers, and initiate instant EIP-712 withdrawals whenever desired.

6.7 Security Considerations

Security is a foundational pillar of the CypherRoll system:

- **Smart Contract Invariants:** `CypherRollVault.sol` implements nonces per user and strict deadline checks to neutralize transaction replay attacks.
- **Reentrancy Neutralization:** Payouts update internal reserves and state variables prior to triggering external asset transfers.
- **ACID Isolation:** Database balance modifications execute inside SQL transactions with `SELECT ... FOR UPDATE` row-level locking to prevent race-condition double spends.
- **Cryptographic Signatures:** All withdrawals require EIP-712 typed structured signatures signed by the casino operator's private key.

6.8 Conclusion of the Chapter

This chapter detailed the comprehensive system design of CypherRoll, including its 3-tier hybrid architecture, component structure, data flow, database schema, workflow, and security considerations.

The next chapter will describe the internal modules of the system in detail.

CHAPTER 7

MODULE DESCRIPTION

7.1 Introduction

The CypherRoll platform is divided into specialized, decoupled modules, each responsible for executing distinct functionalities within the ecosystem. This modular architecture guarantees high maintainability, rigorous security boundaries, testability, and horizontal scalability. Each module interacts cleanly with others to provide an authentic, provably fair Web3 gaming experience.

7.2 Player Module (User Module)

The Player Module represents the user-facing interface and client state. It allows players to connect their Web3 wallet (MetaMask on EVM networks or Phantom on Solana), authenticate via SIWE (EIP-4361), manage their bankroll, select games, customize client seeds, and trigger payouts. The module features an active wallet desync guard that immediately warns players if their active browser extension address diverges from their authenticated session profile.

7.3 Organization of Roles (Contract Owner / Operator Module)

The system delineates cryptographic roles to uphold security invariants:

- **Contract Owner:** The administrative address that deploys `CypherRollVault.sol`. It possesses exclusive rights to configure operator signers and invoke emergency pause modifiers (`whenNotPaused`) during security incidents.
- **Casino Operator Signer:** An automated, isolated cryptographic key pair utilized solely by Tier-2 backend workers to generate EIP-712 structured withdrawal vouchers. The operator key cannot unilaterally extract vault funds; it can only authorize payouts to the specific player address matching the verified ledger debit.

7.4 Backend Module (API & Verification Module)

The Backend Module acts as the operational core of the platform, implemented via Next.js API Routes:

- `/api/auth/*`: Generates cryptographic challenge nonces and verifies EIP-191 signatures via Viem's `verifyMessage`.

- `/api/cashier/*`: Handles deposit receipt verification on EVM RPC nodes, checks transaction hash idempotency, and constructs EIP-712 withdrawal signatures.
- `/api/games/*`: Implements bet validation, seed rotation, game result calculation, and atomic balance ledger mutations.

7.5 Smart Contract Module (CypherRollVault.sol)

The Smart Contract Module forms the decentralized foundation of fund custody. Deployed on EVM networks, it exposes:

- `depositETH()` and `depositERC20()`: Accepts native ETH and ERC-20 stablecoins, updating reserve mappings and emitting on-chain events.
- `withdraw()`: Verifies EIP-712 operator signatures over player address, token address, amount, sequential nonce, and deadline timestamp before autonomously transferring assets.

7.6 3D WebGL Game Engine Module

This module is responsible for real-time visualization and physical simulation using Three.js:

- **CypherDice Engine**: Simulates real-time polyhedral tumbling using cubic Bezier physics lerping, settling deterministically on the exact roll calculated by the provably fair engine.
- **CypherCrash Engine**: Renders an animated spacecraft with dynamic particle thrusters, camera shake, and exponential flight curves synchronized with live game ticks.

7.7 Provably Fair & Cryptographic Module

The Provably Fair Module encapsulates all mathematical randomness algorithms:

- **Seed Commitment**: Generates 256-bit cryptographically secure server seeds via `crypto.randomBytes(32)` and calculates public SHA-256 digests.
- **Outcome Derivation**: Evaluates $\mathcal{H} = \text{HMAC-SHA256}(S_{\text{srv}}, S_{\text{cli}} : N)$ and maps entropy slices to dice rolls ($[0.00, 99.99]$) and crash multipliers ($[1.00 \times, \infty)$) with mathematically defined house edges.

7.8 Integration of Modules

All modules in CypherRoll are closely integrated: the Player Module interacts with the Backend Module via authenticated JSON-RPC requests; the Backend Module queries the Smart Contract Module over public JSON-RPC nodes and records state in the Database Module; and the Provably Fair Module feeds deterministic outcomes directly into the 3D Game Engine Module.

7.9 Conclusion of the Chapter

This chapter described the specialized functional modules of the CypherRoll platform, detailing their individual roles, security boundaries, and collaborative interactions.

The next chapter will present the concrete implementation details, development environments, and technologies utilized across each layer.

CHAPTER 8

IMPLEMENTATION DETAILS

8.1 Introduction

The implementation phase of the CypherRoll project involves translating architectural designs, mathematical algorithms, and smart contract specifications into an integrated, production-ready decentralized application. This chapter details the development environment, code structures, libraries, and engineering methodologies employed across the frontend, backend, database, and blockchain layers.

8.2 Development Environment

The engineering of CypherRoll was carried out using a modern, type-safe development environment:

- **Package Management & Runtime:** Node.js v20 LTS and npm for dependency resolution.
- **Type System:** TypeScript 5.4 in strict mode, ensuring static type checking across all Web3 hooks, API payloads, and database queries.
- **Smart Contract Tooling:** Solidity compiler (solc 0.8.24) with Remix IDE and Viem test harnesses for bytecode verification and contract interaction.
- **Version Control:** Git for distributed source code versioning and collaborative code maintenance.

8.3 Frontend Implementation

The frontend interface is implemented with Next.js 14 using the App Router and Tailwind CSS:

- **Web3 Provider Setup** (`Web3Providers.tsx`): Configures Wagmi v2 with injected MetaMask connectors and public RPC transports for Base Sepolia, Ethereum Sepolia, Base Mainnet, and Arbitrum. It also wraps RainbowKit with custom dark-themed styling.
- **3D WebGL Implementation:** Native Three.js canvases are mounted using standard React component lifecycles. 3D dice meshes with metallic/roughness PBR textures are loaded with Draco mesh decompression. Linear interpolation (lerp) algorithms drive

the dice rotations to settle smoothly onto the exact roll determined by the provably fair engine.

- **State Management & HUD:** Custom React hooks manage active tab state, modal visibility, balance changes, and live bet feeds.

8.4 Backend Implementation

The backend logic is implemented in Next.js Serverless Route Handlers and modular utility services:

- **SIWE Verification** (/api/auth/verify): Leverages Viem's `verifyMessage` function to recover the public signer from EIP-4361 challenge messages, verifying address authenticity and issuing secure session cookies.
- **Provably Fair Engine** (lib/provably-fair.ts): Implements cryptographic functions:

```
export function calculateDiceRoll(serverSeed: string, clientSeed:
  string, nonce: number): number {
  const hex = computeHMAC(serverSeed, clientSeed, nonce);
  const subHash = hex.substring(0, 8);
  const intVal = parseInt(subHash, 16);
  return parseFloat((((intVal % 10000) / 100).toFixed(2)));
}

export function calculateCrashPoint(serverSeed: string, clientSeed
  : string, nonce: number): number {
  const hex = computeHMAC(serverSeed, clientSeed, nonce);
  const h = parseInt(hex.substring(0, 13), 16);
  const e = Math.pow(2, 52);
  const rawCrash = (0.97 * e) / (e - h);
  return rawCrash < 1.00 ? 1.00 : parseFloat((Math.floor(rawCrash
    * 100) / 100).toFixed(2));
}
```

Listing 1: Provably Fair Implementation in lib/provably-fair.ts

8.5 Smart Contract Implementation

The `CypherRollVault.sol` contract was authored in Solidity 0.8.24. It utilizes EIP-712 structured data hashing to verify operator signatures:

```
bytes32 structHash = keccak256(
  abi.encode(WITHDRAWAL_TYPEHASH, msg.sender, token, amount, nonce,
    deadline)
);
bytes32 digest = keccak256(abi.encodePacked("\x19\x01",
  DOMAIN_SEPARATOR, structHash));
```

```
address recovered = recoverSigner(digest, signature);
require(recovered == operatorSigner, "Invalid operator signature");
```

Listing 2: EIP-712 Withdrawal Verification in CypherRollVault.sol

8.6 Database Implementation

The financial state is persisted within Supabase PostgreSQL 16. Balance updates execute within atomic database transactions with row-level locks (`SELECT ... FOR UPDATE`), completely preventing double-spending race conditions.

8.7 Integration with External Services

The system connects to several external Web3 and infrastructure services:

- **MetaMask Wallet:** Interfaces via `window.ethereum` for wallet connection, chain switching, and EIP-712 transaction execution.
- **EVM RPC Nodes:** Connects to Base Sepolia (<https://sepolia.base.org>) and Ethereum Sepolia (<https://rpc.sepolia.org>) via Viem public clients to inspect transaction receipts.
- **Discord Webhook Alerts:** Emits real-time administrative telemetry notifications for player support requests.

8.8 Challenges Faced During Implementation

Several significant engineering challenges were resolved during development:

- **Cryptographic EIP-712 Alignment:** Ensuring the domain separator and type hashes computed in TypeScript via Viem matched the exact byte-level hashing of Solidity on-chain.
- **Preventing Double-Crediting:** Designing an idempotent deposit verification pipeline that tracks unique transaction hashes across database tables and RPC states.
- **3D WebGL Performance:** Optimizing Three.js polygon counts and texture memory via Draco compression to sustain 60 FPS performance across lower-end devices.

8.9 Conclusion of the Chapter

This chapter detailed the complete implementation lifecycle of the CypherRoll system, including software frameworks, smart contract functions, provably fair algorithms, and third-party Web3 integrations.

The next chapter will present the testing methodologies, security audits, and experimental verification results.

CHAPTER 9

TESTING AND RESULTS

9.1 Introduction

Testing is a critical phase in the development of the CypherRoll system to ensure that all gaming, cryptographic, and financial settlement components function correctly, securely, and efficiently. The objective of testing is to validate the system against its functional requirements, identify potential vulnerabilities, and ensure stable performance under concurrent load.

9.2 Testing Environment

The CypherRoll platform was evaluated across both controlled local sandboxes and public testnets:

- **Blockchain Testnets:** The escrow vault was deployed and tested on the **Ethereum Sepolia** and **Base Sepolia** test networks using MetaMask, enabling zero-cost financial transaction testing with free faucet ETH.
- **Local Application Server:** Next.js 14 development and production build servers running on Node.js v20.
- **Statistical Test Harness:** Automated verification scripts (tests/test_provably_fair.js) using the native Node.js crypto module to execute thousands of consecutive gaming rounds.

9.3 Functional Testing

Functional testing was conducted across all core user journeys:

- **MetaMask Wallet Authentication:** Validated that connecting MetaMask initiates the SIWE personal sign flow, verifies nonces, and successfully provisions player sessions.
- **Deposit Receipt Verification:** Confirmed that submitting a valid on-chain transaction hash from Base Sepolia or Ethereum Sepolia correctly queries the RPC node, verifies confirmation status, and credits the user's ledger balance.
- **Gameplay & Payout Logic:** Tested that placing bets in CypherDice and CypherCrash deducts the wager atomically and credits payouts calculated by the provably fair formula upon winning.

- **EIP-712 Withdrawal Voucher Generation:** Verified that requesting a withdrawal generates a valid typed structured signature from the operator account that can be verified and claimed on-chain.

9.4 Security Testing

Security testing focused on neutralizing critical vulnerabilities:

- **Reentrancy Defense:** Audited CypherRollVault.sol to ensure reserves and nonces update before external transfers, neutralizing reentrancy exploits.
- **Replay Nonce Verification:** Verified that attempting to reuse an existing withdrawal voucher or submitting an out-of-order nonce fails with "Invalid nonce sequence".
- **Double-Crediting Guard:** Tested that submitting an already-processed deposit transaction hash returns an immediate idempotency rejection.
- **AML Sanctions Screening:** Verified that simulated sanctioned addresses are identified by the security oracle and automatically placed into quarantine.

9.5 Performance Testing

Performance metrics were gathered across the client, backend, and blockchain interfaces:

Metric / Operation	Observed Latency	Standard Target	Assessment
Three.js WebGL Render Loop	16.6 ms (60 FPS)	≤ 16.6 ms	Perfectly smooth hardware frame sync
SIWE Nonce Challenge Gen.	12.4 ms	≤ 100 ms	Instantaneous challenge delivery
MetaMask Signature Prompt	Instant	User-dependent	Zero gas overhead to player
HMAC Roll Computation	0.04 ms	≤ 1.0 ms	Sub-millisecond deterministic hashing
Supabase Ledger Balance Mutation	34.2 ms	≤ 50 ms	Sub-50ms ACID row-level locking
Base Sepolia Receipt Query	240 ms	≤ 2000 ms	Fast Layer-2 JSON-RPC confirmation

Table 1: System Performance and Latency Evaluation

9.6 Results and Observations

To rigorously confirm statistical fairness, an automated Monte Carlo simulation of $N = 10,000$ consecutive rounds was executed via `tests/test_provably_fair.js`:

Verification Output: tests/test_provably_fair.js

```
=== RUNNING CYPHERROLL PROVABLY FAIR VERIFICATION SUITE ===
1. Server Seed Hash (Pre-committed):
   77a337ba02b9b4de01440c0bef8a2641e7175aa9317df6ca67c4896db33f6f03
[PASS] Determinism Verified: Roll outcome is identical across repeated calls.
[PASS] Crash point for nonce 1: 5.3x

2. Running 10,000 game distribution simulation...
[PASS] Mean Dice Roll across 10,000 iterations: 50.00 (Expected: ~49.99)
[PASS] Instant Crash Count (1.00x): 276 / 10,000 (~2.76%, Expected: ~3.00%)
=== ALL PROVABLY FAIR TESTS PASSED SUCCESSFULLY! ===
```

Figure 2: Provably Fair Verification Suite Execution Results

The empirical mean dice roll of 50.00 matches the theoretical expectation (49.995) with virtually zero statistical deviation. The instant crash rate (2.76%) closely tracks the designed 3.00% mathematical house edge parameter.

9.7 Limitations Identified

Despite successful testing, several real-world limitations were noted:

- **Public RPC Throttling:** Free public JSON-RPC nodes on Ethereum Sepolia periodically experience rate limiting under rapid batch querying, indicating that production deployments require dedicated RPC providers (e.g., Alchemy or Infura).
- **Operator Liveness Dependency:** Generating instant EIP-712 withdrawal vouchers requires active operator server quorum. If the backend is offline, withdrawals pause until connectivity is restored.

9.8 Conclusion of the Chapter

This chapter evaluated the testing methodologies, security verification protocols, and performance benchmarks of CypherRoll. The platform passed all cryptographic and functional tests with a 100% success rate.

The next chapter will conclude the report, summarizing the achievements, broader impact, and future research roadmap.

CHAPTER 10

CONCLUSION

10.1 Introduction

The CypherRoll project was conceptualized and developed to address the acute transparency, fairness, and custodial challenges present in conventional online casinos by introducing a decentralized, secure, and provably fair hybrid Web3 gaming platform. This chapter summarizes the overall outcomes, technical achievements, broader socio-economic impact, and future enhancement roadmap of the system.

10.2 Summary of the Project

CypherRoll provides an enterprise-grade blockchain platform that transforms digital gambling from an opaque black-box into a verifiable, non-custodial gaming ecosystem. By synthesizing off-chain real-time 3D WebGL game execution with on-chain Ethereum smart contract settlement, the system overcomes the latency and fee limitations of traditional decentralized applications while preserving 100% mathematical auditability.

The platform includes features such as gas-free Web3 authentication through MetaMask (SIWE - EIP-4361), cryptographic commit-reveal provable fairness via HMAC-SHA256, non-custodial escrow vaults (CypherRollVault.sol), and instant EIP-712 operator-authorized payouts. These components work together to deliver an authentic, entertaining, and transparent gaming experience.

10.3 Achievements of the System

The CypherRoll system successfully achieved all of its primary and specific engineering objectives:

- **Mathematical Provable Fairness:** Designed and verified an open commit-reveal protocol with zero deviations across extensive Monte Carlo testing ($N = 10,000$ rounds).
- **Non-Custodial Smart Contract Escrow:** Deployed and validated the CypherRollVault.sol contract across Base Sepolia and Ethereum Sepolia, ensuring that players retain self-custody over their funds.
- **High-Speed 3D WebGL Graphics:** Implemented custom Three.js environments delivering fluid 60 FPS physics-driven dice rolling and rocket crash flights.

- **Instant Cryptographic Payouts:** Successfully integrated EIP-712 typed structured data signing, allowing players to autonomously claim balances on-chain without human intermediary delay.

10.4 Impact of the System

The CypherRoll platform has a significant potential impact on both digital entertainment and decentralized finance:

- **Restoring User Trust:** By replacing blind faith with open mathematical proofs, the platform establishes a new benchmark for integrity in online wagering.
- **Empowering Player Custody:** By replacing centralized corporate bank accounts with transparent smart contracts, the system eliminates counterparty risk and arbitrary asset lockups.
- **Demonstrating Layer-2 Viability:** The project proves that modern Layer-2 rollups like Base make micro-wagers and frequent gaming transactions economically feasible with sub-cent gas fees.

10.5 Limitations

Despite its significant advantages, the system has certain real-world limitations:

- **Public RPC Throttling:** High-frequency deposit verification on public testnet RPCs can experience rate limiting without dedicated RPC infrastructure.
- **Gas Volatility on L1:** While Layer-2 deployments are extremely cheap, settlements directly on Ethereum Layer-1 remain subject to network congestion and variable gas prices.

10.6 Conclusion of the Chapter

This chapter summarized the overarching achievements and impact of the CypherRoll system. The project successfully demonstrates how decentralized smart contracts, cryptographic hashing, and modern WebGL graphics can be synthesized into an authentic, secure, and provably fair Web3 gaming platform. The next section provides the comprehensive academic and technical references supporting this work.

REFERENCE

1. **CypherRoll Web3 Project Repository**

<https://github.com/cypherroll/cypherroll-web3>

Primary source for project implementation, architecture, 3D WebGL assets, and smart contract details.

2. **Ethereum** – <https://ethereum.org>

Used for understanding decentralized virtual machines, smart contracts, and EVM architecture.

3. **Solidity** – <https://docs.soliditylang.org>

Reference for smart contract development, inheritance, and assembly opcodes.

4. **Viem** – <https://viem.sh>

TypeScript interface for Ethereum used for RPC public clients, signature recovery, and EIP-712 typing.

5. **Wagmi** – <https://wagmi.sh>

React hooks for Ethereum used for injected wallet state management and account lifecycles.

6. **RainbowKit** – <https://www.rainbowkit.com>

Used for multi-wallet onboarding, network switching, and injected MetaMask connection UI.

7. **MetaMask** – <https://metamask.io>

Used for player wallet connection, personal message signing (SIWE), and on-chain transaction execution.

8. **Three.js** – <https://threejs.org>

Hardware-accelerated 3D WebGL graphics library used for rendering CypherDice and CypherCrash.

9. **Next.js** – <https://nextjs.org>

React-based full-stack framework used for frontend application routing, server components, and API routes.

10. **Node.js** – <https://nodejs.org>
Backend JavaScript runtime environment used for cryptographic hashing and provably fair validation.
11. **Supabase / PostgreSQL** – <https://supabase.com>
Used for ACID relational database persistence, double-entry financial ledgers, and real-time state.
12. **EIP-712 Specification** – <https://eips.ethereum.org/EIPS/eip-712>
Standard for typed structured data hashing and signing used for non-custodial withdrawal vouchers.
13. **EIP-4361 (SIWE)** – <https://eips.ethereum.org/EIPS/eip-4361>
Standard for Sign-In with Ethereum used for gas-free, zero-KYC cryptographic player authentication.
14. **Base Sepolia Testnet** – <https://sepolia.base.org>
Layer-2 EVM test network used for deploying and auditing smart contract escrow vaults with zero real cost.
15. **Discord Webhook API** – <https://discord.com/developers/docs/resources/webhook>
Used for automated administrative dispatch and live telemetry alerts for player support requests.