Name: Pratyush Jaiswal

Roll: 18EE30021

HARDWARE:

Histicon Kivin 65x browssor:

4:6250 Hardware:

4 x Contex - A53 CPV : 4x Corten - A53

Process ;

lones:

480 MH2-1709 MH2 Frequencies:

1402 MH2-2362 MHZ

Interactive Geovernor:

braphics:

ARM Vendor:

hPV: Mali-T830

Openfil: OPen 6.L ES 3.2 v1. r28 po-01 rel 0.7 140 56 f gede 632.

Wilhow libbarto No.1

Vulkan Support: Yes

Resolution: 2160 × 1080

Screen density: 480 dp? (xxhdpi)

Screen Size: 5.9 in/ 151 mm

18:9 Aspert Ratio:

Frame Rate: 60.00004 Hz

Memory:

· Storage:

RAM : 46R Size: 326B

Type: LPDDR3 932 MH2 Internal Storage: {2ts

Channels: 32-bit Qual Felesystem: 1245
Channel System Storage:
Telesystem: ent4

```
SYSTEM:
DEVICE: Huawei Honor FX
 Model: BND-AL10
 Product: BND-AL 10
  Device: HWAND-H
  Roard; BND-L22
  Mont: HUWAEI
  Radio: 21660B269SOD7COOO, 21660B269SOD7COOO
DRERATING SYSTEM:
  Android Version: 9 (Android Pie)
                OND-AL10 9.1.0.168 (C675E2R111)
                28
   APT .º
   Build :
  EMUI: EmotionUI 9.1.0
  Architectore: aarch 6+ (64 bit)
  Instruction Sets: arm 64-v&a armabi-v7a armeani
  Kernel: 4.9.148 # 1 SMP PREEMPT The Jun 23
                13:56:48 CST 2020 aarch 64.
Battery:
 Information:
            broad
    Health:
    Capacity: 3340 mAh
Technology: Li-Poly.
           3340 mAh.
              Non removable
Network:
```

Technology: GESM MISPAL LITE

CAMERA:

FRONT CAMERA; 8.00 MD HOO MAIN CAMERA: 15.9 MP 6/2-2 3624 × 2448 Kesolution 6 460\$ 13456 Insordize: 5.25 x 3.95 nm Vixel Size; 1.14 pur 2-84 mm Focal length: 3-83 mm 9.48. 65.7° Horizontal (rop factor: 6.6x Field of View; 68.9° Hoxizondal 1/10000 - 18 Shutter Speed: 1/10000 - 1 8. 50-1166 TSO semishvity 50-3200 range: No Mash: Supported No Video Stabilization: No No Optred Trage No . Stabilization : No . Supported At lock: Supported Supported WR bek: Supported Manual Exposure Modes: Manuel, Anto, flowh Monwal Antofocus Modes: Manual, Anto flash Continuous Video & picture Scene modes: Face priority, Action, Portrait asame off Color effects: Of 10 Mex ferer Court: 10 Simple Tou detect Mode: Simple Limited Courses 2 API limited. support :

Senson: Tenpercotures: Temperature Sensors ush port, Rattery, pa-0, Shell frame, charreger, docxoo, Systemh, gpu, sor-thermal, galustero, denstor 1 LAYROSCOPE: ST Meroelectronies Cry ros cope ACCELEROMETER: KIONIX KX023 biravity; MAGNETIC FIELD: Hurawer brown ty LINEAR ALLELERATION; MAG: - ALM 09918 Husar Merawil Linear Acceleration ORIENTATION: Musael Orientation Rotation Vector: Ko tation Vector becomagnetic Hurawei Rotation Vector Rotation Vector lthHT; Drago ADDS 9922 Step Coenter 3 Proximity: Avago AP 059922 Huavei Step Counter

Body:

Demensions: 15(.5 x75.3 x 7.6 mm

Demensions: 165 g 15.8202)

Weight: Glass front, aluminium back & frame

Ruild: Glass front, aluminium back & frame

SIM: Hybrid Aual Sim (Naw SIM, dual Stand-by)