OOPJ: CCEE Practice Quiz 1

Total points 18/20



Duration: 30 Mins

The respondent's email (pratyushmahajan06@gmail.com) was recorded on submission of this form.

0 of 0 points

Name *		
Pratyush Mahajan		
PRN *		
240840320076		
Centre *		
Kharghar	•	

18 of 20 points Questions

✓	What will the output of the code be? *	1/1
	public class PrintTest {	
	<pre>public static void main(String[] args) {</pre>	
	System.out.print("Hello ");	
	System.out.println("World!");	
	System.out.printf("Number: %d", 10);	
	}	
	}	
0	Hello World!Number: 10	
0	Hello World! Number: 10	
•	Hello World! /n Number: 10	~
0	HelloWorld!Number: 10	
×	What is the significance of using String args instead of String[] args in the main method?	*0/1
0	It is an invalid syntax.	
	It allows passing multiple string arguments in the command line.	×
0	It does not affect functionality; both are equivalent.	
0	It prevents passing arguments to the program.	
Corr	rect answer	
	It does not affect functionality; both are equivalent.	

✓ What concept is demonstrated in Line 1? *	1/1
public class Test {	
<pre>public static void main(String[] args) {</pre>	
int a = 10;	
Integer b = a; // Line 1	
System.out.println(b);	
}	
}	
Implicit Unboxing	
Explicit Boxing	
Implicit Boxing	~
Explicit Unboxing	

```
What concept is demonstrated in Line 2? *
                                                                                1/1
 public class Test {
 public static void main(String[] args) {
 Integer a = 15;
 int b = a; // Line 2
 System.out.println(b);
 }
 Explicit Boxing
 Implicit Unboxing
 Implicit Boxing
 Explicit Unboxing
```

✓	What will happen when the code at Line 1 is executed? *	1/1
	public class Test {	
	<pre>public static void main(String[] args) {</pre>	
	String str = "abc";	
	int num = Integer.parseInt(str); // Line 1	
	System.out.println(num);	
	}	
	}	
0	It will compile and print abc.	
0	It will compile and print 0.	
•		✓
0	It will throw a NullPointerException.	

/	What will happen when the code at Line 1 is executed? *	1/1
	public class Test {	
	<pre>public static void main(String[] args) {</pre>	
	String[] arr = new String[3];	
	arr[0] = "Java";	
	System.out.println(arr[1].toUpperCase()); // Line 1	
	}	
	}	
0	It will compile and print null.	
0	It will compile and print JAVA.	
0	It will throw an ArrayIndexOutOfBoundsException.	
•	It will throw a NullPointerException.	✓
~	Which of the following is a correct example of Widening Conversion in Java?	*1/1
0	int i = 10; byte b = i;	
0	double d = 10.5; int i = d;	
0	float f = 10; double d = f;	✓

Ong I = 100; int i = I;

✓ Which of the following requires an explicit cast for Narrowing Conversion in Java?	* 1/1
 double d = 100.25; int i = (int) d; int i = 50; long l = i; byte b = 100; int i = b; loat f = 10.5F; double d = f; 	✓

✓ Which of the following statements is true about the memory storage of a *1/1 and b in the given code?
 public class Test {
 public static void main(String[] args) {
 int a = 10; // Line 1
 String b = "Hello"; // Line 2
 }
 }

 Both a and b are stored in the heap memory.

 a is stored in the stack memory, while b is stored in the heap memory.
 Both a and b are stored in the stack memory.
 a is stored in the heap memory, while b is stored in the stack memory.

✓	What are the default values of primitive and non-primitive data types in Java?	*1/1
0	Primitive types have default values of null, and non-primitive types have default values of 0.	
•	Primitive types have default values based on their type (e.g., 0 for int, false for boolean), and non-primitive types have null as their default value.	✓
\bigcirc	Both primitive and non-primitive types have null as their default value.	
0	Both primitive and non-primitive types have 0 as their default value.	
¥	Which of the following static methods is common to all wranner classes	* 0/1
×	Which of the following static methods is common to all wrapper classes in Java (such as Integer, Double, and Character)?	*0/1
×	in Java (such as Integer, Double, and Character)?	*0/1
×		*0/1
×	in Java (such as Integer, Double, and Character)?	*0/1
× ·	in Java (such as Integer, Double, and Character)? parseInt(String s)	*0/1 ×
× ·	in Java (such as Integer, Double, and Character)? parseInt(String s) valueOf(String s)	
	in Java (such as Integer, Double, and Character)? parseInt(String s) valueOf(String s) toString()	
	in Java (such as Integer, Double, and Character)? parseInt(String s) valueOf(String s) toString() compareTo(T another)	

```
✓ What will be the output of this code? *

                                                                                    1/1
    public class Test {
    public static void main(String[] args) {
    double d = 9.78;
    int i = (int) d; // Line 1
    System.out.println(i);
     9.78
     Error
```

```
✓ Consider the following Java code:

                                                                             *1/1
    public class BankAccount {
    static double interestRate = 0.03;
    static void updateInterestRate(double newRate) {
    interestRate = newRate;
    }
    double balance;
    void deposit(double amount) {
    if (amount > 0) {
    balance += amount;
    public class Main {
    public static void main(String[] args) {
    BankAccount.updateInterestRate(0.05);
    BankAccount account = new BankAccount();
    account.deposit(500.00);
    System.out.println("Interest Rate: " + BankAccount.interestRate);
```

	System.out.println("Account Balance: " + account.balance);
	}
	}
	Which of the following statements is correct regarding the code execution?
0	updateInterestRate can be called on the BankAccount instance, and deposit can be called on the class BankAccount.
	updateInterestRate can be called directly on the BankAccount class, and deposit must be called on an instance of BankAccount.
0	updateInterestRate can only be called on an instance of BankAccount, and deposit can be called on the BankAccount class.
0	Both updateInterestRate and deposit can be called directly on the BankAccount class.

✓	Given the following Java class:	* 1/1
	public class Customer {	
	String customerName;	
	double accountBalance;	
	void deposit(double amount) {	
	if (amount > 0) {	
	accountBalance += amount;	
	}	
	}	
	static void setDefaultBalance(double defaultBalance) {	
	// This method should set a default balance for all customers	
	}	
	}	
	Which of the following statements is correct about customerName, accountBalance, and setDefaultBalance?	
0	customerName and accountBalance are static variables; setDefaultBalance is a non-static method.	
	customerName and accountBalance are instance variables; setDefaultBalance is a static method.	✓
0	customerName is a static variable, accountBalance is a non-static variable, and setDefaultBalance is an instance method.	
0	Both customerName and accountBalance are static variables; setDefaultBalanc an instance method.	e is

✓ Consider the following Java method and its invocation:	*1/1
public class Calculator {	
void addNumbers(int num1, int num2) {	
System.out.println("Sum: " + (num1 + num2));	
}	
<pre>public static void main(String[] args) {</pre>	
Calculator calc = new Calculator();	
calc.addNumbers(10, 20);	
}	
}	
Which of the following statements correctly describes the terms "parameters" and "arguments" in the context of the provided code?	
num1 and num2 are arguments, and 10 and 20 are parameters.	
10 and 20 are parameters, and num1 and num2 are arguments.	
num1 and num2 are parameters, and 10 and 20 are arguments.	✓
Both num1 and num2, as well as 10 and 20, are parameters.	

✓	Given the following code snippet: *	1/1
	public class Test {	
	<pre>public static void main(String[] args) {</pre>	
	System.out.print("Hello, ");	
	System.out.print("World!");	
	}	
	}	
	What is the role of out in this context?	
•	out is an instance of the PrintStream class used for printing output to the console.	✓
0	out is a method that formats the output before printing it to the console.	
0	out is a variable that stores the current state of the system.	
0	out is a class that handles file operations in Java.	
✓	The JVM divides memory into different regions such as the Heap, Stack, and Method Area.	*1/1
	2. The Garbage Collector (GC) primarily manages the Stack memory.	
	3. The Method Area stores class metadata and static variables.	
	Which of the following statements is correct?	
•	Only statements 1 and 3 are correct; the Garbage Collector manages the Heap memory, not the Stack.	✓
0	All statements are correct.	
0	Only statement 1 is correct; the Garbage Collector does not manage the Method Area.	
0	Only statement 3 is correct; the Stack and Heap memory are not managed by the Garbage Collector.	e

/	Which of the following accurately describes the role of the JVM Execution Engine?	*1/1
0	It compiles Java bytecode into native machine code for execution on the host system.	
0	It translates Java source code into bytecode, which is then executed by the Java Compiler.	1
•	It interprets or compiles Java bytecode into native machine code for execution, and manages runtime optimizations such as Just-In-Time (JIT) compilation.	✓
0	It handles network communication and database interactions during Java application execution.	
/	Which of the following statements about Java data types is correct? *	1/1
0	The float data type has a higher precision than the double data type.	
•	char can hold any Unicode character and is stored as a 16-bit integer.	✓
0	The boolean data type can store multiple values like true, false, and null.	
0	The long data type is used to store decimal numbers with higher precision than float.	
~	Which of the following option leads to the portability and security of Java?	*1/1
•	Bytecode is executed by JVM	~
0	The applet makes the Java code secure and portable	
0	Use of exception handling	
0	Dynamic binding between objects	

Feedback of Mock 0 of 0 points

Level of exam *
EasyModerateTough
I promise, I will give my best in everything. * Yes
How was your Mock's experience? (No one word answer) * Good experience, have covered almost all concepts covered until now.

This content is neither created nor endorsed by Google. Report Abuse - Terms of Service - Privacy Policy

Google Forms