

```

#include <stdio.h>

int gcd(int a, int b) {
    while (b) {
        int t = b;
        b = a % b;
        a = t;
    }
    return a;
}

int lcm(int a, int b) {
    return (a * b) / gcd(a, b);
}

struct Task {
    int id;
    int burst;
    int period;
    int remaining;
};

int main() {
    int n;

    printf("1WA24CS216\n");
    printf("Enter number of processes: ");
    scanf("%d", &n);
    struct Task t[n];
    printf("Enter burst times:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &t[i].burst);
        t[i].id = i + 1;
    }
    printf("Enter periods:\n");
    for (int i = 0; i < n; i++) {

```

```

scanf("%d", &t[i].period);
t[i].remaining = 0;
}
for (int i = 0; i < n - 1; i++) {
    for (int j = i + 1; j < n; j++) {
        if (t[i].period > t[j].period) {
            struct Task temp = t[i];
            t[i] = t[j];
            t[j] = temp;
        }
    }
}
int hyper = t[0].period;
for (int i = 1; i < n; i++)
    hyper = lcm(hyper, t[i].period);
float util = 0;
for (int i = 0; i < n; i++)
    util += (float)t[i].burst / t[i].period;
float bound;
if (n == 1) bound = 1.0;
else if (n == 2) bound = 0.828427;
else if (n == 3) bound = 0.779763;
else bound = 0.693;
printf("\n%f <= %f => %s\n", util, bound, (util <= bound) ? "true" : "false");
printf("\nScheduling occurs for %d ms\n\n", hyper);
int remaining[n];
for (int i = 0; i < n; i++)
    remaining[i] = 0;
int last = -2;
for (int time = 0; time < hyper; time++) {
    for (int i = 0; i < n; i++) {

```

```
if (time % t[i].period == 0)
remaining[i] = t[i].burst;
}
int run = -1;
for (int i = 0; i < n; i++) {
if (remaining[i] > 0) {
run = i;
break;
}
}
if (run != last) {
if (run != -1)
printf("%dms onwards: Process %d running\n", time, t[run].id);
else
printf("%dms onwards: CPU is idle\n", time);
}
if (run != -1)
remaining[run]--;
last = run;
}
return 0;
```

}

OUTPUT

```
"C:\Users\Admin\Desktop\1W X + v
1WA24CS216
Enter number of processes: 3
Enter burst times:
3 2 2
Enter periods:
20 5 10

0.750000 <= 0.779763 ==> true

Scheduling occurs for 20 ms

0ms onwards: Process 2 running
2ms onwards: Process 3 running
4ms onwards: Process 1 running
5ms onwards: Process 2 running
7ms onwards: Process 1 running
9ms onwards: CPU is idle
10ms onwards: Process 2 running
12ms onwards: Process 3 running
14ms onwards: CPU is idle
15ms onwards: Process 2 running
17ms onwards: CPU is idle

Process returned 0 (0x0)  execution time : 18.102 s
Press any key to continue.
|
```