PROFESSIONAL
 EDUCATION
 STORE
 Search on Arduino.cc
 SIGN IN

 HARDWARE
 SOFTWARE
 CLOUD
 DOCUMENTATION
 COMMUNITY
 BLOG
 ABOUT

This page is also available in 2 other languages Change language

English



VARIABLES

STRUCTURE

LIBRARIES

IOT CLOUD API

GLOSSARY

The Arduino Reference text is licensed under a Creative Commons Attribution-Share Alike 3.0 License.

Find anything that can be improved? Suggest corrections and new documentation via GitHub.

Doubts on how to use Github? Learn everything you need to know in this tutorial.



Last Revision: 2019/02/21 Last Build: 2021/12/08

EDIT THIS PAGE

Reference > Language > Functions > Math > Map

map()

[Math]

Description

Re-maps a number from one range to another. That is, a value of **fromLow** would get mapped to **toLow**, a value of **fromHigh** to **toHigh**, values in-betv to values in-between, etc.

Does not constrain values to within the range, because out-of-range values sometimes intended and useful. The constrain() function may be used eith before or after this function, if limits to the ranges are desired.

Note that the "lower bounds" of either range may be larger or smaller than "upper bounds" so the map() function may be used to reverse a range of numbers, for example

$$y = map(x, 1, 50, 50, 1);$$

The function also handles negative numbers well, so that this example

$$y = map(x, 1, 50, 50, -100);$$

is also valid and works well.

The map() function uses integer math so will not generate fractions, when the math might indicate that it should do so. Fractional remainders are truncate and are not rounded or averaged.

Syntax

map(value, fromLow, fromHigh, toLow, toHigh)

Parameters

value: the number to map.

fromLow: the lower bound of the value's current range.

fromHigh: the upper bound of the value's current range.



COMMUNITY

BLOG

ABOUT

HARDWARE

 PROFESSIONAL
 EDUCATION
 STORE
 Search on Arduino.cc
 SIGN IN

DOCUMENTATION

Returns

CLOUD

SOFTWARE

The mapped value.

Example Code

```
/* Map an analog value to 8 bits (0 to 255) */
void setup() {}

void loop() {
  int val = analogRead(0);
  val = map(val, 0, 1023, 0, 255);
  analogWrite(9, val);
}
```

Appendix

For the mathematically inclined, here's the whole function

```
long map(long x, long in_min, long in_max, long out_min, long out_max) {
  return (x - in_min) * (out_max - out_min) / (in_max - in_min) + out_min;
}
```

Notes & Warnings

As previously mentioned, the map() function uses integer math. So fractions might get suppressed due to this. For example, fractions like 3/2, 4/3, 5/4 w be returned as 1 from the map() function, despite their different actual valu So if your project requires precise calculations (e.g. voltage accurate to 3 decimal places), please consider avoiding map() and implementing the calculations manually in your code yourself.

See also

Trademark Help Center NEWSLETTER FOLLOW US

Contact Us
Distributors

Careers

© 2021 Arduino

Terms Of Service Privacy Policy Security Cookie Settings

