

[Reference](#) [Language \(//www.arduino.cc/en/Reference/HomePage\)](https://www.arduino.cc/en/Reference/HomePage) | [Libraries \(//www.arduino.cc/en/Reference/Libraries\)](https://www.arduino.cc/en/Reference/Libraries) | [Comparison \(//www.arduino.cc/en/Reference/Comparison\)](https://www.arduino.cc/en/Reference/Comparison) | [Changes \(//www.arduino.cc/en/Reference/Changes\)](https://www.arduino.cc/en/Reference/Changes)

loop()

After creating a `setup()` function, which initializes and sets the initial values, the `loop()` function does precisely what its name suggests, and loops consecutively, allowing your program to change and respond. Use it to actively control the Arduino board.

Example

```
const int buttonPin = 3;

// setup initializes serial and the button pin
void setup()
{
  Serial.begin(9600);
  pinMode(buttonPin, INPUT);
}

// loop checks the button pin each time,
// and will send serial if it is pressed
void loop()
{
  if (digitalRead(buttonPin) == HIGH)
    Serial.write('H');
  else
    Serial.write('L');

  delay(1000);
}
```

[Reference Home \(//www.arduino.cc/en/Reference/HomePage\)](https://www.arduino.cc/en/Reference/HomePage)

Corrections, suggestions, and new documentation should be posted to the Forum (<http://arduino.cc/forum/index.php/board,23.0.html>).

The text of the Arduino reference is licensed under a Creative Commons Attribution-ShareAlike 3.0 License (<http://creativecommons.org/licenses/by-sa/3.0/>). Code samples in the reference are released into the public domain.

