

This page is also available in **2 other languages** [Change language](#)

English

## ◇ LANGUAGE

## FUNCTIONS

## VARIABLES

## STRUCTURE

## LIBRARIES


## IOT CLOUD API

## GLOSSARY

The Arduino Reference text is licensed under a [Creative Commons Attribution-Share Alike 3.0 License](#).

Find anything that can be improved? [Suggest corrections and new documentation via GitHub](#).

Doubts on how to use Github? Learn everything you need to know in [this tutorial](#).



Last Revision: 2019/12/09

Last Build: 2021/10/13

[EDIT THIS PAGE](#)[Reference](#) > [Language](#) > [Functions](#) > [Communication](#) > [Serial](#) > [Print](#)

# Serial.print()

## Description

Prints data to the serial port as human-readable ASCII text. This command can take many forms. Numbers are printed using an ASCII character for each digit. Floats are similarly printed as ASCII digits, defaulting to two decimal places. Bytes are sent as a single character. Characters and strings are sent as is. For example-

- `Serial.print(78)` gives "78"
- `Serial.print(1.23456)` gives "1.23"
- `Serial.print('N')` gives "N"
- `Serial.print("Hello world.")` gives "Hello world."

An optional second parameter specifies the base (format) to use; permitted values are BIN(binary, or base 2), OCT(octal, or base 8), DEC(decimal, or base 10), HEX(hexadecimal, or base 16). For floating point numbers, this parameter specifies the number of decimal places to use. For example-

- `Serial.print(78, BIN)` gives "1001110"
- `Serial.print(78, OCT)` gives "116"
- `Serial.print(78, DEC)` gives "78"
- `Serial.print(78, HEX)` gives "4E"
- `Serial.print(1.23456, 0)` gives "1"
- `Serial.print(1.23456, 2)` gives "1.23"
- `Serial.print(1.23456, 4)` gives "1.2345"

You can pass flash-memory based strings to `Serial.print()` by wrapping them with `F()`. For example:

```
Serial.print(F("Hello World"))
```

To send data without conversion to its representation as characters, use [Serial.write\(\)](#)

## Syntax

```
Serial.print(val)
```

```
Serial.print(val, format)
```

Help

val: the value to print. Allowed data types: any data type.

## Returns

print() returns the number of bytes written, though reading that number is optional.

Data type: size\_t.

## Example Code

```
/*
 * Uses a for loop to print numbers in various formats.
 */
void setup() {
  Serial.begin(9600); // open the serial port at 9600 bps:
}

void loop() {
  // print labels
  Serial.print("NO FORMAT"); // prints a label
  Serial.print("\t");        // prints a tab

  Serial.print("DEC");
  Serial.print("\t");

  Serial.print("HEX");
  Serial.print("\t");

  Serial.print("OCT");
  Serial.print("\t");

  Serial.print("BIN");
  Serial.println(); // carriage return after the last label

  for (int x = 0; x < 64; x++) { // only part of the ASCII chart, change to suit
    // print it out in many formats:
    Serial.print(x); // print as an ASCII-encoded decimal - same as "DEC"
    Serial.print("\t\t"); // prints two tabs to accommodate the label length

    Serial.print(x, DEC); // print as an ASCII-encoded decimal
    Serial.print("\t"); // prints a tab

    Serial.print(x, HEX); // print as an ASCII-encoded hexadecimal
    Serial.print("\t"); // prints a tab

    Serial.print(x, OCT); // print as an ASCII-encoded octal
    Serial.print("\t"); // prints a tab

    Serial.println(x, BIN); // print as an ASCII-encoded binary
    // then adds the carriage return with "println"
    delay(200); // delay 200 milliseconds
  }
  Serial.println(); // prints another carriage return
}
```

## Notes and Warnings

For information on the asynchronicity of `Serial.print()`, see the Notes and Warnings section of the [Serial.write\(\) reference page](#).

## See also

LANGUAGE [begin\(\)](#)

Help

HARDWARE

SOFTWARE

CLOUD

DOCUMENTATION

COMMUNITY

BLOG

ABOUT

- LANGUAGE peek()
- LANGUAGE flush()
- LANGUAGE println()
- LANGUAGE write()
- LANGUAGE SerialEvent()
- LANGUAGE Memory

Back to top

Trademark

Help Center

NEWSLETTER

FOLLOW US

Contact Us

Distributors

Careers

Enter your email to sign up

SUBSCRIBE

Help