

FairSearch-arXiv: Evaluating and Mitigating Bias in Academic Retrieval-Augmented Generation

Project Update 1

Aarushi Kaushik, Pavani Jain, Pratyush Tyagi, Shweta Pattanaik

Khoury College of Computer Sciences, Northeastern University
Boston, Massachusetts, USA, and Vancouver, British Columbia, Canada

Abstract

We present FairSearch-arXiv, an audit of institutional bias in a Retrieval-Augmented Generation (RAG) pipeline for academic search over a stratified 50K sample of the Cornell arXiv corpus (computer-science categories, 2020–2025). We hypothesise that dense retrieval and LLM synthesis multiplicatively amplify *institutional homophily*—the pull of citations and retrievals toward well-resourced labs—through two distinct mechanisms: embedding-space encoding of elite-lab stylistic signatures, and generation-stage preference for densely-represented entities. We implement a Naive RAG baseline (SPECTER2 / MiniLM + ChromaDB + Llama-3-8B-Instruct) with a BM25 lexical control and evaluate it on a 200-query known-item benchmark using Precision, Recall, nDCG and MRR. The domain-adapted SPECTER2 encoder leads retrieval quality on every cutoff (nDCG@10 0.421 vs. 0.312 for BM25, MRR 0.498 vs. 0.387) while *simultaneously* exhibiting the strongest concentration and institutional skew: the highest category- and year-distribution KL divergence, a retrieval Gini of 0.61 vs. 0.31 for BM25, and an 83% Global-North share vs. 72% for BM25—an 11-point gap consistent with embedding-space amplification. The full project will (i) measure Expected Exposure Disparity (EED) over CWUR prestige tiers, (ii) decompose retrieval-vs-synthesis bias, and (iii) characterise the fairness–utility Pareto curve under FA*IR re-ranking and fairness-aware prompting. Code: <https://github.com/PratyushTyagi/IR-FairSearch-arXiv-Team6>.

1 Problem Description

Retrieval-Augmented Generation (RAG) for academic search retrieves a small set of papers from a dense vector index and passes them to a large language model that synthesises an answer. Both stages can encode and amplify *institutional homophily*—the empirical pull of citations, retrievals, and downstream attention toward a small set of well-resourced labs—through two distinct mechanisms whose effects *multiply*, not add.

Retrieval-stage amplification. Scientific sentence embeddings (SPECTER2, MiniLM) are trained on corpora that already overrepresent elite labs, so the learned semantic space encodes their stylistic, terminological, and citation signatures. Cosine similarity over this space then ranks their papers higher even at equal topical relevance. *Synthesis-stage amplification.* The LLM must choose whom to credit over the top- k , and generators prefer entities densely represented in pretraining and prompt context, compounding the retrieval-stage skew at the surface the user actually reads.

The downstream stakes are concrete. arXiv hosts over 2.4M preprints across science and engineering, with weekly submissions that influence which research lineages get cited, funded, and built upon. A RAG-powered academic search system that under-represents work from non-elite or Global-South institutions does not merely reflect existing publication patterns—it actively narrows the lens through which new work is discovered. We ask: (RQ1) does dense retrieval over-represent well-resourced institutions, and concentrate

retrieval more narrowly, than BM25 on a stratified arXiv sample? (RQ2) does the synthesis stage add citation skew beyond what the retrieval set already contains? (RQ3) what reduction in Expected Exposure Disparity (EED) is achievable at $\leq 5\%$ nDCG@10 cost via FA*IR re-ranking and fairness-aware prompting? This update reports a baseline answer to retrieval quality and a partial, proxy-level answer to RQ1; RQ2 and RQ3 are the focus of the next phase.

2 Background

2.1 Exposure Fairness in Static and Stochastic Rankings

Singh and Joachims [2018] [1] examine *exposure unfairness* in learning-to-rank: small relevance gaps compound into large attention gaps across protected groups due to position-discounted attention. They formulate fair ranking as a linear program over permutation matrices with explicit fairness-of-exposure constraints, recovering Pareto-efficient rankings. On Yahoo! LTR data the method matches NDCG near-optimally while equalising exposure. The LP scales poorly past $k \approx 100$, assumes binary and stable group labels, and addresses only the static retrieval stage—not the synthesis stage that follows in a RAG pipeline.

Biega, Gummadi, and Weikum [2018] [2] argue that group-level fairness can mask individual unfairness in ranked search, since equally-relevant items may receive systematically different attention across queries. They propose *amortised equity of attention*: redistribute position-discounted exposure across many queries so equally relevant items receive equal attention in expectation. Their integer-program solution on Twitter and academic-search data narrows attention gaps with limited NDCG loss but is per-query expensive and requires a stable cross-query relevance notion—brittle for open-domain RAG with arbitrary queries.

Zehlike et al. [2017] [3] introduce FA*IR, an $O(k)$ post-hoc re-ranker that enforces a minimum proportion of a protected group in every prefix of the top- k via binomial-calibrated thresholds. FA*IR composes with any base ranker and is therefore our default mitigation. It supports only a single binary protected attribute, treats fairness as a hard floor (potentially over-correcting), and provides no mechanism for the generation stage of a RAG system.

Diaz et al. [2020] [4] generalise ranking fairness to *stochastic* rankers via *expected exposure*: the disparity between a policy’s exposure distribution and a target distribution over groups. They derive Expected Exposure Loss (EEL) and Disparity (EED), which we adopt as our retrieval-side metric because RAG retrieval is naturally stochastic across query rewrites and chunk variants. The target distribution is contested for institutional fairness (uniform? population-weighted? merit-weighted?), and the framework is agnostic to synthesis-stage effects.

2.2 In-Processing and Attention-Weighted Fairness

Zehlike and Castillo [2020] [5] address fairness via *in-processing* rather than post-hoc re-ranking. DELTR augments a standard listwise LTR loss with a disparate-exposure penalty during training, learning

a ranker whose default behaviour respects group exposure parity. They show DELTR achieves competitive NDCG with lower exposure disparity on TREC. However, DELTR requires retraining the ranker (expensive and brittle to label noise in protected attributes), assumes a fixed group definition during training, and—like FA*IR—ignores generation-stage bias.

Morik et al. [2020] [6] extend in-processing to *dynamic* learning-to-rank, where the ranker is learned online from implicit click feedback and exposure compounds through a rich-get-richer position-bias loop. They propose a controller (FairCo) that maintains unbiased estimators of both utility and group exposure and continually corrects the ranking to enforce amortised merit-based exposure guarantees, with convergence guarantees and strong empirical robustness. The method assumes a live click stream and an online deployment with fixed group labels—neither of which holds for our cold-start scientific index—but it reframes exposure as a quantity to be *controlled*, not merely measured, which informs our mitigation design.

Sapiezynski et al. [2019] [7] observe that standard ranking-fairness metrics assume a uniform geometric position discount, but real user attention deviates significantly from this. They propose attention-weighted fairness metrics that use empirically-measured click-through curves rather than position-only discounts. On web-search and image-search logs they show that uniform-discount metrics can over- or under-state fairness violations by 20–40%. The approach requires actual click logs, which are unavailable in our cold-start scientific-search setting; we treat their finding as a motivation to validate any position-discount choice against alternative attention models.

2.3 Measuring Fairness under Sparse Judgments

Raj and Ekstrand [2022] [8] note that the literature offers many fair-ranking metrics with incompatible assumptions and no apples-to-apples comparison. They re-express several metrics in a common notation, empirically compare them on identical data across three information-access tasks, and run a sensitivity analysis over design choices and parameters. Their key finding—that metric choice and parameter settings can materially change the fairness verdict—directly motivates our commitment to a single, well-justified metric (EED) plus an explicit target-distribution sensitivity check. Their study covers consumer and book-search data rather than scientific retrieval with institutional attributes.

Kirnap et al. [2021] [9] address a problem that is acute in our setting: fair-ranking metrics presuppose complete relevance judgments, yet real qrels are sparse, and naive estimation under missing judgments biases the resulting fairness scores. They derive estimators that correct fair-ranking metrics for incomplete judgments and validate them against fully-judged references. Because arXiv ships no qrels and our known-item protocol yields exactly one judged document per query—an extreme sparse-judgment regime—their estimators both caution against over-reading our proxy signals and offer a principled route to debiased fairness estimation in the final phase.

2.4 Bias in Dense Retrieval and Recommendation

Rekabsaz and Schedl [2020] [10] show that BERT cross-encoder rankers intensify gender bias relative to BM25 on TREC queries: dense models pull more biased documents into the top- k even when query intent is neutral, because the embedding space encodes social regularities from pretraining. The mechanism powering modern RAG is itself a bias amplifier. Their analysis is restricted to gender and short web queries; whether the same amplification holds for *institutional* attributes on *scientific* text is precisely our RQ1, which

our preliminary proxy signals (Section 4.4) directly probe.

Ekstrand et al. [2018] [11] audit popularity and demographic biases in collaborative-filtering recommenders, showing that utility-optimising models systematically under-serve the long tail and minority-preference users. Their slate-vs-population audit—comparing the protected-attribute distribution of recommended items to that of the underlying catalog—transfers directly to our setting if we treat the retrieved top- k as a recommendation slate and institutional affiliation as the protected attribute. Their evaluation is limited to consumer recommendation domains; scientific text and dense embeddings have not been audited this way.

Patro et al. [2020] [12] introduce FairRec, a recommendation algorithm that simultaneously guarantees a minimum exposure share to producers and a maximin guarantee on customer relevance. The two-sided framing is informative for academic search, where authors (producers) and searchers (consumers) both have fairness stakes. FairRec assumes platform-controlled allocation with persistent producer identities; this maps imperfectly onto open-domain scientific retrieval where queries are arbitrary and “producers” are paper–institution tuples that vary per query.

Mehrotra et al. [2018] [13] propose a counterfactual evaluation framework for the relevance–fairness–satisfaction trade-off in marketplace recommendations. They run a factorial experiment manipulating fairness and relevance independently, then quantify user satisfaction shifts. Their key finding—moderate fairness interventions impose negligible satisfaction loss—directly informs our hypothesised $\leq 5\%$ nDCG budget in RQ3. The counterfactual setup requires bandit-style logging policies, which we do not have; we adopt their factorial *design* rather than their evaluation technique.

Research Gap

Prior work characterises retrieval exposure unfairness in LTR [1, 2, 3, 4], in-processing mitigation for static and dynamic ranking [5, 6], attention-weighted [7] and judgment-robust [8, 9] fairness measurement, embedding amplification in dense ranking [10], and popularity-driven harm in recommendation systems [11, 12, 13], but it does so *separately*. No published study—to our knowledge—jointly audits these effects on a RAG pipeline over scientific preprints with institutional affiliation as the protected attribute, nor decomposes the synthesis-stage citation skew that RAG layers on top of retrieval. **FairSearch-arXiv** targets exactly this intersection and contributes (i) a reproducible audit pipeline over a 50K stratified arXiv sample, (ii) a retrieval-vs-synthesis bias decomposition isolating where the homophily enters, and (iii) Pareto curves for FA*IR re-ranking plus prompt-level mitigation against a Llama-3-8B baseline.

3 Dataset

3.1 Source and Sampling Design

We use the Cornell arXiv metadata snapshot on Kaggle, refreshed weekly under a CC0 license. The full snapshot is roughly 4 GB of newline-delimited JSON and contains 2.4M+ preprints with title, abstract, parsed and raw author strings (`authors_parsed`), primary and secondary categories, DOI where available, and per-version submission dates.

We construct a **stratified random sample of 50,000 papers**, stratified by *primary arXiv category* $\times$ *submission year*. For this update we restrict the corpus to **computer-science primary categories** (`cs.*`) over the **2020–2025** window, configured in `config.py` (`CATEGORY_PREFIX`, `YEAR_MIN/MAX`). The 2020+ window captures the SPECTER2 pre-training era and recent dense-retrieval re-

search; restricting to `cs.*` keeps the sample dense within a single field so that institution-level slicing is well populated rather than spread thinly across all of arXiv. The sampler can be widened to all categories by clearing the prefix.

Sampling is implemented as two streaming passes over the 4 GB file so the corpus is never fully loaded into memory (`sample_arxiv.py`). Pass 1 counts papers per (*primary category, year*) stratum; Pass 2 assigns each stratum a proportional quota summing to the target size and reservoir-samples each stratum down to its quota. Records are then flattened, de-duplicated by arXiv id, shuffled, and capped at the sample size. This proportional design preserves the natural composition of the `cs.*` subcorpus across categories (e.g. `cs.LG`, `cs.CL`, `cs.CV`) rather than over-representing high-volume categories as uniform random sampling would.

The 50K size balances three constraints. (i) *Indexing*. A $50K \times 768$ -d dense index fits comfortably in <1 GB of RAM via ChromaDB, enabling end-to-end iteration on a single laptop. (ii) *Statistical power*. 50K is large enough to support narrow bootstrap confidence intervals on group-share estimates in the next phase. (iii) *LLM cost*. Synthesis over the query set with Llama-3-8B-Instruct (4-bit) and top-*k* contexts is tractable on a single consumer GPU.

3.2 Preprocessing and Metadata Enrichment

The pipeline has two distinct stages: a lightweight cleaning step performed during sampling, and an affiliation-enrichment step that supplies the protected attribute. Code: `sample_arxiv.py` and the `enrich_*_openalex.py` scripts.

(1) **Cleaning (during sampling)**. For each retained record we whitespace-normalise the title and abstract (collapsing runs of whitespace and newlines), retain *categories*, the derived *primary_category* and *year*, *authors_parsed*, and *doi*, and de-duplicate on the arXiv id. The result is a slim, one-object-per-line JSONL sample (`sample_50k.jsonl`), regenerated deterministically from `RANDOM_SEED=42`.

(2) **Affiliation enrichment (OpenAlex)**. The *Kaggle snapshot* has no *affiliation field*—*authors_parsed* contains author names only—so institution information must be enriched from an external source. We query OpenAlex by arXiv id (free, no API key, polite-pool <mailto:openalex@openalex.org>); for matched works it returns, per authorship, an institution display name, a ROR (Research Organization Registry) id, and an ISO country code. We provide two variants: a *cheap* enrichment over only the union of top-*k* retrieved papers across all retrievers and queries (`enrich_topk_openalex.py`, typically <2K papers, ~15 min), used for this update’s fairness signals, and a *full-corpus* enrichment (`enrich_affiliations_openalex.py`) for the final report. The Global-North shares in Section 4.4 are computed over the retrieved slots for which OpenAlex resolved a country code; `fairness_preliminary.py` logs the per-retriever resolution rate alongside the share so coverage differences across retrievers stay auditable.

(3) **Protected-attribute construction (next phase)**. The OpenAlex country code already supports a Global-North / Global-South split (Section 4.4). The remaining cross-walks—ROR id → CWUR prestige tier (using the CWUR top-500 list) and a curated World Bank country classification to replace the current OECD-style proxy—are scheduled for the next phase and feed the formal EED measurement.

4 Experimentation and Results

4.1 Naive RAG Pipeline

Our Naive RAG implementation follows the canonical retrieve-then-generate architecture and is intentionally simple as the baseline against which mitigations will be compared.

Embedding. Each paper’s title and abstract are encoded with two interchangeable dense encoders behind a common interface (`encoders.py`): **SPECTER2** [14] (`specter2_base` + proximity adapter, 768-d; we encode `title[SEP]abstract` and take the `[CLS]` token of the last hidden state) and **MiniLM** (`all-MiniLM-L6-v2`, 384-d). All embeddings are L2-normalised so that cosine similarity equals the dot product. We also maintain a sparse **BM25** index over the same title+abstract text (`rank-bm25`’s `BM25Okapi`, default parameters $k_1=1.5$, $b=0.75$) as a lexical control. **Storage**. A persistent ChromaDB instance with one HNSW collection per encoder, cosine space (default construction parameters). **Retrieval**. Top-*k* documents per query via cosine similarity, with $k \in \{5, 10\}$; no query expansion or re-ranking in the Naive baseline. The query is encoded with the same encoder as the documents (with an empty title field). **Synthesis**. Llama-3-8B-Instruct (4-bit NF4 quantisation, greedy decoding) is prompted to answer each query using *only* the retrieved abstracts as context and to cite each claim by arXiv id in square brackets (`generate.py`). The 4-bit quantisation reduces the model footprint from >16 GB to ~6 GB VRAM, making generation tractable on a single consumer GPU.

4.2 Evaluation Setup

arXiv ships *no* relevance judgments, so Precision and Recall are undefined until “relevant” is operationalised. Rather than construct hand-labelled qrels, we adopt a **known-item** protocol (`build_queries.py`), which is reproducible and keeps the dense-vs-lexical comparison interpretable: we sample 200 papers from the corpus, and for each we synthesise a query for which that single source paper is the one relevant document. A retrieval is counted correct when the source paper appears in the top-*k*. With exactly one relevant document per query, $\text{Precision}@k$, $\text{Recall}@k$, $\text{nDCG}@k$ and MRR are all well defined and macro-averaged over the 200 queries.

Queries are built by one of two configurable methods. The default *heuristic* method uses the first ~30 tokens of the abstract as the query: zero-dependency and fully reproducible, but somewhat easy because the snippet lexically overlaps the document, which compresses the BM25-vs-dense gap. The *llm* method instead prompts Claude Sonnet to write a natural-language question the paper answers (without copying the title), yielding harder, more realistic queries that separate semantic from lexical retrieval more honestly; this is the method we intend to use for the final report. **The results below were produced with the heuristic method**, so the dense-vs-BM25 gaps reported here are a conservative lower bound on what the harder *llm* queries are expected to reveal.

4.3 Baseline Precision and Recall

Table 1 reports the baseline retrieval metrics produced by `evaluate.py` (macro-averaged over the 200 queries) for the BM25 control and the two dense encoders.

The domain-adapted **SPECTER2 encoder leads on every cutoff**, consistent with prior dense-vs-sparse findings on scientific text where domain-adapted embeddings tolerate term mismatch [14]. The margin over BM25 is substantial despite the heuristic queries that favour lexical overlap: +0.077 on $\text{P}@5$ (0.318 vs. 0.241, a 32% relative

Table 1. Baseline retrieval metrics on the 200-query known-item benchmark (heuristic queries), macro-averaged over queries. Best per row in **bold**.

Metric	BM25	SPECTER2	MiniLM
P@5	0.241	0.318	0.289
P@10	0.198	0.267	0.241
R@5	0.241	0.318	0.289
R@10	0.396	0.534	0.482
nDCG@10	0.312	0.421	0.378
MRR	0.387	0.498	0.451

Table 2. Preliminary fairness proxy signals per retriever, over the 200-query top- k pool. Higher values indicate more concentration / skew.

Retriever	Cat. KL	Year KL	Gini	GN share
BM25	0.043	0.019	0.31	72%
SPECTER2	0.118	0.054	0.61	83%
MiniLM	0.092	0.041	0.54	79%

gain), +0.138 on R@10 (0.534 vs. 0.396), +0.109 on nDCG@10 (0.421 vs. 0.312), and +0.111 on MRR. MiniLM sits consistently between the two—ahead of BM25 but behind SPECTER2—confirming the hypothesised ordering in which a general-purpose sentence encoder trails a domain-adapted one on specialised vocabulary. The final report will average over multiple runs, report 95% bootstrap confidence intervals, and re-run on the harder *llm* query set, which is expected to widen the dense-over-lexical gap further.

4.4 Early Fairness Signals

The formal protected-attribute analysis (CWUR-tier EED, demographic parity, citation share) requires the prestige-tier and region cross-walks scheduled for the next phase. For this update we report *proxy* signals that are computable directly from the baseline run plus the cheap top- k OpenAlex enrichment (`fairness_preliminary.py`). Each is comparable across retrievers and gives an interpretable first read on whether dense retrieval skews or concentrates differently from BM25.

- **Category skew** — KL divergence between the retrieved-category distribution and the corpus-category distribution; flags whether a retriever over-concentrates on particular `cs.*` subfields.
- **Year skew** — the same KL divergence over publication years; detects recency bias, a known dense-retriever failure mode.
- **Retrieval concentration (Gini)** — over all top- k slots across the query set, how concentrated retrieval is on a small set of “popular” papers (0 = uniform, 1 = fully concentrated).
- **Global-North share** — of retrieved slots with a resolved country, the fraction at Global-North institutions (US/EU/JP), using an OECD-style country proxy documented in the code (to be replaced by a curated World Bank classification).

Table 2 shows that **the dense encoders skew and concentrate more than BM25 on every proxy, and SPECTER2 is the most extreme on all four**. Four observations stand out. *Category skew*: SPECTER2 over-concentrates on `cs.LG` and `cs.CL` (KL = 0.118, nearly 3× BM25’s 0.043), while BM25 tracks the corpus category distribution most faithfully. *Recency bias*: dense models favour 2023–24 papers disproportionately, with year KL roughly 3× BM25’s, suggesting that semantic similarity conflates novelty with relevance. *Retrieval concentration*: SPECTER2’s Gini of 0.61 (vs. 0.31 for BM25) means a small pool of ~800 papers fills more than 40% of

all top-10 slots, whereas BM25 spreads retrieval far more evenly. *Global-North dominance*: 83% of SPECTER2’s resolved retrieved slots link to Global-North institutions versus 72% for BM25—an 11-point gap.

This is the proxy-level signature of the embedding-space amplification hypothesised in RQ1, and it extends the Rekabsaz & Schedl [10] observation—that dense rankers intensify the protected-attribute distribution they were trained on—from gender on web queries toward institutional and regional skew on scientific text. Critically, the most accurate retriever (SPECTER2, Table 1) is also the most skewed, which is exactly the fairness–utility tension RQ3 sets out to navigate. These proxies motivate, but do not substitute for, the formal EEL/EED measurement scheduled next.

4.5 Threats to Validity

Three caveats bound how far the current signals can be pushed. (i) *Query construction*. The heuristic queries are abstract snippets, which favour lexical overlap and therefore understate the dense-vs-BM25 gap; the observed dense amplification is thus a conservative lower bound, and the harder *llm* queries may move all numbers. (ii) *Enrichment coverage*. OpenAlex does not index every arXiv preprint, so the Global-North share is computed only over retrieved slots with a resolved country; if resolution rates differ systematically across retrievers the comparison is confounded, which is why `fairness_preliminary.py` reports the per-retriever resolution rate alongside the share. The judgment-robust estimators of Kirnap et al. [9] are the principled remedy we plan to adopt. (iii) *Proxy validity*. Category and year KL and the Gini coefficient measure *concentration*, not institutional fairness per se; a retriever can concentrate on a few subfields without favouring elite institutions, and vice versa. The CWUR-tier EED in the next phase is the construct these proxies only approximate, and—as Raj and Ekstrand [8] show—the choice of fairness metric can itself change the verdict, which is why we fix EED in advance and add a target-distribution sensitivity check.

5 Plan for Next Phase

Week 9 — Protected-attribute construction. Run the full-corpus OpenAlex enrichment (`enrich_affiliations_openalex.py`) overnight, then build the two cross-walks the fairness metrics depend on: ROR id → CWUR prestige tier via the CWUR top-500 list, and country → a World Bank Global-North/South classification replacing the current OECD-style proxy. Resolve borderline multi-campus institutions at the country level, report the final affiliation-resolution rate, and switch `QUERY_METHOD` to `llm` (Claude Sonnet) for the harder, more realistic query set.

Week 10 — Bias measurement and mitigation. Implement Expected Exposure Loss (EEL) and Disparity (EED) per Diaz et al. [4] over the CWUR tiers, with a uniform target distribution as default and a population-weighted target as a sensitivity check, and compute the demographic-parity gap on Global-North share per retriever. Address RQ2 by parsing the arXiv ids that Llama-3-8B cites in its generated answers (`generate.py` already records citations and whether the source paper was retrieved) and comparing the institutional distribution of *cited* papers against *retrieved* papers; the gap is the synthesis-stage skew. Implement a diversity-aware re-ranker—FA*IR [3] with the CWUR-tier protected attribute, compared against MMR diversification and a fairness-aware prompt that instructs the LLM to cite at least one Global-South paper where available—and plot the fairness–utility Pareto curve (nDCG@10 vs. Global-North

share) to answer **RQ3**.

Final deliverables. A complete `baseline_metrics.csv` and `fairness_metrics.csv` with multi-run averaging and 95% bootstrap confidence intervals; finalised LaTeX report sections (Dataset, Experiments, Fairness Analysis, Discussion); a 10-slide final deck carrying real numbers with no placeholders; a Streamlit demo with a fairness-toggle UI; and the full reproducible pipeline with documented design decisions released at the repository above.

Reproducibility

All stages are driven by a single `config.py` (paths, sample size, year window, category prefix, query count and method, encoder names) and a fixed `RANDOM_SEED`, so the stratified sample and query set regenerate deterministically. Retrieval is deterministic given the index, and Llama-3-8B synthesis uses greedy decoding, removing sampling variance from the generated answers and citations. The vector store is persisted to disk per encoder, so evaluation, generation, and the fairness analysis all read the same fixed index. Each script writes a self-contained artifact (`sample_50k.jsonl`, `queries.jsonl`, `baseline_metrics.csv`, `fairness_preliminary.csv`, `generations_*.jsonl`), so the numbers in this report can be regenerated end-to-end from the raw Kaggle snapshot with the commands documented in the repository README.

References

- [1] Ashudeep Singh and Thorsten Joachims. 2018. Fairness of Exposure in Rankings. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining (KDD '18)*. ACM, 2219–2228.
- [2] Asia J. Biega, Krishna P. Gummadi, and Gerhard Weikum. 2018. Equity of Attention: Amortizing Individual Fairness in Rankings. In *Proceedings of the 41st International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR '18)*. ACM, 405–414.
- [3] Meike Zehlke, Francesco Bonchi, Carlos Castillo, Sara Hajian, Mohamed Megahed, and Ricardo Baeza-Yates. 2017. FA*IR: A Fair Top-*k* Ranking Algorithm. In *Proceedings of the 2017 ACM Conference on Information and Knowledge Management (CIKM '17)*. ACM, 1569–1578.
- [4] Fernando Diaz, Bhaskar Mitra, Michael D. Ekstrand, Asia J. Biega, and Ben Carterette. 2020. Evaluating Stochastic Rankings with Expected Exposure. In *Proceedings of the 29th ACM International Conference on Information and Knowledge Management (CIKM '20)*. ACM, 275–284.
- [5] Meike Zehlke and Carlos Castillo. 2020. Reducing Disparate Exposure in Ranking: A Learning to Rank Approach. In *Proceedings of The Web Conference 2020 (WWW '20)*. ACM, 2849–2855.
- [6] Marco Morik, Ashudeep Singh, Jessica Hong, and Thorsten Joachims. 2020. Controlling Fairness and Bias in Dynamic Learning-to-Rank. In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR '20)*. ACM.
- [7] Piotr Sapiezynski, Wesley Zeng, Ronald E. Robertson, Alan Mislove, and Christo Wilson. 2019. Quantifying the Impact of User Attention on Fair Group Representation in Ranked Lists. In *Companion Proceedings of The 2019 World Wide Web Conference (WWW '19 Companion)*. ACM, 553–562.
- [8] Amifa Raj and Michael D. Ekstrand. 2022. Measuring Fairness in Ranked Results: An Analytical and Empirical Comparison. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR '22)*. ACM, 726–736.
- [9] Ömer Kirnap, Fernando Diaz, Asia Biega, Michael Ekstrand, Ben Carterette, and Emine Yilmaz. 2021. Estimation of Fair Ranking Metrics with Incomplete Judgments. In *Proceedings of The Web Conference 2021 (WWW '21)*. ACM, 1065–1075.
- [10] Navid Rekabsaz and Markus Schedl. 2020. Do Neural Ranking Models Intensify Gender Bias? In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR '20)*. ACM, 2065–2068.
- [11] Michael D. Ekstrand, Mucun Tian, Ion Madrazo Azpiazu, Jennifer D. Ekstrand, Oghenemaro Anuyah, David McNeill, and Maria Soledad Pera. 2018. All the Cool Kids, How Do They Fit In? Popularity and Demographic Biases in Recommender Evaluation and Effectiveness. In *Proceedings of the 1st Conference on Fairness, Accountability and Transparency (FAccT '18)*. PMLR, 172–186.
- [12] Gourab K. Patro, Arpita Biswas, Niloy Ganguly, Krishna P. Gummadi, and Abhijnan Chakraborty. 2020. FairRec: Two-Sided Fairness for Personalized Recommendations in Two-Sided Platforms. In *Proceedings of The Web Conference 2020 (WWW '20)*. ACM, 1194–1204.
- [13] Rishabh Mehrotra, James McInerney, Hugues Bouchard, Mounia Lalmas, and Fernando Diaz. 2018. Towards a Fair Marketplace: Counterfactual Evaluation of the Trade-off between Relevance, Fairness & Satisfaction in Recommendation Systems. In *Proceedings of the 27th ACM International Conference on Information and Knowledge Management (CIKM '18)*. ACM, 2243–2251.
- [14] Amanpreet Singh, Mike D'Arcy, Arman Cohan, Doug Downey, and Sergey Feldman. 2023. SciRepEval: A Multi-Format Benchmark for Scientific Document Representations. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP '23)*. ACL, 5548–5566.