

FairSearch-arXiv: Evaluating and Mitigating Bias in Academic Retrieval-Augmented Generation

Aarushi Kaushik, Pavani Jain, Pratyush Tyagi, Shweta Pattanaik
Khoury College of Computer Sciences, Northeastern University
Boston, Massachusetts, USA

Abstract

We audit a Retrieval-Augmented Generation pipeline over the Cornell arXiv dataset (2M+ preprints), decomposing retrieval- and synthesis-stage amplification of institutional homophily and characterising the fairness-utility trade-off of FA*IR re-ranking and fairness-aware prompting.

1 Problem Description

RAG for academic search retrieves papers from a dense vector index and passes them to an LLM that synthesises an answer. Both stages encode and amplify *institutional homophily*—the empirical pull of citations and retrievals toward well-resourced labs. *Retrieval-stage*: scientific sentence embeddings (SPECTER2, MiniLM) trained on corpora that overrepresent elite labs encode their stylistic and citation signatures, so cosine similarity ranks their papers higher *even at equal topical relevance*. *Synthesis-stage*: the LLM must choose whom to credit over the top- k and prefers densely-represented entities, compounding retrieval skew at the surface the user reads. The two effects multiply, not add. On 2M+ arXiv preprints, which papers get surfaced for a query like “*recent advances in retrieval*” decides which research lineage the next reviewer or grant panelist reads. We ask: (RQ1) does dense retrieval over-represent top-tier institutions vs. BM25? (RQ2) does synthesis add citation skew given a balanced top- k ? (RQ3) what EED reduction is achievable at $\leq 5\%$ nDCG@10 cost?

2 Background

Singh and Joachims [2018] [1] examine *exposure unfairness* in learning-to-rank: small relevance gaps compound into large attention gaps across protected groups. Their LP-based fair ranker matches NDCG on Yahoo! LTR but scales poorly past $k \approx 100$ and assumes binary, stable group labels.

Biega, Gummadi, and Weikum [2018] [2] propose *amortised equity of attention*: redistribute position-discounted exposure so equally relevant items receive equal attention in expectation. The IP solution narrows attention gaps with limited NDCG loss but is per-query expensive and assumes a stable cross-query relevance notion—brittle for open-domain RAG.

Zehlike et al. [2017] [3] introduce FA*IR, an $O(k)$ re-ranker enforcing a minimum proportion of a protected group in every top- k prefix via binomial thresholds. It composes with any base ranker (our default mitigation) but supports only one binary attribute and ignores generation-stage bias.

Diaz et al. [2020] [4] generalise ranking fairness to *stochastic* rankers via expected exposure (EEL/EED), our retrieval-side metric since RAG retrieval is stochastic across query rewrites. The required target distribution is contested for institutional fairness, and the framework is agnostic to synthesis-stage effects.

Rekabsaz and Schedl [2020] [5] show BERT cross-encoders intensify gender bias relative to BM25 on TREC: dense models pull biased documents into the top- k even at neutral query intent. Their analysis is restricted to gender on short web queries; the institutional analogue on scientific text is exactly our RQ1.

Ekstrand et al. [2018] [6] audit popularity and demographic biases in collaborative-filtering recommenders, showing utility-optimising models under-serve the long tail. Their slate-vs-population audit transfers if we treat the top- k as a slate, but their evaluation is limited to consumer domains—scientific text with dense embeddings is unaudited.

Research gap. Prior work characterises retrieval exposure [1–4], embedding amplification [5], and recommender popularity bias [6] separately. No published study jointly audits these on a RAG pipeline over scientific preprints with institutional affiliation as the protected attribute, nor decomposes synthesis-stage citation skew. **FairSearch-arXiv** contributes (i) a reproducible audit pipeline, (ii) a retrieval-vs-synthesis bias decomposition, and (iii) Pareto curves for FA*IR plus prompt-level mitigation. Code: <https://github.com/PratyushTyagi/IR-FairSearch-arXiv-Team6>.

3 Project Plan and Milestones

Table 1: Week 3–14 milestones with explicit exit gates.

Week	Phase	Milestone & exit gate
W3–W5	Data	Pull Kaggle snapshot; stratified 50K sample by category $\times$ year; ROR/CWUR affiliation extraction; EDA. <i>Gate</i> : $\geq 90\%$ affiliations resolved.
W6–W8	Baseline	SPECTER2 + MiniLM embed; ChromaDB index; Llama-3-8B synthesis; metrics (EEL/EED, parity@ k , citation-share). <i>Gate</i> : end-to-end query ≤ 3 s.
W9–W12	Eval + Mitig.	Measure RQ1/RQ2; FA*IR re-rank, MMR, fairness-aware prompt; fairness-utility Pareto curve.
W13–W14	Deliver	Streamlit UI with fairness toggle; final ACM report, code release, demo, slides.

References

- [1] Ashudeep Singh and Thorsten Joachims. 2018. Fairness of Exposure in Rankings. In *Proc. KDD '18*. ACM, 2219–2228.
- [2] Asia J. Biega, Krishna P. Gummadi, and Gerhard Weikum. 2018. Equity of Attention: Amortizing Individual Fairness in Rankings. In *Proc. SIGIR '18*. ACM, 405–414.
- [3] Meike Zehlike, Francesco Bonchi, Carlos Castillo, et al. 2017. FA*IR: A Fair Top- k Ranking Algorithm. In *Proc. CIKM '17*. ACM, 1569–1578.
- [4] Fernando Diaz, Bhaskar Mitra, Michael D. Ekstrand, et al. 2020. Evaluating Stochastic Rankings with Expected Exposure. In *Proc. CIKM '20*. ACM, 275–284.
- [5] Navid Rekabsaz and Markus Schedl. 2020. Do Neural Ranking Models Intensify Gender Bias? In *Proc. SIGIR '20*. ACM, 2065–2068.
- [6] Michael D. Ekstrand, Mucun Tian, Ion Madrazo Azpiazu, et al. 2018. All the Cool Kids, How Do They Fit In? Popularity and Demographic Biases in Recommender Evaluation. In *Proc. FAccT '18*. PMLR, 172–186.