

EX.NO : 10

**IMPLEMENTING ARTIFICIAL NEURAL NETWORKS FOR AN
APPLICATION USING PYTHON - REGRESSION**

AIM :

To implementing artificial neural networks for an application in Regression using python.

SOURCE CODE :

```
from sklearn.neural_network import MLPRegressor
from sklearn.model_selection import train_test_split
from sklearn.datasets import make_regression
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
%matplotlib inline

X, y = make_regression(n_samples=1000, noise=0.05, n_features=100)

X.shape, y.shape = ((1000, 100), (1000,))
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, shuffle=True, random_state=42)
clf = MLPRegressor(max_iter=1000)
clf.fit(X_train, y_train)
print(f'R2 Score for Training Data = {clf.score(X_train, y_train)}')
print(f'R2 Score for Test Data = {clf.score(X_test, y_test)}')
```

OUTPUT :

R2 Score for Test Data = 0.9686558466621529

RESULT :

Thus the python code is implemented successfully and the output is verified.

EX.NO : 11a

DECISION TREE CLASSIFICATION

AIM:

To classify the Social Network dataset using Decision tree analysis

Source Code :

```
from google.colab import drive
drive.mount("/content/gdrive")

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
dataset=pd.read_csv('/content/gdrive/My Drive/Social_Network_Ads.csv')

X = dataset.iloc[:, [2, 3]].values
y = dataset.iloc[:, -1].values
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.25, random_state =0)

from sklearn.preprocessing import StandardScaler
sc = StandardScaler()
X_train = sc.fit_transform(X_train)
X_test = sc.transform(X_test)

from sklearn.tree import DecisionTreeClassifier
classifier = DecisionTreeClassifier(criterion = 'entropy', random_state = 0)
classifier.fit(X_train, y_train)
y_pred = classifier.predict(X_test)


from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, y_pred)
print(cm)
from matplotlib.colors import ListedColormap
X_set, y_set = X_train, y_train
```

```

X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() -
1, stop = X_set[:, 0].max() + 1, step = 0.01), np.arange(start = X_set[:, 1].min() -
1, stop = X_set[:, 1].max() + 1, step = 0.01))
plt.contourf(X1, X2, classifier.predict(np.array([X1.ravel(), X2.ravel()]).T).reshape(X1.shape), al
pha = 0.75, cmap = ListedColormap(('red', 'green')))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1], c = ListedColormap(('red', 'green'))(i), label
=j)
plt.title('Decision Tree Classification(Training set)')
plt.xlabel('Age')
plt.ylabel('Purchase')
plt.legend()
plt.show()

```

OUTPUT:



RESULT:

Thus the python code is implemented successfully and the output is verified.