



Arrays & ArrayLists

Brandon Krakowsky



1



Arrays



2

Arrays

- An array is a way to store a collection of items, as a single unit
 - It's like a list in Python, but not exactly ...
- Arrays are defined with a *fixed number of slots*, each of which holds an individual item
 - You can add and delete items from those slots as needed
- Each item in an array is distinguished by a numerical *index* between 0 and the array size minus 1
 - This works exactly the same as list indexing in Python
- Arrays *can* contain any type of element value (primitive types or Objects), but you *can't* store different types in a single array
 - You can have an array of ints, an array of Strings, or even an array of arrays, but you can't have an array that contains, for example, both Strings and ints
- An array itself, is an *Object*



3

Creating Arrays – 1st Step

To create an array in Java, you first declare a variable to hold the array

- Array variables indicate the type of object the array will hold, followed by empty brackets [], and the name of the array
- For example, this declares an array of ints:
`int[] myArrayOfInts;`
- This declares an array of Strings:
`String[] myArrayOfStrings;`
- Imagine we have a Customer class. This declares an array of Customers:
`Customer[] myArrayOfCustomers;`

Ref: <https://docs.oracle.com/javase/8/docs/api/java/lang/reflect/Array.html>

4

Creating Arrays – 2nd Step

- The second step is to create an array object and assign it to that variable. There are two ways to do this.
- One way is to use the `new` operator to create a new instance of an array
- This creates a new array of Strings with 10 slots (sometimes called elements)
`String[] names = new String[10];` //declare and create instance of array of 10 Strings
 - When you create an array object using `new`, you must indicate how many slots that array will hold, inside the brackets []
 - This does not put actual String values in the slots -- you'll have to do that later
- This creates a new array of ints with 99 slots
`int[] temps; //declare array`
`temps = new int[99];` //create instance of array with 99 slots

Ref: <https://docs.oracle.com/javase/8/docs/api/java/lang/reflect/Array.html>

5

Creating Arrays – 3rd Step

The third step is to store things in the array

- You can access the value in any slot of an array by specifying the index number inside brackets []
 - Again, this works exactly the same as list indexing in Python
 - Remember, indexing starts at 0
- This creates an array of 3 doubles and sets the values
`double[] myDoubleArray = new double[3];`
`myDoubleArray[0] = 5.0;` //sets 1st value to 5.0
`myDoubleArray[1] = 4.1;` //sets 2nd value to 4.1
`myDoubleArray[2] = 3.9;` //sets 3rd value to 3.9

Ref: <https://docs.oracle.com/javase/8/docs/api/java/lang/reflect/Array.html>

6

Creating Arrays – 3rd Step

- This creates an array of 2 booleans and sets the values

```
boolean[] myBooleanArray = new boolean[2];
myBooleanArray[1] = true; //sets 2nd value to true
myBooleanArray[0] = false; //sets 1st value to false
```
- Note, if you use an index outside of 0 up to myArray.length - 1, you'll get an *ArrayIndexOutOfBoundsException*

Ref: <https://docs.oracle.com/javase/8/docs/api/java/lang/reflect/Array.html>

7

Initializing Arrays in One Line

Another way to create an array is to enclose the elements of the array inside curly braces {}, separated by commas

- This initializes the contents (values) of the array in the array declaration
- For example, this creates an array of ints with actual prime numbers

```
int[] primes = {2, 3, 5, 7, 11, 13, 19};
```
- This creates an array of Strings, with actual programming languages

```
String[] languages = {"Java", "C", "C++"};
```
- Imagine we have a Customer class. This creates an array of Customers, with actual customers

```
Customer[] customers = {new Customer("Brandon"), new Customer("Betsy")};
```
- The syntax above can only be used in the array declaration. You can't do this:

```
int[] composites;
composites = {4, 6, 8, 9, 10, 12, 14, 15, 16, 18, 20}; //illegal
```

Ref: <https://docs.oracle.com/javase/8/docs/api/java/lang/reflect/Array.html>

8

Length of An Array

Every array has a *length* variable, that tells how large the array is

- This array of ints has a length of 10

```
int[] scores = new int[10];
System.out.println(scores.length); //length of 10
```
- And this array of Customers has a length of 2

```
Customer[] customers = {new Customer("Brandon"), new Customer("Betsy")};
System.out.println(customers.length); //length of 2
```
- length* is an instance variable, not a method
 - On the other hand, Strings have a *length()* method
- Arrays cannot be easily resized
 - You'd have to create a new array, copy everything from the old array, and add the new elements to the new array

9

Stepping Through an Array – *for* Loop

You can use a *for* loop to visit (and/or set) every element in an array, using its index

- Here we iterate over an array using its *length*, where *i* represents the index of each item

```
for (int i = 0; i < scores.length; i++) {
    System.out.println(scores[i]);
}
```
- The name *i* is traditional for loops
 - i* is instantly recognizable as the index of an enclosing *for* loop
 - Note, inner (nested) loops typically use *j*, then *k*
- Use of *length* is always preferred over using a constant (hard-coded) value (such as 10)
 - Try not to do this: `for (int i = 0; i < 10; i++) { ... }`

10

Stepping Through an Array – *Enhanced for* Loop

You can also use an *enhanced for* loop to visit every element in an array

- This is like the *for x in list* syntax in Python
- Here we iterate over an array of Strings, where *n* represents each item in the array

```
for (String n : names) {
    System.out.println("Name: " + n);
}
```
- This simple structure allows you to visit each element of an array without explicitly expressing how to go from element to element using an index

11

Default Values for primitives

- If you declare a variable to have a given *primitive* type, for example:

```
int age;
double weight;
boolean graduated;
```
- ... and if you have not yet assigned a value to it, for example, with:

```
age = 23;
weight = 145.6;
graduated = true;
```
- ... then the default value of that variable is:
 0 for non floating-point types (e.g. int, byte, short, long)
 0.0 for floating-point types (e.g. double, float)
 false for booleans

12

Default Values for Objects

- If you declare a variable to have a given **Object** (not **primitive**) type, for example:

```
Person john;
String name;
```
- ... and if you have not yet assigned a value to it, for example, with:

```
john = new Person();
name = "John Smith";
```
- ... then the default value of that variable is **null**
- **null** is a legal value, but there isn't much you can do with it
 - It's an error to refer to its fields, because it has none
 - It's an error to send a message to it, because it has no methods
 - **null** is basically a pointer that doesn't point to anything
 - It's very similar to Python's *None*

13

Default Values for Arrays

- When you create an array of **primitives** or **Objects**, but you haven't yet given values to each element in that array, the slots will have the default values associated with the type of array
 - primitives in a numeric array will default to 0 (or 0.0)
 - primitives in a boolean array will default to **false**
 - Objects in an array of Objects will default to **null**
- For example, here we create an array of 100 ints

```
int[] count = new int[100];
```

 - Every value in this array will default to 0
- We can then iterate over the array to set each value to a new int

```
for (int i = 0; i < count.length; i++) {
    count[i] = i + 1; //set each value to index i plus 1
}
```

14

Copying Arrays

- Array assignment does not copy array values
 - This is equivalent to the concept of assignment *by reference* in Python
- Given an array, we *can not* copy it directly

```
//Define array a
int[] a = {1, 8, 3};

//Create an array b of same size as a
int[] b = new int[a.length];

//Set b = a
//This does NOT copy elements of a to b
//It only makes b refer to same array object [1, 8, 3]
b = a;
```
- How do we know? Use **==** to compare object references

```
System.out.println(a == b); //true
```

15

Copying Arrays – Copy Elements

- You can, however, create a new array and copy the elements directly

```
//Define array a
int[] a = {1, 8, 3};

//Create an array b of same size as a
int[] b = new int[a.length];

//Copy elements of a to b
for (int i = 0; i < b.length; i++) {
    b[i] = a[i];
}
```

- Use == to compare the objects
System.out.println(a == b); //false
- And use the Arrays.equals method to compare the actual array contents (values)
System.out.println(Arrays.equals(a, b)); //true

16

Copying Arrays - Cloning

- You can also clone (create an exact copy of) an array using the clone method
 - Many Java Objects support cloning

```
//Define array a
int[] a = {1, 8, 3};

//Copy elements of a to b
int[] b = a.clone();
```

- Use == to compare the objects
System.out.println(a == b); //false
- Compare the actual array contents (values)
System.out.println(Arrays.equals(a, b)); //true

17

Array of Arrays

- Elements of an array can be arrays themselves
- The following creates an array of 3 arrays, each of which points to an array of 2 ints
int[][] table = new int[3][2];

```
//Then populates each slot in the array with an incremented count
int count = 1;
for (int i = 0; i < table.length; i++) { //get the length of the rows (vertical)
    for (int j = 0; j < table[i].length; j++) { //get the length of the columns (horizontal)
        table[i][j] = count++; //set count value in each array slot, then increment
    }
}
```

- This is like a "table" of 3 rows and 2 columns
 - table.length is 3
 - table[0].length is 2

18

Array of Arrays

- This is the same as defining and directly populating a 2-dimensional array like so

```
int[][] table2 = {
    {1, 2},
    {3, 4},
    {5, 6}
};
```
- To compare 2 nested arrays, you can use the *Arrays.deepEquals* method to do a deep comparison

```
System.out.println(Arrays.deepEquals(table, table2)); //true
```

19

Array of Arrays

- You can also have non-rectangular arrays
- Here we update the 3rd element in the array to point to an array of 20 ints

```
table2[2] = new int[20];
```
- This is the same as initializing a 2-dimensional array like so

```
int[][] table2 = {
    {1, 2},
    {3, 4},
    {0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0}
};
```

20

Accessing Values in Array of Arrays

- To access the value in any slot in a 2-dimensional array, specify the index number of the row inside brackets [], followed by the index number of the column inside brackets []
- For example:

```
int[][] table2 = {
    {1, 2},
    {3, 4},
    {0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0}
};
```
- To print the value in row 0 and column 0, you'd use:

```
System.out.println(table2[0][0]); //prints 1
```

21

22

Accessing Values in Array of Arrays

- To access the value in any slot in a 2-dimensional array, specify the index number of the row inside brackets [], followed by the index number of the column inside brackets []
- For example:

```
int[][] table2 = {  
    {1, 2},  
    {3, 4},  
    {0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0}  
};
```
- To print the value in row 0 and column 0, you'd use:
`System.out.println(table2[0][0]); //prints 1`
- To print the value in row 2 and column 2, you'd use:
`System.out.println(table2[2][2]); //prints 0`

Array Methods

- Arrays have very few attributes/methods
- *length* is useful, but there is no *add*, *remove*, *reverse*, etc.

Ref: <https://docs.oracle.com/javase/8/docs/api/java/lang/reflect/Array.html>

ArrayLists

24

ArrayLists

- An *ArrayList* is like an array, but much more flexible
 - It's just like a list in Python
- *ArrayLists* are *not* defined with a fixed number of slots – they have a *variable* length
- *ArrayLists* can *only* contain *Objects* and you *can't* store different types in a single *ArrayList*
- *ArrayLists* are part of Java's *Collections Framework*
 - *Collections* are defined in `java.util`
 - To use *ArrayLists* specifically, you have to import `java.util.ArrayList`
 - All *Collections* share similar methods (*add*, *remove*, *size*, etc.)
 - We'll learn more about *Collections* later in this course

Ref: <https://docs.oracle.com/javase/8/docs/api/java/util/ArrayList.html>

25

ArrayLists

- The syntax to create an *ArrayList* is:
`ArrayList<Data Type> myArrayList = new ArrayList<Data Type>();`
- Since you can't store *primitive* values in an *ArrayList*, you have to use the *wrapper* classes associated with *primitive* types
 - For *int*, use *Integer*; for *double* use *Double*, etc.
 - These are essentially the *Object* versions of the *primitive* data types, with additional methods/attributes
- This creates an *ArrayList* of *Integers*
`ArrayList<Integer> numberList = new ArrayList<Integer>();`
- And this creates an *ArrayList* of *Strings*
`ArrayList<String> stringList = new ArrayList<String>();`

Ref: <https://docs.oracle.com/javase/8/docs/api/java/util/ArrayList.html>

26

Size of An ArrayList

- Every *ArrayList* has a *size* method, that tells how large the *ArrayList* is
- This *ArrayList* of *Integers* has a size of 3

```
ArrayList<Integer> scores = new ArrayList<Integer>();
scores.add(23); //adds element 23
scores.add(15); //adds element 15
scores.add(0); //adds element 0
System.out.println(scores.size()); //size of 3
```
- *size* is a method, not a variable
- *ArrayLists* can be easily resized
 - You don't initialize *ArrayLists* with a specific size
 - You can *add/remove* elements without worrying about it
 - *ArrayLists* will take care of the resizing for you

27

ArrayList Methods

- ArrayLists have *many* attributes/methods
- There is *add*, *remove*, *size*, *get*, etc.

Ref: <https://docs.oracle.com/javase/8/docs/api/java/util/ArrayList.html>

28

toString

29

Printing primitives vs. Objects

- You can easily print primitive values in Java

```
int a = 5;
System.out.println("a = " + a); //prints "a = 5"
```
- You know what to expect when you print a *primitive*

```
boolean b = false;
System.out.println("b = " + b); //prints "b = false"
```
- Printing Objects is not as straightforward

```
Customer c = new Customer("Brandon");
System.out.println("c = " + c); //what would you expect this to print?
```
- You need to tell Java what to print by defining the *toString* method in the class
 - For reference, this is the same as defining the `__str__` method in a Python class
 - The *toString* method must return a String
- The syntax of the *toString* method is:

```
public String toString() {
    return "someString";
}
```

30

Printing primitives vs. Objects

- Below is an implementation of the `toString` method in a `Customer` class

```
public class Customer {  
    //Name of Customer  
    String name;  
  
    public Customer(String name) {  
        this.name = name;  
    }  
  
    //toString method must return a String  
    public String toString() {  
        return this.name; //return name, to be printed by Java  
    }  
}
```
- Now, print a customer

```
Customer c = new Customer("Brandon");  
System.out.println("c = " + c); //prints "c = Brandon"
```

31

Classroom Project

32

Classroom Project

- In Eclipse, create a new "Classroom" project
 - This program will represent an actual classroom, with ways (methods) of adding students and assigning seats
- Create 3 classes:
 - Classroom
 - The classroom itself, with seats and students
 - Make sure `public static void main(String[] args)` is checked
 - Seat
 - A seat in the classroom
 - Student
 - A student assigned to the classroom and sitting in a seat

33

36

Classroom Project – Seat Class

```

38  /**
39   * Assigns the given student to this seat.
40   * @param student to assign
41   */
42  public void putStudentInSeat(Student student) {
43      this.studentInSeat = student;
44  }
45  //methods
46
47  /**
48   * Returns row, column, and student for this seat.
49   */
50  @Override
51  public String toString() {
52      return this.row + ", " + this.column + ", " + this.studentInSeat; //calls the toString method in student
53  }
54  }

```

37

Classroom Project – Student Class

```

1
2  /**
3   * Represents a student for a class.
4   * Each student has a name and ID.
5   * @author Brandon
6   */
7  public class Student {
8
9      //instance variables
10
11      /**
12       * Name of student.
13       */
14      String name;
15
16      /**
17       * ID for student.
18       */
19      String ID;
20
21      //constructor
22
23      /**
24       * Creates a student with given name and ID.
25       * @param name for student
26       * @param ID for student
27       */
28      public Student(String name, String ID) {
29          this.name = name;
30          this.ID = ID;
31      }
32  }

```

38

Classroom Project – Student Class

```

36  /**
37   * Returns name of student.
38   */
39  @Override
40  public String toString() {
41      return this.name;
42  }

```

39

Classroom Project – Classroom Class

```

69 //method
70 /**
71  * Adds the given student to the classroom.
72  * @param student to add
73  */
74 public void addStudent(Student student) {
75     this.students.add(student);
76 }
77
78 /**
79  * Finds a seat and assigns to the given student.
80  * @param student to assign
81  */
82 public void assignStudentToSeat(Student student) {
83     int rows = this.seats.length; //gets number of rows
84     int columns = this.seats[0].length; //gets number of columns in first row
85
86     //iterate over rows and columns
87     for (int i = 0; i < rows; i++) {
88         for (int j = 0; j < columns; j++) {
89             //find available seats, if student in that seat is null (empty)
90             if (this.seats[i][j].studentIndex == null) {
91                 //assign student
92                 this.seats[i][j].putStudentToSeat(student);
93                 //we're done, break out of loop (and method)
94                 return;
95             }
96         }
97     }
98 }
99
100 }
101

```

40

Classroom Project – Classroom Class

```

102 /**
103  * Prints all the students in the class.
104  */
105 public void printAllStudents() {
106     System.out.println("Students in class: ");
107     //use enhanced for loop to print each student
108     for (Student student : this.students) {
109         System.out.println(student); //calls the toString in the Student class
110     }
111 }
112
113 /**
114  * Returns layout of classroom, with seat and student info.
115  */
116 @Override
117 public String toString() {
118     String s = "\n";
119
120     int rows = seats.length; //gets number of rows
121     int columns = seats[0].length; //gets number of columns in first row
122
123     for (int i = 0; i < rows; i++) {
124         for (int j = 0; j < columns; j++) {
125             s += seats[i][j].toString(); //calls the toString method in the Seat class
126         }
127         s += "\n";
128     }
129     return s;
130 }
131

```

41

Classroom Project – Classroom Class

```

134
135 public static void main(String[] args) {
136
137     //create classroom
138     Classroom huntsman = new Classroom("HR", "185", 10, 5);
139
140     //create students
141     Student finegan = new Student("finegan", "finegan");
142     Student bob = new Student("bob", "roberts");
143
144     //add students to class
145     huntsman.addStudent(finegan);
146     huntsman.addStudent(bob);
147
148     //assign students to seats
149     huntsman.assignStudentToSeat(finegan);
150     huntsman.assignStudentToSeat(bob);
151
152     //print list of students in class
153     huntsman.printAllStudents();
154
155     //print the classroom itself
156     //calls the toString method in classroom
157     System.out.println(huntsman);
158 }
159
160 }

```

42